The documentation and process conversion measures necessary to comply with this amendment shall be completed by 5 July 2002.

INCH POUND

MIL-PRF-19500/660
AMENDMENT 2
5 April 2002
SUPERSEDING
AMENDMENT 1
21 February 2001

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, FIELD EFFECT RADIATION HARDENED
(TOTAL DOSE ONLY) TRANSISTOR, P-CHANNEL
SILICON TYPES 2N7424, 2N7425 AND 2N7426
JANTXVR, JANTXVF, JANSR AND JANSF

This amendment forms a part of MIL-PRF-19500/660, dated 27 May 1998 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.3, column P_T 1/ T_A = +25°C (free air); delete "1/".

1.3, type 2N7426, I_{D1}, delete "-23" and substitute "-27".

1.3, type 2N7426, I_{D2}, delete "-15" and substitute "-17".

1.3, type 2N7426, I_S, delete "-23" and substitute "-27".

1.3, type 2N7426, I_{DM}, delete "-92" and substitute "-108".

1.4, type 2N7426, $r_{ds(on)}$, delete "0.230Ω" and substitute "0.160Ω".

1.4, type 2N7426, $r_{ds(on)}$, delete "0.530Ω" and substitute "0.340Ω".

PAGE 7

4.5.2, drain heating current (I_H), delete "8 A" and substitute "10 A".

4.5.2, drain-source heating voltage (V_H), delete "25 V" and substitute "20 V".

PAGE 8

TABLE I, subgroup 2, static drain to source "ON" state resistance, $r_{ds(on)1}$, type 2N7426, max limits, delete "0.230Ω" and substitute "0.160Ω".

TABLE I, subgroup 2, static drain to source "ON" state resistance, $r_{ds(on)2}$, type 2N7426, max limits, delete "0.240Ω" and substitute "0.170Ω".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:34Z
Check the source to verify that this is the current version before use.

PAGE 9

TABLE I, subgroup 3, static drain to source "ON" state resistance, $r_{ds(on)3}$, type 2N7426, max limits, delete "0.46Ω" and substitute "0.315Ω".

TABLE I, subgroup 4, turn-on delay time, type 2N7426, max limits, delete "70" and substitute "37".

TABLE I, subgroup 4, rise time, type 2N7426, max limits, delete "240" and substitute "83".

TABLE I, subgroup 4, turn-off delay time, type 2N7426, max limits, delete "220" and substitute "140".

TABLE I, subgroup 4, fall time, type 2N7426, max limits, delete "220" and substitute "172".

TABLE I, subgroup 4, add:

"

Inspection 1/	MIL-STD-750		Symbol	Limits		Unit
	Method	Conditions		Min	Max	
Subgroup 4						Vdc
Forward transconductance	3475	I_D = rated I_{D2}, V_{DD} = 15 V (see 4.5.1)	g_{FS}			
2N7424				18		S
2N7425				15		S
2N7426				13		S

"

PAGE 10

TABLE I, subgroup 7, gate to source charge, type 2N7426, delete "75" and substitute "60".

TABLE I, subgroup 7, gate to drain charge, type 2N7426, delete "90" and substitute "70".

TABLE I, subgroup 7, reverse recovery time, type 2N7426, delete "775" and substitute "600".

PAGE 12

TABLE II, subgroup 2, static drain to source on-state voltage, type 2N7426, delete "-3.45" (three places) and substitute "-2.72" (three places).

PAGE 18

4.5.3, drain heating current (I_H), delete "8 A" and substitute "10 A".

4.5.3, drain-source heating voltage (V_H), delete "25 V" and substitute "20 V".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:34Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA – CC

Preparing activity:
DLA - CC

(Project 5961-2594)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T04:34Z
Check the source to verify that this is the current version before use.