INCH-POUND

MIL-DTL-32139/18
28 November 2023

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, NANOMINIATURE, DUAL ROW, RECEPTACLE, POLARIZED SHELL, SOCKET CONTACTS, HORIZONTAL PCB SURFACE MOUNT SHELL TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-32139.




FIGURE 1. Nano connector dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.


Size	A	B BSC	C BSC	D BSC	E	F THREAD	G MAX	H	J
9	.375 (9.53)	.270 (6.86)	.163 (4.14)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.175 (4.45)	.225 (5.71)	.187 (4.75)
15	.450 (11.43)	.345 (8.76)	.238 (6.05)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.250 (6.35)	.225 (5.71)	.187 (4.75)
21	.525 (13.34)	.420 (10.67)	.313 (7.95)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.325 (8.26)	.225 (5.71)	.187 (4.75)
25	.575 (14.61)	.470 (11.94)	.363 (9.22)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.375 (9.53)	.225 (5.71)	.187 (4.75)
31	.650 (16.51)	.545 (13.84)	.438 (11.13)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	450 (11.43)	.225 (5.71)	.187 (4.75)
37	.725 (18.42)	.620 (15.75)	.513 (13.03)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.525 (13.34)	.225 (5.71)	.187 (4.75)
51	.900 (22.86)	.795 (20.19)	.688 (17.48)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.700 (17.78)	.225 (5.71)	.187 (4.75)
65	1.075 (27.31)	.970 (24.64)	.863 (21.92)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.875 (22.23)	.225 (5.71)	.187 (4.75)
69	1.125 (28.58)	1.020 (25.91)	.913 (23.19)	.0725 (1.84)	.140 (3.56)	#0-80 UNF	.925 (23.50)	.225 (5.71)	.187 (4.75)
85	1.377 (34.97)	1.246 (31.65)	1.113 (28.27)	.085 (2.16)	.165 (4.19)	#2-56 UNC	1.120 (28.45)	.270 (6.86)	.210 (5.33)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm) angular tolerance ±2°
4. Shell shall be flush to insulator within ±.004 inch (0.10 mm)
5. Leads to be co-planar within .004 above to .001 below mounting surface.
6. Tail finish is tin/lead or gold.

Inches	mm	Inches	mm
.0015	.038	.0185	.470
.003	.08	.020	.51
.004	.10	.025	.64
.005	.13	.037	.94
.010	.25	.040	1.02
.0125	.318	.042	1.07
.0135	.343	.050	1.27
.015	.38	.100	2.54
.018	.46	.110	2.79

FIGURE 1. Nano Connector Dimensions and Configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.




Inches	mm
.0015	0.038
.033	0.84
.075	1.91
.098	2.49
.108	2.743
.110	2.79

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm).

FIGURE 2. Nano Connector Interface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.




NOTES:

1. Engaging face of insert shown.
2. Cavity identification numbers are for reference only and do not appear on the part.


FIGURE 3. Nano Connector Insert Arrangement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.

SIZE	L	M
9	.100 [2.54]	.075 [1.90]
15	.175 [4.44]	.150 [3.81]
21	.250 [6.35]	.225 [5.71]
25	.300 [7.62]	.275 [6.98]
31	.375 [9.52]	.350 [8.89]
37	.450 [11.43]	.425 [10.79]
51	.625 [15.87]	.600 [15.24]
65	.800 [20.32]	.775 [19.68]
69	.850 [21.59]	.825 [20.96]
85	1.050 [26.67]	1.025 [26.04]



RECOMMENDED PC BOARD LAYOUT
FOR SIZE 9 THROUGH 69
(COMPONENT SIDE)



RECOMMENDED PC BOARD LAYOUT
FOR SIZE 85
(COMPONENT SIDE)

Inches	mm	Inches	mm
.0125	.318	.050	1.27
.016	.41	.054	1.37
.025	.64	.085	2.16
.0365	.93	.098	2.49
.040	1.02		

Figure 4. Recommended PC Board Layout (Component Side).

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ±.005 inch (0.13 mm).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration see figures 1, 2, and 3.


This specification sheet describes the pin side of a rectangular connector. This connector uses reverse gender contacts, i.e., the live pin recessed in the insulator with the static socket protruding from a shrouded interface.

Contact connection: The pin contact, which is recessed in the insulator, is normally connected to the live side of the circuit.

Pins are terminated to a printed circuit board (PCB) as specified on figure 4.

Mating plug: Shall be in accordance with MIL-DTL-32139/3, MIL-DTL-32139/9, MIL-DTL-32139/11, MIL-DTL 32139/13, MIL-DTL-32139/15, and MIL-DTL-32139/17

Part or Identifying Number (PIN):



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.

Insert arrangement	Tail finish	Hardware [1/]
A = 9	01 = Tin/Lead	T = Threaded hole [3/]
B = 15	02 = Gold	
C = 21		
D =25		
E = 31		
F = 37		
G = 51		
K = 65		
J = 69		
K = 85		

Shell finish	Space class
C = Aluminum shell, cadmium finish	Blank for non-space class
N = Aluminum shell, electroless nickel finish [2/]	
S = Passivated stainless steel shell	
T = Titanium shell	
A = Pure Electrodeposited Aluminum	
F = Nickel Fluorocarbon Polymer	
Z = Zinc Nickel	

1/ Supplied installed.
2/ When aluminum shells are required for space applications, electroless nickel finish shall be used. Cadmium finish is not acceptable (see MIL-DTL-32139).
3/ The aluminum shell may require additional thread components.

Alternate shell finishes:

Pure Electrodeposited Aluminum. Pure dense electrodeposited aluminum shall be in accordance with MIL-DTL-83488, type II shall withstand 48 hour salt spray. Color shall be non-reflective and shall meet the requirements as specified herein.

Nickel Fluorocarbon Polymer. High phosphate nickel with fluorocarbon polymer additive over a suitable underplate shall withstand 48 hour salt spray. Color shall be non-reflective and shall meet the requirements as specified herein.

Zinc Nickel. Zinc Nickel Alloy in accordance with ASTM B841, over a suitable underplate shall withstand 48 hour salt spray. Color shall be non-reflective and shall meet the requirements as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-DTL-32139, this document references the following:

MIL-DTL-32139/3
MIL-DTL-32139/9
MIL-DTL-32139/11
MIL-DTL-32139/13
MIL-DTL-32139/15
MIL-DTL-32139/17
MIL-DTL-83488
ASTM B841

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2023-085)

Review activities:
Army - AV, MI
Navy – AS

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T04:56Z
Check the source to verify that this is the current version before use.