NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/129B
1 May 1997
SUPERSEDING
MIL-D-3943/129A
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, EXCEPTIONAL ENGINEERING ACHIEVEMENT MEDAL, NASA

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Gold Plated, Rose Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 20.

DIMENSIONS:
HEIGHT (Including Lug):
-1: 1-5/8 inches (4.13 cm) (REF)
-2: 13/16 inch (2.06 cm) (REF)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T00:58Z
Check the source to verify that this is the current version before use.

DIAMETER:
-1: 1-1/2 inch (3.81 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

THICKNESS (At Edge):
-1: 0.150 inch ± 0.010 inch (0.381 cm ± 0.025 cm)
-2: 0.080 inch ± 0.010 inch (0.203 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The reverse side shall be flat, plain and suitable for engraving.

3. Reverse side of the wreath shall be engraved with the word "EXCEPTIONAL ENGINEERING ACHIEVEMENT". The letters shall be 1/16 inch (0.16 cm) block letters, centered on the midpoint of the wreath with the first letter "E" and the last letter "T" equidistant from the integral lug for Dash -1 only.

4. Piercing shall be as indicated.

5. Decoration set shall consist of a regular size medal, a miniature medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type XV, Style 1 with a Class 2 or 2a pad.

6. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/340.

7. The lapel button shall conform to MIL-DTL-11484/165.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0887)

Civil Agency Coordinating Activities:
NASA - NA

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T00:58Z
Check the source to verify that this is the current version before use.