MIL-P-21343(SHIPS)
AMENDMENT 2
23 August 1985
SUPERSEDING
AMENDMENT 1
1 September 1964

MILITARY SPECIFICATION

PUMPS, CENTRIFUGAL, SUBMARINE TRIM AND DRAIN
(SERIES TYPE ONLY)

This amendment forms a part of Military Specification MIL-P-21343(SHIPS), dated 9 Nay 1958, and is approved for use within the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: Under Military Specifications add:

"MIL-I-45208 - Inspection System Requirements."

PAGE 2

2.1: Delete:

"NAVY DEPARTMENT
General Specifications for Inspection of Material."

* 3.1: Delete and substitute:

"3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.1.1 and 6.2)."

PAGE 12

* 4.1: Delete "Qualification" and substitute "First article".

* 4.1.1: Delete and substitute:

"4.1.1 First article tests at a laboratory. First article tests shall be conducted at a laboratory satisfactory to the Naval Sea Systems Command. The head, capacity and other characteristics of units for first article tests shall be as specified by the Naval Sea Systems Command."

* 4.1.2: Delete.

l 4.1.3: Delete.

FSC 4320

DISTRIBUTION STATEMENT A Approved for public release; distribution unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:18Z
Check the source to verify that this is the current version before use.

PACE 13

4.2.2: Delete and substitute:

"4.2.2 Each pump shall be tested at designed maximum operating speed by a continuous nonstop run of at least 30 minutes to check operation and smoothness of running. While running at this speed the pump need not be loaded except as necessary to prevent injury."

4.2.3, second sentence: Delete.

4.3.3, lines 1 and 2: Delete "as selected by the Government inspector,"

PAGE 14

4.3.11: Delete and substitute:

"4.3.11 Where shock tests are conducted at a Government laboratory, copies of the applicable master drawings shall accompany the units."

PAGE 15

4.4, second sentence: Delete and substitute:

"Ordinarily material analysis and physical test specimens will not be required; however, procedures shall be employed to assure that parts are made of the same materials and by the same processes as for assembled pumps."

* 4.5: Delete and substitute:

"4.5 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

"4.5.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The Inspection set forth In this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:18Z
Check the source to verify that this is the current version before use.

"4.5.1.1 All instruments used in performance acceptance tests shall be calibrated before and after tests.

"4.5.1.2 No instruments containing mercury shall be used in the manufacture or testing of any equipment destined for installation on a nuclear powered ship. This point shall be covered in the manufacturer's inspection system procedures. Test reports shall contain a certification signed by a responsible official of the manufacturer that no mercury containing instruments have been used in the manufacture or testing of the equipment."

* 6.1: Add: "(i) If first article Inspection is required (see 3.1)."

PAGE 16

* 6.2: Delete and substitute:

"6.2 First article inspection. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection as to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

* 6.2.1: Delete.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing activity:
Navy - SH
(Project 4320-N251)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:18Z
Check the source to verify that this is the current version before use.

U.S. GOVERNMENT PRINTING OFFICE: 1985 - 508-038/24100