MIL-C-28914(MC)
21 March 1969

MILITARY SPECIFICATION

CONTROL UNIT - RECTIFIER, C-7673/PCC-1

1. SCOPE

1.1 This specification covers requirements for one type transportable control unit-rectifier.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-152	-	Treatment, Moisture and Fungus-Resistant, of Communications, Electronic and Associated Electrical Equipment.
MIL-T-704	-	Treatment and Painting of Materiel.
MIL-P-15024	-	Plates, Identification-Information and Marking for Identification of Electrical, Electronic and Mechanical Equipment.
MIL-E-16400	-	Electronic Equipment, Naval Ship and Shore, General Specification.
MIL-E-17555	-	Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of.
MIL-E-21981	-	Electronics Type Designations, Identification Plates and Markings, Requirements for.
MIL-R-22732	-	Reliability Requirements for Shipboard and Ground Electronic Equipment.

STANDARDS

MILITARY

MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-810	-	Environmental Test Methods.
MIL-STD-826	-	Electromagnetic Interference Test Requirements and Test Methods.

27143

FSC 5805

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General. The Control Unit-Rectifier, C-7673/PCC-1, shall provide a central connecting and switching point for power supply and radio connections to Terminal Telegraph-Telephone, TH-81/GCC. Power shall be obtained from 115 alternating current volts (Vac), from a 24-volt (V) vehicle battery, from a Battery, BB-451/U, or from the BA-386/PRC-25 batteries of the Receiver-Transmitter, RT-505/PRC-25's. Rectifiers and converters shall be provided so that the correct voltages are provided from each power supply. A mode-of-operation switch shall connect a Handset, H-138/U, or Handset, H-189/GR, to either receiver-transmitter (rt) as a single-channel simplex telephone circuit or connect the handset to one receiver and the other transmitter as a duplex telephone circuit with the unused transmitter and receiver as a standby or connect the carrier terminal to one receiver and the other transmitter, with the unused transmitter and receiver as a standby and with the handset connected to the carrier terminal.

3.1.1 Type and function of equipment. The Control Unit-Rectifer, C-7673/PCC-1, shall constitute a lightweight, high performance, tactical, transistorized power supply and switching unit. The unit shall also have the following characteristics:

(a) High reliability and ease of maintainability.

(b) Small physical size.

3.2 First article. Prior to submission of any complete production units for acceptance, the contractor shall furnish first articles for testing under the direction and supervision of the cognizant Government inspector to determine conformance to this specification. First article is defined as a production sample which will be identical to the production items which the contractor will subsequently produce in fulfillment of the contract. Unless otherwise specified, a quantity of five first articles shall be furnished (see 6.2). Approval of the first articles by the

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

activity concerned shall not relieve the contractor of the responsibility to supply equipment conforming to this specification. Examination and testing shall be as specified herein. Any changes or deviations of the production units from the first articles shall be subject to the approval of the contracting officer. The items subjected to first article tests may be included in the final shipment as part of the total quantity to be supplied under the contract, provided they have been completely refurbished.

3.3 Reliability assurance. Reliability shall receive major emphasis during the design, fabrication and construction of units. This emphasis shall be reflected in the assembly processes and the determination of operational techniques. The first article, production and sample items shall be subjected to the mechanical and electrical tests specified in Section 4. Mechanical wear shall be such that mechanical or functional performance is not affected. Abrasion of painted surfaces is allowable. Electrical performance of the unit shall not be degraded. The contractor is required to demonstrate that the unit is capable of calculated mean time between failure (MTBF) of not less than 15,000 hours. The contractor is required to demonstrate actual MTBF of not less than 500 hours under standard and service conditions. Test level No. 2 of MIL-R-22732 shall be utilized in establishing demonstrated test conditions.

3.4 Design and construction. Design and construction shall be as follows:

3.4.1 Mechanical parts. Where mechanical parts are employed, whose functions are to rotate, cam or oscillate against other mechanical parts and the best choice of materials includes other than those specified in MIL-E-16400, use of the other materials may take precedence.

3.4.2 Parts and materials. In the selection of parts and materials, the fulfillment of major objectives shall be the prime consideration. In all cases, general material requirements as to flammability, fungus-resistance and nontoxicity as specified in MIL-T-152 shall be met.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

3.4.3 Nonstandard parts. When it has been determined that requirements cannot be met by use of parts and materials specified in MIL-E-16400, the contractor shall immediately inform the contracting officer by submission of detailed data as required by MIL-E-16400, and shall request approval.

3.4.4 Components. Parts and materials approved by specifications listed in MIL-E-16400 shall be given first consideration.

3.4.5 Case material. The construction of the case and top panel for the unit shall be made of cast aluminum alloy. Where panels are removable from the basic case and interconnecting cables permanently enter the case, the openings shall be protected with gaskets and packing to assure watertight protection for the equipment in transit.

3.4.6 Treatment and painting. Treatment and painting shall conform to MIL-T-704. Color shall match Marine Corps green, No. 23 (see 6.3).

3.4.7 Standard conditions. The following conditions shall be used as the basis for establishing normal requirements for conducting laboratory and bench test of the equipment.

(a) Room ambient temperature, range +20° C to +40° C.

(b) Altitude, normal ground.

(c) Room ambient humidity, up to 95 percent relative.

3.4.8 Service conditions. The unit shall operate satisfactorily under any of the following service conditions.

(a) Ambient temperature range -40° Centigrade (C) to +65° C.

(b) Altitude, sea level to 10,000 feet.

(c) Ambient humidity range, 0 to 95 percent relative.

(d) Vibration (see 4.3).

(e) Shock (see 4.4).

(f) Immersion (leakage) (see 4.5).

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

(g) Salt fog environment (see 4.11).

(h) Blowing sand and dust (see 4.12).

(i) Temperature shock (see 4.8).

(j) High temperature (see 4.6).

(k) Low temperature (see 4.7).

3.4.9 Storage conditions. The equipment shall be capable of being stored under the following conditions with a subsequent period of operation:

(a) Ambient temperature range -62° C to -71° C
(b) Altitude - Sea level to 50,000 feet.

3.4.10 Stability

3.4.10.1 Electrical. The equipment shall operate as specified herein for at least 500 hours, either continuously or intermittently independent of component failure without necessity for readjustment of any controls other than those located on the front panel.

3.4.10.2 Mechanical. All controls and adjustments shall be designed so that their position of adjustment will not be altered when the equipment is subjected to the specified service conditions.

3.4.11 Interchangeability. All components and parts shall be physically, functionally, mechanically and electrically interchangeable with any other equipment produced under this specification.

3.4.12 Identification marking. Subassemblies shall be identified with the manufacturer's part numbers, steel stamped, rubber stamped or silk screened on a fixed surface if available, or on a permanent tag affixed in a manner which shall not impair operation of the assembly, and shall not be easily removable. This marking shall be visible when mounted in the assembly.

3.5 Fungus resistance. The unit shall be rendered fungus proof by the selection of parts and materials which are nonnutrient for fungus.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

3.6 Electrical characteristics. The electrical characteristics shall be as specified in the following paragraphs at nominal line voltage of 115 Vac 60 hertz (Hz) or 400 Hz single-phase or 24 direct current volts (Vdc) unless otherwise specified herein.

3.6.1 Power supply.

3.6.1.1 Normal power.

(a) When powered from the following inputs:

Input	Voltage		
	Minimum	Nominal	Maximum
115 Vac	103.5	115	126.5
24-V vehicle battery and BB-451/U, dc	22	24	32

(b) The output voltages shall be as follows for all working load conditions:

Output	Voltage Vdc	
	Minimum	Maximum
Terminal, Telegraph-Telephone TH-81/GCC	21	32
Receiver-Transmitter RT-505/PRC-25 (3 V)	2.25	3.5
Receiver-Transmitter RT-505/PRC-25 (15 V)	10	15

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

3.6.1.2 Emergency power.

(a) When powered from the following inputs for emergency use.

Input	Voltage Vdc		
	Minimum	Nominal	Maximum
BA-386/PRC-25 (3 V)	2.35	2.5	3.5
BA-386/PRC-25 (15 V)	12	12.5	15

(b) The output voltages shall be as follows for all working load conditions:

Output	Voltage Vdc	
	Minimum	Maximum
Terminal, Telegraph-Telephone TH-81/GCC - Telegraph OFF	18	32
Receiver-Transmitter RT-505/PRC-25 (3 V)	2.25	3.0
Receiver-Transmitter RT-505/PRC-25 (15 V)	10	15

3.6.1.3 Load current. The Control Unit-Rectifier, C-7673/PCC-1, shall be capable of supplying the following simultaneous continuous load currents to associated equipment at the nominal input voltages specified in 3.6.1.1.

(a) Terminal, Telegraph-Telephone, TH-81/GCC : 550 milliampere (mA)

(b) Receiver-Transmitter, RT-505/PRC-25 (3 V): 376 mA

(c) Receiver-Transmitter, RT-505/PRC-25 (15 V): 1.2 ampere (A).

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

3.6.1.4 Surge current. The Control Unit-Rectifier shall be capable of supplying the following simultaneous surge currents for a duration of 1.0 millisecond following turn-on.

(a) Terminal, Telegraph-Telephone, TH-81/GCC : 550 mA

(b) Receiver-Transmitter, RT-505/PRC-25 (3 V) : 0.8 A

(c) Receiver-Transmitter, RT-505/PRC-25 (15 V) : 6.0 A

3.6.1.5 Ripple content. The root mean square (rms) ripple content of each output, including direct battery connections, shall be as follows:

(a) Terminal, Telegraph-Telephone, TH-81/GCC : 2 V rms maximum.

(b) Receiver-Transmitter, RT-505/PRC-25 (3 V): 0.05 V rms maximum.

(c) Receiver-Transmitter, RT-505/PRC-25 (15 V): 0.15 V rms maximum, or for equivalent loads.

3.6.2 Handset circuit. Provision shall be made for switching a Handset, H-138/U, or Handset, H-189/GR, connected to the control unit-rectifier as follows:

(a) All handset connections to Receiver-Transmitter, RT-505/PRC-25 No. 1.

(b) All handset connections to Receiver-Transmitter, RT-505/PRC-25 No. 2.

(c) Microphone and handset switch to Receiver-Transmitter, RT-505/PRC-25 No. 1 receiver to Receiver-Transmitter, RT-505/PRC-25 No. 2.

(d) Microphone and handset switch to Receiver-Transmitter, RT-505/PRC-25 No. 2 receiver to Receiver-Transmitter, RT-505/PRC-25 No. 1.

(e) All handset connections to handset connector of Terminal, Telegraph-Telephone, TH-81/GCC.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

3.6.3 High frequency (hf) circuit. Provision shall be made for switching the hf input and output of a Terminal, Telegraph-Telephone, TH-81/GCC, connected to the control unit rectifier as follows:

(a) Input and output grounded.

(b) Input and output open circuited.

(c) Input to Receiver-Transmitter, RT-505/PRC-25 No. 2; output to Receiver-Transmitter, RT-505/PRC-25 No. 1.

(d) Input to Receiver-Transmitter, RT-505/PRC-25 No. 1; output to Receiver-Transmitter, RT-505/PRC-25 No. 2.

3.6.4 Terminal, Telegraph-Telephone, TH-81/GCC, power circuit. Provision shall be made for switching power to Terminal, Telegraph-Telephone, TH-81/GCC as follows:

(a) No power to Terminal, Telegraph-Telephone, TH-81/GCC.

(b) Apply power to Terminal, Telegraph-Telephone, TH-81/GCC. No power to telegraph channels of Terminal, Telegraph-Telephone, TH-81/GCC.

(c) Apply power to telegraph channels of Terminal, Telegraph-Telephone, TH-81/GCC.

3.7 Controls and connections.

3.7.1 Front panel. The front panel of the Control Unit-Rectifier, C-7673/PCC-1, shall contain the following operator controls and shall be identified as follows:

Control or Connector	Switch Position	Function
MODE switch, S11 (6-position rotary)	SX RT 1	Applies power to rt and connects the handset to No. 1.
	SX RT 2	Applies power to rt and connects the handset to No. 2.
	ONE CHAN DX RT 1 TR	Applies power to rt No. 1 and No. 2; connects the handset microphone to the transmitter of rt No. 1 and the receiver of the handset to rt No. 2.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

Control or Connector	Switch Position	Function
	ONE CHAN DX RT 2 TR	Applies power to rt No. 1 and No. 2; connects the handset microphone to the transmitter of rt No. 2 and the receiver of the handset to rt No. 1.
	MULTI CHAN DX RT 1 TR	Applies power to rt No. 1 and No. 2 and to the carrier terminal; connects the hf transmit output of the terminal to the transmitter of rt No. 1 and the output of the receiver of rt No. 2 to the hf receiving input of the terminal; connects the handset to the terminal through its handset connector.
	MULTI CHAN DX RT 2 TR	Applies power to rt No. 1 and No. 2 and to the carrier terminal; connects the hf transmit output of the terminal to the transmitter of rt No. 2 and the output of the receiver of rt No. 2 and the output of the receiver of rt No. 1 to the hf receiving input of the terminal; connects the handset to the terminal through its handset connector.
TLG CHANS switch, S12 (2-position toggle)	ON	Connects power to the telegraph circuits of the terminal.
	OFF	Removes power from the telegraph circuits of the terminal.
HANDSET connector, J21		Provides connection for the handset.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

Control or Connector	Switch Position	Function
POWER SOURCE switch, S13 (5-position rotary)	DRY BAT.	Connects the BA-386/PRC-25 batteries in the battery boxes of the rt through S1 and to the voltage doubler to supply the terminal.
	BB-451	Connects the Battery, BB-451/U to the terminal through S1 and to the voltage divider to supply the rt.
	OFF	Disconnects all power.
	VEH	Connects the vehicle battery to the terminal through S1 and to the voltage divider to supply the rt.
	115 VAC	Connects 115 Vac to the rectifiers to provide power to the rt and the terminal.
3A AC fuses F5 and F6 (3-ampere)		Protect the alternating current (ac) connections.
VEH 5A fuse F7 (5-ampere)		Protects the connection from the vehicle battery.
BB-451 5A Fuse F8 (5-ampere)		Protects the connection from Battery, BB-451/U.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

3.7.2 Rear panel. The rear panel of the Control Unit-Rectifier, C-7673/PCC-1, shall contain the following connectors and shall be identified as follows:

Captive cable connectors	Function
TH-81 HANDSET	Connects to HANDSET connector of Terminal, Telegraph-Telephone, TH-81/GCC.
TH-81 HF	Connects to hf connector of Terminal, Telegraph-Telephone, TH-81/GCC.
BB-451	Connects to Battery, BB-451/U
24 V BAT	Connects to 24-V vehicle battery.
115 VAC	Connects to 115 Vac Supply.
RT-505 POWER No. 1	Connects to Receiver-Transmitter, RT-505/PRC-25 No. 1.
RT-505 POWER No. 2.	Connects to Receiver-Transmitter, RT-505/PRC-25 No. 2.

3.7.3 Protective fuse. There shall be an internal 3/8-A fuse to protect modules in the event of failure of regulator Transistor, Q1, to ensure that correct operation of the circuit is verified before fuse replacement.

3.8 Dimensions. The maximum external dimensions of the control unit-rectifier shall not exceed 9.750 inches wide by 7.500 inches deep by 2.125 inches high.

3.9 Weight. The weight shall not exceed 8 pounds.

3.10 Identification plates. Identification plates shall be in accordance with MIL-P-15024 and shall be of aluminum alloy where possible. Drawings for identification plates shall be submitted for approval 90 days prior to first

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

article tests. Nomenclature shall be requested in accordance with MIL-E-21981 and shall be submitted 90 days prior to the first article testing.

3.11 Workmanship. Units covered by this specification shall be manufactured and finished in accordance with MIL-E-16400.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contractor or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Inspection and tests. Inspection and tests shall consist of all tests specified herein to demonstrate that the units submitted for approval meet all requirements of this specification. First article testing will be witnessed by a representative of the contracting officer.

4.2.1 Tests. Table I lists the tests required for first article production and sample tests.

4.2.1.1 Inspection and test procedures. The detailed procedures for conducting tests shall be prepared by the contractor and submitted to the contracting officer for approval 30 days prior to the initiation of any official testing.

4.2.1.2 Tests to be performed. Units to be tested shall be the quantities indicated.

(a) First article. Unless otherwise specified, a quantity of five complete units shall be used to complete these tests (see 3.2). Tests performed on one unit need not be repeated on another. The Government representative will select which unit will be subjected to each test.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

Table I Tests

Electrical Para.		Environmental	Para.
Output voltage	3.6.1.1	Standard Condition	3.4.6
Load current	3.6.1.2	Vibration	4.3
Surge current	3.6.1.3	Shock	4.4
Ripple voltage	3.6.1.4	Immersion	4.5
Handset circuit	3.6.2	High temp. +65° C	4.6
Interference	4.13	Low temp. -40° C	4.7
		Humidity	4.9
		Low pressure	4.10
		Salt fog	4.11
		Sand and dust	4.12
		Temp. shock	4.8

Output voltage	Load current	Surge current	Ripple voltage	Handset circuit	Interference	Standard Condition	Vibration	Shock	Immersion	High temp. +65° C	Low temp. -40° C	Humidity	Low pressure	Salt fog	Sand and dust	Temp. shock
FA P	FA P	FA	FA	FA P	FA	FA P										
FA	FA			FA			FA	FA	FA	FA S	FA S	FA	FA	FA	FA	FA
FA	FA	FA	FA S	FA												
FA	FA	FA	FA S	FA												
FA	FA	FA	FA S	FA												
FA	FA	FA		FA												
FA	FA	FA		FA												
FA	FA	FA		FA												
FA	FA	FA		FA												

NOTE: FA= First article test S= Sample test P= Production test

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

(b) Production. All units shall be subjected to the production tests.

(c) Samples. Sample units shall be randomly selected by the cognizant Government inspector.

Qty. produced	Qty. to be tested
1-49	1
50-99	2
100-149	3
150-199	4
200-300	5
	One additional equipment per 100 units.

4.3 Vibration test. One unit shall be subjected to the following vibration test with the unit operating. The unit shall be affixed to the vibration table and be subjected to the following conditions. Vibration in the frequency range of 10 to 55 Hz at 5 gravity (g) or 0.060 inch total excursion, whichever is the limiting value. The frequency change shall be at a rate of less than 1 Hz. The duration of the test shall be 1/2 hour in each of three planes. There shall be no rigid body resonances and no signs of internal or external physical deterioration.

4.4 Shock test. One unit shall be subjected to the following shock test with the unit operating. The unit shall be mounted rigidly on the adapter plate of the LAB package testing machine. The machine shafts shall be operated in phase and adjusted in speed to produce average peak accelerations of 10 g's with occasional peaks of 20 g's as measured on the case of the equipment. Malfunction is permissible provided that normal operation can be restored by adjustment of front panel controls. There shall be no signs of internal or external physical deterioration.

4.5 Immersion (leakage) test. The unit shall be submerged in water to a depth of 3 feet, measured from its highest point. The unit shall be held in this position for 1 hour, and during the test all panel controls shall be operated three times through their full travel. There shall be no entry of water into the unit. There shall be no signs of internal or external physical deterioration.

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

4.6 High temperature test. The unit shall be tested in accordance with procedure I, method 501, of MIL-STD-810. The unit shall be operated at a temperature not less than 60° C nor greater than 65° C.

4.7 Low temperature test. The unit shall be tested in accordance with procedure I, method 502, of MIL-STD-810. The unit shall be operated at a temperature not greater than -40° C.

4.8 Temperature shock test. The unit shall be tested in accordance with procedure I, method 503, of MIL-STD-810, with exception that the maximum temperature shall be 71° C.

4.9 Humidity test. The unit shall be tested in accordance with procedure I, method 507, of MIL-STD-810.

4.10 Low pressure test. The unit shall be tested in accordance with procedure I, method 500, of MIL-STD-810.

4.11 Salt fog test. The unit shall be tested in accordance with procedure I, method 509, of MIL-STD-810. Salt deposits shall be removed by rinsing with tap water.

4.12 Sand and dust test. The unit shall be tested in accordance with procedure I, method 510, of MIL-STD-810.

4.13 Interference test. The unit shall be tested for conducted interference and radiated interference in accordance with MIL-STD-826.

4.14 Test reports. The contractor shall prepare and submit to the procuring agency copies of all test reports not less than 10 days after completion of tests.

4.15 Approval. Approval of the first articles shall be by the contracting officer upon satisfactory completion of all tests.

4.16 Acceptance. With exception of the first articles, acceptance of all items shall be by the cognizant Government inspector.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing. Preservation, packaging and packing shall be level A or C in accordance with MIL-E-17555 as specified in the contract or order (see 6.2).

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

5.2 Marking. In addition to any special marking required by the contract or order, unit packages, intermediate packages, and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. This unit is to be employed with the Terminal, Telegraph-Telephone, TH-81/GCC, to provide power and switching of this unit and the associated rt sets under tactical conditions.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Quantity of first articles required (see 3.2 and 4.2.1.2(a)).
(c) Level of preservation, packaging, and packing (see 5.1).

6.3 Color. Color chips for Marine Corps green, No. 23, may be obtained from the Commandant of the Marine Corps (Code CSY-10), Headquarters, U. S. Marine Corps, Washington, D. C. 20380.

6.4 First article. The first articles shall be examined and tested for approval, at the contractor's plant or at an independent commercial testing laboratory acceptable to the procuring activity. First article tests shall be witnessed by a Government representative of the procuring activity. Approval of the first articles shall be by the contracting officer.

Preparing activity:
Navy - MC
Project No. 5805-N137

27143

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 APR 63 1426

REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

Commandant of the Marine Corps (CSY-10)
Headquarters, U. S. Marine Corps
Washington, D. C. 20380

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:56Z
Check the source to verify that this is the current version before use.