MIL-T-28916(MC)
AMENDMENT 1
30 July 1969

MILITARY SPECIFICATION

TERMINAL, TELEGRAPH-TELEPHONE: TH-81/GCC

This amendment forms a part of Military Specification MIL-T-28916(MC), dated 26 March 1969.

PAGE 5

3.4.8(f): Delete "22" and substitute "20".

PAGE 6

3.6.1.2: Delete and substitute:

"3.6.1.2 Delay distortion. The delay distortion in the frequency band between 600 and 3,200 Hz shall not exceed 175 microseconds (μs) and in the frequency band between 1,000 and 2,500 Hz shall not exceed 100 μs, for the temperature range of -25°C to +65°C. The delay distortion in the frequency band between 600 and 3,200 Hz shall not exceed 230 μs for the temperature range of -40°C to -25°C."

PAGE 7

3.6.1.5, line 1: Delete "2-wire"and substitute "4-wire".

PAGE 9

3.6.2.3: Add the following under the headings shown:

Input	Output
"-9.0 dBm	-16 dBm ±3 dBm"

Source: https://assist.dla.mil -- Downloaded: 20260-20T20:57Z
Check the source to verify that this is the current version before use.

PAGE 11

3.6.4.4: Delete column "Transmit level dBm" and substitute:

"Transmit level dBm

-6 to -8
-4 to -6
-2 to -4
0 to -2

-15 to -19
-15 to -19
-15 to -19
-15 to -19

-6 to -8
-16.5 to -17.5".

Preparing activity:
Navy - MC
Project No. 5805-N149

Source: https://assist.dla.mil -- Downloaded: 202610-20T20:57Z
Check the source to verify that this is the current version before use.