MILITARY SPECIFICATION

CUTTER, STRAP

This Amendment forms a part of Military Specification MIL-C-48774(PA), dated 30 May 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

Paragraph 2, APPLICABLE DOCUMENTS:
QQ-Z-325, Change title to "Zinc Coating, Electrodeposited, Requirements for".

Paragraph 3.1, Material:
Delete "applicable drawings and specifications" and substitute "dwg 9297887 and applicable specifications".

Paragraph 4.4.2: Delete in its entirety and substitute:
"4.4.2 Examination. - In place of the normal sampling associated with the Classification of Defects, a sample of at least five (5) parts shall be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of three (3) parts shall be selected from the last hour of each eight (8) hours of production for dimensional inspection as a control of the tool used during production. As a control of each tool during production, the above quantity of parts shall be inspected for at least the defects listed in paragraphs 4.4.2.1 and 4.4.2.2. If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be inspected for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request."

FSC: 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use

Paragraph 4.4.2.1:
Re-number the major B defects as follows:
"131, 132, 133, 134, 135, 136 and 137"
Major B defect 134: Delete "traverse" and substitute "transverse".

Paragraph 4.4.2.2:
Re-number the major B defects as follows:
"131, 132, 133 and 134"

Paragraph 4.4.3.2:
Change, as follows:
"4.4.3.2 Salt Spray (Fog) Test (see 3.2) - The strap cutters shall be sampled as specified in the applicable sampling paragraph of QQ-Z-325, using an AQL of 2.5 percent. The test shall be performed as specified in 4.5.2."

Custodian:
ARMY - PA

Preparing Activity:
ARMY - PA

Project Number 8140-A149

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.