MILITARY SPECIFICATION SHEET

CIRCUIT BREAKERS, MAGNETIC, LOW-POWER, SEALED, TRIP-FREE
ONE-POLE, AUXILIARY CONTACTS

This amendment forms a part of MIL-C-39019/2F, dated 26 June 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, change terminal (bottom) view to the following:



3 AUXILIARY CONTACT TERMINALS (SEE NOTE 7)

PAGE 2

FIGURE 1, delete circuit diagram and substitute the following:



CIRCUIT DIAGRAM
(MAIN CONTACTS OPEN)
(SEE NOTE 11)

In front view: Change "1 780 MAX" to "1.810 MAX" In right end view, add note "INSULATING BLOCK (SEE NOTE 12)" with arrow pointing to dashed line. Change terminal (bottom) view to the following:



138-32 X 250 (6 35) SCREW (NO 6 LOCKWASHER) SEE NOTE 12

3 AUXILIARY CONTACT TERMINALS SEE NOTE 7)

PAGE 3

NOTE 12, delete first two sentences and substitute:

"For configuration 2, add "S" at end of the dash number for screw terminals with insulating block (see table I). When circuit breakers are subjected to the resistance to solvents test, the insulating block shall be removed, and shall not be tested. Main terminal screw MS35265-26 or equivalent "

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:07Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL Delete and substitute as printed below.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI
Air Force - 99
NASA - NA
DLA - ES

User activities:
Army - AV, AT
Navy - AS, MC
Air Force - 19

Preparing activity:
Army - ER

Agent.
DLA - ES

(Project 5925-0224)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:07Z
Check the source to verify that this is the current version before use.