MILITARY SPECIFICATION SHEET

CIRCUIT BREAKERS, MAGNETIC, LOW-POWER, SEALED,
TRIP-FREE, TWO-POLE, AUXILIARY CONTACTS

This amendment forms a part of Military Specification MIL-C-39019/4E, dated 4 October 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, add the following:

Dash number		Current rating (amps)	Time delay	Resistance or impedance (ohms - max) 1/		
Standard delay	High inrush			DC	60 Hz	400 Hz
260	340	1.25	A	.9	1.0	1.1
261	341	1.25	B	.9	1.0	1.1
262	---	1.25	C	.9	1.0	1.1
263	342	1.5	A	.65	.70	.75
264	343	1.5	B	.65	.70	.75
265	---	1.5	C	.65	.70	.75

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI, SC
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AR, AV
Navy - AS, MC, SH
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5925-0149-4)

FSC 5925

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:08Z
Check the source to verify that this is the current version before use.