MILITARY SPECIFICATION SHEET

CIRCUIT BREAKERS, MAGNETIC, LOW-POWER, SEALED, TRIP-FREE
TWO-POLE, AUXILIARY CONTACTS

This amendment forms a part of MIL-C-39019/4F, dated 26 June 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1, VIEW A-A, change terminal screw from " 138 - 32 x 187 (4 75)" to ".138 - 32 x .250 (6 35)"

FIGURE 1, in right end view, add note "INSULATING BLOCK (SEE NOTE 15)" with arrow pointing to dashed line.

PAGE 3

NOTE 15, delete first two sentences and substitute.

"For configuration 2, add "S" at end of the dash number for screw terminals with insulating blocks (see table I). When circuit breakers are subjected to the resistance to solvents test, the insulating blocks shall be removed, and shall not be tested Main terminal screw MS35265-26 or equivalent "

PAGE 8

CONCLUDING MATERIAL. Delete and substitute as printed below.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Air Force - 99
NASA - NA
DLA - ES

User activities:
Army - AV, AT
Navy - AS, MC
Air Force - 19

Preparing activity.
Army - ER

Agent.
DLA - ES

(Project 5925-0226)

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:08Z
Check the source to verify that this is the current version before use.