INCH-POUND

MIL-C-39019/5F
AMENDMENT 1
24 March 1992

MILITARY SPECIFICATION SHEET

CIRCUIT BREAKERS, MAGNETIC, LOW-POWER, SEALED, TRIP-FREE
THREE-POLE

This amendment forms a part of MIL-C-39019/5F, dated 26 June 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1, VIEW A-A, change terminal screw from ".138 - 32 x 187 (4 75)" to " 138 - 32 x .250 (6.35)"

FIGURE 1, in right end view, add note "INSULATING BLOCK (SEE NOTE 14)" with arrow pointing to dashed line.

PAGE 3

NOTE 14, delete first two sentences and substitute:

"For configuration 2, add "S" at end of the dash number for screw terminals with insulating blocks (see table I) When circuit breakers are subjected to the resistance to solvents test, the insulating blocks shall be removed, and shall not be tested Main terminal screw MS35265-26 or equivalent."

PAGE 8

CONCLUDING MATERIAL Delete and substitute as printed below

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Air Force - 99
NASA - NA
DLA - ES

User activities
Army - AV, AT
Navy - AS, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5925-0227)

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:09Z
Check the source to verify that this is the current version before use.