MIL-M-81844C
19 September 1986
SUPERSEDING
MIL-M-81844B
22 November 1983

MILITARY SPECIFICATION

MITTENS, FLYER'S, ANTI-EXPOSURE, INFLATABLE, HAU-12/P

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1. Scope. This specification covers the requirements for one type and size of inflatable, anti-exposure, flyer's mittens designated as HAU-12/P.

2. APPLICABLE DOCUMENTS

2.1. Government documents.

2.1.1. Specifications, and standards The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip Thin Gauge Polyolefin
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing

MILITARY

MIL-C-5040	-	Cord, Nylon
MIL-E-20652	-	Eyelets, Metallic and Eyelet Washers, Metallic, General Specification for
MIL-C-83489	-	Cloth, Coated, Nylon, Polyurethane Coated

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Air Engineering Center, Systems Engineering and Standardizations Department, (SESD), (Code 93) Lakehurst, NJ, 08733-5100, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC-N/A FSC 8475

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:16Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A, Approved for public release: distribution is unlimited.

STANDARDS

FEDERAL

FED-STD-191	-	Textile Test Methods
FED-STD-595	-	Colors

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-130	-	Identification Marking of U.S. Military Property

2.1.2. Government drawings. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

NAVAL AIR SYSTEMS COMMAND

1640AS100 - Mitten Assembly, Flyer's, Anti-Exposure, Inflatable, HAU-12/P

1640AS101 - Mitten Patterns, Flyer's, Anti-Exposure, Inflatable, HAU-12/P

(Copies of specifications, standards, and government drawings, required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein,(except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable law and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1. First article. When specified in the contract or purchase order a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.2. Materials and components. The materials and components shall conform to the applicable specifications and standards as listed or required herein (see 6.2.1h). Unless otherwise specified in the contract, the materials and components, used in the construction of the HAU-12/P, inflatable, anti-exposure, flyer's mittens, shall have been manufactured not more than 12 months prior to the date of delivery of the HAU-12/P, inflatable, anti-exposure, flyer's mittens (see 6.2.1h).

3.2.1. Outer and inner shells. The outer and inner shells of the mittens shall be fabricated from the polyurethane coated nylon cloth conforming to MIL-C-83489, Type II. The color of the cloth shall match lusterless blue, number 35042, FED-STD-595.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

3.2.2. Oral valve. The heat sealable oral valve shall be as manufactured by the Halkey Roberts Corp., St. Petersburg, FL 33702-1098, Part Number 330-AC, or equivalent. When the top portion is extended, the air shall be able to enter and escape from the air chamber of the mitten through the valve into the atmosphere. The top portion, when depressed, shall seal off the flow of air through the valve and shall prevent entry of any kind of foreign matter.

3.2.3. Tie cord. The tie cord shall be fabricated from the nylon cord conforming to MIL-C-5040, Type IA, color optional. The cut length of the cord shall be 5 feet ± one inch. The cut ends of the cord shall be seared or treated to prevent raveling. No sharp edges shall be formed. The searing or treatment of the cut edges shall not damage the cord in any manner. One end shall be inserted through the mitten eyelet and securely knotted to prevent loss. The remainder of the tie cord shall be faked into four inch hanks. The hanks shall be held together at each end by the use of polychloroprene rubber bands.

3.2.4. Metal eyelet. One metal eyelet, in accordance with MIL-E-20652, part number M20652/1-BNE109, shall be installed in the center of a circular heat-sealed bond located as shown on Drawing 1640AS101. The metal eyelet shall accommodate the tie cord specified in 3.2.3.

3.3. Design. The mittens shall consist of an outer and inner shell, heat-sealed together to form an air chamber, an oral valve, for orally inflating the air chamber, and capability to seal off the flow of air into the atmosphere and to prevent entry of any foreign matter into the air chamber; and a tie cord. The mittens shall conform in appearance to Drawing 1640AS100.

3.4. Construction. The construction of the mittens shall be accomplished by the use of heat-sealed seams and bar bonded areas for flexibility and contour shaping of the mittens, when inflated. The heat-sealed seams shall be straight, continuous and parallel to the edge of the mittens. The coated side of the cloth shall be on the innerside of the mittens air chamber as specified in Drawing 1640AS100. The upperside of the base of the valve shall also be heat-sealed to the coated side of the outer shell. The mittens shall be constructed in accordance with Drawings 1640AS100 and 1640AS101.

3.4.1. Cutting. The outer and inner shells shall be cut in strict accordance with drawing 1640AS101 patterns furnished by the Government (see 6.4) which show location of the heat-sealed area, metal eyelet, and oral valve, and markings for proper assembly of the mittens. The Government patterns shall not be altered in any manner and shall be used for making the working patterns. The working patterns shall be identical to the Government furnished patterns.

3.4.2. Shade marking. The outer and inner shells shall be marked and ticketed by any commercial method or bundled with the top ply of each individual component part marked with the bundle number, to assure the proper assembly of the mittens. No metal fastening device or sewn-on ticket shall be used. The shade markings shall be accomplished by the use of an ink pad numbering machine, rubber stamp, or pencil, provided the markings do not show through to the outerside of the mittens and are not deleterious to the cloth.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

The markings which are placed on the seam allowance shall not be visible on the outerside. The adhesive type shade marking tickets may be used for the shade markings (see 3.4.2.1). The assembled mittens shall not contain any shade marking tickets.

3.4.2.1. Adhesive shade marking tickets. The adhesive shade marking tickets shall be fabricated from paper with a thermo-activated adhesive applied on one side. The adhesive shall not discolor or damage the cloth and the adhesive mass shall not adhere to the cloth, upon removal of the ticket. The heat used to attach the thermo-activated adhesive tickets shall not stiffen, harden, scorch, or damage the cloth in any manner.

3.5. Performance requirement.

3.5.1. Seam adhesion. The seam adhesion of all heat-sealed areas, regardless of their geometrical configuration (circular/straight), shall be 12 pounds or more.

3.5.2. Leakage. When inspected as specified in 4.6.3, the pressure in the mitten shall not drop below 1.5 inches (water column). The seams, bar-bonded areas and the base of the oral valve shall remain perfectly intact and shall show no indication of separation. There shall be no evidence of constructional or material failure in any respect. There shall be no evidence that the air entering the mitten air chamber is hindered or that the front or back of the oral valve is blocked by talc, zinc stearate or other foreign matter. There shall be no evidence of any loss of air from the mitten air chamber, when the top portion is depressed fully in the oral valve. When the top portion of the oral valve is fully extended, it shall permit the air to flow through the valve into the atmosphere. The flow of the air shall not be blocked or restricted by talc, zinc stearate or other foreign matter. The attachment of the base of the oral valve to the mitten shall remain perfectly intact.

3.6. Markings. The markings on the mittens shall be in accordance with MIL-STD-130 and Drawing 1640AS100. Ink, color, size and location of markings shall be as specified in Drawing 1640AS100. All markings shall be thoroughly dry prior to packaging and packing.

3.6.1. Serial Numbers. Each pair of mittens shall be identified by a serial number located as specified in 1640AS100. Markings shall be in accordance with 3.6. Serial numbers shall be assigned by the manufacturer and shall consist of a block of consecutive numbers to cover the entire acquisition quantity. One serial number shall be used for each pair of mittens.

3.7. Workmanship. The mittens shall be thoroughly cleaned and all loose fiber, lint and foreign matter shall be removed. The mittens shall not contain any spot, stain, nonspecified hole, abraded area, tear, cut, mend or patch. Because of the emergency and life support use of these mittens, the importance of providing a product of uniform excellent quality cannot be overemphasized. The mittens shall be uniform in quality and shall be free from irregularities or defects which could adversely affect performance, reliability, or durability. The mittens shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the acceptance criteria established herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1. Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2. Classification of inspections. The inspections specified herein are classified as follows:

a. First article inspection. First article inspection shall conists of examinations and tests performed on samples which are representative of the production item after the award of a contract to determine that the production item meets the requirements of this specification (see 4.3.).

b. Quality conformance inspection. Quality conformance inspection shall consists of examinations and tests performed on individual products or lots to determine conformance of the products or lots with the requirements set forth in this specification (see 4.4.).

4.3. First article inspection. The first article inspection of the KAU-12/P, inflatable, anti-exposure, flyer's mittens shall consist of examinations and tests for all of the requirements of this specification.

4.3.1. First article samples. Unless otherwise specified in the contract, as soon as practicable after the award of the contract or purchase order, the manufacturer shall submit three pairs of mittens. The samples shall be representative of the construction, workmanship, components, and materials to be used during production. When a contractor is in continuous production of these mittens from contract to contract, submission of further first article inspection samples on the new contract may be waived at the discretion of the acquiring activity (see 6.2.1f.). Approval of the first article inspection samples or the waiving of the first article inspection does not waive the requirements for performing the quality conformance inspection. The first article inspection samples shall be furnished to the Government as directed by the contracting officer (see 6.2.1g.).

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:16Z
Check the source to verify that this is the current version before use.

4.3.2. First article sample approval. Upon completion of the first article inspection program, the Government activity responsible for coordinating the inspection program (see 6.2.1g.) shall report the results of the inspection program, with appropriate recommendations, to the Contracting Officer. One pair of the approved first article inspection samples will be returned to the manufacturer for use in monitoring production. The other two pairs of the mittens will be destroyed in the first article inspection and shall not be considered as part of the quantity to be delivered under the contract or purchase order.

4.4. Quality conformance inspection. The sampling and inspection levels shall conform to MIL-STD-105. The quality conformance inspection shall consist of the following:

a. Visual examinations of the assembled mittens
b. Leakage
c. Packaging

4.4.1. Sampling.

4.4.1.1. Inspection lot.

4.4.1.1.1. Assembled mittens. An inspection lot size shall be expressed in units of one assembled mitten, but the lot shall consist of pairs of assembled mittens, made essentially under the same conditions and from the same materials and components. The sample unit shall be one assembled mitten.

4.4.1.1.2. Packaging. An inspection lot size shall be expressed in units of one fully prepared shipping container, containing pairs of mittens, fully prepared for delivery from essentially the same materials and components. The sample unit shall be one shipping container, containing pairs of mittens, fully prepared for delivery with the exception that it need not be sealed.

4.4.1.2. Sampling for tests and examinations of the mittens and packaging. The sample size, acceptance criteria, tests and examinations required for the mittens or the packaging, as applicable, shall be as specified in table I.

4.5. Inspection conditions.

4.5.1. Atmospheric conditions. Unless otherwise specified in the contract, all the inspections required by this specification shall be conducted at an atmospheric pressure of 28 to 32 inches of mercury and at a temperature of 77°± 18°F (25° ± 10°C). When the inspections are conducted at an atmospheric pressure or temperature different from the above values, proper correction shall be made for the change in instrument reading.

4.5.2. Inspection area and equipment. The area in which the mittens are inspected shall be adequately protected to preclude damage to the units. The area and inspection equipment shall be free of sharp or rough edges, burrs, protrusions, etc., which will cut, tear or damage the mittens or the components.

4.5.3. Air. When use of air is specified in an inspection, the air used shall not contain any oil or liquid water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

4.6. Inspection methods.

4.6.1. Seam adhesion. Three specimens, 1 ± 1/16 inch wide and 3 ± 1/16 inches long, shall be cut across and perpendicular to the seam of the outer shell of the mitten. Three additional specimens shall be similarly cut to determine the seam adhesion of the inner shell to the outer shell. Each set of the three specimens shall be marked for identification as to location. The specimens shall be cut from different locations so as to be representative of the sealing of the entire mitten. The specimens shall be taken from the straight portion of the mitten. One free end of one specimen (end not bonded) shall be placed in the upper jaw and the other free end in the lower jaw of a suitable inspection apparatus equipped with an autographic recording device (see FED-STD-191, Method 5100). The seam portion of the specimen shall be in the center between the two jaws. The jaws shall be separated until failure occurs, either breaking of the cloth or separation of the bond. In either case, the result obtained shall be not less than that specified in 3.5.1. The highest value obtained shall be taken as the result, for the seam adhesion, for the individual inspected specimen. The rate of jaw separation, under no load, shall be 12 ± 1/2 inches per minute. The front clamp of each jaw shall be 1 by 3 inches. The remaining two specimens shall be similarly treated and inspected. The results of the three inspected specimens shall not be averaged. Each individual specimen shall conform to the seam adhesion requirement specified in 3.5.1.

4.6.2. Visual examination.

4.6.2.1. Mittens. Every mitten shall be examined visually for major defects to determine conformance to this specification. Each mitten, selected as a sample unit from the lot, shall be examined visually for minor defects to determine conformance to this specification. The classification of defects, table II, shall be used to classify the defects found.

4.6.2.2. Packaging. Each of the fully prepared shipping containers, containing pairs of mittens, selected as a sample unit from the lot, shall be visually examined to determine that the packaging, packing and marking conform to this specification. The list of defects, table III, shall be used to enumerate the defects found.

4.6.3. Leakage. After not less than 24 hours has elapsed from the heat sealing of the seams, bar areas and the oral valve, the mitten shall be inflated with air (see 4.5.3.) to a pressure of 2 inches (water column). The air supply shall be completely shut off and after not less than 5 minutes, the pressure in the mitten air chamber shall be checked and adjusted, if necessary, to the original pressure of 2 inches (water column). At the end of not less than 5 minutes after the readjustment period, the pressure in the mitten air chamber shall be measured (see 3.5.2.). While inflated, the mitten shall be examined for material and construction failure and separation of the seams, bar bonded areas and the attachment of the base of the oral valve to the mitten air chamber (see 3.5.2.). The air introduced into the mitten through the oral valve shall be observed to determine whether the flow of the air through the oral valve is restricted or blocked by talc, zinc stearate or other foreign matter (see 3.5.2.). Upon completion of the testing and examination, the method of introducing the air through the oral valve shall be removed from the oral valve and the top portion fully depressed.

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:16Z
Check the source to verify that this is the current version before use.

The valve shall be observed for leakage (see 3.5.2.). Upon completion of the examination for leakage, the top portion shall be fully extended, and the flow of the air through the oral valve into the atmosphere shall be observed (see 3.5.2.). Upon completion of the examination for the release of the air from the mitten air chamber, the attachment of the base of the valve to the mitten shall be examined (see 3.5.2.). Upon completion of the valve-base attachment examination, the mitten air chamber shall be completely deflated.

5. PACKAGING

5.1. Preservation. Preservation shall be Level A (see 6.2.11.).

5.1.1. Level A. The air chamber of each mitten shall be completely evacuated of air and the top portion of the oral valve shall be fully depressed. The mittens shall be paired, one right hand with one left hand. Each set of paired mittens, palm side to palm side, shall be placed into a separate snug fitting clear bag constructed of polyolefin material conforming to Federal Specification L-P-378, Type I, Class 4, Grade B, Finish 2, Thickness 0.00125 ± 25 percent inch gage film. A label conforming to 5.3.1. shall be inserted into each bag, or the markings specified in 5.3.1. shall be printed directly on the bag. The heat-sealed seams shall be straight, continuous and parallel to each other and the edges of the bag. The seam for closing and sealing the bag shall be as close as possible to the edge. No mitten shall be deformed or distorted in the bagged condition. Also, there shall be no damage to the polyolefin bag. No part of the mitten shall be caught in any heat-sealed seam. One corner of each bag shall contain a hole, 1/4 inch in diameter, to allow excess air to escape. Six pairs of bagged mittens, with every other pair reversed, shall be packaged within a snug fitting commercial type, folding or set up box. The boxes shall be sealed with kraft paper tape. Full telescopic boxes, if used, need not be sealed.

5.2. Packing. Packing shall be Level A, B or Industrial, as specified (see 6.2.11.).

5.2.1. Level A. Sixteen boxes, 96 pairs of mittens, packaged as specified in 5.1, shall be packed as specified in 5.2.2, except that the fiberboard container shall be Weather-Resistant Class, Grade V3c or V3s. Each container shall be constructed, closed and reinforced with flat steel strapping or tape banding in accordance with the appendix to PPP-B-636.

5.2.2. Level B. Sixteen boxes, 96 pairs of mittens, packaged as specified in 5.1., shall be packed within a snug fitting, fiberboard container, conforming to PPP-B-636, Type CF or SF, Domestic Class, Variety SW, Grade 200. All seams, corners, and manufacturer's joints of the container shall be sealed with tape not less than 3 inches wide conforming to PPP-T-45, Type III, Class 2; Grade A, B or C. Each container shall be constructed and closed in accordance with the appendix to PPP-B-636.

5.2.3. Industrial. The packaged mittens, which require packing for acceptance by the carrier, shall be packed within exterior type shipping containers in a manner that shall insure safe transportation, at the lowest rate, to the point of delivery. The containers shall conform to the minimum requirements of the rules and regulations applicable to the mode of transportation selected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

5.3. Marking. In addition to any special marking required by the contract or purchase order (see 6.2.1j.), the interior and exterior fiberboard containers shall be marked in accordance with MIL-STD-129 and shall include the date of manufacture (month and year).

5.3.1. Label. A white paper label, with legible and durable black letters and numerals, shall be placed inside each polyolefin bag. The label shall be placed so that the information on the label shall be capable of being read through the bag. If desired, instead of a white paper label, the markings may be imprinted directly onto the outerside of the bag. The paper label or polyolefin bag, as applicable, shall contain the following information:

a. Government Part Number
b. National Stock Number
c. Nomenclature
d. Quantity
e. Date of Manufacture (month and year)

6. NOTES

6.1. Intended use. The HAU-12/P inflatable, anti-exposure, flyer's mittens covered by this specification are intended to be used to protect the hands of the wearer from exposure to cold water, wind and spray as a result of emergency ditching of an aircraft at sea. The mittens are intended to be used with anti-exposure coveralls.

6.2. Ordering data.

6.2.1. Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification including any amendments.

b. Applicable Government drawings, inluding revisions.

c. Government Part Number.

d. National Stock Number.

e. Quantity Desired.

f. Whether first article inspection is waived (see 4.3.1.)

g. Name and address of the first article inspection laboratory (see 4.3.1.) and the name and address of the Government activity responsible for coordinating the first article inspection program (see 4.3.2.).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

h. Certificate of compliance to be provided by the contractor for:

1. Materials and components conforming to applicable specifications and standards (see 3.2.)

2. The age of materials (see 3.2 and 6.2.2.)

i. Preservation requirements (see 5.1) and applicable level of packing (see 5.2)

j. Whether any special markings are required (see 5.3.)

6.2.2. Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

Paragraph no	Data requirement no.	Applicable DID no.	Options
(a) 3.2	Certificate of compliance for the age of materials and components.	DI-E-2121	-------
(b) 4.3.2	First article inspection reports	DI-T-5329	-------

(Copies of data item descriptions required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3. First article. When a first article inspection is required, the items should be a first article sample. The first article should consist of three units. The contracting officer should include specific instrunctions in acquisition documents reguarding arrangements for examinations, approval of first article test results and disposition of first article. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4. Patterns. The patterns for the mittens will be furnished by the contracting officer to the contractor for use in cutting working patterns (see 3.4.1.).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

6.5 Subject term (keyword) listing.
Oral valve
Tie cord
Anti-exposure

6.6. Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians

Navy - AS
Army - GL

Preparing activity:

Navy - AS

(Project 8475-0201)

Review activities:
Army - AV

Source: https://assist.dla.mil - Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

TABLE I. Sample size, acceptance criteria, tests and examinations of the mittens and packaging.

Inspection	Paragraph Requirement	Paragraph Method	Sample Size	Acceptance Criteria
Visual Examination	3.3 through 3.4.2.1, 3.6, 3.7 and Drawing 1640AS100	4.6.2.1 and Table II	a.Every mitten for major defects. b. Inspection Level II 2/ for minor	a.Reject all units with any major defect. b.An Acceptable Quality Level of 6.5 defects per 100 units for minor defects.
Leakage 1/	3.5.2	4.6.3	Every mitten	Reject all defective units
Packaging	Section 5	4.6.2.2 and Table III	Inspection Level S-2, 2/	An Acceptable Quality Level of 2.5 defects per 100 units.

1/ The results of the leakage inspection shall be identifiable by the assigned serial numbers. (see 3.6.1)

2/ The sample size shall be based only on the applicable sample size code letter corresponding to the specified inspection level of MIL-STD-105.

Source: https://assist.dla.mil Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for the visual examination of the mittens.

Defect	Major	Minor
GENERAL		
a. Any non-specified hole (including pin hole), scissors or knife cut, tear, burn, mend, patch, or weakening defect such as smash, multiple float, loose slub or abraded area.	X	
b. Any portion of the cloth stiffened or hardened by any process of manufacturing	X	
c. Color of any component not as specified, not uniform, any part shaded or any shade bar		X
d. Coated side of the cloth on the outerside of the mitten or any pair of mittens tacked together	X	
e. Any spot or stain, any shade ticket not removed, excluding the metal fastening device or sewn-on kind, or any shade identification stamping visible on the outerside of the mitten		X
f. Any metal fastening device or sewn-on shade marking ticket attached to the mitten	X	
g. Any portion of any heat-sealed seam or bar bonded area open	X	
h. Any heat-sealed seam not straight, continuous or parallel to the edge of any mitten or the seam edge, as applicable	1/	
i. Any trapped air, wrinkle or crease in the area of the oral valve		X
j. Base of any oral valve heat sealed to the cloth side of the outershell cloth	X	
k. Any oral valve not located on the back of any mitten	X	
l. Any tie cord not faked into four inch hanks or not held together as specified		X
METAL EYELETS		
a. Missing or improperly located	X	
b. Not as specified	X	
c. Not securely clinched in material	X	
d. Contains sharp edges, cracks or protrusions	X	
e. Inner or outer diameter out of round by more than 1/16 inch		X

Source: https://assist.dla.mil -- Downloaded: 202610-23T06:16Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects for the visual examination of the mittens. - Continued

Defect	Major	Minor
COMPONENTS AND ASSEMBLY		
a. Any component not as specified or any defect of a component or defect of assembly not herein classified	1/	
b. Any component, component part, or required operation omitted, or any operation improperly performed not herein classified	1/	
c. Any components part not cut in accordance with the patterns	1/	
MARKINGS		
a. Missing, incomplete, incorrect, illegible, not specified size, or improperly located		X

1/ The defect shall be classified as major, when it seriously affects the appearance or serviceability, otherwise it shall be classified as a minor defect.

TABLE III. List of defects for packaging.

Item	Defect
Exterior and interior markings	Missing, incorrect, incomplete, illegible; of improper size, location, sequence or method of application; markings not the same on the interior and exterior containers; information on the label in the polyolefin bag not readable through the film, no label in the polyolefin bag, or no markings on the polyolefin bag, as applicable.
Materials	Any non-conforming component; any component missing, damaged or otherwise defective.
Workmanship	Inadequate application of the components, such as incomplete closure of any container flap, film bag seam, or loose strapping; bulging or distortion of any container; any portion of any mitten distorted or caught in any heat sealed seam; any polyolefin bag damaged or any open or non-continuous heat sealed seam.
Content	Number per container is more or less than required; gross or net weight exceeds the requirements; any mittens not paired; any mitten air chamber not completely evacuated of air; any top portion not fully inserted into the oral valve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-81344C	MITTENS, FLYER'S, ANTI-EXPOSURE, INFLATABLE, HAU-12/P

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:16Z
Check the source to verify that this is the current version before use.