MILITARY SPECIFICATION

PROJECTILE, HEP-T, 106MM, M346A1
METAL PARTS

1. SCOPE

1.1 This specification is the applicable detail specification for Projectile, HEP-T, 106MM, M346A1 Metal Parts.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extend specified herein.

SPECIFICATION
Military
MIL-A-2550 - Ammunition and Special Weapons, General Specification For
MIL-P-10025 - Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition Components, General Specification For

STANDARDS
Federal
Federal Test Method Standard No. 151 - Metals; Test Method

Military
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-639 - Surface Roughness Values Preferred for Army Ordnance Materiel
MIL-STD-1167 - Ammunition Data Cards
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

DRAWINGS
Munitions Command

F8596145	- Projectile, HEP-T, 106MM, M346A1, Metal Parts
F7548604	- Pallet, for Fixed and Semifixed Projectile Assembly
IEL-8596145	- Inspection Equipment List for Projectile, HEP-T, 106MM, M346A1, Metal Parts

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings, referenced specifications, and the following:

3.2 First article sample.- Requirements for the submission of first article sample by the contractor shall be as specified in the contract.

3.3 Heat treatment or stress relief.- Heat treatment or stress relief applied shall be uniform throughout each lot of components, and shall be conducted as to produce in any component the minimum mechanical properties specified. No forming of metal involving plastic flow is permitted without subsequent stress relief.

3.4 Mechanical properties.- The mechanical properties shall conform to the requirements as stated in the applicable specification and on the applicable component drawing.

3.5 Rotating band.

3.5.1 Band Seat.- Prior to application of the welded overlay rotating band, the band seat shall be clean and free of oil, grease, dirt, rust, and other foreign matter.

3.5.2 Rotating band application.- Rotating band shall be overlay welded in accordance with the applicable drawing and specification.

3.6 Protective coatings.- Protective coating shall be in accordance with the applicable drawing and specifications referenced thereon.

3.7 Functional.

3.7.1 Metal parts security.- Testing for metal parts security under all service conditions of pressure and temperature shall be mandatory. There shall be no breakup of the rotating band in flight, nor shall there be evidence of failure of components or excessive deformation due to firing stresses.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:41Z
Check the source to verify that this is the currentversion before use.

3.7.2 Velocity-accuracy.- Testing for velocity-accuracy shall be for information only.

3.8 Workmanship.- The requirements for workmanship are as shown on the applicable drawings, referenced specifications and the following:

3.8.1 Metal defects, steel.- All components shall be free from cracks, splits, seams, cold shuts, inclusions, porosity and any similar defect.

3.8.2 Metal defects, nonferrous.- Soundness of material shall be as required by the applicable specifications.

3.8.3 Surface finish.- Surface finish of all components shall be in accordance with the applicable drawings.

3.8.4 Threads.- Threads shall be full and undamaged for the entire minimum length or depth as specified on the applicable component drawing, and shall be in accordance with the provisions of MIL-A-2550.

3.8.5 Burr.- No component shall have a burr which might interfere with the assembly or function of the projectile or which might be injurious to personnel handling the item.

3.8.6 Foreign matter.- All parts and assemblies shall be free of chips, dirt, grease, oil, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550, except as specified herein.

4.2 First article sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of twenty-nine assemblies as follows:

22 Metal parts assemblies complete (painted)
2 Metal parts assemblies complete (unpainted)
5 Sets of component parts, unassembled

Twenty of the above metal parts assemblies (painted) shall be forwarded to a designated Proving Ground for ballistic testing. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection Provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The contractor shall submit the product in accordance with MIL-STD-105 or MIL-STD-1235, as applicable.

4.3.1.2 Heat treated or stress relief lots.- Heat treated or stress relieved lots shall contain bodies from not more than one heat of steel that has been heat treated or stress relieved in the same furnace, at the same temperature and for the same length of time. After heat treatment or stress relief, samples shall be selected and subjected to the hardness test hereinafter prescribed.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plans contained in MIL-STD-105 or MIL-STD-1235, as applicable. An AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect shall be used. All nonconforming material shall be rejected. The Ordnance Standard Finish Blocks prescribed by MIL-STD-639 shall be used as a basis of comparison for surface roughness determination.

4.3.2.1 Plug base, Drawing C8596148, covering a detail of Drawing F8596145

Defect	Method of Inspection
CRITICAL	
None defined	

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect		Method of Inspection
MAJOR		
101.	Concentricity of pitch diameter of body thread with pitch diameter of fuze thread, including perpendicularity with body seat and fuze seat.	Gage
102.	Caulking groove functionally concentric with pitch diameter of fuze thread	Gage
103.	Fuze seat counterbore functionally concentric with pitch diameter of fuze thread	Gage
104.	Perpendicularity of body seat with pitch diameter of body thread	Gage
105.	Pitch diameter of body thread, min.	Gage
106.	Major diameter of body thread, min.	Gage
107.	Pitch diameter of fuze thread, max.	Gage
108.	Minor diameter of fuze thread, max.	Gage
109.	Diameter of caulking groove (at rear)	Gage
110.	Angle of caulking groove wall	Gage
111.	Metal defective	Visual
MINOR		
201.	Pitch diameter of body thread, max.	Gage
202.	Pitch diameter of fuze thread, min.	Gage
203.	Diameter of body thread chamfer, min.	Gage
204.	Diameter of fuze thread chamfer, max.	Gage
205.	Diameter of gasket boss	Gage
206.	Diameter of fuze seat counterbore	Gage
207.	Diameter of flange	Gage
208.	Diameter of flat between body thread and gasket boss	Gage
209.	Depth to bottom of fuze seat	Gage
210.	Depth to bottom of caulking groove	Gage
211.	Length, total	Gage
212.	Thickness of flange	Gage
213.	Width of gasket boss	Gage
214.	Width from end of body thread to start of gasket boss	Gage
215.	Width of flat between body thread and gasket boss, min.	Gage
216.	Width of flat at rear of caulking groove, max. (if applicable)	Gage
217.	Prescence and location of wrench holes	Visual (See 6.2)
218.	Radii or chamfers missing or incorrect	Visual (See 6.2)
219.	Surface finish, improper	Visual (See 6.2)
220.	Protective coating inadequate or damaged	Visual (See 6.2)
221.	Burr	Visual
222.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.2 Gasket, Drawing B8596149, covering a detail of Drawing F8596145

Defect		Method of Inspection
CRITICAL		
None defined		
MAJOR		
101.	Hardness	Approved method
MINOR		
201.	Diameter, inside	Gage
202.	Diameter, outside	Gage
203.	Thickness	Gage

4.3.2.3 Body, Drawing F8596146, covering a detail of Drawing F8596145

CRITICAL		
None defined		
MAJOR		
101.	Location of index button hole	Gage
102.	Wall thickness at index button hole, min.	Gage
103.	Metal defective	Visual
MINOR		
201.	Radii or chamfers, missing or incorrect	Visual (See 6.2)
202.	Surface finish improper	Visual (See 6.2)
203.	Burr	Visual
204.	Foreign matter	Visual

4.3.2.4 Metal Parts Assembly, Drawing F8596145 (before paint)

CRITICAL		
None defined		
MAJOR		
101.	Concentricity exterior of nose with bourrelet	Gage
102.	Concentricity interior of nose with bourrelet	Gage
103.	Concentricity of body with bourrelet	Gage
104.	Concentricity of pitch diameter of threads with bourrelet, including perpendicularity with rear face	Gage
105.	Rotating band lands functionally concentric with bourrelet	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.4 MAJOR (Cont'd)

	Defect	Method of Inspection
106.	Rotating band groove functionally concentric with rotating band lands	Gage
107.	Alignment of index button(s) with rotating band lands	Gage
108.	Diameter of bourrelet, min.	Gage
109.	Diameter of rotating band lands	Gage
110.	Diameter of rotating band grooves	Gage
111.	Diameter from rear face to first inside basic length	Gage
112.	Diameter from rear face to second inside basic length	Gage
113.	Diameter from rear face to third inside basic length	Gage
114.	Diameter from rear of face to fourth inside basic length	Gage
115.	Height of index button	Gage
116.	Length from nose to first outside basic diameter	Gage
117.	Length from nose to second outside basic diameter	Gage
118.	Length of rotating band	Gage
119.	Length, total	Gage
120.	Location of rotating band from rear face	Gage
121.	Location of bourrelet from front of rotating band, max.	Gage
122.	Location of crimp groove rib	Gage
123.	Wall thickness, min. (indicated area)	Gage
124.	Wall thickness at nose	Gage
125.	Width of rotating band lands	Gage
126.	Width of crimp relief groove	Gage
127.	Width of crimp groove rib	Gage
128.	Width of groove forward of rib	Gage
129.	Radius rear of crimp relief groove	Gage
130.	Metal defective	Visual
MINOR		
201.	Diameter of crimp relief groove	Gage
202.	Diameter of body front and rear of rotating band	Gage
203.	Diameter forward of thread	Gage
204.	Diameter of chamfer at rear of thread	Gage
205.	Length from rear of rotating band to rear of angle	Gage
206.	Depth of undercut front and rear of rotating band (if applicable)	Visual (See 6.2)
207.	Width of undercut front and rear of rotating band (if applicable)	Visual (See 6.2)
208.	Radii or chamfers missing or incorrect	Visual (See 6.2)
209.	Surface finish, improper	Visual (See 6.2)
210.	Burr	Visual
211.	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.5 Metal parts assembly, Drawing F8596145 (after paint)

Defect	Method of Inspection
CRITICAL	
1. Hydrostatic stamp missing (signifying failure to comply with requirements)	Visual
2. Air pressure stamp missing (signifying failure to comply with requirements)	Visual
MAJOR	
101. Weight	Approved scale
102. Pitch diameter of thread, max.	Gage
103. Minor diameter of thread, max.	Gage
104. Diameter of bourrelet, max.	Gage
105. Length of effective thread, min.	Gage
106. Paint in cavity, inadequate or excessive	Visual
107. Improper assembly	Visual and Manual
MINOR	
201. Pitch diameter of thread, min.	Gage
202. Length of thread, max.	Gage
203. Rotating band damaged	Visual
204. Paint on rotating band bearing surfaces and rear face	Visual
205. Paint on threads	Visual
206. Paint inadequate or damaged	Visual
207. Paint not dry	Visual and Tactile
208. Marking missing, incorrect or illegible	Visual
209. Burr	Visual
210. Foreign matter	Visual

4.3.2.6 Carton, packing - prior to sealing.

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Improper assembly	Visual
202. Incorrect number in carton	Visual
203. Separator, missing or damaged	Visual

4.3.2.7 Carton, Packing - After Sealing

CRITICAL

None defined

MAJOR

None defined

MINOR	
201. Carton, damaged, cut or gouged through all layers	Visual
202. Carton, improperly sealed	Visual
203. Contents loose	Visual/Manual
204. Marking, missing, incorrect or illegible	Visual

4.3.2.8 Pallet, Drawing F7548604

CRITICAL

None defined

MAJOR

None defined

MINOR	
201. Strapping missing, loose or broken	Manual/Visual
202. Pallet damaged	Visual
203. Improperly packed	Visual
204. Marking, missing, incorrect or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4.

4.3.3.1 Mechanical properties.

4.3.3.1.1 Hardness.- One projectile body from each heat treatment or stress relieved lot as defined in 4.3.1.2 shall be selected from each 8-hour production or fraction thereof, of the final heat treatment furnace and subjected to this test. Failure of an average of the hardness values in any zone to comply with the requirements of the applicable drawing shall be cause for rejection of the production represented by the sample.

4.3.3.1.2 Base plug.- The sample size and acceptance criteria for the base plug material shall be as specified in the applicable material specification, except that the mechanical property requirements of the drawing shall apply.

4.3.3.2 Hydrostatic test.- After cleaning, but prior to surface treating and painting, each metal parts assembly shall be subjected to a hydrostatic pressure to determine compliance with the requirements of the applicable drawing. Failure of any assembly to comply shall be cause for rejection. Assemblies which comply shall be stamped with the letter "H" as indicated on the assembly drawing.

4.3.3.3 Air pressure.- Each body assembly that has passed the hydrostatic pressure test, as indicated by the letter "H" stamped on the body, shall after completion of the drying cycle be subjected to a submerged air pressure test. Failure of any body assembly to comply with the requirements of the applicable drawing, as evidenced by air bubbles in the vicinity of the nose or rising to the surface of the water shall be rejected. Assemblies which comply shall be stamped with the letter "A" as indicated on the assembly drawing.

4.3.3.4 Cleaning and application of protective coating.- The sample size and acceptance criteria for the inspection of cleaning the item and the application of protective coating shall be as specified in the applicable specification. Failure to comply with the requirements shall be cause for taking the corrective action recommended therein.

4.3.4 Functional.- The following functional (Proving Ground) tests will be performed by the Government.

4.3.4.1 First article sample.

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.4.1.1 Initial production sample.- The quantities listed in Table I shall be ballistically tested in the phases indicated.

TABLE I

Phase	Quantity
Security	10
Velocity-Accuracy	10

4.3.4.2 Production lot sample.- The quantities listed in Table II shall be ballistically tested in phases indicated.

TABLE II

Phase	Quantity
Security	10
Velocity-Accuracy	5 (See 6.1)

Failure of any round fired for security to comply with 3.7.1 shall be cause for rejection of the lot. Velocity-Accuracy data will be recorded for information only (See 6.1).

4.3.5 Inspection equipment.- Index of Inspection Equipment Lists IEL-8596145 identifies the inspection equipment required to perform the examination and tests prescribed herein. Equipment design shall be in accordance with the code designation on the applicable IEL (Reference is made to Inspection Equipment List for definition of coding format).

4.4 Test methods and procedures.

4.4.1 Mechanical properties.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.4.1.1 Hardness.- From the sample supplied in accordance with 4.3.3.1.1, 2 full-length specimens, 1-inch wide shall be removed from the body, parallel to the longitudinal axis, 180 degrees apart. Five hardness readings shall be taken on each specimen in each zone at midpoint of cross-section as indicated by the applicable drawing. A total of 10 readings for each zone (5 on each side). Hardness values for each zone shall be averaged to determine compliance with the hardness requirements as specified on the applicable drawing. The test shall be performed utilizing the equipment and procedures prescribed by Federal Test Method Standard No. 151.

4.4.2 Base plug.- Procedures for performing the mechanical properties tests on the aluminum bar material shall be in accordance with the criteria prescribed by Federal Test Method Standard No. 151.

4.4.3 Hydrostatic test.- The body assembly shall be hydrostatically tested using equipment capable of performing the test accurately and consistently. In performing the test the hydrostatic pressure will be applied gradually until the required minimum internal pressure is reached, after which the pressure will be held for a minimum of 30 seconds. The equipment shall be calibrated prior to the start of each day's operation and at intervals of not over 4 hours continuous operation, it shall also be calibrated prior to re-starting the operation after a layoff of 2 hours or more.

4.4.4 Air pressure test.- The body assembly shall be subjected to this test using equipment capable of performing this test accurately and consistently. The body assemblies shall be mounted in an approved test fixture in such manner that the assembly will be completely submerged in water such that the nose area may be directly observed for leakage. The air pressure shall then be applied and held for a minimum of 15 seconds, and shall be observed for the entire time the assembly is required to be pressurized. The equipment shall be calibrated prior to the start of each day's operation and at intervals of not over 4 hours continuous operation. It shall also be calibrated prior to re-starting the operation after a layoff of 2 hours or more.

4.4.5 Protective coating.- The procedures for testing the cleaning and surface treatment methods for the components and assemblies shall be in accordance with the methods and criteria for testing as specified in the applicable specification. The salt spray prescribed shall be performed in compliance with Federal Test Method Standard No. 151. A 20 percent sodium chloride solution shall be used.

4.4.6 Functional.

4.4.6.1 Metal parts security.- The samples selected in accordance with 4.3.4.1 or 4.3.4.2 inert loaded and assembled into complete cartridges will be fired in a gun for which the round is standard. The propellant charge will be adjusted to produce 112 percent rated maximum pressure of cartridge in a new gun. An attempt will be made to recover all projectiles fired. Each recovered projectile will be examined for deformation of the projectile body occurring in the gun tube, rotating band damage, or damaged base plug assembly due to firing stresses or leakage of propellant gases around the base plug threads. Results of the examination will be recorded and forwarded to the cognizant engineering agency.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:41Z
Check the source to verify that this is the current version before use.

4.4.6.2 Velocity-Accuracy.- The metal parts assemblies selected in accordance with 4.3.4.1 or 4.3.4.2 inert loaded and assembled into complete cartridges will be fired at service pressure in a gun for which the round is standard. All rounds will be fired to impact on a vertical target placed approximately 2000 meters from the muzzle of the gun. Test rounds will be fired alternately with a similar group of reference rounds for comparison of velocity and accuracy. Accuracy in terms of probable error (PE) in Mils on all rounds fired will be recorded for information only and forwarded to the cognizant engineering agency. Target plots for all rounds fired shall be included as part of the permanent firing record.

5. PREPARATION FOR DELIVERY

5.1 Preservation and Packing.

5.2 Packing.

5.2.1 Level C - Minimum military pack.- The metal parts for projectile, HEP-T, 106MM, M346A1 shall be packed as follows:

5.2.1.1 Metal parts assembly, Part No. 8596145 shall be packed in accordance with Drawing F7548604.

5.2.1.2 Base plug, Part No. 8596148 shall be packed in accordance with MIL-P-10025. Pack 60 base plugs in a 3 x 4 arrangement in 5 layers one to a case using interlocking separators.

5.2.1.3 Gasket, Part No. 8596149 shall be packed in accordance with MIL-P-10025. Pack 1000 gaskets in a 4 x 5 arrangement in 2 layers 25 to a case using interlocking separators.

5.2.1.4 Percentage of Extra Parts-Packing.- Packing for the required percentage of extra parts shall be provided for by furnishing the proper number of containers.

5.2.1.5 Shipping.- When components from more than one lot are shipped as a carload, each lot must be kept separate and the division between lots clearly indicated.

5.2.1.6 Marking.- The pallets shall be marked in accordance with Drawing F7548604. Cartons shall be marked in accordance with MIL-STD-129.

5.2.1.7 Data cards.- Data card information shall be as specified in MIL-STD-1167, Ammunition data cards.

6. NOTES

6.1 Velocity-Accuracy.- Proving Ground tests for velocity-accuracy are not acceptance tests, but the results will be carefully analyzed by the Munitions Command to determine quality of ammunition produced. Evidence of excessive variation in any phase of the Proving Ground test will result in immediate investigation by the Munitions Command.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

6.2 Visual examination qualification.- When compliance with the applicable requirements is in doubt as a result of visual examination, this characteristic may be measured or gaged to determine acceptability.

6.3 Ordering data.- Procurement documents should specify the following:

(a) Title, number, and date of this specification.

Custodian:

Army-MU

Preparing activity:

Army-MU

Project No. 1315-A500

Source: https://assist.dla.mil -- Downloaded: 202640-23T00:41Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE	
CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 61 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.