NOTICE OF
CHANGE

MIL-STD-35-110A(MI)
NOTICE 2
18 SEPTEMBER 1992

MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

BANDS, DECALS, MARKERS AND PLATES

TO ALL HOLDERS OF MIL-STD-35-110A(MI):

1. THE FOLLOWING PAGES OF MIL-STD-35-110A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
v	18 SEPTEMBER 1992	v	27 SEPTEMBER 1985
1	27 SEPTEMBER 1985	(Reprinted without change)	
2	18 SEPTEMBER 1992	2	27 SEPTEMBER 1985
3	18 SEPTEMBER 1992	3	27 SEPTEMBER 1985
4	18 SEPTEMBER 1992	4	27 SEPTEMBER 1985
5	18 SEPTEMBER 1992	5	27 SEPTEMBER 1985
6	18 SEPTEMBER 1992	6	27 SEPTEMBER 1985
35	27 SEPTEMBER 1985	(Reprinted without change)	
36	18 SEPTEMBER 1992	36	27 SEPTEMBER 1985
37	18 SEPTEMBER 1992	37	27 SEPTEMBER 1985
38	27 SEPTEMBER 1985	(Reprinted without change)	
41	27 SEPTEMBER 1985	(Reprinted without change)	
42	18 SEPTEMBER 1992	42	27 SEPTEMBER 1985
43	18 SEPTEMBER 1992	43	27 SEPTEMBER 1985
44	18 SEPTEMBER 1992	44	27 SEPTEMBER 1985
45	18 SEPTEMBER 1992	45	27 SEPTEMBER 1985
46	27 SEPTEMBER 1985	(Reprinted without change)	
55	27 SEPTEMBER 1985	(Reprinted without change)	
56	18 SEPTEMBER 1992	56	27 SEPTEMBER 1985
57	18 SEPTEMBER 1992	57	27 SEPTEMBER 1985
58	27 SEPTEMBER 1985	(Reprinted without change)	
63	18 SEPTEMBER 1992	63	27 SEPTEMBER 1985
64	18 SEPTEMBER 1992	64	27 SEPTEMBER 1985
65	18 SEPTEMBER 1992	65	27 SEPTEMBER 1985
66	27 SEPTEMBER 1985	(Reprinted without change)	
75	27 SEPTEMBER 1985	(Reprinted without change)	
76	18 SEPTEMBER 1992	76	27 SEPTEMBER 1985
77	18 SEPTEMBER 1992	77	27 SEPTEMBER 1985
78	27 SEPTEMBER 1985	(Reprinted without change)	

AMSC N/A AREA EGDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:02Z
Check the source to verify that this is the current version before use.

2. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

3. Holders of MIL-STD-35-110A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or canceled.

Custodians:
Army-MI

Review activities:
Army-AT, AV, CR, ER
ME, MR, SC

User activity
Army - AR

Preparing activity:
Army - MI

(Project EGDS-A449)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

CONTENTS

			Page
Paragraph	1.	SCOPE	1
	1.1	General	1
	1.2	Purpose	1
	1.3	Utilization	1
	1.4	Military Specification Exception Title Index	1
	2.	APPLICABLE DOCUMENTS	5
	2.1	Government documents	5
	2.2	Non-Government publications	6
	3.	DEFINITIONS	8
	4.	GENERAL REQUIREMENTS	9
	4.1	Introduction	9
	4.2	Specification Requirement Sheet (SRS)	9
	4.3	Configuration	9
	4.3.1	Dimensions	9
	4.3.2	Illustrations	9
	4.4	Units of measure	9
	5	DETAILED REQUIREMENTS	10
	5.1	Introduction	10
	5.2	MSE Formats	10
	5.3	Referenced documents	10
	5.4	Tabulation	10
	5.5	Keyword Code Index (KCI) and Standard Paragraphs	13
	5.5.1	Interrelationship of Codes	13
	5.5.2	Automatic MSE Data	13
	5.5.3	DOD-STD-35 Tables	13

TABLES

Table	I.	Title Index	2
	III.	Tabulation Candidates	11

APPENDICES

Appendix	A.	Illustrations	86
	B.	Characteristic Code Index	98
		Index	102

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 General. This dash-numbered part of the Automated Engineering Document Preparation System (AEDPS), provides detailed requirements for the preparation of Military Specification Exception (MSE) documentation for Bands, Decals, Markers and Plates.

1.2 Purpose. This military standard provides the necessary information to prepare a Specification Requirement Sheet (SRS) which will be used to generate a MSE by automated data processing.

1.3 Utilization. General instructions, quality assurance provisions, packaging, and notes, applicable to all AEDPS dash-numbered parts have been included in the basic document (DOD-STD-35) to avoid redundancy. Unless otherwise specified in this dash-numbered part, the following list contains additional subjects that are applicable to all AEDPS dash-numbered parts and are included in DOD-STD-35:

a. Writing Methodology
b. Document and Part Numbering
c. Applicable Documents
d. Single and Multi-item Specifications (Tabulation)
e. Keyword Code Index (KCI)
f. General Requirements of AEDPS

1.4 Military Specification Exception Title Index. The title code for a MSE shall be selected from one of the MSE titles listed in the Title Index (see table I). Data bases have been established for the generation of MSEs for the MSE titles indicated. If a suitable title code is not contained in the Title Index, leave the title code spaces on the SRS blank, and attach a request for the assignment of a title code. Include in the request the desired title and the base document identifier. A code will be assigned and the code, title, and base document will be made a part of the Title Index.

One of the six-digit codes listed in the Title Index, entered on an SRS, will specify that the title of the MSE will be the title shown in the Title Index.

Each MSE title listed in the Title Index is compatible with the document(s) listed with that title under base document. The list of base documents may or may not be a complete listing. The information shown under coverage is intended for the user's reference; when more than one document is listed for a MSE title, this information will be found useful in determining which of the documents is most suitable for use as the base document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
BAND, INFANT IDENTIFICATION	510001	A-A-30044	SIZE 1, MOTHER-INFANT; SIZE 2, PEDIATRIC; SIZE 3, ADULT
BAND, MARKER	510002	MIL-B-43436	BLANK, CRIMP STYLE, 2 & 3 PRONG, BELT SINGLE & DOUBLE
BAND, PATIENT IDENTIFICATION	510003	A-A-30044	SIZE 1, MOTHER-INFANT; SIZE 2, PEDIATRIC; SIZE 3, ADULT
DECAL	510004	MIL-M-43719	LIFE RAFT, PAULINS
MARKER, CASUALTY	510006	MIL-M-36233	ARCTIC REGIONS, CLOTH
MARKER, IDENTIFICATION	510007	MIL-M-3935	PERSONNEL, VEHICLE, AIRCRAFT
		MIL-M-17321	MAINTENANCE OF TRAFFIC CONTROL
		MIL-T-9906	TAPE, AIRCRAFT TUBING NON/CORR HEAT & SOLVENT RESISTANT

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:02Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
MARKER, SELF-LUMINOUS	510008	MIL-M-3935	PERSONNEL, VEHICLE, AIRCRAFT
		MIL-M-17321	MAINTENANCE OF TRAFFIC CONTROL
MARKER, SIGNAL	510009	MS27838	TAPE, PRESSURE SENSITIVE
MARKER, TRAFFIC	510010	MIL-M-17321	MAINTENANCE OF TRAFFIC CONTROL
MARKER, TRAFFIC CONTROL DEVICE	510011	MIL-M-17321	MAINTENANCE OF TRAFFIC CONTROL
PLATE, IDENTIFICATION	510013	MIL-P-15024	DATA INFORMATION
		MIL-P-19834	METAL, FOIL SMOOTH SURFACE
		MS53007	EMERGENCY AND SERVICE AUTO
		MIL-P-15024	END-ITEM-ATTACHMENT
PLATE, INSTRUCTION	510014	MIL-P-514	ATTACHMENT, IDENTIFICATION
		MIL-P-3558	TAG FOR RAILWAY CARS
		MS63045	MISCELLANEOUS
		MS63203	MODIFICATION

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

TABLE I. TITLE INDEX (CONT)

MSE TITLE	TITLE CODE	BASE DOCUMENT NUMBER	BASE DOCUMENT COVERAGE
PLATE, MARKING, BLANK	510015	MIL-P-15024 MIL-P-19834	DATA INFORMATION METAL FOIL, SMOOTH SURFACE

The MSE title may or may not be the same as the title used in DODISS, FIIG, or the base document. In general, the MSE title uses the basic federal item name listed in cataloging handbook H6. However, titles with additional modifying and identifying words are provided to assist in defining the scope of the MSE. Also, less restrictive titles are provided to prevent exclusion of items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-30044	Band, Personal Identification
A-A-53318	Marker Set, X-Ray Film Identification
P-C-437	Cleaning Compound, High Pressure (Steam) Cleaner
PPP-T-60	Tape, Packaging, Waterproof

MILITARY

MIL-P-514	Plates, Identification, Instruction and Marking, Blank
MIL-P-3558	Plates, Identification: Locomotive Railway Cars
MIL-M-3935	Markers, Self-Luminous
MIL-T-9906	Tape, Aircraft Tubing Identification Marking, Non-Corrosive, Heat and Solvent Resistant
MIL-P-15024	Plates, Tags and Bands for Identification of Equipment
MIL-M-17321	Markers, Traffic
MIL-P-19834	Plates, Identification or Instruction, Metal Foil, Adhesive Backed General Specification for

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

MIL-B-43436	Band Marker, Blank
MIL-M-43719	Marking Materials and Markers, Adhesive Elastomeric, Pigmented, General Specification for
MIL-C-87936	Cleaning Compound, Aircraft Exterior Surfaces, Water Dilutable

STANDARDS

FEDERAL

FED-STD-141	Paint, Varnish, Lacquer and Related Materials; Methods of Inspection Sampling and Testing
FED-STD-191	Textile Test Methods
FED-STD-595	Colors

MILITARY

MIL-STD-202	Test Methods for Electronic and Electrical Components Parts
MIL-STD-810	Environmental Test Methods
MS63045	Plate, Identification - Miscellaneous

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation.

ASTM B 117	Method of Salt Spray (Fog) Testing
ASTM D 573	Rubber Deterioration in an Oven Standard Test Method for

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1898	ACCELERATED WEATHERING. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1898.
1902	ACCELERATED WEATHERING. THERE SHALL BE NO EVIDENCE OF PEELING, CHALKING, BLISTERING, BLEEDING, OR COLOR CHANGE.
1880	ACCELERATED WEATHERING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1880.
1884	ACCELERATED WEATHERING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH TEST METHOD 6151 OF FED-STD-141.
1886	ACCELERATED WEATHERING. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH TEST METHOD 6152 OF FED-STD-141.
1888	THE DURATION OF EXPOSURE SHALL BE 1888 DAY(S).
1922	ADHESION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1922.
1920	ADHESION. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
1924	MAXIMUM REMOVAL OF TEST FILM ON EITHER SIDE OF THE SCORED LINE SHALL BE 1924 INCH(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SI	
(MILLIMETERS)	1926
NO REMOVAL OF TEST FILM.	1928
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1906
PER MIL-P-43719.	1910
TEST FILM, AIR-DRYING DURATION (HOURS)	1912
APPLICATION AND REMOVAL OF TAPE INTERVAL (SECONDS)	1914
TAPE STRIPPED FROM TEST FILM ANGLE (DEGREES)	1916
TAPE TYPE PER PPP-T-60 (ROMAN NUMERAL)	1918
BRIGHTNESS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1942

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1926	MAXIMUM REMOVAL OF TEST FILM ON EITHER SIDE OF THE SCORED LINE SHALL BE 1926 MILLIMETER(S).
1928	THERE SHALL BE NO REMOVAL OF TEST FILM BY THE TAPE.
1906	ADHESION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1906.
1910	ADHESION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-P-43719.
1912	THE DURATION OF AIR-DRYING OF THE TEST FILM SHALL BE 1912 HOUR(S).
1914	THE MAXIMUM INTERVAL BETWEEN APPLICATION AND REMOVAL OF TAPE SHALL BE 1914 SECONDS.
1916	THE TAPE SHALL BE STRIPPED FROM THE TEST FILM AT AN ANGLE OF 1916 DEGREES.
1918	TAPE TYPE PER PPP-T-60 ROMAN NUMERAL 1918 SHALL APPLY.
1942	BRIGHTNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1942.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the currentversion before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
AS FOLLOWS:	1940
BRIGHTNESS (SELECT ONE)	
U.S.	
MINIMUM (MICROLAMBERTS)	1944
NOMINAL (MICROLAMBERTS)	1946
MAXIMUM (MICROLAMBERTS)	1948
SI	
MINIMUM (MICROCANDELA PER SQUARE METER)	1945
NOMINAL (MICROCANDELA PER SQUARE METER)	1947
MAXIMUM (MICROCANDELA PER SQUARE METER)	1949
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1932
PER MIL-M-3935.	1934
TEST METHOD (SELECT ONE)	
COMPARISON.	1936
VISUAL PHOTOMETER.	1938

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1978	CHEMICAL RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1978.
1980	CHEMICAL RESISTANCE. THERE SHALL BE NO DISCOLORATION, CHANGE IN GLOSS, BLISTERING, WRINKLING, SOFTENING, SWELLING OR LOSS OF ADHESION.
1952	CHEMICAL RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1952.
1954	CHEMICAL RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH ASTMD1308.
1956	A MINIMUM OF 1956 TEST ITEMS SHALL BE TESTED.
1958	THE TEST TYPE SHALL BE SPOT, COVERED.
1960	THE TEST TYPE SHALL BE SPOT, OPENED.
1962	THE TEST TYPE SHALL BE IMMERSION.
1964	THE DURATION OF REAGENT EXPOSURE SHALL BE 1964 HOUR(S).
1966	THE REAGENT SHALL BE 1966.
1968	THE REAGENT SHALL HAVE A TEMPERATURE OF 1968 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CLEANING RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2002
NO EVIDENCE OF PHYSICAL DAMAGE.	2004
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1984
PER (DOC DES)	1986
CLEANING METHOD AS FOLLOWS:	
COLD STEAMING.	1990
HOSING.	1992
BRUSHING.	1994
HAND-WIPING.	1996
CLEANING DURATION (MINUTES)	1998
CLEANING AGENT (SELECT ONE)	
PER P-C-437.	1988
PER MIL-C-87936.	1989

Source: https://assist.dla.mil -- Downloaded: 20261O-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2002	CLEANING RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2002.
2004	CLEANING RESISTANCE. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
1984	CLEANING RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1984.
1986	CLEANING RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 1986.
	THE CLEANING METHOD SHALL BE AS FOLLOWS:
1990	COLD STEAMING.
1992	HOSING.
1994	BRUSHING.
1996	HAND-WIPING.
1998	THE DURATION OF THE CLEANING SHALL BE 1998 MINUTE(S).
1988	THE CLEANING AGENT SHALL BE IN ACCORDANCE WITH P-C-437.
1989	THE CLEANING AGENT SHALL BE IN ACCORDANCE WITH MIL-C-87936.

Supersedes page 43 of 27 SEPTEMBER 1985

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
DUCTILITY	
REQUIREMENT (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2030
AS FOLLOWS:	2028
NO RUPTURE OR FAILURE WITH A MINIMUM DEEP DRAW (SELECT ONE)	
U.S.	
(INCHES)	2032
SI	
(MILLIMETERS)	2034
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2008
PER (DOC DES)	2010
MINIMUM TEST ITEMS (QUANTITY)	2012
PLATE HOLE SIZE TOP AND BOTTOM MINIMUM (SELECT ONE)	
U.S.	
(INCHES)	2014

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2030	DUCTILITY. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2030.
2028	DUCTILITY. THE REQUIREMENT(S) SHALL BE AS FOLLOWS:
2032	THERE SHALL BE NO RUPTURE OR FAILURE WITH MINIMUM DEEP DRAW OF 2032 INCH(S).
2034	THERE SHALL BE NO RUPTURE OR FAILURE WITH MINIMUM DEEP DRAW OF 2034 MILLIMETER(S).
2008	DUCTILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 2008.
2010	DUCTILITY. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 2010.
2012	THERE SHALL BE A MINIMUM OF 2012 TEST ITEMS.
2014	THE MINIMUM TOP AND BOTTOM SPECIMEN HOLDING PLATE HOLE SIZE SHALL BE 2014 INCH(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
SI	
(MILLIMETERS)	2016
STEEL BALL PRECISION GROUND DIAMETER (SELECT ONE)	
U.S.	
(INCHES)	2018
SI	
(MILLIMETERS)	2020
BALL HARDNESS ROCKWELL "C" SCALE (NUMBER)	2022
DEPTH OF CUP GAUGE GRADUATIONS (SELECT ONE)	
U.S.	
(INCHES)	2024
SI	
(MILLIMETERS)	2026
FILM THICKNESS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	2058

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
2068	FLEXIBILITY. TESTING SHALL BE AS FOLLOWS:
2074	THERE SHALL BE 2074 BENDS, OR FOLDING AND UNFOLDING CYCLES.
2096	THE CYLINDER DIAMETER SHALL BE 2096 INCH(S).
2098	THE CYLINDER DIAMETER SHALL BE 2098 MILLIMETER(S).
3016	FLUORESCENT COLOR. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3016.
3014	FLUORESCENT COLOR. THE REQUIREMENT SHALL BE AS FOLLOWS:
3018	THE MINIMUM DOMINANT WAVE LENGTH SHALL BE 3018 NANOMETER(S).
3020	THE MAXIMUM DOMINANT WAVE LENGTH SHALL BE 3020 NANOMETER(S).
3010	FLUORESCENT COLOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3010.
3012	FLUORESCENT COLOR. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-M-3935.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
FUEL RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3046
NO EVIDENCE OF LOOSENING, WARPING OR CRACKING	3048
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3024
PER MIL-P-19834.	3026
PAINTED AND UNPAINTED TEST PANELS DURATION (HOURS)	3028
IMMERSION DEPTH (PERCENT OF WIDTH)	3030
FLUID PER TT-S-735.	3032
IMMERSION DURATION (HOURS)	3034
FLUID PER (DOC DES)	3041
IMMERSION DURATION (HOURS)	3045
TEST TEMPERATURE (DEGREES CELSIUS)	3047

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3046	FUEL RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3046.
3048	FUEL RESISTANCE. THERE SHALL BE NO EVIDENCE OF LOOSENING, WARPING, OR CRACKING.
3024	FUEL RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3024.
3026	FUEL RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH MIL-P-19834.
3028	THE DURATION AFTER THE DEVICE IS APPLIED TO PAINTED AND UNPAINTED TEST PANELS SHALL BE 3028 HOUR(S).
3030	THE IMMERSION DEPTH SHALL BE 3030 PERCENT OF THE WIDTH.
3032	THE FLUID SHALL CONFORM TO TT-S-735.
3034	THE IMMERSED DURATION SHALL BE 3034 HOUR(S).
3041	THE FLUID SHALL BE IN ACCORDANCE WITH 3041.
3045	THE IMMERSED DURATION SHALL BE 3045 HOUR(S).
3047	THE TEST TEMPERATURE SHALL BE 3047 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
EXAMINATION INTERVAL AFTER TEST (SELECT ONE)	
IMMEDIATELY.	3042
(HOURS)	3043
FUNGUS	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4760
FUNGUS RESISTANT BY CERTIFICATION OR BY TEST.	4761
NO EVIDENCE OF FUNGUS GROWTH WHEN TESTED.	4762
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4754
PER MIL-STD-810, METHOD 508.	4755
TEST PERIOD (DAYS)	4756

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3070	HEAT RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3060.
3072	HEAT RESISTANCE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH 3072.
3074	THE TEST TEMPERATURE SHALL BE 3074 DEGREES CELSIUS.
3076	THE TOLERANCE SHALL BE 3076 DEGREES CELSIUS.
3078	THE TEST DURATION SHALL BE 3078 HOUR(S).
4819	IMMERSION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4819.
4820	IMMERSION. THERE SHALL BE NO EVIDENCE OF PHYSICAL DAMAGE.
4822	ITEM(S) SHALL REMAIN WITHIN SPECIFIED TOLERANCE.
4809	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 4809.
4810	IMMERSION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 104 OF MIL-STD-202.
4811	TEST CONDITION LETTER 4811 SHALL APPLY.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
LEGIBILITY RETENTION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	3102
NO EVIDENCE OF BLEEDING AFTER DRYING	3104
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	3088
PER A-A-30044.	3090
IMMERSION MEDIA (PERCENT WATER)	3092
IMMERSION MEDIA (PERCENT ALCOHOL)	3094
TEST DURATION (HOURS)	3096
TEST TEMPERATURE (DEGREES CELSIUS)	3098
MOISTURE RESISTANCE	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ___	1400
NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.	1396
CLEARLY VISIBLE AND LEGIBLE.	3105

Source: https://assist.dla.mil -- Downloaded: 202640-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3102	LEGIBILITY RETENTION. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3102.
3104	LEGIBILITY RETENTION. THERE SHALL BE NO EVIDENCE OF BLEEDING AFTER DRYING.
3088	LEGIBILITY RETENTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3088.
3090	LEGIBILITY RETENTION. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH A-A-30044.
3092	THE IMMERSION MEDIA SHALL BE 3092 PERCENT WATER.
3094	THE IMMERSION MEDIA SHALL BE 3094 PERCENT ALCOHOL.
3096	THE DURATION SHALL BE 3096 HOUR(S).
3098	THE TEST TEMPERATURE SHALL BE 3098 DEGREES CELSIUS.
1400	MOISTURE RESISTANCE. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 1400.
1396	MOISTURE RESISTANCE. THERE SHALL BE NO EVIDENCE OF CORROSION OR PHYSICAL DAMAGE.
3105	THE MARKING SHALL BE CLEARLY VISIBLE AND LEGIBLE.

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	1391
PER MIL-STD-202, METHOD 106.	1397
STEP 7A NOT APPLICABLE.	4985
STEP 7B NOT APPLICABLE.	4986
MOUNT PER DOCUMENT (DOC DES)	1449
PAINT ADHESION	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3118
NO EVIDENCE OF CRACKING OR LIFTING.	3120
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3108
PER MIL-STD-17321.	3110
DURATION AFTER DRYING (HOURS)	3112
COMPRESSION DURATION (SECONDS)	3114

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
7307	THE TEST TEMPERATURE SHALL BE 7307 DEGREES CELSIUS.
7308	THE TEST TEMPERATURE TOLERANCE SHALL BE PLUS OR MINUS 7308 DEGREES CELSIUS.
3150	SPECULAR GLOSS, 60-DEGREES. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3150.
3152	SPECULAR GLOSS, 60-DEGREE. THE REQUIREMENT SHALL BE IN ACCORDANCE WITH METHOD 6101 OF FED-STD-141.
3154	THERE SHALL BE A MINIMUM GLOSS OF 3154 PER METHOD 6101 OF FED-STD-141.
3156	THERE SHALL BE A MAXIMUM GLOSS OF 3156 PER METHOD 6101 OF FED-STD-141.
3144	SPECULAR GLOSS, 60-DEGREE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3144.
3146	SPECULAR GLOSS, 60-DEGREE. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH METHOD 6101 OF FED-STD-141.
3176	STIFFNESS. THE REQUIREMENT(S) SHALL BE IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3176

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
AS FOLLOWS:	3174
MINIMUM MACHINE DIRECT (MILLIGRAMS)	3178
MINIMUM CROSS MACHINE DIRECT (MILLIGRAMS)	3180
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	3160
PER A-A-30044.	3162
TEST STRIPS (QUANTITY)	3164
TEST STRIP LENGTH (SELECT ONE)	
U.S.	
(INCHES)	3166
SI	
(MILLIMETERS)	3168
TEST STRIP WIDTH (SELECT ONE)	
U.S.	
(INCHES)	3170
SI	
(MILLIMETERS)	3172

Source: https://assist.dla.mil -- Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
3174	STIFFNESS. THE REQUIREMENT SHALL BE AS FOLLOWS:
3178	THE MINIMUM MACHINE DIRECT SHALL BE 3178 MILLIGRAM(S).
3180	THE MINIMUM CROSS MACHINE DIRECT SHALL BE 3180 MILLIGRAM(S).
3160	STIFFNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH THE BASE DOCUMENT, EXCEPT 3160.
3162	STIFFNESS. TESTING SHALL BE PERFORMED IN ACCORDANCE WITH A-A-30044.
3164	THERE SHALL BE 3164 TEST STRIPS.
3166	THE LENGTH OF TEST STRIPS SHALL BE 3166 INCH(S).
3168	THE LENGTH OF TEST STRIPS SHALL BE 3168 MILLIMETER(S).
3170	THE WIDTH OF TEST STRIPS SHALL BE 3170 INCH(S).
3172	THE WIDTH OF TEST STRIPS SHALL BE 3172 MILLIMETER(S).

Source: https://assist.dla.mil - Downloaded: 202610-23T21:02Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
TEMPERATURE, LOW	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6318
NO EVIDENCE OF PHYSICAL DAMAGE.	6319
TEST METHODS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	6231
PER MIL-STD-810, METHOD 502.	6232
STORAGE TEMPERATURE (DEGREES CELSIUS)	6234
STORAGE DURATION (HOURS)	6235
CHAMBER AIR VELOCITY (SELECT ONE)	
(FEET PER SECOND)	6237
(METERS PER SECOND)	6238
THERMAL SHOCK (TEMPERATURE CYCLING)	
REQUIREMENTS (SELECT ONE)	
PER BASE DOCUMENT EXCEPT ____	4722
NO EVIDENCE OF PHYSICAL DAMAGE.	4723

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T21:02Z
Check the source to verify that this is the current version before use.