MILITARY SPECIFICATION

TRANSMITTER GROUP, SIMULATED RADIAC OT-51( )/T

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. - This specification covers the Transmitter Group, Simulated Radiac OT-51/T. The OT-51/T is an RF transmitter and antenna which simulates a radioactive fallout pattern with radio waves. The OT-51/T consists of the one Transmitter, Simulated Radiac T-1254/T, one Case, Simulated Transmitter CY-7349/T, one Antenna Assembly AS-2919/T and miscellaneous cables and support components.

2. APPLICABLE DOCUMENTS

2.1 Documents. - The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein

SPECIFICATIONS

FEDERAL

PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Box, Wood, Cleated-Plywood
PPP-B-621	Box, Wood, Nailed and Lock-Corner
PPP-B-636	Box, Fiberboard
PPP-F-320	Fiberboard, Corrugated and one Solid, Sheet Stock Container Grade and Cut Shapes
PPP-P-291	Paperboard, Wrapping, Cushioning
PPP-T-45	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, Water Resistant, for Carton Sealing

FSC 6665

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	Steel, Strapping, Flat

MILITARY

MIL-P-116	Preservation, Methods of
MIL-C-3098	Crystal Unit Quartz
MIL-P-11268	Parts, Materials and Processes Used in Electronic Communication Equipment
MIL-M-13231	Marking of Electronic Items

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-252	Wired Equipment, Classification of Visual and Mechanical Defects
MIL-STD-454	Standard General Requirements for Electronic Equipment
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics Measurement of
MIL-STD-810	Environmental Test Methods

DRAWINGS

ELECTRONICS COMMAND

DLSM-B-748187	Transmitter Group, Simulated Radiac OT-51/T

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

DRAWINGS

ELECTRONICS COMMAND

SM-A-678028 Burn-In Procedure for Transmitter, Simulated Radiac T-1254/T

(Copies of specifications standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First Article. - When specified in the contract or purchase order, the contractor shall furnish first article units in accordance with 4.3.

3.2 Construction. - The Transmitter Group, Simulated Radiac OT-51/T shall be constructed in accordance with the requirements of this specification and drawing DLSM-B-748187.

3.3 Parts, Materials and Processes. - In addition to any requirements of this specification covering parts, materials and processes, such items shall conform to MIL-P-11268, including the selection requirements therein.

3.4 Marking. -

3.4.1 General. - Marking shall conform to MIL-M-13231. (See 4.4)

3.4.2 Serial Numbers. - Each equipment shall bear a serial number in accordance with the requirements of MIL-M-13231.

3.5 Interchangeability. - Like units, assemblies, subassemblies and replaceable parts shall conform to requirement 7 of MIL-STD-454. (See 4.6)

3.6 Performance Characteristics. -

3.6.1 Transmitter, Simulated Radiac T-1254/T. -

3.6.1.1 Operating Frequency and Stability. - The operating frequency shall be within 138 to 144 MHz and shall be crystal controlled. At variations of input voltage and power output specified in 4.9.1.1 the output frequency shall not vary more than

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

± 2.5 KHz. The above criteria shall be met over the entire band utilizing available Military Standard (MS) crystals selected from MIL-C-3098/60 (See 4.9.1.2).

3.6.1.2 Power Output and Stability. - At input voltages of 22, 24, 28 VDC ±5%, the function switch at High and Low positions, vary power control at the clockwise (cw) and counterclockwise (ccw) limits, the power output shall be as listed below (See 4.9.1.3):

Power Control	Function Switch Position	Power Output
Fully Clockwise	High	20 watt ± 10%
Fully Counterclockwise	High	Between 600 & 900 mW
Fully Counterclockwise	Low	Greater than 400 mW
Fully Counterclockwise	Low	Less than 20 mW

3.6.1.3 Signal Identification. - Amplitude modulation, Class A1 (ON-OFF) Keying) shall be utilized to provide signal identification. When the transmitter is in operation, the keying cycle shall automatically transmit a programmable morse code signal three times at 15 ± 3 minute intervals. (See 4.9.1.4)

3.6.1.4 Weight. - The weight of the Transmitter, Simulated Radiac T-1254/T shall not exceed 13 pounds. (See 4.8.1)

3.6.2 Antenna Assembly AS-2919/T. -

3.6.2.1 Beam Width. - The radiation pattern of the directional antenna shall have a beam width of not less than 20 degrees not more than 50 degrees (See 4.9.3).

3.6.3 Case, Simulated Transmitter CY-7349/T. -

3.6.3.1 Weight. - When loaded with antenna, miscellaneous components and transmitter T-1254/T (ie, a complete Transmitter Group OT-51/T as per DLSM-B-748187) the carrying case assembly shall not exceed 135 pounds. (See 4.8.2)

3.7 Environmental. - The Transmitter, Simulated Radiac T-1254/T shall meet the performance requirements specified below under any combination of the service conditions.

3.7.1 Temperature. -

3.7.1.1 Low Temperature. The transmitter shall be subjected to the low temperature extremes of 0 ± 2.5°F operating and -60 ± 2.5°F storage and shall meet the requirements of 3.6.1.2 when tested. (See 4.10.5.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

3.7.1.2 High Temperature. - The transmitter shall be subjected to the high temperature extremes of 125 ± 2.5°F operating and 160 ± 2.5°F storage and shall meet the requrirements of 3.6.1.2 when testing. (See 4.10.5.2)

3.7.2 Electromagnetic Interference (EMI) Characteristics. - The transmitter shall meet the requirements of MIL-STD-461 for Methods CE06 and RE02 except as modified in Table 1. (See 4.10.9)

Table 1 Deviation from MIL-STD-461

CE06	RE02
3rd Harmonic Output Key Up X Key Down 27 dBm	Narrowband fo Max Dev. 50 dBu V/M Other Freq Max. Dev. 35 dBu V/M Broadband X

NOTE a. "X" denotes compliance with limits of MIL-STD-461.

b. Any deviation listed is added to the specified limit delineated in MIL-STD-461

3.7.3 Humidity. - During testing as specified in 4.10.3 the transmitter shall maintain a power output of 20 watts ± 10%. Upon completion of test the transmitter shall meet the performance of 3.6.1.2 and 3.6.1.3.

3.7.4 Dust. - After testing as specified in 4.10.4 the transmitter shall meet the performance requirements of 3.6.1.2.

3.7.5 Altitude (elevation). - During testing as specified in 4.10.1 the transmitter shall maintain a power output of 20 watts ± 10%. Upon completion of test the transmitter shall meet the performance of 3.6.1.2 and 3.6.1.3.

3.7.6 Vibration. - The transmitter shall meet the performance requirements of 3.6.1.2 both before and after testing as specified in 4.10.6.

3.7.7 Leakage (immersion). -

3.7.7.1 Immersion, transmitter. - The transmitter shall show no evidence of leakage after it is tested as specified in 4.10.2.1.

3.7.7.2 Immersion, case. - The case shall show no evidence of leakage after it is tested as specified in 4.10.2.2.

3.7.8 Salt fog. - After testing as specified in 4.10.7 the transmitter shall meet the performance requirements of 3.6.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

3.7.9 Tropicalization. -

3.7.9.1 Fungus. - Upon completion of the test, there shall be no deterioration, corrosion or change in configuration that will prevent the maintenance or operation of the transmitter. (See 4.10.8)

3.8 Burn-In. - Each transmitter shall be capable of meeting the performance requirements specified herein after being subjected to the specified burn-in cycle of 4.9.2.

3.9 Workmanship. - The equipment shall be manufactured and assembled in accordance with requirement 9 of MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection. - Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may utilize his own facilities, facilities of a subcontractor or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that the supplies and service conform to prescribed requirements.

4.2 Classification of Inspections. - Inspections shall be classified as follows:

a. First article inspection. (Does not include preparation for delivery) (See 4.3)

b. Inspection covered by subsidiary documents. (See 4.4)

c. Quality conformance inspections.

(1) Quality conformance inspection of equipment before preparation for delivery. (See 4.5)

(2) Quality conformance inspection of preparation for delivery. (See 4.7)

4.3 First Article. - Unless otherwise specified in the contract or purchase order, the first article inspection shall be performed by the contractor.

4.3.1 First Article Units. - The contractor shall furnish the number of first article units in accordance with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

a. Four (4) each Transmitter, Simulated Radiac T-1254/T.

b. One (1) each Antenna Assembly AS-2919/T.

c. One (1) each, Case, Simulated Transmitter CY-7349/T.

4.3.2 First Article Inspection. - The first article inspection shall consist of the inspections specified in Table II, and shall be performed in the order specified therein.

4.3.3 First Article Data. - The first article test plan and test report(s) shall be as required in the contract or purchase order.

Table II First Article Inspection. -

Inspection	Reqt Para	Test Para	Unit 1	Unit 2	Unit 3	Unit 4
1. Inspections covered by subsidiary documents.	3.3	4.4	Inspections to be performed on all units.			
2. Burn-in	3.8	4.9.2	Inspections to be performed on all units.			
3. Group A inspection	See Table III		Inspections to be performed on all units.			
4. Group B inspection	See Table IV		Inspections to be performed on all units.			
5. EMI	3.7.2	4.10.9	1			
6. Environmental						
Low Temperature	3.7.1.1	4.10.5.1		1		
High Temperature	3.7.1.2	4.10.5.2				
Altitude	3.7.5	4.10.1		2		
Humidity	3.7.3	4.10.3		3		
Vibration	3.7.6	4.10.6				1
Dust	3.7.4	4.10.4				2
Immersion	3.7.7	4.10.2	2			
Salt Fog	3.7.8	4.10.7				3
Fungus	3.7.9.1	4.10.8			1	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

NOTES:

1. The inspection 1 to 4, in the order shown, shall be performed on all first article units before subjecting these units to any other inspection requirements specified in the table.

2. The implementation of inspections 5 and 6 shall be expedited to satisfy contract delivery requirements.

3. The numbers in the unit columns in the table, covered by 5and 6 specify the order of inspections for the indicated unit.

4.4 Inspections covered by subsidiary documents.- The following shall be inspected under the applicable subsidiary documents as part of the inspection required by this specification, and the inspection requirement specified in the contract or purchase order.

Item	Where required
Parts, Materials and processes-general	3.3
Marking	3.4
Workmanship	3.9

4.5 Quality conformance inspection of equipment before preparation for delivery.- The contractor shall perform the inspections specified in 4.4, 4.9.2, and 4.5.1 through 4.5.4. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements.

4.5.1 Group A inspection.- Each unit on contract or purchase order shall be inspected for conformance to the inspections specified in Table III. Discrete lots shall be formed from units that passed this inspection. Factors of lot composition not defined herein, or in the contract or purchase order, shall be in accordance with MIL-STD-105. Each lot shall be subject to sampling inspection, utilizing the procedures of MIL-STD-105, using the general inspection levels, and AQL's indicated in Table III.

4.5.1.1Order of inspection within Group A. - Group A inspection shall be performed in the order listed in Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

Table III Group A inspection. -

Inspection	Requirement Paragraph	Test Para	AQL Major	AQL Minor
Visual & Mechanical	3.9	4.11	2.5%	4.0%
Electrical				
Operating Frequency & Stability	3.6.1.1	4.9.1.1	2.5% for	**
Power Output & Stability	3.6.1.2	4.9.1.3	the	**
Signal Identification	3.6.1.3	4.9.1.4	group	**

**All electrical defects are major.

4.5.2 Group B inspection. - Group B inspection shall be performed on inspectic lots that have passed Group A inspection and on samples selected from units that have been subjected to and met the Group A inspection. This inspection shall conform to Table I and to the special inspection levels of the Table I of MIL-STD-105.

4.5.2.1 Group B sampling plans. - The Group B sample plans, for the AQL's listed in Table IV, shall be as follows

AQL	Inspection Level
4.0 percent	S-4
6.5 percent	S-4

4.5.2.2 Order of inspection within Group B. - Group B inspection shall be performed in the order listed in Table IV.

Table IV Group B inspection. -

Inspection	Requirement Paragraph	Test Para	AQL
Interchangeability	3.5	4.6	4.0%
Operating frequency range	3.6.1.1	4.9.1.1	4.0%
Weight (Transmitter)	3.6.1.4	4.8.1	4.0%
Electrical			
Beam width (Antenna)	3.6.2.1	4.9.3	4.0%
Weight (Case)	3.6.3.1	4.8.2	4.0%
Immersion (Case)	3.7.7.2	4.10.2.2	4.0%

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

4.5.3 Group C inspection. - Group C inspection shall be performed on units that have passed Group A and Group B inspection. The inspection shall consist of the inspections specified in Table V. Samples shall be selected in accordance with 4.5.3.1.

Table V Group C inspection. -

Inspection	Requirement Paragraph	Test Paragraph
Subgroup 1		
Altitude	3.7.5	4.10.1
Dust	3.7.4	4.10.4
Subgroup 2		
Vibration	3.7.6	4.10.6
Fungus*	3.7.9	4.10.8
Subgroup 3		
Low temperature	3.7.1.1	4.10.5.1
High temperature	3.7.1.2	4.10.5.2
Leakage (immersion) (Transmitter)	3.7.7.1	4.10.2.1
Subgroup 4		
Humidity	3.7.3	4.10.3
Subgroup 5		
Salt fog*	3.7.8	4.10.7
Subgroup 6		
EMI	3.7.2	4.10.9

*The transmitter T-1254/T shall be thoroughly washed, cleaned, dried and refurbished after this inspection before proceeding with subsequent inspection.

4.5.3.1 Sampling for Group C inspection. -

4.5.3.1 Six samples of the complete transmitter shall be selected at random, one sample for each Subgroup 1 through Subgroup 6 in Table V from every (production rate basis) or fraction thereof produced. The samples shall be selected at the start of the contract from the first quality conformance inspection lot. These samples shall constitute

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

the Group C requirement for first twenty units produced. Subgroup 6 EMI and Subgroup 2 Fungus inspections shall be performed only on first production lot.

4.5.3.2 Order of inspection within Group C. - Group C inspection shall be performed in the order specified in Table V.

4.5.3.3 Group C failures. - Actions required relative to Group C failure shall be specified in the contract or purchase order.

4.5.3.4 Reinspection of conforming Group C sample units. - Unless otherwise specified, sample units which have been subjected to and passed Group C inspection may be accepted on the contract provided all damage is repaired and the sample units are resubjected to and Group B inspection and Group A inspection in that order.

4.6 Inspection for dimensional interchangeability. - The dimensions listed below shall be gaged or measured to determine conformance to the physical interchangeability requirement of 3.5. When a listed dimension is not within specified or design limits, it shall be considered a major defect.

(a) External and internal dimensions of cases, covers, and insertable assemblies, when such dimensions affect mating of parts.

(b) Dimensions of cavities, when such dimensions affect insertion of items.

(c) Location of hinges and fasteners on separable parts or assemblies which must mate, such as cases, covers, and mountings.

(d) Location of connectors, locking pins, fasteners, slides, and mountings which receive mating parts of plug-in assemblies and major units, and location of the mating parts on the plug-in assembly or major unit.

(e) Size and form of special threads.

4.7 Quality conformance inspection of preparation for delivery. - Preparation for delivery shall be inspected in accordance with MIL-P-116 to determine conformance to the requirements of section 5.

4.8 Weight. -

4.8.1 Weight (transmitter). - Using a calibrated scale the transmitter T-1254/T shall meet the requirement of 3.6.1.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

4.8.2 Weight (case). - Using a calibrated scale when fully loaded, the case assembly shall meet the requirement of 3.6.3.1.

4.9 Performance characteristics. -

4.9.1 Transmitter, Simulated Radiac T-1254/T. -

4.9.1.1 Operating Frequency and Stability. - Using the appropriate crystals to obtain a frequency of 141MHz and with input voltage variations of 22 VDC ± 5%, 24 VDC ± 5% and 28 VDC ± 5%, the output frequency shall meet the requirements of 3.6.1.1. The test will be conducted with the variable power control fully CW in both the high and low range. (See 3.6.1.1)

4.9.1.2 Operating Frequency Range. - Utilizing the methods and criteria of 4.9.1.1, the transmitter will be tested at 138 MHz and 144 MHz. (See 3.6.1.1)

4.9.1.3 Power Output and Stability. - With the variable power control fully clockwise and function switch set at Low and High positions, the transmitter shall meet the requirements of 3.6.1.2 with a dummy load of 50 ohms.

4.9.1.4 Signal Identification. - Completely fill rows 1, 2, 5 and 6 with shorting pins. Turn power on. Count the number of deflections on the transmitter power meter. A total of 48 deflections should be counted before the keying cycle stops. The keying cycle should then repeat after 15 ± 3 minutes. Remove the pins, place them in rows 3, 4, 7 and 8 and repeat the test. (See 3.6.1.3)

4.9.2 Burn-in. - Each transmitter submitted for acceptance shall be subjected to burn-in in accordance with drawing SM-A-678028. (See 3.8)

4.9.3 Antenna Beamwidth. - The beamwidth of the antenna shall be determined by a field strength meter in an actual field application. The beamwidth in degrees shall be determined as measured 3 dB down from maximum reading obtained. The beamwidth shall meet the requirements of 3.6.2.1.

4.10 Environmental. - The transmitter T-1254/T shall be tested in accordance with the following conditions.

4.10.1 Altitude (elevation) Test. - The transmitter shall be tested in accordance with Method 500, Procedure 1, of MIL-STD-810. Prior to testing the transmitter shall meet full specification performance for the measurements specified in 3.6. During test measure the maximum power output and perform the test of 4.9.1.4, filling only rows 1, 2, 5 and 6 with shorting pins. All tests shall be conducted at a supply voltage of 24 VDC ± 5%. The power output shall be preset at 20 watts ± 10%. Following completion of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

test, perform the tests of 4.9.1 except for 4.9.1.2. (See 3.7.5)

4.10.2 Leakage (immersion) Test. -

4.10.2.1 Immersion, transmitter. - The transmitter shall be tested in accordance with Method 512, Procedure 1 of MIL-STD-810. (See 3.7.7.1)

4.10.2.2 Immersion, case. -The case shall be tested in accordance with Method 512, Procedure 1 of MIL-STD-810. (See 3.7.7.2)

4.10.3 Humidity (moisture-resistance) Test. - The transmitter shall be tested in accordance with Method 507, Procedure II, of MIL-STD-810. Prior to testing the transmitter shall meet full specification performance for the measurements specified in 3.6. During the periods shown on Figure 507-2 of MIL-STD-810, measure the maximum power output and perform the test of 4.9.1.4 filling only rows 1, 2, 5 and 6 with shorting pins. All tests shall be conducted at a supply voltage of 24 VDC ± 5%. The power output shall be preset at 20 watts ± 10%. Following completion of the test, perform the tests of 4.9.1 except for 4.9.1.2. (See 3.7.3)

4.10.4 Dust Test. - The transmitter shall be tested in accordance with Method 510, Procedure 1 of MIL-STD-810. Following completion of the test, perform the tests of 4.9.1 except for 4.9.1.2. (See 3.7.4.)

4.10.5 Temperature Tests. -

4.10.5.1 Low Temperature Procedure. - The following test shall be performed on the transmitter in accordance with MIL-STD-810, Method 502, Procedure 1. Perform the tests of 4.9.1.3 as pre-environmental data. Place the transmitter in the temperature chamber and reduce the temperature to -60 ± 2.5°F. The test will start when the ambient temperature has stabilized. Hold the temperature for a period of 8 hours. At the end of 8 hours increase the ambient temperature to 0 ± 2.5°F. When the temperature of the transmitter has stabilized, operate the transmitter for six hours. During this time perform the tests of 4.9.1.3. Return the transmitter to room ambient temperature. Perform the tests of 4.9.1.3 as post environmental data. The readings at the low temperature shall not vary more than ± 20% from those readings at room temperature and corresponding input voltages. (See 3.7.1.1)

4.10.5.2 High Temperature Procedure. - The following test shall be performed on the transmitter in accordance with MIL-STD-810, Method 501, Procedure 1. Perform the tests of 4.9.1.3 as pre-environmental data. Place the transmitter into the temperature chamber and increase the ambient temperature to 160 ± 2.5°F. The test will start when the ambient temperature has stabilized. Hold the temperature for a period of 8 hours minimum At the end of 8 hours reduce the ambient temperature to 125 ± 2.5°F. When the temperature of the transmitter has stabilized, operate the transmitter for six hours. During this time perform the tests of 4.9.1.3. Return the transmitter to room ambient temperature. Perform the tests of 4.9.1.3 as post environment data. The readings at the high temperatu

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

shall not vary more than ± 20% from those readings at room temperature and corresponding input voltages. (See 3.7.1.2)

4.10.6 Vibration. - The case, fully loaded, shall be vibrated in accordance with MIL-STD-810, Method 514.1, Procedure X, Curve AW and AY of Figure 514.1.7. Pre and post testing shall be performed on the transmitter in accordance with 4.9.1 except 4.9.1.2. (See 3.7.6)

4.10.7 Salt fog test. - The transmitter (including accessories) in its normal operating position shall be tested in accordance with Method 509, Procedure 1, of MIL-STD-810. Pre and post test shall be performed in accordance with 4.9.1.1. (See 3.7.8)

4.10.8 Fungus test. - The transmitter (including accessories) shall be tested in accordance with Method 508, Procedure 1, of MIL-STD-810. Spraying shall include parts and materials on and under the chassis, and the interior of the equipment case. The transmitter shall remain in an open condition during the test. Operation is not required. (See 3.7.9)

4.10.9 EMI. The transmitter shall be tested in accordance with MIL-STD-462 and meet the requirements of 3.7.2.

4.11 Visual and mechanical inspection. - Equipment shall be examined for the defects listed in MIL-STD-252.

5. PREPARATION FOR DELIVERY.

5.1 Preservation and packaging. - Preservation and packaging shall be level A or C, as specified. (See 6.2.b)

5.1.1 Level A. -

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

5.1.1.1 Cleaning. - Transmitter Group, Simulated Radiac OT-51/T shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. - Transmitter Group, Simulated Radiac Group OT-51/T shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. - None required.

5.1.1.4 Unit packaging. - Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. - Each technical literature shall be packaged method 1C-1.

5.1.1.4.2 Spare fuses. - Spare fuses shall be packaged method III as follows: Cushion the fuses by wrapping together in paperboard conforming to PPP-P-291, type I. Secure the wrap with gummed paper tape conforming to PPP-T-45, type III, grade A.

5.1.1.4.3 Spare lamps. - Each spare lamp shall be individually packaged method III as follows: Cushion each lamp by wrapping in paperboard conforming to PPP-P-291, type I. Secure the wrap with gummed paper tape conforming to PPP-T-45, type III, grade A.

5.1.1.4.4 Transmitter Group, Simulated Radiac OT-51/T. - Each Transmitter Group, Simulated Radiac OT-51/T shall be individually packaged method III as follows Stow all units within the designated compartments of the transit case includin the items packaged as specified in 5.1.1.4.2 and 5.1.1.4.3. Close cover and secure all fasteners. Cushion the transit case on all four corners with corner pads fabricated of fiberboard conforming to PPP-F-320, type CF, class weather-resistant, variety SW, grade W5c, designed to protect all projections and absorb the shock of impact in handling and transit. Secure the corner pads to the transit case with tape conforming to PPP-T-76. Place the cushioned unit within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Box closure shall be in accordance with the appendix of the box specification.

5.1.2 Level C. - Transmitter Group, Simulated Radiac OT-51/T, shall be preserved and packaged in a manner that will afford adequate protection against physical and environmental damage during shipment, handling and limited intransit storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

5.2 Packing. - Packing shall be level A, B or C as specified. Shipping containers for all levels shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents. (See 6.2.b)

5.2.1 Level A.- Transmitter Group, Simulated Radiac Group OT-51/T, packaged as specified in 5.1, shall be individually packed within a close-fitting box conforming to PPP-B-601, overseas type, PPP-B-621, style 4, class 2, or PPP-B-585, style 2 or 3, class 3. Fiberboard boxes being placed directly in the shipping containers shall be waterproofed with tape conforming to PPP-T-76, in accordance with the taping requirements of the appendix of the box specification. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Skids, 3x4 inch, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification in a manner which will adequately support the item and facilitate the use of handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that the metal strapping shall conform to QQ-S-781, type I, finish "A".

5.2.2 Level B.- Transmitter Group, Simulated Radiac OT-51/T, packaged as specified in 5.1, shall be individually packed within a close-fitting box conforming to PPP-B-601, domestic type, PPP-B-621, style 4, class 1; or PPP-B-585, style 2 or 3, class 3. Skids, 3x4 inch, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto.

5.2.3 Level C.- Transmitter Group, Simulated Radiac OT-51/T packaged as specified in 5.1, shall be packed in shipping containers that comply with federal or military specifications, in a manner that will afford adequate prorection to the package and its contents against physical and environmental deterioration and damage, during limited shipment, handling and intransit storage.

5.3 Marking. - In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES. -

6.1 Intended use. - The Transmitter Group, Simulated Radiac OT-51/T used

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

with the Receiver Group, Simulated Radiac CR-114 comprises a training system which allows safe instruction and practical exercise in the survey and mapping of radiological contamination.

6.2 Ordering data. - Procurement documents should specify the following

a. Title, number, and date of this specification and any amendment thereto.

b. Levels of preservation and packaging and packing. (See Section 5)

c. When rough handling and functional tests are required.

d. The contractor should apply for nomenclature in accordance with the applicable clause in the contract.

e. Marking and shipping of samples.

f. Place of final inspection.

Custodian:
Army-EL

Preparing Activity
Army - EL

Project No. 6665-A315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side staple in corner and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements

SPECIFICATION MIL-T-55401(EL) TRANSMITTER GROUP, SIMULATED RADIAC OT-51( )/T

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes" in what way?)*

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED

ESC-FM 1068-68

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.

FOLD

Department of the Army
Headquarters
U.S.Army Electronics Command
Fort Monmouth, New Jersey 07703

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding General
U.S.Army Electronics Command
ATTN AMSEL- RD-TS-S
Fort Monmouth, New Jersey 07703

FOLD

To detach this form, cut along this line

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:19Z
Check the source to verify that this is the current version before use.