INCH.-POUND

MIL-T-70835A (AR)
29 Mar 1991
SUPERSEDING
MIL-T-70835 (AR)
15 April 1990

MILITARY SPECIFICATION

TRANSMITTER, ASSEMBLY: 11784701

This Specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes requirements for a remote controlled transmitter assembly which is part of the Target Holding Mechanism/Tank Gunnery (THM/TG) Unit.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-F-13926	- Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-A-70833	- Automatic Tank Target: 11784501
MIL-R-70834	- Receiver, Channel X: 11784801

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5895

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T04:09Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-454	- Standard General Requirements for Electronic Equipment
MIL-STD-810	- Environmental Test Methods and Engineering Guidelines
MIL-STD-2000	- Standard Requirements for Soldering Electrical and Electronic Assemblies

Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extend specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWINGS (See 6.4)

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

11784701	- Transmitter Assembly
11784801	- Receiver, Channel X

SPECIAL PACKAGING INSTRUCTIONS

PS11784701	- Special Packaging Instructions for the Transmitter Assembly

(Copies of drawings, publications, and other Government documents required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

3.1 General description. The transmitter is a component of the Target Holding Mechanism/Tank Gunnery (THM/TG) and shall transmit commands to the receiver: MIL-R-70834 of the automatic

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

tank target component of the THM/TG unit, to raise and lower armor/tank targets.

3.2 Fabrication. The transmitter assembly shall be manufactured in accordance with drawing 11784701 and Military Specifications MIL-F-13926 and MIL-STD-454.

3.2.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2.2 Components and assemblies. The components and assemblies shall comply with all requirements specified in this specification and on Drawing (Dwg) 11784701 and all associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Performance.

3.3.1 Commands. The transmitter shall transmit commands to the Channel X Receiver in the Automatic Tank Target Assembly MIL-A-70833. Commands shall raise targets, lower targets and activate one of the hit indicators: the Visual Hit Indicator Lamp (VHIL) or the Gunfire Simulator (GUFS). Each command shall have a separate push button switch for each receiver (24 switches total).

3.3.2 Channel operation. The transmitter shall be capable of performing the three commands per 3.3.1 and shall demonstrate an octal addressing capability per 3.4.1.

3.3.3 Frequency operation. The transmitter shall be capable of sending the three commands per 3.3.1 at any frequency in the operating frequency range as noted in 3.4.a.

3.4 Electrical requirements.

a. The transmitter shall operate within a frequency range of 138 and 165 Mhz.

b. The transmitter shall have a frequency tolerance of $\pm$ 2.5 Khz.

c. The transmitter shall have frequency spacing of 50 Khz $\pm$ 5 %.

d. The transmitter shall have frequency stability not to exceed 2.5 Khz between -25 degrees F and +125 degrees F.

e. The transmitter shall have a frequency deviation of less than 3 Khz from the specified frequency.

f. The transmitter shall have a transmitting power, minimum of 6 watts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

g. The transmitter antenna impedance shall not exceed 50 ohms.

h. The transmitter current drain in a standby mode shall be less than 0.1 mA. The transmitter operating mode current drain shall be less than or equal to 1.5 amps.

i. The transmitter harmonic radiation shall be less than or equal to 2 microwatts.

j. The transmitter spurious radiation shall be less than or equal to 2 microwatts.

k. The transmitter shall receive power from an internal 12V ni-cad battery.

l. The transmitter shall have five channels capable of operating eight receivers per channel. The transmitter shall be capable of addressing each of the eight receivers individually or all eight receivers simultaneously.

3.5 Environmental requirements.

3.5.1 Temperature.

3.5.1.1 Operating. The transmitter assembly shall meet the requirements of 3.3 and 3.4 when stabilized thermally at -25 degrees F and +125 degrees F.

3.5.1.2 Non-operating (storage). The transmitter assembly when subjected to at least four hours at each temperature extreme of -40 degrees F and +160 degrees F shall meet the requirements of 3.3 and 3.4 when returned to and thermally stabilized at ambient temperature (+60 degrees F to +90 degrees F).

3.5.2 Vibration. The transmitter assembly shall meet the requirements of 3.3. and 3.4 after being subjected to Method 514, Procedure I-3.3.1, using figure 514.4-1 of MIL-STD-810, for one hour of random vibration in the vertical axis.

3.5.3 Shock. The transmitter assembly shall meet the requirements of 3.3 and 3.4 after being subjected to mechanical shock in accordance with Method 516, Procedure IV, Transit Drop Test, of MIL-STD-810.

3.5.4 Drop test. The transmitter shall meet the requirements of 3.3 and 3.4 when dropped three feet from a random position onto a hard surface.

3.5.5 Immersion (non-operating). The transmitter assembly shall show no evidence of internal moisture after being subjected to at least two hours of immersion in three feet of water per MIL-STD-810, Method 512.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

3.6 First article inspection. When specified in the contract or purchase order, a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.2).

3.7 Soldering. All soldering shall be in accordance with the general requirements of MIL-STD-2000 in addition to detail requirement (TASK) F paragraph 1.2 of MIL-STD-2000.

3.8 Workmanship. The workmanship requirements of MIL-F-13926 shall apply.

4. QUALITY ASSURANCE PROVISIONS.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5 and all applicable drawings. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 General provision. The component and subassembly inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of quality terms shall be as listed in MIL-STD-109.

4.2 First article inspection.

4.2.1 First article submission. The contractor shall submit a first article sample as designated by the contracting officer consisting of three (3) Transmitter assemblies for inspection in accordance with 4.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

4.2.2 Inspections to be performed. First article assemblies, components and test specimens may be subjected by the Government to any or all of the examinations and tests specified in Table I (Functional Test) and Table II (Special Sampling) herein and to any or all requirements of the applicable drawings.

4.2.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any of the stated requirements.

4.3 Inspection provisions.

4.3.1 Submission of product. Shall be as specified by the contracting officer under submission of product.

4.3.2 Examination and tests.

4.3.2.1 Components and subassemblies. All components and subassemblies shall be inspected in accordance with the inspection provisions contained in Quality Assurance Provisions (QAPs) listed in the Technical Data Package (TDP). In the absence of a QAP, the applicable quality assurance provision of MIL-STD-454 and MIL-F-13926 shall apply.

4.3.2.2 Final acceptance inspection. Subsequent to first article approval, examination and tests related to Section 3 herein shall be performed on a single defect (individual characteristic) basis in accordance with the sampling plans specified in Table I herein. Examination and test for packaging and marking shall be in accordance with Section 5 herein. The tabulated classification of defects in Table I shall constitute the minimum inspection to be performed by the supplier after first article approval and prior to Government acceptance or rejection by item or lot.

TABLE I. Functional Test

(100% inspection)

Characteristic		Requirement	Test Procedure
Critical:		None	
Major:			
101.	Performance and compatibility	3.3	4.5.4
102.	Power requirements	3.4	4.5.4.3
103.	Soldering	3.7	4.6
104.	Workmanship	3.8	Visual
Minor:		None	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

4.3.3.1 Special sampling. One transmitter assembly shall be selected at random by a Government representative as a control sample from each 50 produced or from each month's production, whichever occurs first. The control sample shall meet the requirements and tests in Table II.

TABLE II. Special sampling

Control Test	Requirement	Test Procedure
201. Temperature (operating)	3.5.1.1	4.5.2, 4.5.2.2
202. Vibration (non-operating)	3.5.2	4.5.3.3
203. Shock	3.5.3	4.5.3.4
204. Drop test	3.5.4	4.5.3.5
205. Immersion test	3.5.5	4.5.3.6

4.3.3.2 Failure of sample. If any item of the special sample fails to meet the specified test requirements, acceptance of the product shall be suspended by Government until necessary corrections have been made by the contractor and a resubmitted sample has been approved (see 4.3.3).

4.4 Inspection equipment. Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of the contract. Prior to acceptance, inspection equipment designs shall be submitted and approved by the Government (see 6.3).

4.4.1 Government-furnished inspection equipment. Where the contract provides for Government-furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements of the contract.

4.4.2 Contractor-furnished inspection equipment.

4.4.2.1 Government design. Unless otherwise specified in the contract, all inspection equipment specified by drawing number in specifications or QAPs forming a part of the contract shall be supplied by the contractor in accordance with the applicable technical data listed in the TDP.

4.4.2.2 Contractor design. The contractor shall design and supply inspection equipment compatible with the "Methods of Inspection" specified in 4.5 of this specification and with the component inspection procedures specified in "Examination" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10 percent of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions, and tolerances used in the design of test equipment shall be so selected and controlled as to ensure that the test equipment will reliably indicate acceptability of a product which does not exceed 90 percent of the prescribed tolerance limit and permit positive rejection when nonconforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5 Methods of inspection.

4.5.1 Environment. Environment tests shall be conducted in accordance with the general requirements and test methods of MIL-STD-810 unless otherwise specified herein. Testing equipment used in environmental tests shall be in accordance with "Test Facilities and Apparatus" requirements of MIL-STD-810. If any one of the following tests are not met the item shall be rejected.

4.5.2 Operating.

4.5.2.1 Low temperature. Test shall be as specified in MIL-STD-810, Method 502, Procedure II, stabilized at -25 Degrees F. The assembly shall be operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

4.5.2.2 High temperature. Test shall be performed as specified in MIL-STD-810, Method 501 Procedure II. stabilized at +125 Degrees F. The assembly shall be operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

4.5.3 Non operating.

4.5.3.1 Low temperature. Test shall be performed as specified in MIL-STD-810, Method 502, Procedure I, Storage. After temperature stabilization for four hours at -40 Degrees F, the temperature shall be maintained for four additional hours. After temperature testing, the assembly shall be returned to ambient and stabilized for 4 hours and then operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

4.5.3.2 High temperature. Test shall be performed as specified in MIL-STD-810, Method 501, Procedure I, Storage. After temperature stabilization for four hours at +160 Degrees F, the temperature shall be maintained for four additional hours. After temperature testing, the assembly shall be returned to ambient and stabilized for 4 hours and then operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

4.5.3.3 Vibration. This test shall be performed as specified in MIL-STD-810, Method 514, Basic Transportation Test, Common Carrier, for one hour of random vibration along the vertical axis. After vibration the assembly shall be operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

4.5.3.4 Shock. This test shall be performed as specified in MIL-STD-810, Method 516 Procedure IV, Table 516.4-II. After the shock impulses, the assembly shall be operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

4.5.3.5 Drop test. This test shall be performed with the transmitter held in a random position and dropped three feet onto a surface of hard packed sand, one foot in depth. After the drop test, the assembly shall be operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

4.5.3.6 Immersion test. The test shall be performed on the transmitter as specified in MIL-STD-810, Method 512. The transmitter shall be immersed in water and subjected to a positive pressure equivalent to a three foot head of water for a two hour ± five minutes duration. After completion of the test, the transmitter shall meet the requirements of 3.5.5. After the immersion test, the assembly shall be operationally checked as specified in 4.5.4 to determine compliance with 3.3 and 3.4.

4.5.4 Performance and compatability tests.

4.5.4.1 Channel operational tests. The channel operational test shall be conducted per 3.3.2.

4.5.4.1.1 Government furnished materiel. Government furnished materiel (GFM) crystal set shall be installed in the transmitter. The frequency range of the crystal set shall be such that the transmitter shall operate at 138.0 MHz, 141.3 MHz, 143.4 MHz, 148.2 MHz and 150.77 MHz. GFM receivers per MIL-R-70834 will be provided to operate at each of the aforementioned frequencies. The first receiver shall be modified to adjust the octal (8) addressing capability (jumpers) per pattern identified in TDP 11784801.

4.5.4.1.2 Initial test setup. The GFM receiver for the first channel shall be installed in a GFM automatic tank target assembly per MIL-A-70833. Set the electronic control unit (ECU) to position one. Attach the GUFS simulator (GUFSS). No wooden target is required for the target lifting arm.

4.5.4.1.3 Transmitter test (column 1).

a. Place the transmitter channel selector knob to position A.

b. Operate the raise target push button switch (column 1) on the transmitter for the first receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

c. Operate the lower target push button switch (column 1) for the first receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

d. Operate the hit indicator push button switch (column 1) for the first receiver position. The GUFSS will light.

e. Change the octal addressing jumpers of the first GFM receiver to test the column 2 position of the transmitter.

f. Repeat paragraphs b. thru d. above, target lifting arm and GUFSS should not function.

4.5.4.1.4 Transmitter test (column 2).

a. Operate the raise target push button switch (column 2) on the transmitter for the second receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

b. Operate the lower target push button switch (column 2) for the second receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

c. Operate the hit indicator push button switch (column 2) for the second receiver position. The GUFSS will light.

4.5.4.1.5 Transmitter test (column 3).

a. Change the octal addressing jumpers of the first GFM receiver to test the column 3 position of the transmitter.

b. Operate the raise target push button switch (column 3) on the transmitter for the third receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

c. Operate the lower target push button switch (column 3) for the third receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

d. Operate the hit indicator push button switch (column 3) for the third receiver position. The GUFSS will light.

4.5.4.1.6 Transmitter test (column 4).

a. Change the octal addressing jumpers of the first GFM receiver to test the column 4 position of the transmitter.

b. Operate the raise target push button switch (column 4) for the fourth receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

c. Operate the lower target push button switch (column 4) for the fourth receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

d. Operate the hit indicator push button switch (column 4) for the fourth receiver position. The GUFSS will light.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

4.5.4.1.7 Transmitter test (column 5).

a. Change the octal addressing jumpers of the first GFM receiver to test the column 5 position of the transmitter.

b. Operate the raise target push button switch (column 5) for the fifth receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

c. Operate the lower target push button switch (column 5) for the fifth receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

d. Operate the hit indicator push button switch (column 5) for the fifth receiver position. The GUFSS will light.

4.5.4.1.8 Transmitter test (column 6).

a. Change the octal addressing jumpers of the first receiver to test the column 6 position of the transmitter.

b. Operate the raise target push button switch (column 6) for the sixth receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

c. Operate the lower target push button switch (column 6) for the sixth receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

d. Operate the hit indicator push button switch (column 6) for the sixth receiver position. The GUFSS will light.

4.5.4.1.9 Transmitter test (column 7).

a. Change the octal addressing jumpers of the first GFM receiver to test the column 7 position of the transmitter.

b. Operate the raise target push button switch (column 7) for the seventh receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

c. Operate the lower target push button switch (column 7) for the seventh receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

d. Operate the hit indicator push button switch (column 7) for the seventh receiver position. The GUFSS will light.

4.5.4.1.10 Transmitter test (column 8).

a. Change the octal addressing jumpers of the first GFM receiver to test the column 8 position of the transmitter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

b. Operate the raise target push button switch (column 8) for the eighth receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

c. Operate the lower target push button switch (column 8) for the eighth receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

d. Operate the hit indicator push button switch (column8) for the eighth receiver position. The GUFSS will light.

4.5.4.2 Frequency operation test. The frequency operation test of the transmitter shall be conducted per 3.3.3 at the maximum and minimum frequency ranges and at approximately equally spaced frequencies within this range.

4.5.4.2.1 Transmitter test (channel B, column 2).

a. Change the octal addressing jumpers of the second GFM receiver to test the channel B and the column 2 position of the transmitter.

b. Set the transmitter channel selector knob to position B.

c. Operate the raise target push button switch (column 2) for the second receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

d. Operate the lower target push button switch (column 2) for the second receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

e. Operate the hit indicator push button switch (column 2) for the second receiver position. The GUFSS will light.

4.5.4.2.2 Transmitter test (channel C, column 4).

a. Change the octal addressing jumpers of the third GFM receiver to test the channel C and the column 4 position of the transmitter.

b. Set the transmitter channel selector knob to position C.

c. Operate the raise target push button switch (column 4) for the fourth receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

d. Operate the lower target push button switch (column 4) or the fourth receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

e. Operate the hit indicator push button switch (column 4) for the fourth receiver position. The GUFSS will light.

4.5.4.2.3 Transmitter test (channel D, column 6).

a. Change the octal addressing jumpers of the fourth GFM receiver to test the channel D and the column 6 position of the transmitter.

b. Set the transmitter channel selector knob to position D.

c. Operate the raise target push button switch (column 6) for the sixth receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

d. Operate the lower target push button switch (column 6) for the sixth receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

e. Operate the hit indicator push button switch (column 6) for the sixth receiver position. The GUFSS will light.

4.5.4.2.4 Transmitter test (channel E, column 8).

a. Change the octal addressing jumpers of the fifth GFM receiver to test the channel E and the column 8 position of the transmitter.

b. Set the transmitter channel selector knob to position E.

c. Operate the raise target push button switch (column 8) for the eighth receiver position. The target lifting arm will rotate 90 degrees and raise to the up position.

d. Operate the lower target push button switch (column 8) for the eighth receiver position. The target lifting arm will rotate 90 degrees and return to the down position.

e. Operate the hit indicator push button switch (column 8) for the eighth receiver position. The GUFSS will light.

4.5.4.3 Power output test. Operate transmitter and measure power output with use of suitable power meter which has the RF transmitted capability of measuring a 6 watt output at the frequencies specified in 3.4a.

4.6 Soldering. Soldering processes shall be inspected by certified inspectors to the requirements and acceptance criteria of MIL-STD-2000 as specified in 3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 General. Preservation, packaging, packing and marking shall be in accordance with special packaging instructions PS11784701.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This specification details the specific requirements for performance, quality assurance, and testing for the transmitter assembly. The transmitter shall remotely operate with the Target Holding Mechanism/Tank Gunnery (THM/TG) in the operation of raising and lowering armored targets for the training of armored, infantry and airborne units.

6.2 Acquisition requirements. Procurement documents shall specify the following:

6.2.1 Procurement requirements.

a. Title, number and date of this specification.

b. Quantity required and delivery schedules. Crystal sets required per technical data.

c. Place of inspection, if not at place of manufacture.

d. Instructions for shipment of production lot samples.

e. Provision for preparation for delivery, if required for indefinite storage of inter-plant shipment.

f. Provisions for the supply, maintenance and disposition of test equipment for acceptance inspection process.

g. Procuring activity designation assembly number(s) and nomenclature(s).

h. Serialization requirement, if applicable.

i. Packaging requirements, if other than specified in Section 5.

j. Certificate of conformance for each lot or shipment of product.

k. Group code and frequencies.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

6.3 Submission of contractor inspection equipment designs for approval. Submit two copies of designs as required to: Commander, U.S. Army AMCCOM, ATTN: AMSMC-QAF-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament, Research, Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as, U.S. Army Armament, Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Definitions.

6.5.1 Trainers. Training device terms are defined in MIL-HDBK-220. Other definitions, if required, will be furnished upon written request to the Procuring Contracting Officer.

6.5.2 Contractor. Unless otherwise specified, the word Contractor used throughout this specification shall mean any supplier or producer of items or material to the Government. This shall include commercial contractors, sub-contractors, Government Owned-Contractor Operated (GOCO), and Government Owned-Government Operated (GOGO) plants.

6.5.3 Technical data package. A technical description of an item adequate for use in procurement. The description defines the required design configuration and assures adequacy of item performance. It consists of all applicable technical data such as plans, drawings, and associated lists, specifications, standards, models, performance requirements, quality assurance provisions and packaging data.

6.6 Subject term (Keyword) listing

a. Target Holding Mechanism/Tank Gunnery (THM/TG)
b. Gunfire Simulator (GUFS)
c. Gunfire Simulator Simulator (GUFSS)
d. Visual Hit Indicator Lamp (VHIL)

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 5895-A422)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:09Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-70835A(AR)	29 March 1991

3. DOCUMENT TITLE

TRANSMITTER, ASSEMBLY: 11784701

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
US ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial (201) 724-6662	(2) AUTOVON 880-6662
c. ADDRESS (Include Zip Code) ATTN: SMCAR-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:09Z
Check the source to verify that this is the current version before use.