INCH-POUND

MIL-DTL-83729/3D
28 February 2018
SUPERSEDING
MIL-DTL-83729/3C
02 April 2013

DETAIL SPECIFICATION SHEET

CHOPPERS, ELECTROMECHANICAL, HERMETICALLY SEALED, SINGLE POLE, DOUBLE THROW, BREAK BEFORE MAKE, BRACKET MOUNT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83729.





Letter	Inches	mm	Letter	Inches	mm
A	1.750	44.45	F	.562	14.27
B	1.438	36.53	G	.282	7.16
C	.800	20.32	H	.719	18.26
D	.025	.64	J	.125	3.18
E	.562	14.27	K	.125	3.18

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ± .005 (.13 mm).
4. When the coil is de-energized the center reed may be in any of 3 positions.
5. Pierced pin .043 (1.09 mm) diameter hole typical pin location to match standard 7 pin miniature tube socket.
6. Letter G has a tolerance of ± .015 (.38 mm).

FIGURE 1. Outline drawing, terminal arrangement and schematic diagram.

AMSC N/A

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Single pole, double throw, break before make.
Polarity: With pins 7 and 6 open apply positive voltage to pin 3 and negative voltage to pin 4. Pins 7 and 6 shall show closed condition.
Voltage and current: 0.1 millivolt to 10 volts direct current, 2 milliamperes resistive, maximum.

Coil data:

Voltage rated: 6.3Vrms.
Resistance: 155 ohms ± 10 percent.
Impedance: 250 ohms ± 25 percent at 400 Hz with 6.3 volts applied at 25°C ± 5°.
Frequency range: Single phase, 400 ± 20 Hz sine wave.

Waveform characteristics (at 25°C):

Dwell time: See table I.
Dissymmetry: 15° maximum.
Transfer time: 15° maximum.
Phase angle: See table I and table II.

Noise level: 200 microvolts rms at 1 megohms impedance. See figure 2 for test circuit. Use a model RM122 Tektronix, or equivalent, low level preamplifier 1-1,000 gain, bandwidth 0.8 to 1,000 Hz and feed into a Ballantine model 320A vacuum tube voltmeter (VTVM) or equivalent. Drive chopper with center tap grounded source of 6.3 volts, 400 Hz, and switch to connect each of the three contacts, in turn, into the preamplifier. Noise shown on Ballantine meter rms, above system noise, is the chopper noise.

Environmental conditions:

Dielectric withstanding voltage (at sea level): 200 volts rms 60 Hz or 280 Vdc for 1 minute between contacts and coil terminals, coil terminals and case, and contacts and case.
Insulation resistance: Test condition A, 100 megohms minimum between mutually insulated terminals and between terminals and case.
Vibration II (10 – 500 Hz): MIL-STD-202-204, test condition A.
Before test: Dynamic contact resistance (method II) applicable.
After test: The chopper shall be tested for dynamic contact resistance, dwell time at 25°C only, phase angle, contact bounce, dielectric withstanding voltage, dissymmetry, and transfer time.
Shock: MIL-STD-202-213, test condition H (75 g's).
Electrical load conditions: The chopper coil and contacts shall be energized with rated voltage and load, as applicable, during two of the three shocks in each direction along each of the three mutually perpendicular axes.
Test and measurements: After shock testing, the chopper shall be tested for dynamic contact resistance, dwell time, at 25°C only, phase angle, contact bounce, dielectric withstanding voltage, dissymmetry and transfer time.
Temperature range: -40°C ± 125°C

Life: 2,000 hours.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:31Z
Check the source to verify that this is the current version before use.



FIGURE 2. Noise test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:31Z
Check the source to verify that this is the current version before use.

Mechanical:

Weight: .094 pound, maximum.

Dimensions: See figure 1.

Enclosure: Hermetically sealed.

Terminals: Flattened and pierced, solder type.

Finish: Navy gray enamel, capable of withstanding the environmental conditions specified without chipping, peeling or otherwise deteriorating. Before applying finish, the surface must be conditioned as specified in MIL-DTL-14072.

TABLE I. High and low temperatures.

	Temperature °C	Frequency Hz	Voltage Vrms	Limits
Dwell time	-40 to 85	400 ± 5%	6.3	115° to 165°
	-20 to 85			65° +10° -15°
Phase angle	-40 to 85	400	6.3	65° ± 15°

Room temperature: The chopper shall be tested at 25°C in accordance with table II.

TABLE II. Room temperature.

Frequency Hz	Voltage	Phase angle
400	6.3	65° +5° -10°
420	5.86	79° maximum
380	6.74	51° maximum

Part or Identifying Number (PIN): M83729/3-001.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-DTL-83729, this document references the following:
MIL-STD-202-204 MIL-STD-202-213 MIL-DTL-14072

Custodian activities:
Navy – EC
AF-99
DLA – CC

Preparing activity:
DLA – CC

(Project 5945-2018-007)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:31Z
Check the source to verify that this is the current version before use.