INCH-POUND


MIL-DTL-83729/6C
w/AMENDMENT 1
22 March 2018
SUPERSEDING
MIL-DTL-83729/6C
13 March 2013


DETAIL SPECIFICATION SHEET

CHOPPERS, ELECTROMECHANICAL, HERMETICALLY SEALED, SINGLE POLE, DOUBLE THROW, BREAK BEFORE MAKE

This specification is approved for use by all Departments and Agencies of the Department of the Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83729.





SCHEMATIC DIAGRAM

Letter	Inches	mm
A	.763	19.38
B	1.438 MAX	36.53
B	1.391 MIN	35.33
C	.763 MAX	19.38
C	.745 MIN	18.92
D	.265 MAX	6.73
D	.235 MIN	5.97
E	.375	9.53

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances is ± .005 (.13 mm).
4. Manner of presenting the diagram is optional. Numbers are not required if shown with respect to terminal arrangement.
5. When the coil is de-energized the center reed may be in any of 3 positions.

FIGURE 1. Outline drawing, terminal arrangement and schematic diagram.

AMSC N/A

FSC 5945

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Contact data:

Single pole, double throw, break before make.
Polarity: With positive dc voltage on pin 3 and negative voltage on pin 4, pins 6 and 7 are closed.
Voltage and current: Dry circuit to 100 volts, 2 milliamperes dc resistive (maximum intermittent rating) 10 volts, 1 milliampere continuous dc resistive rating.

Coil data:

Voltage rated: 6.3 volts ± 0.6 volts rms.
Resistance, dc: 155 ohms ± 10 percent at 25°C.
Impedance: See table I.
Frequency range: See table I.

Waveform characteristics (6.3 volts at 25°C ± 5°C):

Dwell time: See table I.
Dissymmetry: 15° maximum.
Transfer time: See table I.
Phase angle: See table I.

Noise level: See table I.

Environmental conditions:

Dielectric withstanding voltage: See table I.
Insulation resistance: Between terminals and case 1,000 megohms at 100 volts dc.
Vibration III: Nonoperating, MIL-STD-202-204, condition A, except 5 g's maximum.
Shock: Nonoperating, 100 g's as specified in MIL-STD-202-213, test condition I.
Temperature range: -65°C to +125°C.

Life: 5,000 hours minimum at dry circuit, 25°C ± 5°C.

Mechanical:

Weight: .09 pound, maximum.
Dimensions: See figure 1.
Enclosure: Hermetically sealed, chopper mates with JAN TS102P01 socket with a TS102U02 tube shield to secure in the socket.
Terminal strength: 2.5 pounds.
Mounting position: Any.

Part or Identifying Number (PIN): M83729/6- (dash number from table I).

TABLE I. Dash number and characteristics.

Dash number	Imped-ance	Frequency range	Dwell time	Transfer time	Phase angle	Noise level	Dielectric Withstanding voltage
001	250 ± 20% at 25°C	400 ± 20 Hz	130° to 165°	15° min	65° ± 15°	200 microvolts rms above system noise level with 1.0 meg-ohm load resistor.	200 V rms at 60 Hz or 280 V dc
002	175 ± 20% at 25°C	60 ± 5%	150° min	3° min	20° ± 5°	50 microvolts rms above system noise level with 1.0 meg-ohm load resistor.	200 V rms at 60 Hz or 280 V dc

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-83729, this document references the following:
MIL-STD-202-204 MIL-STD-202-213

Custodian activities:
Army – CR
Navy – EC
Air Force – 85
DLA – CC

Preparing activity:
DLA – CC

(Project 5945-2018-008)

Review activities:
Army – AT, MI
Navy – AS, MC, OS
Air Force – 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.