INCH-POUND

MIL-PRF-83726/29D
AMENDMENT 2
15 February 2000

SUPERSEDING
AMENDMENT 1
15 October 1999

PERFORMANCE SPECIFICATION SHEET

RELAY, HYBRID, TIME DELAY (ON RELEASE), CLASS B, TYPE IIA,
HERMETICALLY SEALED, DPDT, 10 AMPERES, FIXED TIME, 0.1 TO 500 SECONDS

This amendment forms a part of MIL-PRF-83726/29D, dated 15 June 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1. Outline dimensions and configuration of relay. delete hook terminal length of ".300" and substitute ".310 MAX"

PAGE 4

* Transient: delete "+80 volts in accordance with MIL-STD-704, figure 9, limit 1." and substitute "In accordance with MIL-STD-704 for 28 volts dc system (figure 11)."

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Navy - OS
Air Force - 19

Preparing activity:
DLA - CC

(Project 5945-1076-03)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:29Z
Check the source to verify that this is the current version before use.