INCH-POUND

MIL-PRF-83726/30E
AMENDMENT 2
15 February 2000

SUPERSEDING
AMENDMENT 1
15 October 1999

PERFORMANCE SPECIFICATION SHEET

RELAY, HYBRID, TIME DELAY (ON OPERATE), CLASS B, TYPE I, HERMETICALLY SEALED, DPDT, 10 AMPERES, ADJUSTABLE TIME DELAY (EXTERNAL RESISTOR), 0.1 TO 500 SECONDS

This amendment forms a part of MIL-PRF-83726/30E, dated 15 June 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1. Outline dimensions and configuration of relay. delete "+" sign next to the "C1" terminal.

PAGE 4

* Transients: delete "+80 volts in accordance with MIL-STD-704, figure 9, limit 1." and substitute "In accordance with MIL-STD-704 for 28 volts dc system (figure 11)."

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Navy - OS
Air Force - 19

Preparing activity:
DLA - CC

(Project 5945-1076-04)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:29Z
Check the source to verify that this is the current version before use.