A-A-53640
12 August 1988

# COMMERCIAL ITEM DESCRIPTION

## DRIVER-BENDER-EXTRACTOR, Bone Pin (McNutt, 13 Inches)

The General Services Administration has authorized the use of this Commercial Item Description.

This commercial item description covers a driver-bender-extractor of the McNutt design suitable for use with Rush pin instrumentation during orthopedic procedures.

Salient characteristics:

General. The driver-bender-extractor shall consist of a handle, a slender shaft, and a cannulated ram.

Handle. The handle shall be of one piece construction. The end of the handle shall be beveled out.

Shaft. The shaft shall be permanently attached to the proximal end of the handle at its axial centerline.

Cannulated ram. The cannulated ram shall slide along the shaft without impedance.

Material. The material of the driver-bender-extractor shall be fabricated of a suitable austentic corrosion-resisting steel in accordance with ASTM Designation F899.

Hardness. The driver-bender-extractor shall have a Rockwell C Scale (HRC) of 25 to 30. The hardness shall be tested in accordance with ASTM Designation E18 or ASTM Designations E92 and E140.

Style and design. The driver-bender-extractor shall be in accordance with Figure 1 for style and design.

Finish. The driver-bender-extractor shall have a smooth, satin finish. The driver-bender-extractor shall have no surface depressions, pits, or exhibit porosity.

Passivation. The driver-bender-extractor shall be properly passivated.

AMSC N/A FSC 6515

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:22Z
Check the source to verify that this is the current version before use.

Resistance to corrosion. Driver-bender extractor shall show no evidence of corrosion when tested in accordance with ASTM Designation F1089.

Identification marking. The driver-bender-extractor shall bear the contractor's name or registered trademark and the word "stainless". The driver-bender-extractor shall bear the name of the country of origin.

Workmanship. The driver-bender-extractor shall be free from defects which detract from its serviceability.

Unit. Each (EA). One driver-bender-extractor, as specified, constitutes one unit.

Quality Assurance Provisions.

Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Inspection. Inspection, as used herein, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Tests. Tests shall be conducted to determine compliance with specification requirements. Where feasible, the same sample shall be used for the determination of two or more test characteristics.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:22Z
Check the source to verify that this is the current version before use.

Sampling for tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and as specified herein. The acceptable quality level (AQL) shall be 1.0 for an inspection level of S-2. The unit of product for test purposes shall be one driver-bender-extractor.

Contractor certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producers' own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within the tolerances specified using conversion tables contained in the latest revision of Federal Standard No. 376, and all other requirements of this document are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements.

Federal Food, Drug and Cosmetic Act. If the product covered by this document has been determined by the U.S. Food and Drug Administration to be under its jurisdiction, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of the Federal Food, Drug and Cosmetic Act, as amended, and regulations promulgated thereunder. In addition, the offeror/contractor shall comply, and be responsible for compliance by its subcontractors/suppliers, with the requirements of all other applicable Federal, State, and local statutes, ordinances, and regulations.

Recovered materials. The offeror/contractor is encouraged to use recovered material in accordance with Public Law 94-580, as amended, and as implemented by Federal Acquisition Regulation Subpart 23.4 to the maximum extent practical.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:22Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Unless otherwise specified, preservation, packaging, and packing shall be to a degree of protection to preclude damage to containers and or contents thereof under normal shipping conditions, handling, etc., involving shipment from the supply source to the receiving activity, plus reshipment from receiving activity, and shall conform to applicable carrier's rules and regulations. Intermediate and exterior package quantities and labeling and marking shall be as specified in the contract and/or order.

NOTE: The following National Stock Number is covered by this document:

| NSN | ITEM IDENTIFICATION |
|---|---|
| 6515-01-139-7957 | DRIVER-BENDER-EXTRACTOR, BONE PIN McNutt, 13 Inch (33.02 cm) Long |

Ordering data: Intermediate/exterior package quantities, labeling, and marking must be specified in the contract and or order).

MILITARY INTERESTS:

Custodians:

Army - MD
Navy - MS
Air Force - 03

PREPARING ACTIVITY:

DoD - MB

Agent.

DLA-DM

CIVIL AGENCY COORDINATING ACTIVITIES:

VA-OSS
PHS
FDA-MPQAS

Project No. 6515-3274



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:22Z
Check the source to verify that this is the current version before use.





FIGURE 1 DRIVER-BENDER-EXTRACTOR, BONE-PIN, McNUTT, 13 INCH

| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES | | |
|---|---|---|
| TOLERANCES ON | | |
| FRACTIONS | DECIMALS | ANGLES |
| ± 1/8 | ± | ± |

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:22Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS In [illegible] effort to make [illegible] standardization documents better, the DoD provides this form for [illegible] putting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Commander
Defense Personnel Support Center
ATTN: DPSC-RSTE
2800 South 20th Street
Philadelphia, Pennsylvania 19101-8419

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:22Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1 DOCUMENT NUMBER | 2 DOCUMENT TITLE |
|---|---|
| A-A-53640 | DRIVER-BENDER-EXTRACTOR, Bone Pin (McNutt, 13 Inches) |

| 3a NAME OF SUBMITTING ORGANIZATION | 4 TYPE OF ORGANIZATION (Mark one) |
|---|---|
| | ☐ VENDOR |
| | ☐ USER |
| b ADDRESS (Street, City, State, ZIP Code) | ☐ MANUFACTURER |
| | ☐ OTHER (Specify) _____ |

5 PROBLEM AREAS

a Paragraph Number and Wording

b Recommended Wording

c Reason For Recommendation

6 REMARKS

| 7a NAME OF SUBMITTER (Last, First, MI) – Optional | b WORK TELEPHONE NUMBER (Include Area Code) – Optional |
|---|---|
| c MAILING ADDRESS (Street, City, State, ZIP Code) – Optional | 8 DATE OF SUBMISSION (YYMMDD) |

(FOLD ON THIS LINE)

(FOLD ON THIS LINE)

DD FORM 1426 82 MAR PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:22Z
Check the source to verify that this is the current version before use.