FED. SUP CLASS 5330



** ALL DIAMETERS OF CROSS SECTION SHALL EQUAL W



DASH SIZE	ACTUAL SIZE W DIA		I DIA	
001	.040	±.003	.029	±.004
002	.050		.042	
003	.060		.056	
004	.070		.070	±.005
005			.101	
006			.114	
007			.145	
008			.176	
009			.208	
010			.239	
011			.301	
012			.364	
013			.426	
014			.489	
015			.551	
016			.614	
017			.676	
018			.739	
019			.801	±.006
020			.864	
021			.926	
022			.989	
023			1.051	
024			1.114	
025			1.176	
026			1.239	
027			1.301	
028			1.364	
029			1.489	±.010
030			1.614	
031			1.739	
032			1.864	
033			1.989	
034			2.114	
035			2.239	
036			2.364	
037			2.489	
038			2.614	
039			2.739	±.015
040			2.864	
041			2.989	
042			3.239	
043			3.489	
044			3.739	
045			3.989	
046			4.239	
047			4.489	
048			4.739	
049			4.989	±.023
050	.070	±.003	5.239	
110	.103	±.003	.362	±.005
111			.424	
112			.487	
113			.549	
114			.612	
115			.674	
116			.737	
117			.799	±.006
118			.862	
119			.924	
120			.987	
121			1.049	
122			1.112	
123			1.174	
124			1.237	
125			1.299	
126			1.362	
127			1.424	
128			1.487	
129			1.549	±.010
130			1.612	
131			1.674	
132			1.737	
133			1.799	
134			1.862	
135			1.925	
136			1.987	
137			2.050	
138			2.112	
139			2.175	
140			2.237	
141			2.300	
142			2.362	
143			2.425	
144			2.487	
145			2.550	
146			2.612	
147			2.675	±.015
148			2.737	
149			2.800	
150			2.862	
151			2.987	
152			3.237	
153			3.487	
154			3.737	
155			3.987	
156			4.237	
157			4.487	
158			4.737	
159			4.987	
160			5.237	±.023
161			5.487	
162			5.737	
163			5.987	
164			6.237	
165			6.487	
166			6.737	
167			6.987	
168			7.237	±.030
169			7.487	
170			7.737	
171			7.987	
172			8.237	
173	.103	±.003	8.487	
174	.103	±.003	8.737	±.030
175			8.987	
176			9.237	
177			9.487	
178	.103	±.003	9.737	
210	.139	±.004	.734	±.006
211			.796	
212			.859	
213			.921	
214			.984	
215			1.046	
216			1.109	
217			1.171	
218			1.234	
219			1.296	
220			1.359	
221			1.421	
222			1.484	
223			1.609	±.010
224			1.734	
225			1.859	
226			1.984	
227			2.109	
228			2.234	
229			2.359	
230			2.484	
231			2.609	
232			2.734	±.015
233			2.859	
234			2.984	
235			3.109	
236			3.234	
237	.139	±.004	3.359	
238	.139	±.004	3.484	±.015
239			3.609	
240			3.734	
241			3.859	
242			3.984	
243			4.109	
244			4.234	
245			4.359	
246			4.484	
247			4.609	
248			4.734	
249			4.859	
250			4.984	
251			5.109	±.023
252			5.234	
253			5.359	
254			5.484	
255			5.609	
256			5.734	
257			5.859	
258			5.984	
259			6.234	
260			6.484	
261			6.734	
262			6.984	
263			7.234	±.030
264			7.484	
265			7.734	
266			7.984	
267			8.234	
268			8.484	
269			8.734	
270			8.984	
271			9.234	
272			9.484	
273			9.734	
274			9.984	
275			10.484	
276			10.984	
277			11.484	
278			11.984	
279			12.984	
280			13.984	
281			14.984	
282			15.955	±.045
283			16.955	
284	.139	±.004	17.955	

(C) FOR CHANGES SEE SHEETS 1 & 2

APPROVED 11 Mar 52 REVISED (A) 22 Aug 53 (B) 8 May 63 (C) 16 Sep 64

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Review activities:
Navy - [illegible]
USAF - 11
Army - AT

P.A. USAF-11 Other Cust Navy-AS Army-AT	INTERNATIONAL INTEREST	TITLE PACKING, PREFORMED, HYDROCARBON FUEL RESISTANT, "O" RING
PROCUREMENT SPECIFICATION MIL-P-5315		SUPERSEDES: [illegible]

MILITARY STANDARD

MS29513

SHEET 1 OF 2

DD FORM 1 OCT 54 672-1

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PROJ. NO. 5330-0170

DATE

DRAWN BY ____________ ______

TYPED BY ____________ ______

CHECKED BY ____________ ______

6329

NOTES TO PRINTER: REDUCE BORDER TO 6 3/4 X 9-3/4. PRINT LEFT BORDER-LINE ONE INCH FROM LEFT EDGE OF 8x10-1/2 SHEET. PRINT BOTTOM BORDER LINE 3/4 INCH FROM BOTTOM EDGE OF 8x10-1/2 SHEET. SIGNATURE BOXES NOT TO BE INCLUDED ON 8x10-1/2 SHEET.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:01Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS
5330

RING SIZE	ACTUAL SIZE W DIA		I DIA	
325	.210	±.005	1.475	±.020
326			1.600	
327			1.725	
328			1.850	
329			1.975	
330			2.100	
331			2.225	
332			2.350	
333			2.475	
334			2.600	
335			2.725	±.025
336			2.850	
337			2.975	
338			3.100	
339			3.225	
340			3.350	
341			3.475	
342			3.600	
343			3.725	
344			3.850	
345			3.975	
346			4.100	
347			4.225	
348			4.350	
349			4.475	
350			4.600	
351			4.725	
352			4.850	
353			4.975	
354			5.100	±.023
355			5.225	
356			5.350	
357			5.475	
358	.210	±.005	5.600	
359	.210	±.005	5.725	±.023
360			5.850	
361			5.975	
362			6.225	
363			6.475	
364			6.725	
365			6.975	
366			7.225	±.037
367			7.475	
368			7.725	
369			7.975	
370			8.225	
371			8.475	
372			8.725	
373			8.975	
374			9.225	
375			9.475	
376			9.725	
377			9.975	
378			10.475	
379			10.975	
380			11.475	
381			11.975	
382			12.975	
383			13.975	
384			14.975	
385			15.955	±.045
386			16.955	
387			17.955	
388			18.955	
389			19.955	
390			20.955	
391			21.955	
392			22.940	±.070
393			23.940	
394			24.940	
395	.210	±.005	25.940	
425	.275	±.006	4.475	±.025
426			4.600	
427			4.725	
428			4.850	
429			4.975	
430			5.100	±.033
431			5.225	
432			5.350	
433			5.475	
434			5.600	
435			5.725	
436			5.850	
437			5.975	
438			6.225	
439			6.475	
440			6.725	
441			6.975	
442			7.225	±.030
443			7.475	
444			7.725	
445			7.975	
446			8.475	
447			8.975	
448			9.475	
449			9.975	
450			10.475	
451			10.975	
452			11.475	
453			11.975	
454			12.475	
455			12.975	
456			13.475	
457			13.975	
458			14.475	
459			14.975	
460			15.475	
461			15.955	±.045
462			16.455	
463			16.955	
464			17.455	
465			17.955	
466			18.455	
467			18.955	
468			19.455	
469			19.955	
470			20.955	
471			21.955	
472	.275	±.006	22.940	[illegible]
473	.275	±.006	23.940	±.060
474			24.940	
475	.275	±.006	25.940	

Ⓒ CERTAIN PROVISIONS (RING SIZE (DASH NUMBER), SIZES, AND TOLERANCES) OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT ABC AIR STD 17/[illegible] AND [illegible]. WHEN REVISION OR CANCELLATION OF THIS STANDARD IS PROPOSED, THE DEPARTMENTAL CUSTODIANS WILL INFORM THEIR RESPECTIVE DEPARTMENTAL STANDARDIZATION OFFICE SO THAT APPROPRIATE ACTION MAY BE TAKEN RESPECTING THE INTERNATIONAL AGREEMENT CONCERNED.

DIMENSIONS IN INCHES.

Ⓒ REVISED TO ADD 026 THRU 050, 155 THRU 178, 275 THRU 284, 359 THRU 395, 461 THRU 475.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

APPROVED 13 [illegible] REVISED Ⓒ FOR CHANGES SEE SHEETS 1 AND 2.

This military standard is approved by the Department of Defense and is mandatory on all activities. [illegible] for all new engineering and design applications and for repetitive use shall be made from this document.

Review activities: [illegible]

P.A. USAF-11 Other Cust Navy-AS Army-AV	INTERNATIONAL INTEREST	TITLE PACKING, PREFORMED, HYDROCARBON FUEL RESISTANT, O-RING
PROCUREMENT SPECIFICATION MIL-P-5315	SUPERSEDES USAF 93[illegible]	SHEET 2 OF

MILITARY STANDARD

MS29513

DD FORM 672-1

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

NOTES TO PRINTER: REDUCE BORDER TO 6-27/32x9-3/4. PRINT LEFT BORDER-LINE ONE INCH FROM LEFT EDGE OF 8-1/2x11 SHEET. PRINT BOTTOM BORDER LINE [illegible] FROM BOTTOM EDGE OF [illegible] SHEET. SIGNATURE FORM NOT TO BE INCLUDED ON 8-1/2x11 PRINT.

ASSIGNED BY ______
TYPED BY ______
CHECKED BY ______
DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:01Z
Check the source to verify that this is the current version before use.