FED. SUP CLASS
2995

ENGINE DRIVE PAD		DRIVE RATINGS			ACCESSORY		ACCESSORY ATTACHMENT DATA					ACCESSORY FLANGE DWG. NO.	DRIVE PAD COVER DWG. NO.
MS NO.	DASH NO.	MS3335 SPLINE PITCH DIA., IN.	NOMINAL SPEED, RPM	RATED TORQUE, LB.IN.	RATED POWER, HP	WEIGHT LB.	STATIC OVERHUNG MOMENT LB.IN.	ENGINE STUD SPACING AND SIZE	BOLT CIRCLE DIA.,IN.	FLANGE CONFIGURATION	V-BAND CLAMPING FLANGE DIA., IN.		
MS3325	-1	0.4583	16,000	150	---	5	15	90° .250-28 UNJF-3A	2.653	SQUARE	NONE	MS3330	AN100043
	-2	0.4583	4,200	15	---	5	15						
MS3326	-1	0.600	12,000	---	6	20	60	90° .3125-24 UNJF-3A	5.000	SQUARE	NONE	MS3331	AN100036
	-2	0.600	12,000	---	12	35	150						
	-3	0.800	8,000	600	---	25	100						
	-4	0.800	16,000	300	---	25	100						
	-5S	0.600	3,300	750	---	20	60						
	-6S	0.600	3,300	1,500	---	35	150						
MS3327	-1	0.800	8,000	---	30	80	500	66° .375-24 UNJF-3A	5.000	ROUND	6.400	MS3332	MS9950
	-2	0.800	12,000	---	30	50	300						
	-3	0.800	8,000	500	---	25	125						
	-4	1.200	4,000	1000	---	30	200						
	-5	1.200	6,000	1500	---	50	350						
	-6	1.200	4,000	1500	---	75	625						
	-7S	0.800	3,300	1800	---	70	450						
	-8S	1.200	3,300	4800	---	80	625						
	-9S	1.200	3,300	7200	---	80	700						
MS3328	-1	0.800	8,000	---	30	80	750	45° .375-24 UNJF-3A	8.000	ROUND	9.400	MS3333	MS9949
	-2	0.800	12,000	---	30	100	1200						
	-3	1.200	8,000	---	40	115	1250						
	-4	1.200	8,000	---	65	150	2000						
	-5	0.800	8,000	---	30	65	350						
	-6	0.800	12,000	---	30	50	250						
	-7	0.800	3,000	---	45	75	500						
	-8	1.625	4,000	4000	---	125	600						
	-9	1.625	6,000	4000	---	125	600						
	-10S	1.200	3,300	7200	---	80	860						
	-11S	1.625	3,300	14,400	---	120	1300						
MS3329	-1	1.200	8,000	---	60	135	1700	30° .375-24 UNJF-3A	10.000	ROUND	11.400	MS3334	MS9948
	-2	1.200	8,000	---	80	150	2000						
	-3	1.625	8,000	---	120	175	2500						
	-4	1.625	8,000	---	180	225	3000						
	-5	1.625	8,000	---	240	275	3600						
	-6	0.800	6,000	---	45	90	550						
	-7	0.800	6,000	---	65	100	600						
	-8	1.200	6,000	---	95	125	750						
	-9	1.200	6,000	---	140	150	1100						
	-10	1.200	6,000	---	200	175	1500						
	-11	1.625	4,000	4000	---	125	600						
	-12	2.000	4,000	9000	---	200	1200						

APPROVED 4 June 1970 REVISED

P.A. NAVY - AS
Other Cust

TITLE
ACCESSORY DRIVES, AIRCRAFT ENGINE, REFERENCE CHART FOR

MILITARY STANDARD
MS3336(AS)

PROCUREMENT SPECIFICATION

SUPERSEDES:

SHEET 1 OF 1

DD FORM 672-1 (Limited coordination)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PLATE NO. 17709

This standard has been approved by the NAVAL AIR SYSTEMS COMMAND Department of the NAVY, and is mandatory for use by the Department of the NAVY. All other military activities are required to employ this standard when suitable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:02Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:02Z
Check the source to verify that this is the current version before use.