MS9443 (ASG)

FED SUP CLASS
5306


MARK MS9443 AND MANUFACTURERS IDENTIFICATION PER AS 478 CLASS A
.564
.553
.631 MIN
MS9443
.188 DIA TO DEPTH SHOWN
.070 DIAMETER CSK 90° TO .100 DIA 6 HOLES EQUALLY SPACED AS SHOWN WITHIN .020 OF TRUE POSITION
63
.296
.216
L
K
.118 TO POINT
.016 OR CHAMFER
MAXIMUM 2 IMPERFECT THREADS (SEE NOTE 4)
CHAMFER .047 x 45° APPROX.
63
.562 DIA
.025
.015 R
.351
.341 DIA
THIS SURFACE MUST BE SQUARE WITH SHANK WITHIN .003 FIR
CHAMFER 30° TO .562 DIAMETER (OPPOSITE SIDE OPTIONAL)
.375-24 UNJF-3A MIL-S-8879
32
SECTION THROUGH THREAD PROFILE

PART NUMBER	L	K	APPROX WEIGHT LB/100
MS9443-04	.625	.088- .108	3.69
MS9443-05	.688	.088- .108	3.86
MS9443-06	.750	.088- .108	4.02
MS9443-07	.812	.088- .108	4.19
MS9443-08	.875	.088- .108	4.36
MS9443-09	.938	.088- .108	4.53
MS9443-10	1.000	.088- .108	4.70
MS9443-11	1.062	.088- .108	4.86
MS9443-12	1.125	.125- .145	5.03
MS9443-13	1.188	.128- .188	5.20
MS9443-14	1.250	.190- .250	5.37
MS9443-15	1.312	.252- .312	5.54
MS9443-16	1.375	.315- .375	5.70
MS9443-17	1.438	.378- .438	5.87
MS9443-18	1.500	.440- .500	6.04
MS9443-19	1.562	.502- .562	6.21
MS9443-20	1.625	.565- .625	6.38
MS9443-21	1.688	.628- .688	6.54
MS9443-22	1.750	.690- .750	6.71
MS9443-23	1.875	.815- .875	7.05
MS9443-24	2.000	.940-1.000	7.38
MS9443-25	2.125	1.065-1.125	7.72
MS9443-26	2.250	1.190-1.250	8.06
MS9443-27	2.375	1.315-1.375	8.39
MS9443-28	2.500	1.440-1.500	8.73
MS9443-29	2.625	1.565-1.625	9.06
MS9443-30	2.750	1.690-1.750	9.40
MS9443-31	2.875	1.815-1.875	9.74
MS9443-32	3.000	1.940-2.000	10.07
MS9443-33	3.125	2.065-2.125	10.41
MS9443-34	3.250	2.190-2.250	10.74
MS9443-35	3.375	2.315-2.375	11.08
MS9443-36	3.500	2.440-2.500	11.42
MS9443-37	3.625	2.565-2.625	11.75
MS9443-38	3.750	2.690-2.750	12.09
MS9443-39	3.875	2.815-2.875	12.42
MS9443-40	4.000	2.940-3.000	12.76
MS9443-41	4.125	3.065-3.125	13.10
MS9443-42	4.250	3.190-3.250	13.43
MS9443-43	4.375	3.315-3.375	13.77
MS9443-44	4.500	3.440-3.500	14.10
MS9443-45	4.625	3.565-3.625	14.44
MS9443-46	4.750	3.690-3.750	14.78
MS9443-47	4.875	3.815-3.875	15.11
MS9443-48	5.000	3.940-4.000	15.45
MS9443-49	5.125	4.065-4.125	15.78
MS9443-50	5.250	4.190-4.250	16.12
MS9443-51	5.375	4.315-4.375	16.46
MS9443-52	5.500	4.440-4.500	16.79
MS9443-53	5.625	4.565-4.625	17.13
MS9443-54	5.750	4.690-4.750	17.46
MS9443-55	5.875	4.815-4.875	17.80
MS9443-56	6.000	4.940-5.000	18.14

1. SHANK SHALL BE STRAIGHT WITHIN .0025 FIR PER INCH OF BOLT LENGTH.
2. THE CONCENTRICITY OF THREAD PD IN RELATION TO THE SHANK SHALL BE WITHIN .006 FIR.
3 THE CONCENTRICITY OF THE SHANK IN RELATION TO THE WASHER FACE DIAMETER AND HEXAGON SHALL BE WITHIN .017 FIR
4. INCOMPLETE THREADS NOT TO ENTER FILLET AREA.
5 MATERIAL STEEL AMS 6304.
6. HARDNESS ROCKWELL C42-46.
7. FINISH DIFFUSED NICKEL-CADMIUM PLATE AMS 2416. DIMENSIONS SPECIFIED ARE AFTER PLATING. CONTACT POINTS PERMISSIBLE PD MAY BE REDUCED .0012 MAXIMUM BEFORE PLATING
8. MANUFACTURING SPECIFICATION. AMS 7455. PARTS SUBJECT TO MAGNETIC PARTICLE INSPECTION PER AMS 2640 BEFORE PLATING.
9 SURFACE ROUGHNESS: AS 291; UNLESS OTHERWISE SPECIFIED SURFACES TO BE 125 MICROINCHES EXCEPT HEXAGON.
10. BREAK SHARP EDGES .003 - .015 UNLESS OTHERWISE SPECIFIED
11. DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED TOLERANCES; LINEAR DIMENSIONS ± .010, ANGULAR DIMENSIONS ± 5°.
12. TRUE POSITION TOLERANCES SPECIFIED ARE FOR MAXIMUM MATERIAL CONDITION.
13 DO NOT USE UNASSIGNED PART NUMBERS.

AS-AMS ARE SAE PUBLICATIONS.
THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE ENGINE AND PROPELLER UTILITY PARTS COMMITTEE OF THE SAE

REVISED

APPROVED 21 DEC 62

P.A USAF - AFSC Other Cust NAVY - WEP	TITLE BOLT, MACHINE - STEEL AMS 6304, DIFFUSED NICKEL-CADMIUM PLATED, HEXAGON HEAD, DRILLED, .375-24 UNJF-3A	MILITARY STANDARD MS9443 (ASG)
PROCUREMENT SPECIFICATION NONE	SUPERSEDES:	SHEET 1 OF 1

This standard has been approved by the Department of the and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:17Z
Check the source to verify that this is the current version before use.