MILITARY STANDARD

AUTOMATED ENGINEERING
DOCUMENT PREPARATION SYSTEM

CONNECTOR, ADAPTER

TO ALL HOLDERS OF DOD-STD-35-53A(MI):

1. THE FOLLOWING PAGES OF DOD-STD-35-53A(MI) HAVE BEEN REVISED AND SUPERSEDE THE PAGES LISTED:

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
7	2 February 1979	(Reprinted without change)	
8	18 December 1979	8	2 February 1979
15	2 February 1979	(Reprinted without change)	
16	18 December 1979	16	2 February 1979
17	18 December 1979	17	2 February 1979
18	2 February 1979	(Reprinted without change)	

2. THE FOLLOWING PAGES HAVE BEEN ADDED:

NEW PAGE	DATE	NEW PAGE	DATE

3. RETAIN THIS NOTICE PAGE AND INSERT BEFORE THE TABLE OF CONTENTS.

4. Holders of DOD-STD-35-53A(MI) will verify that page changes and additions indicated above have been entered. The notice page will be retained as a check sheet. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the MIlitary standard is completely revised or canceled.

Custodians:
Army - MI

User activity:
Army - AR

Review activities
Army - AT
Army - AV
Army - ER
Army - ME
Army - MR
Army - SG
Army - CR

Preparing activity:
Army - MI

(Project EDS-A304)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

5. DETAILED REQUIREMENTS

5.1 Introduction. This section provides instructions for completion of the SRS and references for instructions on specific requirements contained in DOD-STD-35.

5.2 MSE formats. AEDPS has the capability to prepare a six-section or a single-section document. The six-section document appears similar to a six-section military specification. The single-section document appears similar to a military specification sheet. Specification requirements described in DOD-STD-35 are applicable to either of the formats selected. It is mandatory that one of the two following codes and an "X" be entered on the SRS to create the desired MSE format:

a. 0700 for a six-section format

b. 0800 for a single-section format

5.3 Referenced documents. Section 2 of the MSE may contain a list of all referenced documents within Sections 3, 4, and 5 of the MSE. Instructions for referencing documents to appear in Section 2 of the forthcoming MSE are contained in DOD-STD-35.

5.4 Tabulation. Instructions for tabulation are provided in DOD-STD-35. Table II provides codes for column headings which may be used for Electrical Adapters characteristics. When different units of measure within one system (U.S. or SI) are available for specifying a characteristic, only one of the units may be tabulated; e.g. either ounces or pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

Reprinted without change

TABLE II. TABULATION CANDIDATES.

CODE	COLUMN HEADING	CODE	COLUMN HEADING	CODE	COLUMN HEADING
1570	IMPEDANCE NOMINAL (OHMS)	1577	MAXIMUM WORKING VOLTAGE AT SEA LEVEL (DC)	1573	MAXIMUM WORKING VOLTAGE AT SEA LEVEL (RMS)
2579	MAXIMUM WORKING VOLTAGE AT ALTITUDE (DC)	1583	MAXIMUM WORKING VOLTAGE AT ALTITUDE (RMS)	1592	MAXIMUM FREQUENCY (GHZ)
1593	ADAPTER TYPE	1594	ADAPTER SERIES	1588	MAXIMUM FREQUENCY (MHZ)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR CODE	STANDARD PARAGRAPH
1593	ADAPTER TYPE 1593 IN ACCORDANCE WITH THE BASE DOCUMENT SHALL APPLY.
1594	ADAPTER SERIES 1594 IN ACCORDANCE WITH BASE DOCUMENT SHALL APPLY.
	ALTITUDE RATING.
5060	THE OPERATING ALTITUDE RATING SHALL BE FROM SEA LEVEL TO 5060 FEET.
5061	THE OPERATING ALTITUDE RATING SHALL BE FROM SEA LEVEL TO 5061 METERS.
5062	THE NONOPERATING ALTITUDE RATING SHALL BE FROM SEA TO 5062 FEET.
5063	THE NONOPERATING ALTITUDE RATING SHALL BE FROM SEA TO 5063 METERS.
	TEMPERATURE RATING.
5069	THE MAXIMUM OPERATING TEMPERATURE RATING SHALL BE 5069 DEGREES CELSIUS.
5071	THE MAXIMUM NONOPERATING TEMPERATURE RATING SHALL BE 5071 DEGREES CELSIUS.
5068	THE MINIMUM OPERATING TEMPERATURE RATING SHALL BE 5068 DEGREES CELSIUS.
5070	THE MINIMUM NONOPERATING TEMPERATURE RATING SHALL BE 5070 DEGREES CELSIUS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.
Reprinted without change

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
ELECTRICAL RATINGS	
FREQUENCY RANGE (SELECT ONE)	
DC TO (MEGAHERTZ)	1588
DC TO (GIGAHERTZ)	1592
IMPEDANCE NOMINAL (OHMS)	1570
VOLTAGE RATING	
MAXIMUM WORKING VOLTAGE AT SEA LEVEL	
(VOLTS DC)	1577
(VOLTS RMS)	1573
MAXIMUM WORKING VOLTAGE AT ALTITUDE	
(VOLTS DC)	1579
(VOLTS RMS)	1583
ALTITUDE (SELECT ONE)	
(FEET)	1585
(METERS)	1587

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

CHAR
CODE STANDARD PARAGRAPH

1588 FREQUENCY RANGE. THE FREQUENCY RANGE OF THE ADAPTER SHALL BE FROM DC TO 1588 MEGAHERTZ.

1592 FREQUENCY RANGE. THE FREQUENCY RANGE OF THE ADAPTER SHALL BE FROM DC TO 1592 GIGAHERTZ.

1570 IMPEDANCE. THE NOMINAL IMPEDANCE OF THE ADAPTER SHALL BE 1570 OHM(S).

VOLTAGE RATING.

1577 THE MAXIMUM WORKING VOLRAGE AT SEA LEVEL SHALL BE 1577 VOLT(S) DC.

1573 THE MAXIMUM WORKING VOLTAGE AT SEA LEVEL SHALL BE 1573 VOLT(S) RMS.

1579 THE MAXIMUM WORKING VOLTAGE AT ALTITUDE SHALL BE 1579 VOLT(S) DC.

1583 THE MAXIMUM WORKING VOLTAGE AT ALTITUDE SHALL BE 1583 VOLT(S) RMS.

1585 THE ALTITUDE RATING FOR VOLTAGE SHALL BE 1585 FEET.

1587 THE ALTITUDE RATING FOR VOLTAGE SHALL BE 1587 METER(S).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.

KEYWORD CODE INDEX (KCI)

CHARACTERISTIC NAME	CHAR CODE
CONFIGURATION	
(ILLUSTRATION NUMBER), SEE APPENDIX A	1009
*UNITS (SELECT ONE)	
U.S.	
(INCHES)	7572
SI	
(MILLIMETERS)	7577
ILLUSTRATIONS	
(NUMBER), SEE APPENDIX A	4950
NOTE: THIS CODE IS USED TO ENTER APPLICABLE ILLUSTRATIONS WHICH DO NOT HAVE DIMENSIONS.	
TABULATED CHARACTERISTICS (SEE TABLE IV, DOD-STD-35)	
MATERIALS (SEE TABLES VI AND VII, DOD-STD-35)	
NOTE: AUTOMATIC WHEN TABLE VII IS USED.	
FINISHES (SEE TABLES VIII AND IX, DOD-STD-35)	
NOTE: AUTOMATIC WHEN TABLE IX IS USED.	

U.S. GOVERNMENT PRINTING OFFICE: 1980 — 603-121/390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:57Z
Check the source to verify that this is the current version before use.
Reprinted without change