


TABLE I. DASH NUMBERS.

| DASH NO | A | B | TEMPER | FORMING 2/ PROCESS |
|---|---|---|---|---|
| 001 | .125 | 1.437 | T6 | C |
| 003 | .250 | 1.000 | T6 | C |
| 005 | .250 | 1.125 | T73 | C |
| 007 | .250 | 1.500 | T6 | C |
| 009 | .250 | 3.000 | T6 | C |
| 011 | .250 | 6.000 | T6 | R,D,C,E |
| 013 | .375 | .750 | T6 | C |
| 015 | .375 | 1.000 | T6 | C |
| 017 | .375 | 1.250 | T6 | C |
| 019 | .375 | 1.500 | T6 | C |
| 021 | .375 | 1.500 | T73 | C |
| 023 | .375 | 2.000 | T6 | C |
| 025 | .500 | .750 | T7351 | C |
| 027 | .500 | 1.000 | T6 | C |
| 029 | .500 | 1.000 | T7351 | C |
| 031 | .500 | 1.250 | T6511 | C |
| 033 | .500 | 1.500 | T6 | C |
| 035 | .500 | 1.500 | T651 | C |
| 037 | .500 | 1.500 | T7351 | C |
| 039 | .500 | 1.750 | T6 | C |
| 041 | .500 | 3.500 | T6 | C |
| 043 | .500 | 4.000 | T6 | C |
| 045 | .500 | 4.000 | T651 | C |
| 047 | .500 | 6.000 | T6 | R,D,C,E |
| 049 | .500 | 6.000 | T351 | R,D,C |
| 051 | .625 | 1.000 | T651 | C |
| 053 | .625 | 2.000 | T6 | C |
| 055 | .625 | 2.500 | T6 | C |
| 057 | .625 | 3.000 | T6 | C |
| 059 | .625 | 4.000 | T6 | C |
| 061 | .625 | 4.000 | T651 | C |
| 063 | .750 | 1.000 | T6 | C |
| 065 | .750 | 1.000 | T651 | C |
| 067 | .750 | 1.000 | T7351 | C |
| 069 | .750 | 1.250 | T6 | C |
| 071 | .750 | 1.250 | T651 | C |
| 073 | .750 | 2.000 | T73 | C |
| 075 | .750 | 2.250 | T7351 | C |
| 077 | .750 | 3.000 | T6 | C |
| 079 | .750 | 3.000 | T651 | C |
| 081 | 1.000 | 1.500 | T6 | C |
| 083 | 1.000 | 1.500 | T6511 | C |
| 085 | 1.000 | 1.750 | T651 | C |
| 087 | 1.000 | 1.750 | T7351 | C |
| 089 | 1.000 | 2.000 | T73 | C |
| 091 | 1.000 | 2.000 | T651 | C |
| 093 | 1.000 | 2.000 | T6511 | C |
| 095 | 1.000 | 2.500 | T651 | C |
| 097 | 1.000 | 2.500 | T6511 | C |
| 099 | 1.000 | 3.000 | T6 | C |
| 101 | 1.000 | 3.000 | T651 | C |
| 103 | 1.000 | 3.000 | T6511 | C |
| 105 | 1.000 | 3.000 | T7351 | C |
| 107 | 1.000 | 3.500 | T6 | C |
| 109 | 1.000 | 4.000 | T6 | C |
| 111 | 1.000 | 4.000 | T651 | C |
| 113 | 1.000 | 4.000 | T6511 | C |
| 115 | 1.000 | 6.000 | T6 | R,D,C,E |
| 117 | 1.125 | 1.375 | T6 | C |
| 119 | 1.250 | 1.500 | T6 | C |
| 121 | 1.250 | 1.750 | T651 | C |
| 123 | 1.250 | 2.000 | T6 | C |
| 125 | 1.250 | 2.000 | T73 | C |
| 127 | 1.250 | 2.000 | T6511 | C |
| 129 | 1.250 | 2.500 | T6 | C |
| 131 | 1.250 | 2.500 | T7351 | C |
| 133 | 1.250 | 3.000 | T6 | C |
| 135 | 1.250 | 3.000 | T651 | C |
| 137 | 1.250 | 3.000 | T6511 | C |
| 139 | 1.250 | 4.000 | T6 | C |
| 141 | 1.250 | 4.000 | T7351 | C |
| 143 | 1.375 | 2.250 | T7351 | C |
| 145 | 1.500 | 1.750 | T6 | C |
| 147 | 1.500 | 2.000 | T6 | C |
| 149 | 1.500 | 2.000 | T73 | C |
| 151 | 1.500 | 2.000 | T651 | C |
| 153 | 1.500 | 2.000 | T6511 | C |
| 155 | 1.500 | 2.500 | T6 | C |

APPROVED 14 SEP 83 REVISED

USER ACTIVITIES:

REVIEWER ACTIVITIES:
Air Force – 84
DLA – IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

| P. A. | INTERNATIONAL INTEREST | TITLE | MILITARY STANDARD |
|---|---|---|---|
| Other Cust AS MR 99 | | BAR, RECTANGULAR, SQUARE CORNERS, ALUMINUM ALLOY 7075 | MS 14254 |
| PROCUREMENT SPECIFICATION QQ-A-200, QQ-A-225 | SUPERSEDES: | | PAGE 1 OF 3 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:38Z
Check the source to verify that this is the current version before use.

TABLE I. DASH NUMBERS. - CONTINUED

| DASH NO | A | B | TEMPER | FORMING 2/ PROCESS |
|---|---|---|---|---|
| 157 | 1.500 | 2.500 | T73 | C |
| 159 | 1.500 | 2.500 | T651 | C |
| 161 | 1.500 | 3.000 | T6 | C |
| 163 | 1.500 | 3.000 | T6511 | C |
| 165 | 1.500 | 3.500 | T7351 | C |
| 167 | 1.500 | 4.000 | T73 | C |
| 169 | 1.500 | 4.000 | T651 | C |
| 171 | 1.500 | 4.000 | T6511 | C |
| 173 | 1.500 | 6.000 | T6 | R,D,C,E |
| 175 | 1.750 | 2.000 | T6 | C |
| 177 | 1.750 | 2.000 | T6511 | C |
| 179 | 1.750 | 2.000 | T7351 | C |
| 181 | 1.750 | 2.500 | T6 | C |
| 183 | 1.750 | 3.000 | T6 | C |
| 185 | 1.750 | 3.000 | T6511 | C |
| 187 | 1.750 | 4.500 | T6 | R,D,C,E |
| 189 | 1.750 | 6.000 | T6 | E |
| 191 | 2.000 | 2.250 | T7351 | C |
| 193 | 2.000 | 2.500 | T6 | C |
| 195 | 2.000 | 2.500 | T73 | C |
| 197 | 2.000 | 2.500 | T651 | C |
| 199 | 2.000 | 2.500 | T6511 | C |
| 201 | 2.000 | 3.000 | T6 | C |
| 203 | 2.000 | 3.000 | T73 | C |
| 205 | 2.000 | 3.000 | T651 | C |
| 207 | 2.000 | 3.000 | T6511 | C |
| 209 | 2.000 | 3.250 | T651 | C |
| 211 | 2.000 | 3.250 | T7351 | C |
| 213 | 2.000 | 3.500 | T73 | C |
| 215 | 2.000 | 4.000 | T6 | C |
| 217 | 2.000 | 4.000 | T651 | C |
| 219 | 2.000 | 4.000 | T6511 | C |
| 221 | 2.000 | 4.500 | T651 | R,D,C |
| 223 | 2.000 | 5.000 | T7351 | R,D,C |
| 225 | 2.000 | 6.000 | T6 | R,D,C,E |
| 227 | 2.000 | 6.000 | T651 | R,D,C |

| DASH NO | A | B | TEMPER | FORMING 2/ PROCESS |
|---|---|---|---|---|
| 229 | 2.250 | 2.500 | T6 | E |
| 231 | 2.250 | 3.000 | T6511 | E |
| 233 | 2.250 | 3.250 | T7351 | R,D,C |
| 235 | 2.250 | 4.500 | T651 | R,D,C |
| 237 | 2.500 | 3.000 | T6 | R,D,C,E |
| 239 | 2.500 | 3.000 | T73 | R,D,C |
| 241 | 2.500 | 3.000 | T6511 | E |
| 243 | 2.500 | 3.500 | T6511 | E |
| 245 | 2.500 | 4.000 | T6 | R,D,C,E |
| 247 | 2.500 | 4.000 | T651 | R,D,C |
| 249 | 2.500 | 4.000 | T6511 | E |
| 251 | 2.500 | 4.125 | T6 | R,D,C |
| 253 | 2.500 | 4.500 | T6 | R,D,C,E |
| 255 | 2.500 | 4.500 | T651 | R,D,C |
| 257 | 2.500 | 4.500 | T7351 | R,D,C |
| 259 | 2.500 | 5.000 | T6 | R,D,C,E |
| 261 | 2.500 | 6.000 | T6 | R,D,C,E |
| 263 | 2.500 | 6.000 | T651 | R,D,C |
| 265 | 2.750 | 4.500 | T7351 | R,D,C |
| 267 | 2.750 | 6.000 | T6 | R,D,C |
| 269 | 3.000 | 4.000 | T6 | R,D,C |
| 271 | 3.000 | 4.000 | T73 | R,D,C |
| 273 | 3.000 | 4.000 | T651 | R,D,C |
| 275 | 3.000 | 4.000 | T6511 | E |
| 277 | 3.000 | 4.500 | T6 | R,D,C,E |
| 279 | 3.000 | 4.500 | T651 | R,D,C |
| 281 | 3.000 | 4.500 | T7351 | R,D,C |
| 283 | 3.000 | 5.000 | T6 | E |
| 285 | 3.000 | 5.000 | T73 | R,D,C |
| 287 | 3.000 | 5.000 | T6511 | E |
| 289 | 3.000 | 5.500 | T7351 | R,D,C |
| 291 | 3.000 | 6.000 | T6 | R,D,C,E |
| 293 | 3.000 | 6.000 | T651 | R,D,C |
| 295 | 4.000 | 5.000 | T6511 | E |
| 297 | 4.000 | 6.000 | T6 | E |
| 299 | 4.000 | 6.000 | T6511 | E |

USER ACTIVITIES:

REVIEWER ACTIVITIES:
Air Force - 84
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 14 SEP 83 REVISED

| P. A. | INTERNATIONAL INTEREST | TITLE | MILITARY STANDARD |
|---|---|---|---|
| Other Cust AS MR 99 | | BAR, RECTANGULAR, SQUARE CORNERS, ALUMINUM ALLOY 7075 | MS14254 |
| PROCUREMENT SPECIFICATION QQ-A-200, QQ-A-225 | SUPERSEDES: | | PAGE 2 OF 3 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:38Z
Check the source to verify that this is the current version before use.


REQUIREMENTS:

1. MATERIAL. ALUMINUM ALLOY 7075, (UNS A97075) AS SPECIFIED IN QQ-A-200/11 AND QQ-A-225/9.

2/ FORMING PROCESS. ROLLED - CODE "R"
DRAWN - CODE "D"
COLD FINISHED - CODE "C"
EXTRUDED - CODE "E"

3. PART NUMBER. THE PART NUMBER CONSISTS OF THE BASIC MS NUMBER, PLUS A FORMING PROCESS CODE, PLUS A DASH NUMBER FROM TABLE I.

EXAMPLE: MS14254 C 001




4. MARKING. ALUMINUM AND ALUMINUM ALLOYS SHALL BE MARKED WITH THE PRODUCER'S NAME OR REGISTERED TRADEMARK, THE PART NUMBER (MILITARY STANDARD (MS) NUMBER PLUS THE APPLICABLE DASH NUMBER), AND THE LOT AND/OR HEAT NUMBER, AND THIS MARKING SHALL BE APPLIED IN ACCORDANCE WITH FED-STD-184.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. STANDARD LENGTH OF BAR IS 10 FEET MINIMUM, 12 FEET MAXIMUM.
3. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSAL, EXCEPT THE REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
4. FOR DESIGN FEATURE PURPOSES THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

APPROVED 14 SEP 83 REVISED

USER ACTIVITIES:

REVIEWER ACTIVITIES:
Air Force - 84
DLA - IS

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

| P. A. / Other Cust | INTERNATIONAL INTEREST | TITLE | MILITARY STANDARD |
|---|---|---|---|
| AS / MR / 99 | | BAR, RECTANGULAR, SQUARE CORNERS, ALUMINUM ALLOY 7075 | MS14254 |
| PROCUREMENT SPECIFICATION: QQ-A-200, QQ-A-225 | SUPERSEDES: | | PAGE 3 OF 3 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:38Z
Check the source to verify that this is the current version before use.