


FED. SUP CLASS
2320





(B) CANCELLED AFTER 5 JUNE 85
NO SUPERSEDING STANDARD.



DIMENSIONS ARE IN INCHES AND ARE SHOWN FOR ENGINEERING REFERENCE ONLY.

MS PART NO	ENGINEERING PARTS LIST	
MS51393-1	8736158	WITH WINCH
MS51393-2	8736149	LESS WINCH

(A) ENTIRE STANDARD REVISED.

P.A. MO (ATAC)
Other Cust
NAVY — MC
AF-84

PROCUREMENT SPECIFICATION
MIL-T-45362

SUPERSEDES

TITLE
CHASSIS, TRUCK, MILITARY DESIGN, M46C, 2-1/2 TON, 6X6, 190 INCH WHEELBASE

MILITARY STANDARD
MS 51393

SHEET 1 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:00Z
Check this source to verify that this is the current version before use.

REVIEW ACTIVITIES: ARMY—SM; AF—85
USER ACTIVITIES: NAVY—YD

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

APPROVED 15 DECEMBER 1961 REVISED (A) 29 OCTOBER 1965 (B) 5 June 1985

FED. SUP CLASS
2320

VEHICLE CHARACTERISTICS

CURB WEIGHT: CHASSIS AND CAB LESS PAYLOAD AND PERSONNEL.

	W/O W	W/W
FRONT AXLE	5510	6010
BOGIE	6770	6680
TOTAL	12280	12690 LBS.

GROSS LOAD:

	W/O W	W/W
PAYLOAD		
CROSS COUNTRY	7600	7200
HIGHWAY	13400	13000 LBS.

TOWED LOAD MAX:

CROSS COUNTRY	6000
HIGHWAY	10000 LBS.

(REFERENCED WEIGHTS ARE FOR INFORMATION ONLY.)

TURNING RADIUS, MINIMUM: OVER BUMPER, W/O W 45 FT., W/W 46 FT.

ENGINE: 8757517

MODEL: OA 331
NO. OF CYL: SIX IN LINE
DISPLACEMENT 331 BORE 4-1/8
STROKE 4-1/8
COMP. RATIO: 6.73:1
GOV. SPEED: 3400 RPM
MAX. BHP: 146 NET 127 @RPM 3400
MAX. TORQUE LB. FT: 270 NET 248 @RPM 1400

TRANSMISSION ASSY: P/N 7520995

TYPE: SYNCHROMESH
FORWARD SPEEDS: (5) REVERSE (1)
GEAR RATIO: HIGH 1.00:1 7.36:1
FOURTH 1.45:1
LOW 7.55:1

TRANSFER TRANSMISSION: INST'N. 8757844

TRANSFER TRANSMISSION: P/N 10871782

GEAR RATIO: HIGH 1.00:1
LOW 1.98:1

FRONT SUSPENSION: INST'N. 8757839

FRONT AXLE		7521734
FRONT SPRINGS	(2)	7368628
SHOCK ABSORBERS	(2)	7539007

REAR SUSPENSION: INST'N. 8757834

REAR AXLE	(2)	7368511
REAR SPRINGS	(2)	7368629
TORQUE ROD ASSY.	(6)	8757685

FRAME ASSY: 8757972

SIDE RAIL: 8 x 3 x 5/16
SECTION MODULUS: 9.54 IN.^{3}

TIE DOWNS: NO. (14) W/W 7373215
LOCATION: (7) EACH SIDE

WHEELS: (10) MS 53044-5
SIZE: 7.5 x 20, OFFSET 6-3/16

TIRES: (10) PLUS (1) SPARE, MS 35388-16
SIZE: 9.00 x 20, (8) PLY, NDCC

TUBES: MS 35392-13

CAB ASSY: SOFT TOP 8757744

ELECTRICAL SYSTEM: INST'N. 10896754-2

POTENTIAL: 24 VOLT
BATTERIES: (2), (12) VOLT, (6TN), MS 35000

STARTING MOTOR:	7762618
GENERATOR 25 AMP	7355736
COIL:	7762685
REGULATOR:	MS 51356-1
B.O. DRIVING LAMP	MS 51318
B.O. MARKER LAMP	MS 51303
STOPLIGHT, TAIL:	MS 53047
STOPLIGHT, B.O.:	MS 51302-1
REFLECTORS:	(4) RED, MS 35387-1
	(4) AMBER, MS 35387-2

BRAKE: SERVICE INST'N. 8757652
HUB & DRUM ASSYS.
FRONT, LH 7529053 RH 7529054
REAR, LH 8757681 RH 8757682
DRUM SIZE, FRT. 15 x 3, REAR 15 x 3
BRAKE, PARKING, SIZE: 14 x 3
ACTUATION: AIR/HYDRAULIC

WINCH: INST'N. 10871532

WINCH: MS 51352-1
20000 LB CAPACITY

PINTLE: INST'N. 7722050

PINTLE: MS 51118-1

PERFORMANCE: LOADED

CRUISING RANGE, HIGHWAY, 224 MILES
MAX. SPEED, HIGHWAY 58 MPH

FORDING DEPTH:

FORDING DEPTH W/O KIT 40 IN.
FORDING DEPTH W/KIT 72 IN.

MISCELLANEOUS EQUIPMENT:

CLOSURE, HARDTOP 7354276

(FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.)

(REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.)

THIS VEHICLE SHALL BE IN ACCORDANCE WITH DRAWINGS IN REFERENCED ENGINEERING PARTS LIST, COPIES OF WHICH MAY BE OBTAINED FROM:

U. S. ARMY TANK-AUTOMOTIVE CENTER
ATTN: STANDARDIZATION BRANCH
WARREN, MICHIGAN 48090.

(B) CANCELLED AFTER 5 JUNE 85
NO SUPERSEDING STANDARD.

APPROVED 15 DECEMBER 1961 REVISED (A) 29 OCTOBER 1965 (B) 5 June 1985

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

P.A.MO (ATAC) Other Cust NAVY-MC AF-84	TITLE CHASSIS, TRUCK, MILITARY DESIGN, M46C, 2-1/2 TON, 6X6, 190 INCH WHEELBASE	MILITARY STANDARD MS 51393
PROCUREMENT SPECIFICATION MIL T 45362	SUPERSEDES:	SHEET 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:00Z
Check the source to verify that this is the current version before use.