INCH-POUND

MS51519D
w/AMENDMENT 1
26 September 2025
SUPERSEDING
MS51519D
23 October 2020

DETAIL SPECIFICATION SHEET

FITTINGS, HYDRAULIC TUBE, FLARED 37 DEGREE, NIPPLE, TUBE, LARGE HEX, FOR USE WITH O-RING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-18866.




FIGURE 1. Nipple tube.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

Suffix designator		Tube OD nom.	B Straight thread ASME B1.1	C_2 Hex flat Nom.	D diameter	
Assembly	Body (see note 6)				Nom. inches (mm)	Tolerance inches (mm)
A2	B2	.1250 (3.175)	.3125-24 UNF-2A	9/16	.062 (1.57)	±.004 (0.10)
A3	B3	.1875 (4.763)	.3750-24 UNF-2A	5/8	.125 (3.18)	
A4	B4	.2500 (6.350)	.4375-20 UNF-2A	11/16	.172 (4.37)	
A5	B5	.3125 (7.936)	.5000-20 UNF-2A	3/4	.234 (5.94)	
A6	B6	.3750 (9.525)	.5625-18 UNF-2A	13/16	.297 (7.54)	±.008 (0.20)
A8	B8	.5000 (12.700)	.7500-16 UNF-2A	1	.391 (9.93)	
A10	B10	.6250 (15.875)	.8750-14 UNF-2A	1-1/81	.484 (12.29)	
A12	B12	.7500 (19.050)	1.0625-12 UN-2A	1-3/8	.609 (15.47)	
A14	B14	.8750 (22.225)	1.1875-12 UN-2A	1-1/2	.719 (18.26)	
A16	B16	1.0000 (25.400)	1.3125-12 UN-2A	1-5/8	.844 (21.44)	
A20	B20	1.2500 (31.750)	1.6250-12 UN-2A	1-7/8	1.078 (27.38)	
A24	B24	1.5000 (38.100)	1.8750-12 UN-2A	2-1/8	1.312 (33.32)	±.012 (0.30)
A32	B32	2.0000 (50.800)	2.500-12 UN-2A	2-3/4	1.781 (45.24)	

Suffix designator		G_1 inches (mm) +.002 (0.05) -.003 (0.08)	L_1 inches (mm) ±.020 (0.51)
Assembly	Body		
A2	B2	.250 (6.35)	1.170 (29.72)
A3	B3	.313 (7.95)	1.230 (31.24)
A4	B4	.364 (9.25)	1.370 (34.80)
A5	B5	.427 (10.85)	1.370 (34.80)
A6	B6	.482 (12.24)	1.410 (35.81)
A8	B8	.660 (16.76)	1.620 (41.15)
A10	B10	.773 (19.63)	1.880 (47.75)
A12	B12	.945 (24.00)	2.160 (54.86)
A14	B14	1.070 (27.18)	2.210 (56.13)
A16	B16	1.195 (30.35)	2.250 (57.15)
A20	B20	1.507 (38.28)	2.430 (61.72)
A24	B24	1.756 (44.60)	2.750 (69.85)
A32	B32	2.381 (60.48)	3.400 (86.36)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Break all sharp edges and remove all burrs and slivers.
4. Dimensions and tolerances not shown shall be in accordance with SAE-J514/1 for 37° flared fittings.
5. The drawing is for identification purposes only and is not intended to restrict designs and shapes not dimensioned.
6. Bodies will be used for production only and shall not be stocked for maintenance.
7. Procure the O-rings separately and install before installation of the fittings.

FIGURE 1. Plug - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Fittings shall be specified on figure 1.

Components of the assemblies shall be of the same material and finish.

O-rings shall not be furnished with the fittings.


Materials shall be in accordance with MIL-DTL-18866.

Finish and finish designators shall be in accordance with MIL-DTL-18866.

Unless otherwise specified in MIL-DTL-18866, all plating's shall be capable of meeting 96-hour salt spray test in accordance with ASTM B117. The fittings shall show no evidence of red corrosion after 96 hours of salt spray. Fluid passages, other openings, and internal threads shall not be subject to the plating thickness requirement and may have bare areas provided they are protected with a light film of oil.

Maximum operating pressure. Maximum operating pressure shall be in accordance with SAE-J514/1.

PIN: The PIN consists of the letters "MS", the specification number, a letter and number for nipple size, and a letter for material finish designator.



PIN example: MS51519A10 indicates a nipple, tube, .6250 inch (15.875 mm), steel cadmium plated.

Marking shall be in accordance with MIL-DTL-18866.

Class I and II ozone depleting substances (ODS) shall not be used in MS51519 or any referenced procedures.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid.

Material designator "SS" has been replaced by "S".

Phosphate coating finish "P" has been replaced by "KA".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

NOTE: The following restrictions do not apply to manufacturers of the fittings and is applicable only to OEM's and users.

Zinc-plated materials should be avoided in hydraulic systems with water-glycol fluids. Reference ASTM MNL37 - Fuels and Lubricants Handbook, "water glycol fluids are highly alkaline due to the presence of amine-based corrosion inhibitors. As a result, these fluids can attack zinc, cadmium, magnesium, and non-anodized aluminum, forming sticky or gummy residues. Consequently, these metals should be avoided when selecting system components.

Cadmium is not recommended. To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when other materials and finishes specified in this document cannot meet performance requirements.

Army and Marine ground forces zinc plating's. PIN codes FC, FD, Z, and ZC finishes have a chromate conversion coating which includes hexavalent chromium and are not recommended for Army and Marine ground systems. The use of coatings depositing hexavalent chromium for Army vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement. For new designs PIN codes FC, FD, Z, and ZC are not to be supplied to Army and Marine ground forces. MIL-PRF-32647 Type KA is intended as a hazardous free plating material and is a direct replacement for zinc plating with a hexavalent chromium conversion coating. KA has an equivalent torque/tension as the plating's replaced.

Army and Marine ground vehicles. The use of cadmium plating for Army and Marine ground vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement.

Army ground vehicle applications cadmium plating. Pin code J or KB may be substituted for cadmium ("Blank" PIN code) for Army ground vehicle applications. MIL-PRF-32647 Type KB is intended as a hazardous free plating material and is a direct replacement for cadmium plating ("Blank" PIN code). KB has an equivalent torque/tension as cadmium.

NAVSEA shipboard owned equipment. Cadmium is prohibited from use in NAVSEA-owned shipboard systems in accordance with the requirements of T9070-AL-DPC-020/077-2, unless otherwise approved by NAVSEA.

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-18866, this document references the following:

MIL-PRF-32647	ASTM MNL37
MS51531	SAE AS28778
MS51533	SAE-J514/1
ASME B1.1	T9070-AL-DPC-020/077-2
ASTM B117	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AR
Navy - OS
Air Force - 71

Preparing activity:
DLA - CC

(Project 4730-2025-072)

Review activities:
Army - AT, MI
Navy - CG, MC, SA, SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:05Z
Check the source to verify that this is the current version before use.