INCH-POUND
MS90310J
w/Amendment 2
21 March 2017
SUPERSEDING
MS90310J
w/Amendment 1
4 May 2012

DETAIL SPECIFICATION SHEET

SWITCH, TOGGLE, POSITIVE BREAK, MINIATURE, TOGGLE SEALED, SOLDER LUG, SINGLE POLE, .469 MOUNTING BUSHING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-DTL-8834.




FIGURE 1. Dimensions and configuration.

AMSC N/A

FSC 5930

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:34Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm	Inches	mm
.002	.05	.024	.61	.072	1.83	.438	11.13
.003	.08	.025	.64	.169	4.29	.469	11.91
.005	.13	.030	.76	.240	6.10	.572	14.53
.010	.25	.032	.81	.338	8.59	.687	17.45
.012	.30	.045	1.14	.364	9.25	.706	17.93
.016	.41	.052	1.32	.432	10.97		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.010 (0.25 mm) on decimals and ±.5º on angles.
4. For hardware detail specifications see appendix of MIL-DTL-8834

FIGURE 1. Dimensions and configurations - Continued.

REQUIREMENTS:

Switching characteristics: See table II. Direction of movement of internal mechanism is opposite to the direction of the toggle movement.

Maximum weight: .0429 pound (19.4 grams).

Dielectric withstanding voltage: 50,000 feet.

Toggle seal test: Method II.

Shock: Method I and Method II (high impact). The switch shall be electrically and mechanically operative at the conclusion of the shock test except there can be mechanical transfer of the contact mechanism at all levels when tested in accordance with Method II (high impact).

Terminal strength: 5 pounds normal to the mounting plane and 2 pounds in other planes.

Altitude: 50,000 feet.

Electrical ratings: See table I.

Part or Identifying Number (PIN): See table II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:34Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical ratings.

Load	28 V dc	115 V ac 60 Hz	115 V ac 400 Hz	5 millivolts
	(amperes)	(amperes)	(amperes)	(microamperes)
Resistive	5	2	3	
Inductive	1 1/	1	2	
Low level	- - -	- - -	- - -	25 2/

1/ With time constant of .020 ±.002 seconds.
2/ Contact resistance not to exceed 50 ohms during life, low level switching.

Table II. Switching characteristics.

PIN MS90310-	Circuit with toggle lever in these positions 1/		
	Opposite keyway side 2/	Center position	Keyway side 2/
-211	ON 2-3	OFF	ON 1-2
-221		NONE	OFF
-231			ON 1-2
-241		OFF	NONE
-271	MOM-ON 2-3		MOM-ON 1-2
-281	NONE		
-311	ON 2-3		

1/ Direction of movement of internal mechanism is opposite to the direction of the toggle movement.
2/ Non functional terminals shall not be supplied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:34Z
Check the source to verify that this is the current version before use.

Referenced documents:
MIL-DTL-8834

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2017-034)

Review activities:
Army - AR, AV, MI
Navy - EC
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:34Z
Check the source to verify that this is the current version before use.