AMENDMENT

TO

FEDERAL SPECIFIATION

PIPE, CORRUGATED (ALUMINUM ALLOY)

This amendment, which forms a part of Federal Specification WW-P-402C, dated November 13, 1969, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Symbol, below "Superseding" delete "Int. Fed. Spec. WW-P-00402B(DOT-PR) February 7, 1969" and substitute:

Int. Fed. Spec. WW-P-00402B(DOT-PR)
February 7, 1969 and
Fed. Spec. WW-P-402A
December 15, 1964

PAGE 9

Paragraph 3.3.1, add the following sentence to the end of the paragraph:

"Smooth-lined pipe when specified (see 6.2) shall be fabricated with a smooth liner and helically corrugated Series A shell, integrally attached at helical lock seams spaced not more than 30 inches apart and extending from end to end of each length of pipe."

PAGE 16

Paragraph 6.2:

(e) Change reference to "(see 3.1.3, 3.3.1 and table III)".

Add new subparagraph as follows:

(o) Class II, smooth-lined pipe when required (see 3.3.1).

Custodians:

Army - ME
Navy - YD
Air Force - 82

User Interest:

Army - CE

Military Coordinating Activity:

Army - ME

Project No. 4710-0295

Preparing activity:

DOT-FHA

FSC 4710

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:22Z
Check the source to verify that this is the current version before use.