MIL-D-82035C
23 March 1984
SUPERSEDING
MIL-D-82035B
6 September 1973

MILITARY SPECIFICATION

DISPENSERS, BEVERAGE, MECHANICALLY REFRIGERATED

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers mechanically refrigerated, counter-mounted. noncarbonated beverage dispensers having rigid, transparent, plastic containers to afford a visual indication of the dispensed by the unit.

1.2 Classification. The beverage dispensers shall be of the following types, styles, sizes, and electrical ratings, as specified (see 6.2.1).

Types I - Dispenser with agitation system plus overhead, spray type aeration system (for syrup drinks and other non-foaming beverages)

Types II - Dispenser with agitation system but without aeration system (for pulpy fruit juices and other beverages not suitable for aeration)

Style A - Single bowl

- Size 4 - Capacity of 3 to 5 gallons, inclusive
- Size 7 - Capacity of 6 to 8 gallons, inclusive
- Size 13 - Capacity of 12 to 15 gallons, inclusive

Style B - Twin bowl

- Size 7 - Capacity of 3 to 4 gallons per bowl, 6 to 8 gallons total capacity, inclusive
- Size 11 - Capacity of 5 to 6 gallons per bowl, 10 to 12 gallons total capacity, inclusive

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

Electrical rating

115/1/60 - Nominal 115-volt, single-phase, 60-hertz current
220/1/50 - Nominal 220-volt, single-phase, 50-hertz current

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-636 - Boxes, Shipping, Fiberboard

Military

MIL-P-116 - Preservation, Method of
MIL-V-173 - Varnish, Moisture- and Fungus-Resistant (for Treatment of Communications, Electronic and Associated Equipment)

STANDARDS

Military

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property
MIL-STD-147 - Palletized Unit Loads
MIL-STD-794 - Parts and Equipment, Procedures for Packaging of

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip, Specification for

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

A176 - Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip, Specification for
D3951 - Commercial Packaging, Standard Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Federal Food and Drug Administration

Federal Food, Drug, and Cosmetic Act and General Regulations for Its Enforcement

(Application for copies should be addresses to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

WD-1 - General-Purpose Wiring Devises

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037.)

NATIONAL SANITATION FOUNDATION (NSF)

No. 18 - Manual Food and Beverage Dispensing Equipment. Listing of Food Service Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, 3475 Plymouth, Ann Arbor, MI 48106.)

UNDERWRITERS LABORATORIES INC. (UL)

UL 471 - Commercial Refrigerators

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The beverage dispensers shall consist essentially of a base assembly containing a complete refrigeration system and supporting a rigid, clear plastic, bowl-type beverage container(s) with cover. Each dispenser shall be equipped with an electrically-powered beverage agitation system, a dispensing faucet, and the controls and appurtenances specified herein. Style A units shall be equipped with one bowl and one or more dispensing faucets, at the option of the supplier except that, when specified (see 6.2), it shall be mandatory that style A, size 13 dispensers be equipped

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

with two faucets. Style B units shall be equipped with two bowls or compartments each with an individual dispensing faucet and agitation system. The numerical designations used herein to identify dispenser sizes shall be interpreted as the nominal capacity. The actual capacity for a particular size shall be equal to the nominal capacity or, at the option of the manufacturer, to any other capacity within the applicable range of capacities specified under 1.2 herein.

3.2 First article. When specified (see 6.2.1), the contractor shall furnish one dispenser of the classification specified for first article inspection and approval (see 4.2.1 and 6.3).

3.3 Standards compliance. The dispensers shall meet the requirements of UL 471 and NSF Std. No. 18.

3.3.1 UL certification. Prior to approval of the sample dispenser submitted for first article inspection or, if first article inspection is not required under terms of the contract, prior to the first shipment, the supplier shall submit to the contracting officer or his authorized representative satisfactory evidence that the units he proposes to supply under this specification meet the requirements of UL 471. Acceptable evidence of meeting the applicable requirements of UL 471 shall either be: (1) The UL-approved listing and marking authorized under the UL. Reexamination Service or (2) a certified test report from a nationally recognized independent testing laboratory, selected by the supplier and approved by the contracting officer, stating that a beverage dispenser of the same model being furnished under this specification has been examined and tested and meets the requirements of UL 471 (see 6.2.2).

3.3.2 NSF certification. The supplier shall submit to the contracting officer or his authorized representative satisfactory evidence that the units he proposes to supply under this specification meet the requirements of NSF Std. No. 18. Acceptable evidence of meeting the requirements of NSF Std. No. 18 shall be (a), (b), or (c) as follows:

a. Display of the NSF seal on the finished dispensers and a listing of the model being furnished in the current edition of the NSF Listing of Food Service Equipment. This evidence shall be made available prior to approval of the first article or, if first article inspection is not required, prior to the first shipment.
b. A certification for the dispensers issued by NSF under their special one-time evaluation/certification service for equipment being furnished under a Government contract. This certification shall be submitted prior to approval of the first article, or, if first article inspection is not required, prior to the first shipment (see 6.2.2).
c. A certified test report from a recognized independent testing laboratory acceptable to the medical department of the service for which the dispensers are being acquisitioned, indicating that a beverage dispenser of the same model being furnished under this specification has been examined and tested and meets the requirements of NSF Std. No. 18. This evidence shall be submitted prior to approval of the first article, or, if first article inspection is not required prior to production of the dispensers to be furnished to the Government (see 6.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

3.3.3 Standards applicability. Details for equipment construction, design, and performance covered by this specification shall be supplementary to the requirements of the standards cited in 3.3 and compliance with and approval under the UL or NSF standard shall not relieve the supplier of the responsibility for meeting the requirements of this specification.

3.4 Interchangeability. All units of the same classification furnished with similar options under a specific contract shall be identical to the extent necessary to insure interchangeability of component parts, assemblies, accessories, and spare parts.

3.5 Materials. Materials shall be as specified herein and in applicable specifications and standards, and other referenced documents. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Materials shall be free of defects which adversely affect performance or serviceability of the finished product.

3.5.1 Stainless steel. Stainless steel sheet, when used for components such as base panels and drip trays, shall be type 302 or 304 of ASTM A167, except that stainless steel side and rear panels not exposed to beverage spills may be type 430 of ASTM A176.

3.5.2 Plastics. Plastic materials used for bowls, faucets, mixing system components, and any other parts in contact with the beverage shall have been approved by the National Sanitation Foundation for potable water applications and shall conform to the applicable requirements of the Federal Food, Drug, and Cosmetic Act and General Regulations for Its Enforcement.

3.6 Performance. The dispensers shall be designed for the refrigeration and dispensing of noncarbonated beverages. The dispensers shall be equipped as specified in 3.7.3 to maintain the stored beverage in a constant state of motion or agitation to prevent settlement of beverage constituents. The refrigeration system shall be capable of automatically maintaining the beverage within the limits of 33.5°F to 40°F inclusive when the dispenser is filled to the manufacturer's rated capacity and is operating in an ambient temperature of 90°F. The dispenser shall be capable of reducing the temperature of the rated capacity of beverage from 72°F to 40°F in not more than the applicable time specified in table I when operating in an ambient temperature of 72°F. The dispenser must be capable of reducing the temperature of the beverage to 45°F within 3 hours. The dispenser shall, in addition, operate satisfactorily in an ambient temperature of 100°F, and 80 percent relative humidity for extended periods without deleterious overloading of the hermetic compressor-condenser unit.

TABLE I. Refrigeration system requirements

Dispenser size	Compressor motor rated horsepower (minimum)	Refrigeration capacity, Btu's per hour (minimum)		Pull-down time, hours (maximum)	
		60-Hertz	50-Hertz	60-Hertz	50-Hertz
4	1/6	1250	1040	2.0	2.4
7	1/6	1250	1040	2.0	2.4
11	1/5	1600	1330	2.5	3.0
13	1/4	2800	2330	3.0	3.6

NOTES: (1) Refrigeration capacity based on 90°F ambient temperature, 80°F suction return gas, and 40°F evaporator refrigerant temperature.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

(2) Pull-down time based on 72°F ambient temperature, 50 percent relative humidity, 72°F initial beverage temperature, and 40°F final beverage temperature.

3.7 Design and construction. The dispensers shall be designed and constructed for counter mounting. The distance from the front edge of the dispenser base (exclusive of drip tray) to the rearmost extension of the dispenser shall not exceed 23 inches. The height of the dispenser, measured from the counter to the top of the cover, shall not exceed 30 inches, except when the weight of a style A, size 13 or a style B, size 11 precludes its classification as movable equipment and the dispensers therefore must be leg-mounted to meet NSF cleanability requirements. When specified for shipboard applications (see 6.2), four holes for 3/8-inch mounting bolts shall be provided in the frame for securing the dispenser to a counter.

3.7.1 Base assembly. The base assembly shall be designed and constructed to house the refrigeration system and to support the container bowls, dispensing faucets, and drip traps. The base shall be equipped with removable panels to provide access to the components therein. At least two opposite panels shall be open-grid or perforated construction to provide an adequate source of cooling air for the refrigeration condenser coils.

3.7.2 Refrigeration system. The refrigeration system shall be of the air-cooled, hermetically-sealed type consisting essentially of a compressor-condenser unit, a drier-strainer, a corrosion-resistant evaporator cooling dome, plate or coil, a capillary tube or expansion valve, and an automatic on-off cycling thermostat. The condensers shall be furnished with cooling fans to provide a positive, forced-circulation flow of air through the coils. The system shall have sufficient capacity to meet the performance requirements of 3.6 at the specified temperatures. In no case, however, shall the condensing unit manufacturer's standard commercial horsepower and capacity ratings be less than the applicable ratings specified in table I. The refrigeration system on each dispenser shall be completely dehydrated and fully charged prior to shipment. A low pressure sensing switch shall be provided in the event that loss of refrigerant charge becomes sufficiently low and shut off the unit automatically. The low pressure sensing switch shall be of the manual reset type.

3.7.3 Agitation system. Each bowl or compartment shall be equipped with an individual agitation system. Agitation systems for type I dispensers shall consist of a rotating impeller in the base of the bowl plus a spray tube for continuous, pumped, overhead, recirculation and aeration of the beverage. Agitation systems for type II dispensers shall consist of a rotating impeller or disk or shall be of the immersed, revolving-paddle type, at the option of the supplier. Pumps for spray-type systems shall be driven by an electro-magnetic coupling to eliminate the need for direct connection to the driving motor through the bottom of the bowl. The motor for operating spray pumps and mixing paddles shall be rated at not less than 1/70 horsepower. The mixing systems shall impart a constant agitative motion to the stored beverage to prevent settlement of beverage constituents and to assist in maintaining the required beverage temperature at the inlet to the dispensing port.

3.7.4 Bowls. Bowls and covers shall be fabricated of a rigid, impact-resistant, colorless, transparent, acrylic or polycarbonate plastic material. The thickness of the bowls shall be not less than 3/32 inch. The bowls shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

have sufficient net volume, exclusive of space occupied by the cooling dome or plate and mixing system components, to meet the capacity requirements applicable to the size specified. Bowls shall be furnished and installed with gaskets and seals required to provide leak-tight containers. Bowls shall be impact-resistant to the extent that, if pushed from a 36-inch counter to a concrete floor, the bowl will not crack or become otherwise damaged. Bowls which are required to be removed for cleaning shall not crack or become otherwise damaged when tested as specified (see 4.5.2.5).

* 3.7.5 Dispensing faucets. Each bowl on style A units and each bowl or compartment on style B units shall be equipped with at least one dispensing faucet. Dispensing faucets shall be designed to be opened by a push-type lever or bale and shall be self-closing. The operating lever or bale and other parts of the faucet shall be stainless steel, plastic, or a combination of both. Faucets shall be designed to permit thorough cleaning of all fluid passages and parts exposed to the beverage.

3.7.6 Drip tray. Each dispenser shall be equipped with a drip tray having a removable perforated or slotted cover.

3.7.7 Water fill valve. When specified for size 7 and larger (see 6.2.1), the dispensers shall be equipped with a manual, inlet fill valve. When such fill valves are furnished, the dispenser shall be protected, in accordance with NSF Std. No. 18, against back siphonage or back flow by an air gap of not less than twice the diameter of the water supply inlet and in no case less than one inch; by an approved type vacuum breaker; or by such other method as is approved by NSF.

3.8 Electrical requirements. The dispensers shall be designed for operation on a nominal 115-volt, single-phase, 60-Hertz alternating current or a nominal 220-volt, single-phase, 50-Hertz alternating current in accordance with the specified electrical rating (see 1.2). Each dispenser shall be equipped with a flexible power supply cord, a thermostatic control, and required switches.

3.8.1 Power supply cord. The power supply cord shall include an equipment grounding conductor and an attachment plug cap of the grounding type. The grounding conductor shall be green and shall be secured to the base assembly by a screw or equivalent means not likely to be removed during servicing operations not involving the cord. The power supply cord shall be provided with means to prevent strain on the cord being transmitted to terminals, with means to prevent strain on the cord being transmitted to terminals, splices, or internal wirings. The edges of the entry hole for the cord shall be smooth and well rounded. The length of the power supply cord external to the base enclosure shall be not less than five feet. The plugs shall conform to NEMA Pub. No. WD-1, figure 5-15 for 115/1/60 dispensers and, unless otherwise specified (see 6.2.1), figure 6-15 for 220/1/50 dispensers.

3.8.2 Thermostatic control. Each dispenser shall be equipped with a thermostatic control to automatically cycle the refrigeration system to maintain the beverage temperature specified herein. The nominal differential between the cut-in and cut-out points shall be not less than four nor more than six degrees. The control shall be calibrated and preset prior to shipment of the dispenser. A tolerance of $\pm$ 1.5°F, will be allowed at either cut-in or cut-out factory settings provided the beverage is maintained within the temperature limits specified in 3.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

3.8.3 Switches. Style A dispensers shall be equipped with at least one on-off switch to control the power supply to the dispenser. Style B units shall be equipped with on-off switch(s) for the mixing system in the bowl(s) or compartment plus a third main power supply or compressor motor switch.

3.9 Identification marking. Each dispenser shall be marked with the following information and in accordance with UL 471:

a. Manufacturer's name or trademark.
b. Manufacturer's model number or equivalent identification.
c. Electrical rating.
d. Kind and amount of refrigerant in pounds or ounces.
e. Factory test pressures for the high- and low-pressure sides.

3.9.1 Military marking. When specified (see 6.2), each dispenser shall be marked in accordance with MIL-STD-130 in addition to the marking required under 3.9.

3.10 Fungus resistance. When specified (see 6.2), electrical components and circuit elements, including terminal and circuit connections, shall be coated with varnish conforming to MIL-V-173, except that:

a. Components and elements inherently inert to fungi or in hermetically sealed enclosures need not be coated.
b. Current-carrying contact surfaces, such as relay contact points, shall not be coated.

Surfaces to be treated shall be cleaned to insure adherence of the varnish. The varnish shall be applied by wet-spraying, brushing, dipping, or a combination thereof to a dry film thickness of at least one mil.

3.11 Technical publications. Technical publications pertinent to dispenser operation, servicing, and spare parts shall be furnished in accordance with the applicable provisions of the contract (see 6.2.2).

3.12. Workmanship.

3.12.1 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions which would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to insure uniformity of size and shape.

3.12.2 Bolted connections. Bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers or lockwashers shall be provided in accordance with good commercial practice, and all bolts, nuts, and screws shall be tight.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.1.2 Standards compliance. The contractor shall make available to the contracting officer or his authorized representative evidence of compliance with the applicable standard(s) cited in 3.3.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1)
b. Quality conformance inspection (see 4.2.2)

4.2.1 First article inspection. The first article inspection shall be performed on one complete dispenser when a first article is required (see 3.2 and 6.3). This inspection shall include the examination of 4.4 and the tests of 4.5.2. The first article may be either a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.4, the tests of 4.5.1, and the packaging inspection of 4.6. This inspection shall be performed on the samples selected in accordance with 4.3.

4.3 Sampling. Sampling and inspection procedures shall be in accordance with MIL-STD-105. All dispensers of the same type, size, style, and electrical rating offered for delivery at one time shall be considered a lot for the purpose of inspection. The inspection level shall be level II and the Acceptable Quality Level (AQL) shall be 2.5 defects per hundred units. If an inspection lot is rejected, the contractor may rework it to correct the defects, or screen out the defective units, and resubmit for a complete reinspection. Resubmitted lots shall be reinspected using tightened inspection. If the rejected lot was screened, reinspection shall be limited to the defect causing rejection. If the lot was reprocessed, reinspection shall be performed for all defects. Rejected lots shall be separate from new lots, and shall be clearly identified as reinspected lots.

4.4 Examination. Each dispenser selected shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specified requirements, or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements shall constitute a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

* 4.5 Tests. Prior to performance of the tests specified herein, the dispensers to be tested shall be operated for a period of time deemed necessary by the manufacturer for proper run-in and adjustment of the units. All tests shall be conducted using the nominal voltage and frequency applicable to the specified electrical rating. When specified (see 6.2.1), water shall be used in the test unless otherwise specified, the beverages used for the tests shall be as follows:

a. Type I dispensers: Either a commercially available, sweetened, non-carbonated, syrup drink or, in lieu thereof, an aqueous sucrose solution in the proportion of 171 grams of granulated sugar per 1000 grams of water.
b. Type II dispensers: Fresh orange or grapefruit juice as prepared when a commercial, electric-motor-operated extractor is used and the strainer furnished therewith, or orange or grapefruit juice prepared from a frozen concentrate which meets the applicable standards of the U.S. Department of Agriculture and is mixed in the proportions recommended by the concentrate producer.

4.5.1 Operation test. Each selected dispenser, after being fully charged and serviced, shall be operated to verify the functional adequacy of the unit. Units furnished for 50-Hertz (Hz) operation shall be tested using 50-Hz current. Each unit shall be filled to rated capacity with the applicable test beverage at a minimum initial temperature of 50°F. The ambient temperature shall be not less than 70°F. The unit shall be operated until the temperature of the beverage, as measured in the bowl or in a sample drawn from the faucet, reaches 40°F. The total volume of samples drawn during the test shall not exeed 10 percent of the rated capacity of the bowl. Style B units shall be operated until the temperature of the beverage in both bowls reaches 40°F. Failure of any unit to reduce and to maintain the temperature at 40°F, and failure to satisfactorily agitate and dispense the beverage, shall be cause for rejection of the dispenser.

4.5.2 First article tests.

4.5.2.1 Performance test. The dispenser shall be filled to rated capacity with the applicabe test beverage. The temperature of the test beverage shall be at least 50°F at the start of the test. The dispenser shall be operated in an ambient temperature of 90°F ± 5°F, until the beverage, as dispensed from the faucet(s), attains a temperature stabilized in the range of 33.5°F to 40°F. The test run shall then continue for at least two hours with sample portions being drawn and checked for temperature at intervals not exceeding five minutes except that, during the last 15 minutes, a sample shall be drawn and checked each minute. The samples shall be drawn in 12-fluid-ounce paper cups and the temperature checked immediately to minimize the environmental effect of the 90°F ambient temperature. The temperature sensing device may be chilled between readings in a 32°F ice-water bath to offset the time lag between taking the sample and reading the temperature. On style B units each bowl or compartment shall be checked alternately at the specified intervals during the test run. Failure of the dispenser to maintain the beverage temperature within the specified 33.5°F to 40°F, limits shall constitute failure of the test.

4.5.2.2 Pull-down test. The first article sample shall be filled to rated capacity with the applicable test beverage. The temperature of the beverage shall be at 72°F ± 1°F, and ambient temperature shall be 72°F ± 2°F. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

dispenser shall be operated until the temperature of the beverage, as measured in the bowl or in a sample drawn from the faucet, reaches 40°F. The total volume of samples drawn during the test shall not exceed 10 percent of the rated capacity of the bowl. On style B units the time for both bowls to reach the required 40°F, temperature shall be recorded. Failure of the units to comply with the specified temperature pull-down time shall constitute failure of the test.

4.5.2.3 Maximum ambient temperature. The first article sample shall be filled to rated capacity with the applicable test beverage. The beverage and dispenser shall be stabilized at, and operated in, an ambient temperature of 100°F, with at least 80 percent relative humidity. The test run shall continue until the unit is under control of the on-off cycling thermostat for minimum of one hour. Any evidence of continuous abnormal overload on the compressor motor during the test run, as indicated by excessive unit heating or frequent shutdowns caused by the motor overload protective device, shall constitute failure of the test.

4.5.2.4 Impact test. The plastic bowl on the first article sample shall be tested to determine compliance with the impact-resistance requirement of 3.7.4. The bowl shall be dropped from a height of 36 inches onto a concrete surface at least three times to cover three different points of impact: (1) The bottom of the bowl which normally rests on the base, (2) the top rim which normally support the cover, and (3) any of the four corners. Failure to withstand any impact without cracking or other damage shall be cause for rejection of the units.

4.5.2.5 Bowl removal test. After the dispenser has successfully passed the operational, pull-down, maximum ambient temperature, and impact tests, the bowl of the same dispenser shall be removed and replaced in accordance with the instruction manual to be furnished with the dispenser. Unless otherwise specified (see 6.2.1), this procedure shall be repeated with the same bowl 25 times to determine compliance with the bowl removal requirements of 3.7.4. Any nonconformance shall constitute failure of this test.

4.6 Packaging inspection. An examination shall be made to determine compliance with the requirements of section 5. The sample unit shall be one unit prepared for shipment. Sampling shall be in accordance with MIL-STD-105. The inspection level shall be S-2 with an AQL of 4.0 percent defective.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A. Dispensers shall be packaged in accordance with method III of MIL-P-116 using a fiberboard container conforming to PPP-B-636, weather-resistant class. The bowl assemblies (with covers) and the chassis may be packed separately to facilitate handling or to comply with size and weight limitations of PPP-B-636. Contents shall be cushioned to prevent movement within the box.

5.1.2 Commercial. Dispensers shall be preserved and packaged in accordance with ASTM D3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.2.1 Levels A and B. Packing shall be accordance with MIL-STD-794. Containers shall be selected from table I for the appropriate level. Only closed containers shall be used.

5.2.2 Commercial. Packing shall be in accordance with ASTM D3951.

5.3 Palletization. Material shall be palletized in accordance with MIL-STD-147 when the following criteria are met:

a. Load to consist of four or more unskidded containers; and,
b. Load shall utilize a minimum of 80 percent of the pallet base.

5.4 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The beverage dispensers covered by this specification are intended to mix, cool, and dispense noncarbonated beverages such as pulpy juices, frozen concentrates, and syrup drinks in mess halls, cafeterias, post exchanges, and similar military facilities.

6.2 Ordering data. Acquisition documents should specify the following:

6.2.1 Acquisition requirements.

a. Title, number, and date of this specification.
b. Type, style, size, and electrical rating required (see 1.2).
c. When two dispensing faucets are required on style A, size 13 units (see 3.1).
d. When a first article inspection is required (see 3.2).
e. When holes for shipboard mounting bolts are required (see 3.7).
f. When a water fill valve is required for size 7 and over (see 3.7.7).
g. When the electrical plug for 220/1/50 dispensers shall be other than NEMA figure 6-15 (see 3.8.1).
h. When military marking in accordance with MIL-STD-130 is required and the information to be marked (see 3.9.1).
i. When fungus treatment is required (see 3.10).
j. When water is used in the test (see 4.5).
k. Number of repititions required if other than specified (see 4.5.2.5).
1. Level of packaging and level of packing required (see 5.1 and 5.2).

6.2.2 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List (CDRL), the data requirements identified below shall be developed as specified by an approved DD Form 1664, Data Item Description (DID), and delivered in accordance with the approved CDRL incorporated into the contract. When the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

Paragraph No.	Data requirements title	Applicable DID No.	Option
3.3.1, 3.3.2	Certificate of Compliance	DI-E-2121	
3.11	Publications, Commercial	UDI-H-24010	

(Copies of Data Item Descriptions required by contractors in connection with specific acquisitioning functions should be obtained from the acquisitioning activity or as directed by the contracting officer).

6.3 First article. When a first article inspection is required, the item will be tested and should be a preproduction sample selected from the first production run, or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one complete dispenser unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

Custodians:

Army - GL
Navy - YD
Air Force - 99

Preparing activity:

Navy - YD

(Project 7310-0671)

Review activities:

Army - MD
Navy - MC
Air Force - 84
DLA - GS

User activity:

Navy - MS, SA

☆U.S. GOVERNMENT PRINTING OFFICE: 1984—705-040/A1938

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY
Commander
Naval Facilities Engineering Command
200 Stovall Street
Alexandria, VA 22332

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commander (156)
Naval Construction Battalion Center
Port Hueneme, CA 93043

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-82035C	DISPENSERS, BEVERAGE, MECHANICALLY REFRIGATED

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:37Z
Check the source to verify that this is the current version before use.