INCH-POUND

MIL-P-71092 (AR)
9 July 1992

MILITARY SPECIFICATION

PROJECTILE, 155MM, INERT, M864 LOADING, ASSEMBLING AND PACKING

This Specification is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading, assembling, and packing for five types of projectiles designated as Projectile, 155MM, Inert, M864.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defence Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-P-48099 - Propellant, M10 (For use in Special Applications)

STANDARDS

FEDERAL

FED-STD-101 - Preservation, Packaging and Packing Materials, Test Procedures

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1320

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

MILITARY

MIL-STD-286 - Propellants, Solid; Sampling, Examination and Testing
MIL-STD-410 - Non-destructive Testing Personnel Qualification and Certification
MIL-STD-453 - Inspection, Radiographic
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

(Unless otherwise indicated, copies of federal and military specifications, standards and handbooks are available from: Military Specifications and Standards, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094).

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (see 6.4)

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKAGING DRAWINGS

8837839 - Pallet for 155MM Projectile 155MM, HE: and GB, Hollow Base Type
12914056 - Projectile, 155MM: Extend Range, Inert, M864
12914057 - Projectile, 155MM: Extend Range, Inert Grenade, M864
12914058 - Projectile, 155MM: Extended Range, Inert, Empty Burner, M864
12914059 - Base Burner Assembly, Empty, M864

INSPECTION EQUIPMENT DRAWINGS

8841732 - Test Fixture
9202990 - Operating Instructions

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

TITLE 49 - Transportation, Parts 100-199

(The Code of Federal Regulations is available from the Superintendent of Documents, US Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 100-199 (latest revision)".)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM E-18 - Standard Methods of Test for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials

(Copies may be purchased directly from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

2.3 Order of precedence. In the event of a conflict between the text of this document and the reference cited herein, (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Projectile. The projectile assembly and parts thereof shall comply with all requirements specified on Drawings 12914056, 12914057, or 12914058, and associated drawings, and with all requirements specified in applicable specifications and standards (see 6.5)

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the currentversion before use.

3.3 Radiographic examination of projectiles. Prior to forwarding the projectiles to the proving ground for ballistic testing, the projectiles shall be subjected to radiographic examination. The projectiles shall be examined for the following:

a. Gap in excess of .015 inches between adapter and base.

b. Gap in excess of .015 inches between adapter and grenade.

c. Gap in excess of .015 inches at take-up pad area between grenade and forward plate.

d. Gap in excess of .015 inches between grenades.

e. Safety pin or safety clip shall not be present.

f. Any missing or improperly positioned component or assembly normally discernible on the radiograph.

g. Presence of gap between base and body.

3.4 Records of results of contractor-conducted examinations and tests. The contractor shall maintain records of the results of all examinations or tests required by this specification.

3.5 Workmanship.

3.5.1 General. All parts and assemblies shall be fabricated, loaded, and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material and protective coating missing per 4.4.3.1 are permitted. All required marking and stamping shall be neat and sharply defined.

3.5.2 Painting and marking. The painting and marking shall be restored by the assembling contractor on any component furnished painted and marked, when such painting and markings have been marred or obliterated.

3.5.3 Rotating band. Care shall be exercised at all times so that the rotating band of the projectile is not nicked, burred or otherwise damaged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of Section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. Quality conformance inspection (see 4.4).

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition each inspection lot of projectiles shall contain:

a. Grenades (M42) inert from one finally accepted lot interfix number from one manufacturer.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the currentversion before use.

b. Grenades (M46) inert from one finally accepted lot interfix number from one manufacturer.

c. Projectile metal parts (body/ogive assembly) from one lot interfix number from one manufacturer.

d. Base burner assemblies from one lot, from one interfix number and from one manufacturer.

e. Adapters from one lot interfix number from one manufacturer.

f. Forward plates from one lot interfix number from one manufacturer.

g. Sleeves from one manufacturer.

h. Spacers from one manufacturer.

i. Splines from one lot interfix number from one manufacturer.

j. Expulsion charge assembly propellant from one manufacturer and no more than two serial lot numbers.

k. Loaded projectiles of one weight zone.

i. Expulsion cups from one lot interfix number from one manufacturer.

4.4.2 Examinations and tests. See MIL-A-48078.

a. Classification of Characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. When "0-1" attributes sampling inspection shall be performed on the designated characteristics using the stated levels in Table I for selection of sample sizes. If one or more defective units of product is found in any sample, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

b. Alternative inspection provisions. Alternative inspection procedures, methods or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods or equipment, the contractor shall describe them in a written proposal submitted to the procuring contracting officer for evaluation and approval by the Government (see 6). When required, the contractor shall demonstrate that the effectiveness of the proposed alternative(s) is equal to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative(s) provide equal assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system as applicable.

c. Automatic gage. Facilities equipped with Government furnished automatic gaging capable of performing 100% inspection of any characteristics shall utilize this capability in accordance with the contract (see 6.11).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

TABLE I SAMPLING

Lot Size	Inspection Level I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	12	4
91 to 150	*	125	32	13	12	5
151 to 280	*	125	32	30	14	6
281 to 500	*	125	32	30	17	7
501 to 1200	*	125	74	35	20	9
1201 to 3200	1250	125	74	43	24	10
3201 to 10000	1250	125	87	50	30	10
10001 to 35000	1250	296	109	61	36	10
35001 to 150000	1250	296	124	74	40	10
150001 to 500000	1250	346	156	91	40	10
500001 and over	1250	431	187	102	40	10

Numbers under inspection levels indicate sample size; asterisk indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

4.4.3 Testing. Testing is required as described herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71092 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.1.	Projectile	1 OF 1	See Note 1

NEXT HIGHER ASSEMBLY: None

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Lifting plug assembly not universal type	100%, 0-1	3.3	Visual
102	Gasket missing or damaged	100%, 0-1	3.2	Visual
103	Lifting plug assy. torque improper	100%, 0-1	3.2	Gage
104	Air pressure test of projectile	100%, 0-1	3.2	4.5.1
105	Bourrelet diameter oversize	100%, 0-1	3.2	Gage
106	Zone marking missing, incorrect, or unidentifiable, as applicable (see 6.5)	100%, 0-1	3.2	Visual
107	Diamond marking missing, incorrect, or unidentifiable	100%, 0-1	3.2	Visual
108	Any part missing or damaged	100%, 0-1	3.2	Visual
109	Weight marking missing, as applicable	100%, 0-1	3.2	Visual/Scale
110	Radiographic examination	100%, 0-1	3.2	4.5.2
Minor				
201	Rotating band damaged	Level V	3.2	Visual
202	Protective coating with bare area in excess of 1/4 square inch (after projectile paint has been retouched)	Level V	3.2	Visual
203	Marking missing or unidentifiable	Level V	3.2	Visual
204	Evidence of poor workmanship	Level V	3.5	Visual

NOTES:

Note 1 - Applicable drawing numbers are 12914056, 12914057, and 12914058.

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-03-04 20:17
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71092 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.2	Projectile	1 OF 1	See Note 1

NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
a	Gap between projectile body and base over max.	100%, 0-1	3.2	4.5.3
Major				
101	Disassembly torque test of base burner assembly	100%, 0-1	3.2	Gage
102	Depth from surface of projectile to expulsion charge cup under min	Level III	3.2	Gage
103	Expulsion charge cup improperly staked	Level III	3.2	Visual/Manual
104	Obturator missing or damaged	100%, 0-1	3.2	Visual
105	Evidence of axial movement of obturator	100%, 0-1	3.2	Manual
Minor				
201	Sealing compound not present between projectile body and base	Level V	3.2	Visual
202	Evidence of poor workmanship	Level V	3.5	Visual

NOTES:

Note 1 - Applicable drawing numbers are 12914056, 12914057, and 12914058.

Source: https://assist.dla.mil - Downloaded: 2026-01-23 10:04:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.3	Projectile, After Assembly of Adapter and Immediately Prior to Assembly of Base Burner	1 OF 1	See Note 1
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Depth between projectile face and adapters or shims as applicable at specified load	100%, 0-1	3.2	4.5.4
102	Seal ring missing or wrong type	Level III	3.2	Visual
103	Seal ring not greased	Level III	3.2	Visual
104	Sealant missing on threads of base burner assembly	100%, 0-1	3.2	Visual
105	Threads damaged on base burner assembly or projectile body	Level III	3.2	Visual
106	Foreign material on threads	Level III	3.2	Visual
Minor				
201	Evidence of poor workmanship	Level V	3.5	Visual

NOTES:

Note 1 - Applicable drawing numbers are 12914056, 12914057, and 12914058.

Source: https://assist.dla.mil - Downloaded: 2026-02-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71092 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.4	Projectile Metal Parts Assembly, Prior to Loading	1 OF 1	9381117
			NEXT HIGHER ASSEMBLY: See Note 1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Threads damaged at base end	Level III	3.2	Visual
102	Threads damaged at nose end	Level III	3.2	Visual
103	Internal lubricant applied improperly	Level III	3.2	Visual
Minor				
201	Foreign matter on interior body surface	Level V	3.2	Visual
202	Evidence of poor workmanship	Level V	3.5	Visual

NOTES:

Note 1 - Applicable drawings are 12914056, 12914057, and 12914058.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71092 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.5	Assembly, Forward Plate and O-Ring	1 OF 1	See Note 1

NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major	None defined			
Minor				
201	O-Ring	Level V	3.2	Visual
202	Evidence of poor workmanship	Level V	3.5	Visual

NOTES:

Note 1 - Applicable drawings are 12914056, 12914057, and 12914058.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71092 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.6.	Adapter	1 OF 1	9215380
			NEXT HIGHER ASSEMBLY: See Note 1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special a	Verification of heat treatment of adapter	100%, 0-1	3.2	4.5.5
Major	None defined			
Minor	None defined			

NOTES:

Note 1 - Applicable drawing numbers are 12914056, 12914057, 12914058.

AMSMC Form 1570a-E, 1 Jul 89

Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71092 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.7	Inert Grenade Assembly, Prior to Loading	1 OF 1	9381451 or 9381454

NEXT HIGHER ASSEMBLY: See Note 1

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Safety clip not removed	Level III	3.2	Visual
102	Ribbon unwound	Level III	3.2	Visual
103	Tape not completely inserted in slots of stiffener	Level III	3.2	Visual
104	Slider lock improperly positioned	100%, 0-1	3.2	Visual
105	Inert marking missing, incomplete, or illegible	100%, 0-1	3.2	Visual
Minor	None defined			

NOTES:

Note 1 - Applicable drawing numbers are 12914056, 12914057, and 12914058

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-P-71092 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.3.8.	Pallet Assembly	1 OF 1	8837839
			NEXT HIGHER ASSEMBLY: None

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Incorrect strapping	Level III	3.2	Visual
102	Pallet improperly assembled	Level III	3.2	Visual
103	Seal strapping missing	Level III	3.2	Visual
104	Lifting plug of projectile missing or damaged	Level III	3.2	Visual
105	Cover support missing (8 places)	100%, 0-1	3.2	Visual
106	Inert marking of projectile missing, incomplete, or illegible	100%, 0-1	3.2	Visual
Minor				
201	Board broken or split	Level V	3.2	Visual
202	FSN number missing or unidentifiable	Level V	3.2	Visual
203	Any other marking missing, incorrect, or unidetifiable	Level V	3.2	Visual

NOTES:

AMSMC Form 1570a-E, 1 Jul 89

Replaces AMSMC Form 1570a, 1 Apr 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4.4.4 Automatic inspection equipment. All automatic inspection equipment, when utilized by the contractor, shall be subjected to periodic verification and/or calibration check during production. Minimum procedures that shall be included are frequency of inspection, method of verification, and the method of retrieval of items produced between verification/calibration. These procedures shall be included in the operation/calibration procedures as required by the above paragraph.

4.5 Test methods and procedures.

4.5.1 Air pressure test of projectile. The assembled projectile, with lifting plug, shall be placed in one or more chambers, (the base to body, body to ogive and ogive to lifting plug joints must be tested) and a pre-determined volume of air shall be delivered to produce the specified pressure between the inside of the chamber and the outside of the projectile. After initiation of test, the pressure must achieve the required level and maintain that level for the specified time interval. Failure to meet either criteria shall be cause for rejection, and that projectile shall be suitable identified and removed from the lot to prevent mixing with acceptable projectiles.

4.5.2 Radiographic inspection of projectile. The projectile assemblies shall be radiographically examined prior to forwarding to the proving ground. Prior to assembly of the base burner assembly, the Government inspector shall indicate the location of the spline by marking the outside of the projectile. In all exposures, the radiographic beam shall be focused along the center axis of the projectile and parallel to the face of the forward plate, with the spline 90 degrees to the right in the direction from the source to the projectile. Radiographic exposure shall, as a minimum, include all of the projectile aft of, and including the forward plate. If necessary, more than one radiograph shall be taken in this view as required to avoid detrimental parallax effects and to observe the conditions specified in 3.5. In the event that the radiograph(s) taken in this view prevent a suitable examination, the projectile shall again be radiographed at a location rotated 90 degrees from the original view, with the spline nearest to the source. Projectiles and radiographs shall be suitably identified to permit cross reference. Radiographs of the projectile. If any defect, per paragraph 3.5 is found, it shall be reported to SMCAR-QAR-Q. The lot represented by this sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

4.5.2.1 Radiographic qualifications. Radiogrphic equipment, operations, and procedures shall be qualified in accordance with MIL-STD-453. The personnel performing this examination shall be qualified and certified, Level 2, per MIL-STD-410. In addition, the radiographic examination shall be performed with the technique capable of producing 2 percent sensitivity (radiographic quality level 2-2T) and the photographic density of the film used shall be of a quality which will produce a sharp definition of internal structure.

4.5.2.2 Failure. If one or more assemblies fail to meet the requirements of paragraph 4.5.2.1.2, the quantity represented by that sample shall be set aside and retested per the procedure defined in paragraph 4.5.2.1.4. Only one reinspection and retest shall be permitted for each failed lot.

4.5.2.3 Reinspection and retest. The quantity represented by the failed sample shall be one-hundred percent (100%) visually reinspected for completeness of seal (top, side, and bottom). Bags defective, and removed from production. Ten (10) assemblies shall be selected from the remaining quantity and subjected to the test described in paragraph 4.5.2.1.2. Failure of one or more samples shall result in the quantity represented by the sample as being defective and removed from production.

4.5.2.4 Acceptance criteria. For the purpose of this test, an assembly which exhibits the presence of wet M10 propellant, as evidenced by the darkening of the propellant, shall be cut open and manually and visually checked for the presence of moisture. Only those assemblies containing moisture shall be considered defective.

4.5.3 Inspection of gap between projectile body and base. Gap shall be inspected using an approved feeler gage as specified on drawing 9381131. The feeler gage shall be cleaned with a clean dry rag immediately after each inspection such that the gage is free of any base/body gap sealant. No solvent or other substance other than a clean dry rag shall be used to clean the gage. The gap between the projectile body and base shall be inspected within fifteen (15) minutes after the sealant is applied to the shoulder of the base.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the current version before use.

4.5.4 Depth to adapters or shims. This measurement shall be performed using automatic or semi-automatic inspection equipment. The design of this equipment shall be "fail-safe" to the extent that the projectile cannot be released for further processing until the proper number of shims have been inserted. Verification that the proper number of shims have been inserted shall be accomplished by re-inspection of this depth.

4.5.5 Verification of heat treatment of adapter (non-destructive). This inspection shall employ the eddy current method, or any other equivalent method approved by the procurement agency. If the eddy current method is used, all personnel operating and calibrating this equipment shall be qualified and certified in accordance with MIL-STD-410. The hardness limits shall be established and submitted to the COR for approval prior to use. If any adapter fails to comply with the requirements specified on the applicable drawing, it shall be classed defective and removed from production.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Packaging. Inert components shall be in accordance with the requirements of MIL-STD-1169.

5.2 Packing.

5.2.1 Domestic shipment. Packing and marking of inert components shall be in accordance with the requirements of specification MIL-STD-1169.

5.2.2 Level A. The projectile shall be palletized in accordance with drawing 8837839.

5.3 Marking.

5.3.1 Marking of the projectile pallet. Marking of the projectile pallet shall be in accordance with drawing 8837839.

6. NOTES

6.1 Intended use. The Projectile, 155mm, Inert, M864 is intended for M864 metal parts testing.

Source: https://assist.dla.mil -- Downloaded: 202640-23T04:20Z
Check the source to verify that this is the currentversion before use.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

6.3 Data requirements. The following Data Item Descriptions (DIDs) must be listed, as applicable, on the Contract Data Requirements List (DD Form 1423) when this specification is applied on a contract, in order to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title
6.9	DI-T-5372	* Procedure Report (Tailored)
4.5.3.2 4.5.3.3 4.5.3.5 4.5.3.7	DI-R-1712	Quality Inspection Defect Report
4.5.3.3 4.5.3.4 4.5.3.6	DI-R-1724	Quality Inspection Test Demonstration and Evaluation Report

* Delete a, b, c and d of paragraph 1 of block 10, DD Form 1664, and substitute contractor designated parameters and limits.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament, Research, Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Projectile. Certain testing/inspection requirements shall not be applicable, as determined by the configuration of the item. Applicability of certain configurational inspections/tests are summarized in, but not limited to, Table II, Questions of applicability should be directed to the technical agency.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the current version before use.

TABLE II

Part Number	Zone Marking (Paragraph 4.4.3.1, Major 106)	Weight (Paragraph 4.4.3.1, Major 109)
12914056-1		X
12914056-2	X	
12914057		X
12914058-1		X
12914058-2		X

(Note: An "X" denotes applicability)

6.6 First article. This specification does not make provision for first article inspection.

6.7 Alternate inspection procedures. The alternate inspection procedures, as a minimum, must include:

a. Frequency (production interval) for validating equipment functioning.

b. Proposed method of verification which includes process and inspection drawings.

c. Description of material control procedures to be imposed during the production interval between validations (Note: Under these provisions, final acceptance will be withheld from material produced during the production interval until conducting satisfactory validation).

6.7.1 Justification for alternate inspection procedures. Submitted documentation must include sufficient information to indicate an economic benefit, and must also clearly identify that there is no reduction in product quality.

6.7.2 Approval of alternate inspection procedures. Proposed plans shall be submitted to the contracting officer for consideration. Upon receipt of such a request, the contracting officer shall advise U.S. Army Armament, Research, Development and Engineering Center, ATTN: SMCAR-QAR-Q, Picatinny Arsenal, NJ 07806-5000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

6.8 Statements of findings. Statements of findings shall show the specific analytical results of each test or inspection performed as required by either the applicable drawing of specification, together with the specified acceptable limits.

6.9 Visual examination qualification. When compliance with the applicable requirements is in doubt as a result of visual examination, this characteristic may be measured or gaged to determine acceptability.

6.10 Automatic inspection equipment. All automatic test and inspection equipment, when utilized by the contractor, shall be subjected to a periodic verification and/or calibration check at frequent intervals during normal production. The procedures shall include, as a minimum: Frequency; method of verification; and the method of retrieval of items produced between verification/ calibration. These procedures shall be included in the operation/ calibration procedures as required by paragraph 4.4.4.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-AC71)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-71092	9 SEPTEMBER 1992

3. DOCUMENT TITLE: PROJECTILE, 155MM, INERT, M864, LOADING, ASSEMBLING AND PACKING

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMACA-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:20Z
Check the source to verify that this is the current version before use.