INCH-POUND


MIL-DTL-3476/9D
31 March 2014
SUPERSEDING
MIL-DTL-3476/9C
20 August 1997

DETAIL SPECIFICATION SHEET

BRASSARD, GAS PERSONNEL, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3476.



MATERIAL:
BASE: Facing Cloth
LETTERING: Felt

COLOR:
BASE: Cobalt Blue (Cable No. White HA 65011)
LETTERS: Golden Yellow (Cable No. 65001)

CONSTRUCTION DETAILS:
1. Letters shall be appliquéd to the base in the position show with cotton thread using Stitch Type 301 having 16 stitches to the inch (See The Institute of Heraldry Drawing Number B-8-37).

2. The brassard shall have a 3/8 inch hem on all sides. Hemming shall be accomplished using stitching Type EFa-1 with 12 stitches to the inch.

3. The thread for hemming and appliquéing shall conform to Type IC2, 3 Ply. Ticket No. A of A-A-52094

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:51Z
Check the source to verify that this is the current version before use.

4. The color of the thread for hemming shall conform to Cobalt blue Cable No. HW 67122 and the color of the thread for appliquéing shall conform to Goldenlight Cable No. HG 67107

5. The base and letters shall be cut from a single ply of the material specified.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2014-083)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:51Z
Check the source to verify that this is the current version before use.