Reviewer/user information is current as of the date of this document For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS (FSC listing)
Navy MC8 YD/
Army OI8 EL/
AF 85/ 82/

FED SUP CLASS
5975



DASH NO	DIMENSIONS			
	A	B	C	D
-1	1 1/2	.091	.180	5/16
-2	2	125	.225	5/16
-3	2 1/2	.125	.225	3/8
-4	3	.125	.225	7/16
-5	1 1/2	091	180	3/8
-6	2	125	225	3/8

NOTES.

1 REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

2 THIS STANDARD TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN

3 RING SHALL BE MADE FROM WIRE COMPLYING WITH FEDERAL SPECIFICATION QQ-W-405. (A1)

4. RING SHALL BE HOT DIP GALVANIZED IN ACCORDANCE WITH MILITARY SPECIFICATION MIL-Z-17871

APPROVED 18 JULY 58 REVISED (A2) 19 December 1967

ALL DIMENSIONS IN INCHES

P.A. EL Other Cust YD 82	TITLE HANGER, CABLE (POLE LINE)	MILITARY STANDARD MS39026
PROCUREMENT SPECIFICATION MIL-H-55053	SUPERSEDES	SHEET 1 OF 1

DD FORM 16 APR 64 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

This military standard has been approved by the Department of Defense and is mandatory for use by all Departments and Agencies of the Department of Defense Selection for all new engineering and design applications and for repetitive use shall be made from this document

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:44Z
Check the source to verify that this is the current version before use.