[INCH-POUND]
A−A−59789/16E
26 November 2025
SUPERSEDING
A−A−59789/16D
16 September 2020


COMMERCIAL ITEM DESCRIPTION
SPECIFICATION SHEET

HOLDER, ELECTRICAL CARD, WEDGE RETAINERS, 5 PIECE, FOR COLD PLATE APPLICATIONS, .365 X .375 INCH (9.27 x 9.53 mm) BODY SIZE, SHAFT MOUNTING BODY, WITH VISUAL LOCK INDICATION, SCREW ACTUATED

The General Services Administration has authorized the use of this commercial item description for all federal agencies.

The complete requirements for procuring electrical card holders described herein shall consist of this document and the latest issue in effect of A−A−59789.

CLASSIFICATION/PART IDENTIFICATION NUMBER (PIN). This commercial item description (CID) specification sheet uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see notes herein).



Example: AA59789/16LE40R is the PIN for a nickel finished, 3.8 inch (97 mm) long card holder with a visual lock indication feature. The card holder also features two counterbored holes for use with rivets and a screw self locking element for added resistance to loosening.

SALIENT CHARACTERISTICS.

Performance. Card holders shall hold the circuit card assembly it is attached to firmly in its installed position and prevent loosening or movement as a result of shock and vibration. The card holder shall also provide a thermal transfer path from the circuit card assembly to the cold plate or heat sink surfaces. Card holders shall also have a visual indicator to show when the assembly is in its relaxed (unlocked) and expanded (locked) state.

Interface and physical dimensions. The card holders supplied to this CID specification sheet shall be as specified herein and meet the general requirements specified in CID A−A−59789.

Material. Unless otherwise specified herein, the card holder materials shall be as specified in A−A−59789.

Actuating screw hex drive socket. The across flats dimension for hex drive socket shall be .140 inch (3.60 mm) for mounting options "R" and "V" and .118 inch (3.0 mm) for mounting option "Y".

Cold plate slot width. The recommend cold plate slot width to accommodate the circuit card assembly with attached card holder is .425 inch (10.80 mm) plus the thickness of the printed board of the circuit card assembly (see A−A−59789).


Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

Installation torque. The recommended nominal installation torque is as follows: 20 inch-pounds (2.3 N-m) for assemblies of configuration "C" and "E" and 23 inch-pounds (2.6 N-m) for assemblies of configurations "L" and "D".

Configuration. The configuration of card holders shall be as specified in table I. The details of a particular configuration consist of those on figures 1 and 2; and may include those on figures 3 or 4.

TABLE I. Configuration.

Configuration	Applicable figures	Hardware options
C	1 and 2	No added hardware
L	1, 2 and 3	Screw self-locking element
E	1, 2 and 4	Additional mounting hole
D	1, 2, 3, and 4	Screw self-locking element and additional mounting hole



Inches	mm	Inches	mm	Inches	mm
.350	8.89	.380	9.65	.49	12.45
.365	9.27	.460	11.68	.75	19.05

FIGURE 1. Relaxed and expanded dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Unless otherwise specified, tolerances are ±.02 inch (0.51 mm) for two place decimals and ±.010 inch (0.25 mm) for three place decimals.
3. Tolerance for the mounting hole spacing is ±.005 inch (0.13 mm).
4. The across flats dimension for actuating screw hex drive socket shall be .140 inch (3.60 mm) or .118 inch (3.0 mm) for the corresponding mounting option (see hex drive socket details).

FIGURE 1. Relaxed and expanded dimensions − Continued.

Visual lock indicator (see figure 2). Card holders shall have a visual indicator to show when the card holder is in its relaxed state (unlocked). When the card holder is in the relaxed state (unlocked), the end of the actuating screw shall display a red band on the side of the screw. When the actuating screw on the card holder has been tightened so that the assembly is in the expanded state (locked), this red band shall be concealed.




FIGURE 2. Visual lock indicator.

Finish. The wedge body finish designator shall be as specified in A−A−59789. The finishes available for this CID specification sheet are as follows: "B" (black anodize), "E" (electroless nickel), "H" (hard black anodize), or "R" (clear chemical film).

Length, expanded, and relaxed dimensions. The length designator shall be as specified in A−A−59789. The lengths available for this CID specification sheet are listed in table II. The length, expanded, and relaxed dimensions shall be as specified on figure 1.

TABLE II. Additional assembly dimensions (see figures 1 and 4). 1/

PIN length designator	Dimension "LENGTH" ±.02 (0.5 mm)	Dimension "M" ±.005 (0.13 mm)	Dimension "M/2" ±.005 (0.13 mm)
28	2.8 (71 mm)	.65 (16.5 mm)	.325 (8.26 mm)
38	3.8 (97 mm)	1.65 (41.9 mm)	.825 (20.96 mm)
48	4.8 (122 mm)	2.65 (67.3 mm)	1.325 (33.66 mm)

1/ Dimensions are in inches. Millimeters, in parenthesis, are given for general information only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

Mounting. The mounting designators shall be as specified in A−A−59789. The mounting options available for this CID specification sheet are as follows: "R" (rivet mount holes with counterbore and countersink), "V" (tapped 4−40 holes), or "M" (tapped metric M3 x 0.5 holes). See figures 1, 4 and table I for mounting hole spacing requirements.

Rivet mount holes. The holes used for rivet mounting shall be .134 to .139 inch (3.40 to 3.53 mm) diameter through holes, countersunk 100 degrees by .150 inch (3.81 mm) deep.

Rivets. This card holder uses rivet style B as specified in A−A−59789 when rivet mounting is used.

Configuration hardware options. Card holders can have the following hardware options: no added hardware, screw self-locking element, an additional mounting hole, or a combination of both screw self-locking element and third mounting hole. See table I for the correct PIN configuration identifier. Card holders requiring no added hardware options shall include configuration identifier "C" in the PIN (see classification and notes section herein).

Screw self-locking element (see figure 3). The use of a screw self-locking element on the screw will provide a prevailing-torque for increased resistance to loosening of the card holder assembly from shock and vibration. The screw self-locking element shall be as specified in A−A−59789. Card holders requiring a screw self-locking element shall include configuration identifier "L" in the PIN (see table I, classification and notes section herein).




FIGURE 3. Screw self-locking element details.

Additional mounting hole (see figure 4). Card holders requiring an additional mounting hole shall include configuration identifier "E" in the PIN (see table I, classification and notes section herein).




FIGURE 4. Additional mounting hole details.

Screw self-locking element and additional mounting hole. Card holders requiring a screw self-locking element and an additional mounting hole option shall include configuration identifier "D" in the PIN (see table I, classification and notes section herein).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

NOTES.

PIN. The PIN should be used for Government purposes to buy commercial products to this CID specification sheet. See the classification section for PIN format example.

Source of documents.

Commercial Item Description

A−A−59789 − Holder, Electrical Card, Wedge Retainers, 5 Piece, For Cold Plate Applications, General Requirements For.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

Ordering data. Ordering data shall be as specified in A−A−59789.

Commercial products. As part of the market analysis and research effort, this CID specification sheet was coordinated with the following manufacturers of commercial products. At the time of CID specification sheet preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID specification sheet. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

Part number supersession data. These CID specification sheet PINs supersede the following manufacturer's part numbers as shown in table III. The CID PINs listed in table III are only for length designator "50". See table IV for CID PIN construction using other available lengths for this CID specification sheet. This information is being provided to assist in reducing proliferation in the Government inventory system.

Manufacturer CAGE	Manufacturer name and address	Manufacturer contact information
5BG68	American Circuit Card Retainers, Inc. 1060 Ortega Way Suite B Placentia, CA 92870−7125	Telephone: (714) 738−6194 Facsimile: (714) 446−0119 E-mail: sales@accrmfg.com URL: www.accrmfg.com
76096	Elma Electronic, Inc. 44350 Grimmer Blvd. Fremont, CA 94538−6385	Telephone: (510) 656−3400 Facsimile: (510) 656−3783 Electronic mail: sales@elma.com URL: www.elma.com
61081	Schroff, Inc. 7328 Trade Street San Diego, CA 92121−3410	Telephone: (858) 740−2400 Facsimile: (858) 740−2430 E-mail: askschroff@nVent.com URL: schroff.nvent.com

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data.

PIN designator AA59789/16	Vendor similar designator or type part number 1/ 2/		
	CAGE 5BG68	CAGE 76096	CAGE 61081
CB50M	5375VBA-4.80TM3	460-B0480T26NVNN	VA280-4.80TM3
CB50R	5375VBA-4.80H	460-B0480T25NVNN	VA280-4.80H
CB50V	5375VBA-4.80T4	460-B0480T27NVNN	VA280-4.80T4
LB50M	5375VBA-4.80TM3L	460-B0480T26LVNN	VA280-4.80TM3L
LB50R	5375VBA-4.80HL	460-B0480T25LVNN	VA280-4.80HL
LB50V	5375VBA-4.80T4L	460-B0480T27LVNN	VA280-4.80T4L
EB50M	5375VBA-4.80ETM3	460-B0480T36NVNN	VA280-4.80ETM3
EB50R	5375VBA-4.80EH	460-B0480T35NVNN	VA280-4.80EH
EB50V	5375VBA-4.80ET4	460-B0480T37NVNN	VA280-4.80ET4
DB50M	5375VBA-4.80ETM3L	460-B0480T36LVNN	VA280-4.80ETM3L
DB50R	5375VBA-4.80EHL	460-B0480T35LVNN	VA280-4.80EHL
DB50V	5375VBA-4.80ET4L	460-B0480T37LVNN	VA280-4.80ET4L
CE50M	5375VEN-4.80TM3	460-N0480T26NVNN	VEN280-4.80TM3
CE50R	5375VEN-4.80H	460-N0480T25NVNN	VEN280-4.80H
CE50V	5375VEN-4.80T4	460-N0480T27NVNN	VEN280-4.80T4
LE50M	5375VEN-4.80TM3L	460-N0480T26LVNN	VEN280-4.80TM3L
LE50R	5375VEN-4.80HL	460-N0480T25LVNN	VEN280-4.80HL
LE50V	5375VEN-4.80T4L	460-N0480T27LVNN	VEN280-4.80T4L
EE50M	5375VEN-4.80ETM3	460-N0480T36NVNN	VEN280-4.80ETM3
EE50R	5375VEN-4.80EH	460-N0480T35NVNN	VEN280-4.80EH
EE50V	5375VEN-4.80ET4	460-N0480T37NVNN	VEN280-4.80ET4
DE50M	5375VEN-4.80ETM3L	460-N0480T36LVNN	VEN280-4.80ETM3L
DE50R	5375VEN-4.80EHL	460-N0480T35LVNN	VEN280-4.80EHL
DE50V	5375VEN-4.80ET4L	460-N0480T37LVNN	VEN280-4.80ET4L

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

TABLE III. Commercial part number supersession data - Continued.

PIN designator AA59789/16	Vendor similar designator or type part number 1/ 2/		
	CAGE 5BG68	CAGE 76096	CAGE 61081
CH50M	5375VBH-4.80TM3	460-H0480T26NVNN	VHA280-4.80TM3
CH50R	5375VBH-4.80H	460-H0480T25NVNN	VHA280-4.80H
CH50V	5375VBH-4.80T4	460-H0480T27NVNN	VHA280-4.80T4
LH50M	5375VBH-4.80TM3L	460-H0480T26LVNN	VHA280-4.80TM3L
LH50R	5375VBH-4.80HL	460-H0480T25LVNN	VHA280-4.80HL
LH50V	5375VBH-4.80T4L	460-H0480T27LVNN	VHA280-4.80T4L
EH50M	5375VBH-4.80ETM3	460-H0480T36NVNN	VHA280-4.80ETM3
EH50R	5375VBH-4.80EH	460-H0480T35NVNN	VHA280-4.80EH
EH50V	5375VBH-4.80ET4	460-H0480T37NVNN	VHA280-4.80ET4
DH50M	5375VBH-4.80ETM3L	460-H0480T36LVNN	VHA280-4.80ETM3L
DH50R	5375VBH-4.80EHL	460-H0480T35LVNN	VHA280-4.80EHL
DH50V	5375VBH-4.80ET4L	460-H0480T37LVNN	VHA280-4.80ET4L
CR50M	5375VCC-4.80TM3	460-R0480T26NVNN	VR280-4.80TM3
CR50R	5375VCC-4.80H	460-R0480T25NVNN	VR280-4.80H
CR50V	5375VCC-4.80T4	460-R0480T27NVNN	VR280-4.80T4
LR50M	5375VCC-4.80TM3L	460-R0480T26LVNN	VR280-4.80TM3L
LR50R	5375VCC-4.80HL	460-R0480T25LVNN	VR280-4.80HL
LR50V	5375VCC-4.80T4L	460-R0480T27LVNN	VR280-4.80T4L
ER50M	5375VCC-4.80ETM3	460-R0480T36NVNN	VR280-4.80ETM3
ER50R	5375VCC-4.80EH	460-R0480T35NVNN	VR280-4.80EH
ER50V	5375VCC-4.80ET4	460-R0480T37NVNN	VR280-4.80ET4
DR50M	5375VCC-4.80ETM3L	460-R0480T36LVNN	VR280-4.80ETM3L
DR50R	5375VCC-4.80EHL	460-R0480T35LVNN	VR280-4.80EHL
DR50V	5375VCC-4.80ET4L	460-R0480T37LVNN	VR280-4.80ET4L

1/ The CID PINs listed are only for length designator "50".
2/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A-A-59789.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.

PIN length examples. The CID PINs listed in table IV are for all available standard card holder lengths for this specification sheet. However, only one specific finish, mounting and configuration are listed (see PIN example for a break-down of the codes).

TABLE IV. Example of PIN with available length designators.

PIN designator AA59789/16	Vendor similar designator or type part number 1/ 2/		
	CAGE 5BG68	CAGE 76096	CAGE 61081
EH30V	5375VBH−2.80ET4	460−H0280T37NVNN	VHA280−2.80ET4
EH40V	5375VBH−3.80ET4	460−H0280T37NVNN	VHA280−3.80ET4
EH50V	5375VBH−4.80ET4	460−H0280T37NVNN	VHA280−4.80ET4

1/ The manufacturer's part number shall not be used for procurement to the requirements of this CID specification sheet. At the time of preparation of this CID specification sheet, the aforementioned commercial products were reviewed and could be replaced by the CID PIN shown. For actual part marking requirements, see the marking paragraph in A−A−59789.

2/ Other lengths are available on request.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

MILITARY INTERESTS:

Custodians:
Army − CR
Navy − EC
Air Force − 85
DLA − CC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA − FAS

Preparing Activity:
DLA − CC

Project 5998−2025−016

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:27Z
Check the source to verify that this is the current version before use.