| INCH-POUND |

00-D-450C
AMENDMENT-1
February 12, 1993

FEDERAL SPECIFICATION

DISPENSERS, BULK MILK, MECHANICALLY COOLED; AND
DISPOSABLE MILK CONTAINERS

This amendment, which forms a part of 00-D-450C, dated 21 January 1985, is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 3

2.1.1, Military Standards: add the following:

"MIL-STD-167/1 - Mechanical Vibration of Shipboard Equipment, (Type I - Environmental and Type II - Internally Excited)
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of
MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities"

PAGE 4

3.1.1, line 2, after "Manually operated," delete comma and add: "smooth convex shape arm handle,".

3.1.1, line 6, add the following sentence to end of paragraph: "Dispensers for shipboard use shall be of the type I category."

PAGE 7

3.6.1, after the first sentence add: "Class 430 steel shall be used with magnetic type door gaskets."

PAGE 8

3.6.3, Delete paragraph in its entirety and substitute: "3.6.3 Refrigerant. Fluorocarbon refrigerants shall conform to BB-F-1421. Refrigerants which would harm the earth's ozone layer shall not be used."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

PAGE 9

Add the following paragraph:

"3.7.4 Human factors criteria. Human factors engineering criteria, principles and practices, as defined in MIL-STD-1472, shall be used in the design of the milk dispensers. The equipment shall permit safe and efficient operation and maintenance by the 5th percentile female to the 95th percentile male as defined in sections 5.6 and 5.9 of MIL-STD-1472. All controls, valves, switches, and gages shall be selected and integrated into the design of the milk dispensers so as to meet the applicable requirements of sections 5.2 and 5.4 of MIL-STD-1472. All controls, valves, switches, and gages shall be clearly and appropriately labeled to identify function. The clearance or free area required around an item shall permit an individual with applicable 5th to 95th percentile body dimensions and physical capabilities (as defined in MIL-STD-1472), to safely operate, maintain, remove, or replace that item. Both physical and visual access shall be provided, along with access for any tools, test equipment, and replacement parts needed. While inspecting for defects and performing tests (see section 4), the equipment shall adhere to the human factors engineering considerations listed herein."

PAGE 10

3.9.4, delete third sentence in its entirety and substitute: "The door shall be fitted with an NSF approved rubber or plastic gasket, or one of the magnetic securing types. When the magnetic securing type door gasket is used, the manufacturer must use class 430 stainless steel for the outer cabinet shell."

PAGE 11

3.10, Delete the last sentence and replace with: "When specified (see 6.2), the low pressure sensing switch shall be of the manual reset type."

PAGE 14

Add the following new paragraphs:

"3.19 Navy shipboard installation. For Navy shipboard installation, mounting, electromagnetic compatibility requirements, inclined operations, and environmental suitability shall be as follows:

3.19.1 Mounting legs. Each type I milk dispenser specified in 1.2.1 shall be provided with mounting legs. The mounting legs shall be secured to the bottom four corners of the milk dispenser one (1) inch from the corner exterior surfaces (i.e., front and sides and back and sides). Each mounting leg shall have a 9/16-inch hole to accept a 1/2-inch bolt.

3.19.2 Electromagnetic compatibility. When specified for shipboard use (see 6.2), the units shall be designed and equipped for electromagnetic compatibility in accordance with the requirements of MIL-STD-461, class A4 for surface ships and class A5 for submarines. The equipment shall meet the emission and susceptibility requirements for CE01, CE03 and RE02 (see 4.6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.19.3 Inclined operation. Type I milk dispensers shall operate satisfactorily when inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other, with no spillage of fluid of product when tested as specified in 4.6.5.

3.19.4 Environmental suitability. When specified for shipboard use (see 6.2), type I milk dispensers shall be capable of withstanding ship's vibration and motion. Controls, switches, moving parts and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage when tested as specified in 4.6.6."

PAGE 19

Paragraph number should be "4.5.2" in lieu of "4.5."

PAGE 20

Add the following new paragraphs:

"4.6.4 Electromagnetic interference test. When required for shipboard use, the unit shall be tested by the contractor in accordance with test methods CE01, CE03, and RE02 of MIL-STD-462. The contractor shall furnish written certification that the equipment meets the requirements of MIL-STD-461. Non-conformance with the requirements specified shall constitute failure of the test.

4.6.5 Inclined operational test (type I only). After the test in 4.6.3 is completed, position the type I milk dispenser with the base set at an angle of 15 degrees, then operate the milk dispenser for 30 seconds at each side of the vertical in each of two vertical planes at right angles to each other. At each of these positions observe for conformance with specified requirements in 3.19.2. For the test, the milk dispenser shall be loaded with milk containers, of the specified size, filled with water or milk.

4.6.6 Shipboard environmental test. The milk dispenser under normal operating conditions, shall be tested in accordance with MIL-STD-167/1, type I equipment. The milk dispenser shall be secured to the test machine in the same manner that it will be secured on shipboard (see 3.19.1). Failure of the milk dispenser to perform its function during and after testing, to meet requirements of 3.19.4 shall constitute failure of this test."

PAGE 22

6.2, add the following after the word "supply" in option "h": "and when the low pressure sensing switch shall be of the manual reset type".

6.2, add the following sentence:

"o. When milk dispenser is required for Naval shipboard use (see 3.19, 3.19.1, 3.19.2, 3.19.3, and 3.19.4)."

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:59Z
Check the source to verify that this is the current version before use.

Add the following paragraph:

"6.6 Technical manuals. The requirement for technical manuals should be considered when this specification is applied on a contract. If technical manuals are required, military specifications and standards that have been cleared and listed in DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL) must be listed on a separate Contract Data Requirements List (DD Form 1423), which is included as an exhibit to the contract. The technical manuals must be acquired under separate contract line item in the contract."

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - CE, MD
Navy - MS, SH
Air Force - 84
DLA - GS

User Activities

Navy - CG, MC, SA

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
VA - OSS

PREPARING ACTIVITY:

Navy - YD

(Project 7310-0757)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.