OO-E-491E
April 17, 1975
SUPERSEDING
Fed. Spec. OO-E-491D
April 3, 1972

FEDERAL SPECIFICATION

EMBOSSING MACHINE, IDENTIFICATION TAPE (MANUALLY OPERATED)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION.

1.1 Scope. This specification covers requirements for manually operated machines for embossing alphanumeric symbols on plastic or metal tape (see 6.2).

1.2 Classification.

1.2.1 Types. The embossing machines shall be of the following types, as specified (see 6.2):

Type I - Nonportable heavy duty table or bench type for embossing plastic or metal tape.

Type III - Portable heavy duty type for embossing plastic or metal tape.

Type V - Portable heavy duty table type for embossing plastic tape.

1.2.1.1 Classes, cutoffs, and hole punches. The embossing machines shall be of the following classes, cutoffs, and hole punches, as specified (see 6.2):

Class 1 - For metal tape.

Cutoff 1 - With square cutoff.
Cutoff 2 - With rounded corners or rounded ends.

Hole punch 1 - With hole punch.
Hole punch 2 - Without hole punch.

Class 2 - For plastic tape.

Cutoff 1 - With square cutoff.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

UU-T-94 - Tape, Embossing.
PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-601 - Boxes, Wood, Cleated-plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Edged and Components.
PPP-B-676 - Boxes, Setup.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-L-10547 - Liner, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.
MIL-P-116 - Preservation-Packaging, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza., Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Standard products. All embossing machines furnished under this specification, shall be the manufacturer's commercial product, except for changes necessary to comply with the requirements of this specification.

3.2 Material. Material shall be as specified. When the material is not definitely specified, it shall be of a quality and composition to assure satisfactory performance in conformity with the requirements of this specification.

3.3 Components. All embossing machines shall essentially consist of a frame, impression medium, feed mechanism, tape holding device, tape guide track(s), and tape cutting device.

3.3.1 Frame. The frame shall be made of material specified, and shall be of such design, construction and strength to assure proper alignment and support of the components and parts of the embossing machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.3.1.1 Type I. The frame shall be metal. A base plate with mounting holes shall be included.

3.3.1.2 Type III. The frame of type III, class 1 shall be made of metal. The frame of type III, class 2 shall be made of plastic, metal, or a combination thereof.

3.3.1.3 Type V. The frame of type V shall be made of plastic, metal or a combination thereof.

3.3.2 Embossing medium.

3.3.2.1 Embossing wheel. The embossing wheel shall contain the impression medium. The embossing wheel shall be an integral or removable part of the embossing machine. Embossing machines with removable embossing wheel(s) shall be so designed to enable the wheel(s) to be installed and removed with ease and without special tools.

3.3.2.1.1 Impression medium. The impression medium of the embossing wheel shall be made of such material, design, construction, hardness, and finish to emboss clear and well defined alphanumeric symbols into metal or plastic, as applicable, when tested as specified in 4.4, 4.4.1, and 4.4.3.

3.3.2.1.2 Alphanumeric symbols. The embossing machines shall contain means to emboss upper case Gothic or Microgramma alphanumeric symbols. Means to emboss lower case alphanumeric symbols shall be included, when specified (see 6.2). The embossing machines shall emboss horizontal or vertical alphanumeric symbols, or both, as specified (see 6.2). On tape, horizontal symbols shall have vertical center line of symbols perpendicular to the length of the embossed tape. Vertical symbols shall have vertical center line of symbols parallel to the length of the embossed tape.

3.3.2.1.3 Letter and numeric symbols. Letter symbols shall include "A" thru "Z". Numeric symbols shall include "0" to "9". The letter symbols "O" may service as zero, and "I" as one, or vice versa.

3.3.2.1.4 Punctuation marks, symbols, and signs. All embossing machines shall include at least a period, and slash or dash. Special punctuation marks, symbols, or signs shall be included, when specified (see 6.2).

3.3.2.1.5 Height of alphanumeric symbols and widths of tape. The embossing machines shall emboss alphanumeric symbols of the following height, as specified (see 6.2): 0.125, 0.1562, 0.1875, 0.25, 0.2812, 0.3125, 0.375, 0.450, 0.5, 0.625, 0.75, 1. inch. A plus tolerance of 0.0312 inch, and a minus tolerance of 0.0156 inch will be permitted in the height of the alphanumeric symbols. The height shall be measured from the centerline of the top vertical symbol line to the centerline of the bottom vertical symbol line. The embossing machines shall be capable of embossing tape(s) of a width(s) specified (see 6.2).

3.3.2.1.6 Depth of alphanumeric symbols. The depth of the symbols shall be not less than 0.010 inch above the tape surface.

3.3.3 Operating handle or lever. The operating handle or lever shall be made of suitable material smoothly finished. The handle or lever shall be of such material, design, construction, size, and shape to insure comfortableness of grip, and perform the function for which it is intended.

3.3.4 Feed mechanism. With each actuation of the handle or lever, the feed mechanism shall automatically advance the tape and assure proper spacing between symbols.

3.3.5 Tape guide track. A tape guide track shall be incorporated in the embossing machine to properly guide and align the tape specified. Machines designed to emboss tapes of more than one width shall be provided with guide tracks to properly perform the required functions (see 3.4.5 and 6.2).

3.3.6 Tape holding device or enclosure. A tape holding device or enclosure shall be incorporated in the assembly to accommodate the embossing tape(s) specified (see 3.3.2.1.5 and 6.2). The tape holding device or enclosure shall insure proper alignment of tape with tape feed and embossing medium.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.3.7 Hole punch. Embossing machines shall be provided with a hole punching device, when specified (see 1.2.1.1 and 6.2). The device shall be of such material, design and construction to assure that perforations are entirely punched out without torn or ragged edges, when tested as specified in (4.4.2).

3.3.8 Shear or finish die. An appropriate shear or finish die shall be incorporated in the embossing machines. The cutting medium shall be of such material, design, and construction to assure end cutoffs without torn or ragged edges, when tested as specified in 4.4.4. The end cutoff shall be square or round, as specified. At the option of the manufacturer, round cutoffs shall have rounded corners or rounded ends.

3.4 Detailed requirements.

3.4.1 All machines. All embossing machines covered by this specification shall be capable of embossing evenly centered and spaced symbols into tape. Each actuation of the operation handle or lever shall activate the embossing medium and emboss one symbol at a time. A shear or finish die shall sever the tape.

3.4.2 Cutoffs 1 and 2. Embossing machines with cutoff 1 requirements shall have square cutoffs. Cutoff 2 machines shall have rounded ends or rounded corners. The cutting medium of the cutoff 2 embossing machines shall sever the tape and simultaneously cut the starting point of the succeeding tape of the same contour as the cutoff of the preceding tape (see 1.2.1.1, 3.3.8 and 6.2). Embossing machines designed to emboss plastic tape shall be provided with a cutting medium to sufficiently cut (indent) the end portion of the tape without completely severing the release liner, to facilitate removing tape release liner with ease.

3.4.3 Hole punch 1. Embossing machines with hole punch 1 requirements shall be provided with a hole punching device (see 1.2.1.1, 3.3.7, and 6.2).

3.4.4 Embossing wheel(s). The embossing wheel(s) shall contain the alphanumeric symbols of a height specified (see 3.3.2.1 thru 3.3.2.1.6, and 6.2).

3.4.5 Tape guide track(s). The embossing machine shall be provided with guide track(s) capable of guiding tape of width(s) specified (see 3.3.5 and 6.2).

3.4.6 Finish. The embossing machines shall be finished in accordance with the manufacturer's commercial practice.

3.5 Performance. When tested as specified in 4.4, the embossing machines shall produce well defined symbols, free from waves, irregularities, or misalignments, and there shall be no closed portion of symbols. The punched holes, when applicable, and the severed tape shall be free of torn or ragged edges. Type I and Type V embossing machines shall be capable of embossing 60,000 embossed symbols, when tested as specified 4.4.3, and shall be capable of cutting and indenting the tape 6,000 times, when tested as specified in 4.4.4. Type III embossing machine shall be capable of embossing 35,000 embossed symbols, when tested as specified in 4.4.3, and shall be capable of cutting and indenting the tape 3,500 times, when tested as specified in 4.4.4.

3.6 Operating instruction. The operating instruction shall contain all necessary instructions in the use of the embossing machine. The instructions shall be clear, concise, and easily followed to enable the users to correctly operate and maintain the machine.

3.7 Embossing tape. When specified (see 6.2), embossing tape conforming to UU-T-94, shall be furnished with each embossing machine in the quantity and of the type, class, color, width, and length specified (see 6.2 and 6.3).

3.8 Identification marking. Unless otherwise specified (see 6.2), each embossing machine shall be permanently and legibly marked with the name or trademark of the manufacturer.

3.9 Workmanship. All exposed plastic parts shall be free from chips, rough or sharp edges and corners. Metal parts shall be devoid of rust, dents and burrs, and except for the cutting medium shall be free of sharp edges or corners. The embossing machines shall be free from defects or imperfections which may affect appearance, impair serviceability, or constitute a hazard to the user.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Size and lot. All embossing machines of the same type, class, cutoff, and hole punch presented for inspection at one time shall be considered a lot for the purpose of examination and tests.

4.2.2 Sampling for inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise specified.

4.2.3 Sampling for visual examination. Random sample of embossing machines shall be taken from each lot in accordance with MIL-STD-105. A sample unit shall be one embossing machine. The embossing machines shall be examined for defects listed in table I. The Inspection Level shall be S-4, and the Acceptable Quality Level (AQL) shall be 4.0 percent defective.

4.2.4 Sampling for preparation for delivery requirements. Sampling shall be in accordance with MIL-STD-105. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed and shall be examined for defects listed in table II. The lot shall be the number of shipping containers offered at one time. The Inspection Level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.2.5 Sampling for performance tests. Random sample of embossing machines shall be taken from each lot in accordance with MIL-STD-105. The sample unit shall be one embossing machine and shall be tested as specified in 4.4. The Inspection Level shall be S-2, and the AQL shall be 4.0 percent defective.

4.3 Examination.

4.3.1 Visual examination. Sample taken in accordance with 4.2.3 shall be examined for defects listed in table I. Any sample having one or more defects shall be rejected. If the number of defective units in the sample exceeds the acceptance number for the sample, the entire lot represented by the sample shall be rejected.

TABLE I. Classification of defects

Examine	Defects
Type.	Type not as specified (see 1.2.1).
Class, cutoff, and hole punch.	Class, cutoff, and hole punch, not as specified (see 1.2.1.1).
Embossing medium.	Embossing medium not as specified (see 3.3.2 thru 3.3.2.1.6 and 3.4.4).
Operating handle or lever.	Operating handle or lever not as specified (see 3.3.3).
Feed mechanism.	Feed mechanism not as specified (see 3.3.4).
Tape guide track.	Tape guide track not as specified (see 3.3.5 and 3.4.5).
Tape holding device or enclosure.	Tape holding device or enclosure not as specified (see 3.3.6).
Hole punch.	Hole punch not as specified (see 3.3.7 and 3.4.3).
Shear or finish die.	Shear or finish die not as specified (see 3.3.8 and 3.4.2).
Operating instruction.	Operating instruction missing, or not as specified (see 3.6).
Embossing tape.	When required, embossing tape not of the quality, type, class, color, width and length specified, or tape is missing (see 3.7).
Identification marking.	Missing, or not as specified (see 3.8).
Workmanship.	Workmanship not in accordance with 3.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.3.2 Inspection of preparation for delivery. Samples selected in accordance with 4.2.4 shall be examined for defects listed in table II, to determine that packaging, packing and marking comply with the requirements of section 5. Defects of closure listed shall be examined on shipping containers fully prepared for delivery.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Marking (exterior and interior).	Omitted; incorrect; illegible; or improper size, location, sequence or method of application.
Materials.	Any component missing, or not as specified. Any component damaged, or affecting serviceability.
Workmanship.	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, inadequate stapling. Bulging or distortion of containers.
Content.	Number per container is more, or less than required.

4.4 Performance tests. Samples taken in accordance with 4.2.5, shall be subjected to the following tests to assure compliance with the applicable requirements in section 3 of this specification. Any embossing machine having one or more defects shall be rejected. If the number of defective embossing machines exceeds the acceptance of that sample, the lot represented by the sample shall be rejected. The embossing machines shall be set up for operation in accordance with the manufacturer's instructions, and the embossing tape shall conform to UU-T-94.

4.4.1 Functional test. The sample embossing machines shall be prepared for operation in accordance with the manufacturer's operation instruction (see 3.6). Each machine shall emboss not less than six separate embossed tags for each applicable tape width, containing all alphanumeric symbols required and available in the machine. During the embossing cycle observation shall be made to determine that the embossing machine functions as intended, and that the tags produced comply to the requirements stated in the applicable paragraphs of section 3.

4.4.2 Hole punch. When applicable, the hole punch device shall be tested by punching 100 holes into the embossing tape to assure compliance with the requirements stated in 3.3.7 and 3.4.3.

4.4.3 Life cycle test. Type I and V embossing machines shall emboss a total of 60,000 symbols, and type III embossing machine shall emboss a total of 35,000 symbols, to assure compliance with the requirements stated in 3.5. A different symbol shall be embossed every time a new embossing tape is inserted. Unless otherwise specified, the force applied to the operating handle or lever shall be sufficient to obtain satisfactory embossing, but shall be not more than 40 pounds for type I and type V embossing machines, and not more than 35 pounds for type III embossing machines. The cycling rate shall be 25 to 35 embossings per minute. The force shall be applied to the operating handle or lever at the point of greatest leverage. The force required to obtain satisfactory embossing, as stated in 3.5, shall be adjusted every time a new tape is inserted, or when necessary.

4.4.4 Cutting and indention test. The shear or finish die of type I and type V embossing machines shall be tested by making 6,000 cuts and indentions, and type III embossing machines shall be tested by making 3,500 cuts and indentions. Before each cut and indention advance tape to start position. The force shall be applied to the operation handle or lever at the point of greatest leverage. Unless otherwise specified, the force applied to the operating handle shall be sufficient to obtain satisfactory cutting and indention, but shall not be more than 40 pounds. The force required to obtain satisfactory cuts and indentions, as stated in 3.3.8, 3.4.2, and 3.5, shall be adjusted to the minimum force necessary every time a new embossing tape is inserted, or when necessary.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packing. Preservation and packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

5.1.1.1 Preservation. All exposed, uncoated ferrous metal surface, except corrosion resisting steel surfaces, shall be cleaned in accordance with process C-1, thoroughly dried, and coated with type P-7 preservation of MIL-P-116. When supplied, embossing tape for the embossing machine shall be preserved in accordance with MIL-P-116, as applicable.

5.1.1.2 Packaging. Each type III embossing machine shall be packaged in a close-fitting paperboard box conforming to PPP-B-566, PPP-B-665 or PPP-B-676. When embossing tape is supplied with the embossing machine, it shall be packaged within the same paperboard box as the embossing machine. Each box shall be closed in accordance with the applicable specification.

5.1.2 Level B. Each type III embossing machine shall be packaged as specified in 5.1.1.2.

5.1.3 Level C. The embossing machine shall be packaged in accordance with the manufacturer's standard practice, providing that this insures protection for the embossing machines during shipment and provides for safe delivery to their destination. When fiberboard is utilized, it shall conform to PPP-F-320.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Type I. Each type I embossing machine, preserved as specified in 5.1, shall be packed in a wood-cleated plywood or nailed-wood shipping container conforming to PPP-B-601, overseas type or PPP-B-621, class 2. Each embossing machine shall be securely bolted to the base of the shipping container (using the mounting holes in the base of the embossing machine) through interior cleats, 3/4 x 2-1/2 inches, which have been previously attached by clinched nails to the base of the shipping container. When cleated plywood shipping container is used, the cleats shall be placed on the exterior of the base and shall extend the full distance between the edge cleats. Each shipping container shall be provided with a sealed case liner conforming to MIL-L-10547. The bottom of the case liner shall be provided with four holes to match the four bolts used to secure the embossing machine to the shipping container. When supplied, embossing tape, preserved as specified in 5.1, shall be packed and secured within the same shipping container as the embossing machine. The shipping container shall be closed and strapped in accordance with the appendix to the applicable box specification.

5.2.1.2 Types III. Twenty type III embossing machines, preserved and packaged as specified in 5.1, of one type only, shall be packed in a fiberboard box conforming to PPP-B-636, class weather resistant. Each shipping container shall be closed, sealed and reinforced in accordance with the appendix to the box specification.

5.2.1.3 Type V. Each type V embossing machine, preserved as specified in 5.1, shall be packed in a fiberboard box conforming to PPP-B-636, class weather resistant. Each shipping container shall be closed, sealed and reinforced in accordance with the appendix to the box specification.

5.2.2 Level B.

5.2.2.1 Type I. Each type I embossing machine shall be packed in a wood-cleated plywood or nailed-wood shipping container conforming to PPP-B-601, domestic type or PPP-B-621, class 1. Each embossing machine shall be securely bolted to the base of the shipping container (using the mounting holes in the base of the embossing machine) through interior cleats, 3/4 x 2-1/2 inches, which have been previously attached by clinched nails to the base of the shipping container. When a cleated plywood shipping container is used, the cleats shall be placed on the exterior of the base and extend the full distance between the edge cleats. When supplied, embossing tape shall be packed within the same container as the embossing machine.

5.2.2.2 Type III. Twenty embossing machines, of one type only, preserved and packaged as specified in 5.1, shall be packed in a fiberboard shipping box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.2.3 Type V. Each embossing machine shall be packed in a close-fitting fiberboard box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The embossing machine, packaged as specified in 5.1.3, shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification rules and the National Motor Freight Classification rules. When fiberboard is utilized, it shall conform to PPP-F-320.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The embossing machines are intended for embossing alphanumeric symbols into metal or plastic tapes for use in labeling, tagging, coding, identifying and marking of items.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, class, cutoff, and hole punch (see 1.2.1 and 1.2.1.1).
(c) Whether horizontal or vertical alphanumeric symbols, or both are required (see 3.3.2.1.2).
(d) Whether lower case letters shall be included (see 3.3.2.1.2).
(e) Whether special punctuation marks, symbols, or signs are required (see 3.3.2.1.4).
(f) Specify height of alphanumeric symbols (see 3.3.2.1.5).
(g) Specify the width(s) of tape(s) the embossing machine shall be capable of embossing (see 3.3.2.1.5).
(h) Specify quantity, type, class, color, and length of embossing tape, when applicable (see 3.7).
(i) Identification marking required, if other than specified (see 3.8).

6.3 Embossing tapes. Embossing tapes are generally available in materials and colors indicated below:

Metal tapes	Plastic tapes
Aluminum:	White characters and the following backgrounds:
Natural color	Black
Lacquered:	Blue
Black	Brown
Blue	Clear
Green	Fluorescent green
Red	Fluorescent red
Yellow	Gold
	Gray
Brass	Green
Copper	Orange
Lead	Purple
Steel, cold-rolled,	Red
Electro-galvanized	Silver
Steel, stainless	Wood grain
Zinc.	yellow

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

6.4 Change of classification. This specification includes major changes in the classification of embossing machine designated in previous documents. Purchasers are urged to review this specification with special emphasis on sections 1 and 3. Type II and Type IV embossing machines of previous documents have been deleted.

DOD HAS WAIVED COORDINATION INTEREST

Preparing activity:

GSA-FSS

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 35 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.