FEDERAL SPECIFICATION

MEAT SLICER, HAND-OPERATED, AND MEAT SLICING MACHINES, ELECTRIC

This amendment, which forms part of Federal Specification 00-M-280G, dated January 17, 1977, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

1.2, under "Type II, Class 1, Style 1, Feed 2": Add "Feed 3 - Two speed".

PAGE 4

2.2, under Underwriters Laboratories Inc., parenthetical paragraph, line 2, after "Inc.,": Delete all addresses and substitute "333 Pfingsten Road, Northbrook, IL 60062."

PAGE 6

3.2.1.2 (1), line 2, after "equipment": Delete "or" and substitute "and".

3.3, line 4, after "specification": Add "(see 6.3)".

3.3.1.1, line 2: Delete and substitute "steel of cutlery grade having not less than 0.40 percent carbon and 13.00 percent chromium when tested as specified in 4.2.1.1."

PAGE 12

Add new paragraphs:

"3.4.12.3 Feed 3 (two speed).

"3.4.12.3.1 Design. The machine shall have a rotating slicing knife and a two speed gravity feed chute. The feed chute shall be equipped with a speed selector to regulate the slicer speed from 45 to 55 strokes per minute and from 80 to 90 strokes per minute. The machine shall be equipped with a gauge plate and either a gravity end weight or spring feed plate. The machine design shall permit manual operation of the gravity feed chute in the event the speed drive becomes inoperative or is not desired. Unless otherwise specified (see 6.2), 4-inch NSF approved legs shall be provided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

PAGE 12 (cont'd)

"3.4.12.3.2 Performance. The machine shall be capable of slicing up to 10-3/4 inches capacity at 45 to 55 strokes per minute, up to 5-1/2 inches capacity at 80 to 90 strokes per minute, and up to 10-3/4 inch capacity when operated manually, when tested as specified in 4.4.5. Each cut surface of each slice shall be smooth and free from tear or bruises.

"3.4.12.3.3 Slice thickness. The slice thickness shall be as specified in 3.4.12.2.3.

"3.4.12.3.4 Slicing knife. The slicing knife shall conform to 3.4.1 and shall be not less than 12-1/2 inches diameter.

"3.4.12.3.5 Motors. The motors shall be as specified in 3.4.12.2.5.

"3.4.12.3.6 Switch and wiring. The switch and wiring shall be as specified in 3.4.12.1.6."

PAGE 13

3.4.13.6, line 1: Delete "3.3.3.1" and substitute "3.3.3".

PAGE 22

4.4.5, line 4, after "3.4.12.2.2": Insert ",3.4.12.3.2,".

PAGE 28

6.2 (cont'd), add the following:

"(k) When 4-inch legs are not required (see 3.4.12.3.1)."

Add new paragraph:

"6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3)."

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD
Navy - MS, SA

User activities:

Navy - CG, MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA - FSS
HEW - FDA
VA - DMS

Project No. 7320-0690

Printing Date: 1981

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:59Z
Check the source to verify that this is the currentversion before use.