INCH POUND

00-M-280G
INT. AMENDMENT-4 (Navy -SA)
23 NOVEMBER 1990

# INTERIM AMENDMENT

# TO

# FEDERAL SPECIFICATION

# MEAT SLICER, HAND-OPERATED, AND MEAT SLICING MACHINES, ELECTRIC

This interim amendment was developed by the Navy Food Service System Office, Bldg. 166/2, WNY, Washington, DC 20374-1662, based upon currently available technical information. It is recommended that federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The general Services Administration has authorized the use of this interim amendment as a valid exception to 00-M-280G, dated January 17, 1977.

PAGE 1

1.2, under "Type II, Class 1, Style 1, Feed 2": Add "Feed 3 - Two speed".

PAGE 4

2.2, under Underwriters Laboratories Inc., parenthetical paragraph, line 2, after "Inc.,": Delete all addresses and substitute "333 Pfingsten Road, Northbrook, IL 60062."

PAGE 6

3.2.1.2 (1), line 2, after "equipment": Delete "or" and sustitute "and".

3.3. line 4, after "specification": Add "(see 6.3)".

3.3.1.1, line 2: Delete and sustitute "steel of cutlery grade having not less than 0.40 percent carbon and 13.00 percent chromium when tested as specified in 4.2.1.1."

AMCS N/A FSC 7320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

PAGE 6 (cont'd)

Add new paragraph:

"3.3.1.1.2 Carriage handle. Carriage handle will be required to be all metal or have a metal insert, if the handle is plastic."

PAGE 8

3.4.3 Add the following new sentence at the end of paragraph: "The meat carriage will be required to incorporate cast iron on steel, oilite bearing surfaces or roller bearings. All gears currently made of plastic will be required to be gear grade laminated phenolic or bronze."

3.4.4 line 3, after "inch": Add "The end-holding device must be non removable or equipped with a positive stop."

Add the following new paragraph:

"3.4.4.1 Slicer adjustment knob. The shaft for the slicer ajustment knob shall have flats for setscrews or both knob and shaft shall have a keyway to prevent rotation or slipping of the adjustment knob on the shaft

PAGE 11

3.4.12.1.6: Delete and substitute:

"3.4.12.1.6 Switch and wiring. The machine shall have an enclosed, quick-break switch which shall open all motor leads. The switch shall be an industrial rated toggle switch in conformance with UL 73. The switch shall be recessed into the body structure of the slicing machine or shielded to guard against accidental operation. The switch shall be provided with a pilot light to indicate when the switch is in the on position". There shall be no electrical or mechanical failure, and no pitting or burning of contacts when the switch is tested as specified in 4.4.3. If the switch is a sealed type, the manufacturer may replace the tested switch with an identical model provided the tested switch satisfactorily passed the test. Unless otherwise specified (see 6.2), slicing machines shall be furnished with a flexible supply cord conforming to type ST, STO, SO, SJO, SJT, or SJTO of UL 73 not less than 8 feet in length. The supply cord shall be a 3-wire grounding type provided with a 3-prong grounding type plug. Cord and plug shall provide grounding for the machine. The motor, switch, and supply cord shall be wired ready for operation. All wires and terminals shall be fully enclosed."



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

PAGE 12

Add new paragraphs:

"3.4.12.3 Feed 3 (two speed).

"3.4.12.3.1 Design. The machine shall have a rotating slicing knife and a two speed gravity feed chute. The feed chute shall be equipped with a speed selector to regulate the slicer speed from 45 to 55 strokes per minute and from 80 to 90 strokes per minute. The machine shall be equipped with a guage plate and either a gravity end weight or spring feed plate. The machine design shall permit manual operation of the gravity feed chute in the event the speed drive becomes inoperrative or is not desired. Unless otherwise specified (see 6.2), 4-inch NSF approved legs shall be provided.

"3.4.12.3.2 Performance. The machine shall be capable of slicing up to 10-3/4 inches capacity at 45 to 55 strokes per minute, up to 5-1/2 inches capacity at 50 to 90 strokes per minute, and up to 10-3/4 inch capacity when operated manually, when tested as specified in 4.4.5." Each cut surface of each slice shall be smooth and free from tears or bruises.

"3.4.12.3.3 Slice thickness. The slice thickness shall be as specified in 3.4.12.2.3.

"3.4.12.3.4 Slicing knife. The slicing knife shall conform to 3.4.1 and shall be not less than 12-1/2 inches diameter.

"3.4.12.3.5 Motors. The motors shall be as specified in 3.4.12.2.5.

"3.4.12.3.6 Switch and wiring. The switch and wiring shall be as specified in 3.4.12.1.6."

PAGE 13

3.4.13.6, line 1: Delete "3.3.3.1" and substitute "3.3.3".

PAGE 14

3.4.14.2 line 5, after "4.4.5": Add "Parellelism will be required between slicing blade and meat carriage plus or minus 1 degree."

PAGE 21

4.4.1 line 1, after "Operational test." Add "During 36 hour continous test running, there shall be no leakage of lubricants.

4.4.1 line 3, after "without": Add ", oil leakage,"



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

PAGE 22

4.4.5, line 4, after "3.4.12.2.2": Insert ", 3.4.12.3.2,".

PAGE 28

6.2 (cont'd), add the following:

"(k) When 4-inch legs are not required (see 3.4.12.3.1)."

Add new paragraph:

"6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3)."

PREPARING ACTIVITY:
Navy - SA

(Project 7320-N871)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.