OO-M-59c
August 5, 1965

SUPERSEDING
Int. Fed. Spec. OO-M-0059b (DSA-IP)
July 1, 1964
Fed. Spec. OO-M-59a
August 28, 1953

FEDERAL SPECIFICATION

MILLING MACHINES, BENCH TYPE, HORIZONTAL, VERTICAL, GENERAL PURPOSE

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers electric motor driven, bench type, vertical or horizontal, power or manual feed milling machines.

1.1.1 *Federal specification coverage.* Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 *Types, classes, styles, and sizes.* The milling machines covered by this specification shall be of the following types, classes, styles, and sizes, as specified (see table II and 6.2).

Type I—Horizontal
- Class 1—Plain table
  - Style A—Power table feed
  - Style B—Hand table feed
- Class 2—Universal table
  - Style A—Power table feed
  - Style B—Hand table feed

Type II—*Vertical*
- Class 1—Swivel head
  - Style A—Power table feed
  - Style B—Hand table feed
- Class 2—Fixed head
  - Style A—Power table feed
  - Style B—Hand table feed

2. APPLICABLE SPECIFICATIONS, STANDARDS, AND OTHER PUBLICATIONS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-P-18058—Preparation for Delivery of Machine Tools (Metal and Wood-Working) Accessories and Repair Parts.

Military Standards:

MIL-STD-129—Marking for Shipment and Storage.

MIL-STD-130—Identification Marking of U. S. Military Property.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Bureau of Standards (NBS) Handbook:

Handbook H28—Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C., 20402.)

American Standards Association (ASA) Standards:

ASA B5.1—T-Slots—Their Bolts, Nuts, Tongues, and Cutters.

ASA B5.10—Machine Tapers, Self-Holding and Steep Taper Series.

ASA B5.18—Spindle Noses and Arbors for Milling Machines.

ASA B6.1—Spur Gear Tooth Form.

ASA B6.6—Gear Tolerance and Inspection.

(Application for copies should be addressed to the American Standards Association, 10 East 40th Street, New York, N. Y., 10016.)

National Machine Tool Builders' Association (NMTBA) Standard:

Machine Tool Electrical Standards.

(Copies may be obtained from the National Machine Tool Builders' Association, 2139 Wisconsin Avenue, N. W., Washington, D. C., 20007.)

3. REQUIREMENTS

3.1 Preproduction sample. Unless otherwise specified (see 6.2), the supplier shall furnish as part of the contractual quantity, one complete machine of each type and style under the contract, for preproduction testing and inspection at the supplier's plant in accordance with section 4. The sample may be a preproduction item or a production item which meets the requirements of this specification. In either case, the sample shall be identical with the proposed items and shall be made by the methods used in production of items to fulfill the terms of the contract. Approval of a preproduction sample shall not relieve the supplier of the responsibility to furnish equipment in accordance with the requirements of this specification.

3.2 Design. The machine shall consist essentially of a table, saddle knee, column, a head for type II machines, overarm, and arbor support for type I machines, and such other features as specified herein. The machine shall be one of the manufacturer's standard commercial models of current design and manufacture and currently offered for sale to the general public, unless changes therefrom are necessary to meet the requirements of this specification. All components, accessories, and parts shall be those normally available with the commercial model to be furnished. Power shall be transmitted to the spindle by belt drive or gear train.

3.2.1 *Safety devices.* The machine shall be fitted with safety devices or covering for all parts that present safety hazards. The devices shall include guards for belts, pulleys, and gears. All guards shall provide easy access to the guarded parts. When special safety devices are required, they shall be as specified (see 6.2).

3.2.2 *Lubrication.* All bearings (except sealed-for-life type), mating gears, and sliding parts shall be provided with an accessible means of lubrication.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.2.3 *Interchangeability.* All parts and accessories subject to replacement shall be manufactured to such standards as to permit replacement or adjustment without modification of parts or machine.

3.3 Construction. The machine shall be complete so that when installed and connected to the specified power source it can be used for any purpose for which it was designed. Construction shall be free from any characteristics or defects that will prevent the machine from passing any of the examination and tests in section 4.

3.3.1 *Castings and forgings.* All castings and forgings shall be free from defects, scale, excessive porosity, and mismatching. In no event shall such processes as welding, peening, plugging, or filling with solders or metallic pastes be used on castings or forgings for reclaiming any defective parts of the machine.

3.3.2 *Welding, brazing, or soldering.* Welding, brazing, or soldering shall be employed only where those operations are required in the original design. These operations shall not be employed as repair measures for defective parts.

3.3.3 *Fastening devices.* All screws, pins, bolts, and similar parts shall be installed with means for preventing loss of tightness. All such parts subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

3.3.4 *Surfaces.* All surfaces of all castings, forgings, molded parts, stampings, and welded parts shall be cleaned and free from sand, dirt, fins, sprues, scale, flux, and other harmful or extraneous materials. External surfaces shall be smooth and all edges shall be either rounded or beveled.

3.3.5 *Painting.* Unless otherwise specified (see 6.2), the machine shall be prepared for painting and painted in accordance with the manufacturer's commercial practice.

3.3.6 *Threads.* All threaded parts shall be in the inch system and shall conform to Handbook H28.

3.3.7 *Gears.* All spur gears and pinions used in the machine and its components shall be machined to the inch system and shall conform to the dimensions and tolerances of ASA B6.1. Helical, herringbone, bevel, and worm gearing shall conform to the dimensions and tolerances of ASA B6.6.

3.3.8 *Dials.* All feed screw dials shall be graduated in the inch system. Dial graduations depicting tool or table movement shall be in increments of not more than 0.001 inch and numerically marked each 0.010 inch. Dial graduations shall be such that the graduation may be easily read, and shall have a nonglare finish.

3.3.9 *Plates.* All speed and feed indicating plates, and all words on instruction plates shall be in the English language, engraved and filled with contrasting color enamel, with plain bold-faced letters that may be easily read from the operator's normal position.

3.4 Performance and accuracy.

3.4.1 When tested in accordance with 4.5.2, the performance and accuracy shall be as specified therein.

3.4.2 *Alignment tolerances.* The machine shall comply with the alignment tolerances shown in table I.

TABLE I. *Alignment tolerances horizontal and vertical milling machines*

	Permissible error (not more than)
Spindle:	
Spindle radial runout on test arbor 2 inches from nose	0.0002 inch TIR
Work Table:	
Rise and fall of table in its longitudinal movement	0.001 inch in 24 inches
Table top parallel with spindle (horizontal machine only)	0.001 inch in 12 inches
Table top square with spindle axis (vertical machines only): Through transverse axis of table	0.001 inch in 12 inches

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

TABLE I. *Alignment tolerances horizontal and vertical milling machines (cont'd)*

	Permissible error (not more than)
Work Table: (*cont'd*)	
Through longitudinal axis of table	0.001 inch in 12 inches
Table surface parallel with its transverse movement	0.001 inch in 12 inches
Center T-Slot parallel with longitudinal movement of table	0.001 inch in 12 inches TIR
Center T-Slot square with transverse movement of table	0.001 inch in 12 inches TIR
Column:	
Quill movement square with table (vertical machine only):	
In plane through transverse axis of table	0.0005 inch in 6 inches
In plane through longitudinal axis of table	0.0005 inch in 6 inches
Knee movement square with table surface:	
In plane through tranverse axis of table	0.001 inch in 12 inches
In plane through longitudinal axis of table	0.001 inch in 12 inches

3.5 Sizes and capacities. Milling machines furnished under this specification shall conform to the minimum requirements specified in table II.

3.5.1 *Power feed rates.* When specified (see 6.2), type I, size 2 machines shall be supplied with not less than 32 power feed rates.

3.6 Components. The vertical and horizontal milling machines shall have the following components:

3.6.1 *Table.* The table shall be a one piece ferrous casting. The bottom of the table shall be machined and fitted to the ways of the saddle. It shall have a locking arrangement for clamping to the saddle. The table surface shall be machine finished with T-slots conforming to ASA B5.1 and of the number and size specified in table II. The front side of the table shall be provided with a means for mounting adjustable stops. Two adjustable table stops shall be furnished. Manual feed of the table in either direction of cross and longitudinal feed shall be provided by means of handwheels, ball cranks, or levers. Feed screws shall have square or acme threads. They shall be heat treated and shall be fitted with dials conforming to 3.3.8. Style A machines shall have longitudinal power feed in either direction as specified in table II. A lever, located in front of the table, shall actuate power table feed and a plate shall be furnished to indicate direction of feed. Power table feed shall be operative only when the spindle is operating. The table shall be provided with adequate means for returning coolant to the coolant reservoir.

3.6.2 *Saddle.* The saddle shall be a ferrous casting of ample size to support the table. The saddle shall be equipped with guides and an adjustable gib to maintain alignment. Bearing surfaces and ways shall be machined and scraped to fit mating parts. The length of the ways shall be not less than the table travel. Saddle shall have means for lubrication of all knee, saddle, and table bearing surfaces and moving mechanisms in the saddle. The saddle manual cross feed shall be by means of a feed screw and ball crank or hand wheel. The feed screw shall be heat-treated steel with acme or square threads and shall be fitted with a dial conforming to 3.3.8.

3.6.3 *Knee.* The knee shall be a ferrous casting, machined and fitted to the column ways by dovetail or square gib construction with adjustable gibs. The knee shall support the saddle and table and shall have vertical movement by means of an elevating screw operated by a crank or hand wheel mechanism. A dial conforming to 3.3.8 shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T11:58Z
Check the source to verify that this is the currentversion before use.

TABLE II. *Sizes and capacities*

	Type I machines Horizontal		Type II machines Vertical	
	Size 1	Size 2	Size 1	Size 2
Table working surface, length by width, inches, minimum	15 by 3-3/4	20 by 5-1/2	15 by 3-3/4	24 by 6
Table feed, inches, not less than:				
longitudinal	8	11	8	15
cross	3	5	3	5
vertical	5	9	5	11-3/8
Power feed rates, style A machines, i.p.m.				
Low, not more than		1/2		1
High, not less than		8.5		6
Number of power feeds, not less than		12		12
Number of T-slots, top of table	1	3	1	3
Size of T-slots, not less than, inches	3/8	7/16	3/8	7/16
Spindle motor horsepower, not less than		1		1/2
Spindle nose to table, type II machines[1]				15-1/2
Spindle axis to table, type I machines[1]		10		
Spindle nose taper, minimum size, ASA Std.	[2]	[3]	[4]	[2]
Spindle speed range, r.p.m.				
Low, not more than	170	110	170	250
High, not less than	1200	1400	1200	3250
Spindle speeds, not less than	3	8	3	6
Quill travel, inches, type II machines, Not less than	—	—	2-1/2	2-1/2
Type II head swivel, right or left degrees when specified	—	—	90	90
Net weight, pounds, minimum		800		700

[1] Distance from spindle nose or spindle axis to table as measured with table in its lowest position.
[2] Spindle nose shall conform to ASA B5.18.
[3] Spindle nose shall be manufacturer's commercial standard and shall conform to 3.6.7.
[4] Spindle nose shall be No. 2 Morse taper as shown in ASA B5.10.

3.6.4 *Column.* The column shall be a one piece ferrous casting of such weight and design as to minimize vibration and assure the accuracies and performance specified herein. The front of the column shall have machined and fitted ways for the knee.

3.6.5 *Mounting base.* Unless otherwise specified (see 6.2), size 1 machines shall be furnished without a mounting base, and size 2 machines shall be furnished with a mounting base. The mounting base for size 2 machines shall be either a floor cabinet fabricated from steel plate or a one piece cast iron pedestal. A cast iron pedestal, when furnished, may serve as mounting base only or may be extended to serve as a column also. The design, construction, and material of the base shall be such as to provide rigid support for the milling machines. The base shall have not less than three holes for securing the machine to the floor.

3.6.6 *Head.* The head of the type II machines shall be of either class 1, the fixed type, or class 2, the swivel type. The swivel head shall be designed to swivel in a vertical plane through the longitudinal axis of the table. The amount of swivel shall conform to the requirements of table II. The head shall include a quill with a lever for rapid quill movement, a handwheel or knob for slow quill movement, a quill locking arrangement, and a micrometer depth stop.

3.6.7 *Spindle.* The spindle nose shall be of heat-treated alloy steel, hardened and precision ground. It shall be mounted on precision ball or roller bearings, with pro-

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the currentversion before use.

vision for easy bearing adjustment. The spindle nose taper shall be as provided in the manufacturer's standard commercial product, and unless otherwise specified (see 6.2) shall (a) conform to a standard listed in ASA B5.18, (b) conform to a Morse or Brown and Sharpe taper described in ASA B5.10, of size not less than Number 2 Morse or Number 7 Brown and Sharpe, or (c) be of the collet type with maximum capacity of not less than 21/32 inch and equipped with draw-in bar.

3.6.8 *Arbor support.* The arbor support for type I machines shall consist of an overarm of solid round bar, dovetail, or square-lock type, and an arbor support yoke which can be securely attached to the overarm by means of a split compression bearing or other suitable means. The arbor yoke shall have a bearing for accommodating the arbor.

3.6.9 *Coolant system.* Unless otherwise specified (see 6.2), a coolant system shall be supplied with each machine. The coolant system shall include a sump or reservoir, a power driven pump, and piping. The coolant reservoir shall incorporate a strainer or settling chambers to remove cutting chips from the coolant. The reservoir shall be equipped with adequate drain facilities. The coolant system shall include oil resistant hoses, tubing, or piping to direct the coolant. The coolant delivery nozzle shall be fitted with a valve to permit the operator to direct and control the amount of coolant flow.

3.6.10 *Table mounting, type I, class 2 machines.* The saddle of the universal type machine shall be made of cast iron and proportioned to support rigidly both the table and swivel block. The swivel shall be of adequate size to properly support the table. A means of locking the swivel shall be provided. The swivel block shall swivel not less than 45° on each side of the zero position and shall be provided with a scale legibly graduated in one degree intervals throughout the full range of angular movement. Except as otherwise specified in this paragraph the table and saddle shall meet the requirements of 3.6.1.

3.6.11 *Ram type mounting for milling head of type II machines.* When specified (see 6.2), the milling head of type I machines shall be mounted on a ram capable of movement in a horizontal plane perpendicular to the axis of longitudinal table movement and parallel to the table surface. The ways of the ram shall be of the dovetail or square lock type. Ram movement shall be not less than 10 inches.

3.7 **Electrical equipment.** Unless otherwise specified (see 6.2), all electrical components including the motors, starters, relays, switches, and wiring shall conform to and shall be located in accordance with NMTBA Electrical Standards.

3.7.1 *Motors.* Motors shall be rated for continuous duty and shall have ball bearings. Motor horsepower shall conform to the requirements shown in table II. Motors shall be dual voltage 110/220 or 220/440 volt, 3 phase, 60 cycle a.c., as specified (see 6.2), and shall be initially wired for operation on the voltage specified (see 6.2). Motors shall have dripproof or better enclosure.

3.8 **Suppression of radio interference.** When required (see 6.2), radio interference suppression shall be as specified.

3.9 **Fungus control.** When required (see 6.2), fungus proofing shall be as specified.

3.10 **Lubrication chart or plate.** Unless otherwise specified (see 6.2), a lubrication chart or plate shall be securely attached to the milling machines. If a chart is furnished, it shall be placed in a transparent plastic folder or laminated between clear plastic, permanently sealed sheets with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application with the following information for each lubrication point:

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

Service interval
Type of lubricant
Viscosity
Federal or military specification number of lubricant (if available)

3.11 Nameplate. Unless otherwise specified (see 6.2), a corrosion resistant metal nameplate, permanently and legibly marked with the following information in accordance with MIL-STD-130 shall be securely attached to each milling machine:

Nomenclature
Manufacturer's name
Manufacturer's model number
Manufacturer's serial number
Power input characteristics and rating
Date of manufacture
Contract or order number
Federal stock number
U S

3.12 Identification plate. When specified (see 6.2), milling machines supplied shall carry a separate identification plate of corrosion resistant material, permanently and legibly marked with the following caption. Characters shall be at least 3/16 inch in height.

Departmental/Activity Identification Number (with ample space for insertion by the Government of 25 characters).

3.13 Standard equipment. Unless otherwise specified (see 6.2), the supplier shall furnish with each machine the following standard equipment in the type, size, and capacity normally furnished with the standard machine.

1 swivel vise
1 set collets
1 collet adaptor
1 set wrenches
1 drill chuck
2 arbors, type I machines
2 sets belts, if belt driven

3.14 Optional equipment. When specified (see 6.2), optional equipment shall be as specified.

3.15 Handbook of instructions. Unless otherwise specified (see 6.2), the contractor shall furnish two copies of the manufacturer's standard handbook.

3.16 Foundation and anchor bolt plans and wiring diagrams. Unless otherwise specified (see 6.2), two copies of foundation and anchor bolt plans and wiring diagrams shall be furnished.

3.17 Workmanship. Workmanship of the milling machine and accessories shall be of the quality prevailing among manufacturers normally producing milling machines of the type specified herein.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction inspection. Preproduction inspection shall be applied to the preproduction sample submitted in accordance with 3.1. Preproduction inspection shall consist of all examination and tests in 4.4 and 4.5. Failure of the preproduction sample to pass any examination or test shall be cause for rejection.

4.3 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Failure of the machine to pass any examination or test shall be cause for rejection. Unless otherwise specified (see 6.2), quality conformance shall consist of all examinations and tests in 4.4, 4.5, and 4.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.4 Examination. The machine and equipment shall be examined for design, construction, materials, components, electrical equipment, and workmanship to determine compliance with the requirements of this specification. Any deviation from these requirements shall be cause for rejection.

4.5 Tests.

4.5.1 *Operational test.* The machine shall be operated at no load for not less than 30 minutes. Proper operation of all controls, motors, adjusting mechanisms and other accessories shall be inspected during the trial period. Failure of any component or accessory to operate satisfactorily shall be cause for rejection.

4.5.2 *Performance test.* The machine shall be tested with a rectangular sample of SAE No. 1045 steel. The sample shall be approximately six inches long by three inches wide by one inch thick. The sample shall be ground flat on one 6 by 3 inch face. It may be drilled to facilitate clamping. The machine shall make a roughing cut to mill metal off one 6 inch by 3 inch face of the test piece at sufficient depth and feed rate to load the spindle drive motor to its maximum rated electrical input. The machine shall be operated at its lowest spindle speed. The type of cutting tool and table feed rate shall be at the discretion of the supplier. The resultant metal removal rate shall be not less than 0.65 cu. in. per minute per spindle horsepower. The surface finish after machining shall show no evidence of tool chatter. A roughing cut shall also be made on an adjacent vertical face of the sample and finishing cuts shall be made on both horizontal and vertical faces. The test tolerances of the sample after the finishing cut shall be as specified in 4.5.2.1 thru 4.5.2.3.

4.5.2.1 *Squareness.* The two adjacent milled sides shall be checked for squareness. The surfaces shall be square with each other within 0.001 inch per foot.

4.5.2.2 *Flatness.* The two milled sides shall be checked for flatness. Each side shall be flat within 0.001 inch, concave only.

4.5.2.3 *Parallelism.* The two six-inch by three-inch sides shall be checked for parallelism. The surfaces shall be parallel within 0.001 inch per foot.

4.5.3 *Accuracy test.* The machine shall be examined to determine compliance with alignment tolerances shown in table I.

4.6 Inspection of preservation, packaging, packing, and marking for shipment and storage. Preservation, packaging, packing, and marking for shipment and storage shall be inspected to determine conformance with the documents referenced in section 5.

5. PREPARATION FOR DELIVERY

(For civil agency procurement, the definitions and application of levels of packaging and packing shall be in accordance with Fed. Std. No. 102.)

5.1 Preservation and packaging. Unless otherwise specified (see 6.2), preservation and packaging shall conform to MIL-P-18058 and shall be either level A or C, as specified (see 6.2).

5.2 Packing. Unless otherwise specified (see 6.2), packing shall conform to MIL-P-18058 and shall be level A, B, or C, as specified (see 6.2).

5.3 Marking.

5.3.1 *Military agencies.* Unless otherwise specified (see 6.2), shipping containers for military agencies shall be marked in accordance with MIL-STD-129.

5.3.2 *Civil agencies.* Interior and exterior shipping containers intended for delivery to civil agencies shall be marked in accordance with Fed. Std. No. 123.

6. NOTES

6.1 Intended use. The milling machines covered by this specification are intended for use in tool rooms, machine shops, and laboratories either fixed or mobile.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.
(*b*) Type, class, style, and size of machine required (see 1.2).
(c) Preproduction inspection, if different (see 3.1).
(*d*) Special safety devices, if required (see 3.2.1).
(*e*) Painting, if different (see 3.3.5).
(*f*) Special power table feed rates, if required (see 3.5.1).
(*g*) Mounting base requirements, if different (see 3.6.5).
(*h*) Spindle nose, if different (see 3.6.7).
(*i*) Coolant system, if not required (see 3.6.9).
(*j*) Ram type mounting for milling heads, type II machines, if required (see 3.6.11).
(*k*) Electrical equipment, if different (see 3.7).
(*l*) Voltage characteristics of machine and voltage for initial wiring (see 3.7.1).
(*m*) Type radio-interference suppression, if required (see 3.8).
(*n*) Type fungus proofing, if required (see 3.9).
(*o*) Lubrication chart or plate, if not required, or if different (see 3.10).
(*p*) Nameplate, if different (see 3.11).
(*q*) Identification plate, if required (see 3.12).
(*r*) Standard equipment, if different (see 3.13).
(*s*) Optional equipment, if required, and type required (see 3.14).
(*t*) Handbook requirements, if different (see 3.15).
(*u*) Foundation and anchor bolt plans and wiring diagrams, if different (see 3.16).
(*v*) Quality conformance inspection, if different (see 4.3).
(*w*) Preservation, packaging, and packing, if different (see 5.1 and 5.2).
(*x*) Level of preservation and packaging, and level of packing (see 5.1 and 5.2).
(*y*) Marking, if different (see 5.3).

6.3 Transportation description. Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Machines, not otherwise indexed by name.
Carload minimum weight 24,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Machines, not otherwise indexed.
Truckload minimum weight 24,000 pounds, subject to Rule 115, National Motor Freight Classification.

CUSTODIANS:
Army—WC
Navy—SH
Air Force—84

Review Activities:
Army—WC
Navy—SH, YD, WP
Air Force—84

User Activities:
Navy—MC

Preparing activity:
DSA-IP

CIVIL AGENCY INTEREST:
General Services Administration

Review/user information is current as of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current Federal Supply Classification Listing of DOD Standardization Documents.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.