00-P-00565a(GSA-FSS)
May 5, 1967
SUPERSEDING
Int. Fed. Spec. 00-P-00565(GSA-FSS)
April 24, 1964

INTERIM FEDERAL SPECIFICATION

POLISHER, FLOOR, ELECTRIC (HOUSEHOLD TYPE)

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The specification covers two brush, concentrated weight, electrically driven household type floor polishing machines.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Sizes. The floor polishers covered by this specification shall be of the following sizes, as specified (see 6.2):

Size 1. - Using two 6-inch diameter brushes.
Size 2. - Using two 8-inch diameter brushes.

2. APPLICABLE DOCUMENTS

2.1 Specification and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

CC-M-636 - Motor, Alternating-Current, (Fractional Horsepower).
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock Corner.
PPP-B-636 - Box, Fiberboard.
PPP-T-45 - Tape, Gummed, Paper, Reinforced.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Military Specification:

MIL-P-116 - Preservation, Methods of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issues in effect on date of invitation for bids or request for proposal shall apply.

Underwriters' Laboratories, Inc. (UL) Standard:

No. 73-Motor Operated Appliances.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, Illinois 60611; 1285 Walt Whitman Road, Melville, Long Island, New York 11749; or 1655 Scott Boulvard, Santa Clara, California 95050.)

Uniform Freight Classification Rules:

Rule 41-Corrugated or Solid Fiberboard Boxes.

(Application for copies should be addressed to the Uniform Classification Committee, Room 202, Union Station, Chicago, Illinois 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Fire and casualty hazards.

3.1.1 Conformance to standards of Underwriters' Laboratories, Inc. (UL). Each contractor shall submit to the contracting agency proof that the floor polishers he proposes to supply under this specification conform to the requirements of UL Std. No. 73. The label, or listing with re-examination, of UL may be accepted as evidence that the floor polishers conform to this requirement.

3.1.2 Data from other laboratories. In lieu of the label, or listing with re-examination, the contractor may submit independent proof, satisfactory to the contracting agency, that the floor polishers conform to the applicable requirements of the published standards including methods of tests of UL Std. No. 73.

3.1.3 Contractor compliance. Compliance with UL requirements regarding fire and casualty hazards does not absolve the contractor from complete compliance with the requirements of this specification in order to secure acceptance of his floor polishers.

3.2 Standard product. The floor polishers furnished under this specification shall be the manufacturer's current standard product except for those modifications or additional changes required in that standard product in order to comply with the requirements of this specification. All accessories and components shall be furnished with each floor polisher that are normally furnished with the standard product offered commercially.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.3 Materials. The materials used shall be suitable for the purpose intended and shall be free from defects affecting the appearance and serviceability of the polishers.

3.4 Design. Size 1 polishers shall operate with two 6-inch diameter brushes and size 2 polishers shall operate with two 8-inch diameter brushes. The effective width of the buffing, polishing, or scrubbing swath on floors shall be not less than 11-inches for the size 1 polishers and not less than 15-inches for the size 2 polishers. The weight of the polishers complete with 2 brushes shall be not less than 14 pounds for size 1 and not less than 30 pounds for size 2. The entire weight of the polisher shall rest on the attached brushes and the polisher shall be known as the commercially designated concentrated weight machine.

3.5 Construction. Each polisher shall be complete, ready to operate, reliable in operation, and constructed so as to be readily desassembled for inspection, adjustment, and replacement of parts. Each part of the polisher shall be interchangeable with the similar part of any other polisher of the same model and size made by the same manufacturer. The polisher housing, driving components, and handle shall be constructed of metal.

3.5.1 Lubrication. The polishers shall be equipped with permanently lubricated sealed bearings or be provided with readily accessible means for lubrication.

3.5.2 Finish and color. Unless otherwise specified (see 6.2), the finish and color of the polishers shall be in accordance with the manufacturer's commercial practice.

3.6 Polisher components.

3.6.1 Housing. The housing shall contain and enclose the power drive mechanism and enclose or provide suitable mounting for the motor. A suitable connection shall be provided on the housing for attaching the operating handle. The lower portion of the housing shall be formed into a skirt or shield covering the upper portion of the brushes in order to prevent cleaning fluids from being thrown against baseboards and walls. A bumper made of resilient nonmarking material shall be provided around the outside of the housing. A fitting shall be provided on the housing for attaching liquid dispensing equipment and for proper distribution of liquids to the brushes. The housing shall be made of corrosion resisting metal or metal suitably plated or coated so as to be corrosion resistant.

3.6.2 Power drive. The brush driving shafts shall be driven by suitable gears interposed between the motor shaft and the brush driving shafts. The brush shafts shall rotate in opposite directions from each other. The polisher shall operate without objectional noise and vibration.

3.6.2.1 Brush speeds. The following brush speeds are no-load speeds. No-load speed is defined as the brush speed when polishing brushes are installed on the machine and the machine is resting on a previously polished composition tile surface.

(a) Size 1 polisher brush speeds shall be not less than 500 revolutions per minute (r.p.m.) nor more than 800 r.p.m.

(b) Size 2 polisher brush speeds shall be not less than 375 r.p.m. nor more than 675 r.p.m.

When specified (see 6.2), an additional slower speed shall be provided on each size polisher for the scrubbing operation.

3.6.3 Operating handle. The operating handle shall be detachable from the housing and shall be hinged at the housing. Means shall be provided for securing the handle in the upright position and various convenient operating positions. The top of the handle shall be angled for optimum one hand polisher control or be provided with twin hand grips.

3.7 Electrical components.

3.7.1 Motor. Unless otherwise specified (see 6.2), motors shall be the universal type conforming to CC-M-636. Unless otherwise specified (see 6.2), the motors shall operate on nominal 115 volt supply circuits. The motors shall be continuous duty type and shall be designed to operate under full rated load conditions in an ambient temperature of 40°C without exceeding the allowable temperature rise. The motor for the size 1 polisher shall have an output rating of 1/4 horsepower (minimum) and the motor for the size 2 polisher shall have an output rating of 1/2 horsepower (minimum).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.7.2 Motor switch. The motor switch shall be of the enclosed, quick make and break type, and shall be adequately insulated. The switch shall be mounted on the polisher handle, in the electric cord, or inside the polisher housing. When mounted inside the housing, the switch shall be actuated by positioning the polisher handle.

3.7.3 Electric cord. The electric cord shall be not less than 16-feet in length for the size 1 polisher and not less than 28-feet in length for the size 2 polisher. The cord length shall be measured from the point of entrance into the polisher to the attachment-plug cap.

3.8 Attachments.

3.8.1 Size 1 polisher. Each size 1 polisher shall be furnished with the following attachments:

(a) One pair of 6-inch diameter buffing pads in accordance with 3.8.3.1.
(b) Either two pairs of 6-inch diameter combination scrubbing and polishing brushes or one pair of 6-inch diameter scrubbing brushes and one pair of 6-inch diameter polishing brushes in accordance with 3.8.3.2.
(c) When specified (see 6.2), one pair of 6-inch diameter rug shampooing brushes in accordance with 3.8.3.2.
(d) When specified (see 6.2), one liquid dispenser in accordance with 3.8.3.3.

3.8.2 Size 2 polisher. Each size 2 polisher shall be furnished with the following attachments:

(a) One pair of 8-inch diameter buffing pads in accordance with 3.8.3.1.
(b) Either two pairs of 8-inch diameter combination scrubbing and polishing brushes or one pair of 8-inch diameter scrubbing brushes and one pair of 8-inch diameter polishing brushes in accordance with 3.8.3.2.
(c) When specified (see 6.2), one pair of 8-inch diameter rug shampooing brushes in accordance with 3.8.3.2.
(d) When specified (see 6.2), one liquid dispenser in accordance with 3.8.3.3.

3.8.3 Attachment details.

3.8.3.1 Buffing pads. Buffing pads shall be made of felt or genuine lambs wool. Felt pads shall be not less than 1/4-inch thick. Lambs wool pads shall have not less that 3/4-inch pile. Snap type metal fasteners or other means shall be provided for securing the pads to brushes or other driving means.

3.8.3.2 Brushes. The brushes shall be the circular one piece type. The brush backs shall be provided with suitable clutch plates for attaching and securing the brushes to the drive shafts. The brushes shall be readily attached to and removed from the polisher drive shafts without the use of tools. The brush diameter shall be measured at the free end of the tufts with no weight resting on the brush. The length of the tufts measured from the brush back shall be not less than 1-1/16 inches. The 6-inch diameter brushes shall have not less than 4 rows of tufts and the 8-inch diameter brushes not less than 5 rows of tufts. The tufts shall be in accordance with 3.8.3.2.1, 3.8.3.2.2, 3.8.3.2.3, or 3.8.3.2.4, as applicable.

3.8.3.2.1 Polishing brushes. The polishing brush tufts shall consist of 100 per cent white tampico fibers.

3.8.3.2.2 Combination scrubbing and polishing brushes. The combination scrubbing and polishing brush tufts shall consist of 60 per cent white tampico fibers and 40 per cent palmyra or palmetto fibers well mixed.

3.8.3.2.3 Scrubbing brushes. The scrubbing brush tufts shall consist of 100 per cent palmyra or palmetto fibers.

3.8.3.2.4 Rug shampooing brushes. The rug shampooing brush tufts shall consist of bristles made of white polyethylene.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.8.3.3 Liquid dispenser. The liquid dispenser shall consist of tank, feed line, if required, and a regulating valve. The dispensing equipment shall be suitable for dispensing floor cleaning solutions, liquid wax, or rug shampoos. The tank shall have a capacity of not less than 2 quiarts and shall be made of corrosion resisting metal, metal suitability plated or coated so as to be corrosion resistant, or plastic. When plastics are used, they shall be rigid, slow burning, high impact polyvinyl or acrylo-nitrile butadiene styrene copolymer suitable for the purpose intended and affording a tank equal in service durability and corrosion resistance to a metal tank. Each tank shall have a cover or a splash apron to prevent the spilling of liquid while the polisher is in operation. The feed line shall be made of suitable flexible tubing or hose. The feed valve shall be suitable for regulating and shutting off the flow of liquid to the brushes. The valve shall be readily accessible to the operator. There shall be no leaks in any part of the dispensing equipment. The liquid dispensing equipment shall be suitable for readily attaching to and removing from the polisher handle or housing without the use of special tools.

3.9 Identification marking. Each polisher shall be plainly and permanently marked with the manufacturer's designation and either his name or a trademark of such known character that the source of manufacture may be readily determined. Complete data for the motor including the voltage, horsepower, watts input, or amperage shall be marked either on the motor name plate or at some other visible place on the polisher.

3.10 Instruction manual and repair parts list. One copy of the manufacturer's manual of instructions for operation and maintenence and a list of repair parts shall be furnished with each polisher. The repair parts list shall include the manufacturer's part number for each part, description of parts, quantity of each part required, and the cost of parts prevailing at the time of contract award. Repair parts for different model polishers shall not have the same part number unless the parts are interchangeable. The repair parts list may be included in the instruction manual.

3.11 Workmanship. The polishers shall be free from external sharp or rough edges and defects which may impair their serviceability and durability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provision set forth in MIL-STD-105, except where otherwise indicated.

4.2.1 Component and material inspection. In accordance with 4.1, the contractor is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements or referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.2.2 End item inspection. All floor polishers of the same size offered for acceptance at one time shall constitute a lot for the purpose of inspection. The sample unit for these inspections shall be one completely fabricated floor polisher and attachments (if applicable).

4.2.2.1 Visual examination. The completely assembled floor polisher shall be examined for the defects listed in table I. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects.

Examine	Defect	Classification	
		Major	Minor
Finish	Type of finish not as specified or blistered, peeled, chipped, or area of no film or thin film		X
	Not finished where required	X	
	Component or assembly that is painted or otherwise coated where serviceability may be affected, e.g., paint on gasket	X	
Material	Component not fabricated of the specified material-	X	
Design	Any characteristic not in accordance with the specified requirements	X	
Construction and workmanship, general (applicable to all components and assemblies)	Part missing or not specified type or size	X	
	Fractured, split, punctured, dented, deteriorated, bowed, malformed, or otherwise impaired affecting serviceability	X	
	Defective or otherwise damaged, but not affecting serviceability		X
	Misplaced, loose or not in proper alignment affecting serviceability	X	
	Sharp burr, sliver or splinter that may be injurious to personnel or may affect serviceability-	X	
	Operation omitted or not properly performed affecting serviceability	X	
	Operation omitted or not properly performed, but not affecting serviceability		X
	Functioning component that requires abnormal force to operate		X
	Not connected or joined as specified or poorly accomplished, affecting serviceability	X	
	Any adjustable assembly that cannot be adjusted or is not properly adjusted to perform the function intended	X	
	Any component not readily accessible for servicing where required		X
Welding and brazing (when applicable)	Not type specified, missing, incomplete, burn holes, cracked, fractured or otherwise not fused	X	
	Slag inclusion, slight undercut, not smooth and uniform, scale or flux deposits not removed		X
Soldering (when applicable)	Missing, not adherent or incomplete	X	
	Not clean (flux or flux residue not removed) not smooth (surface not finished neatly) or pinholes in solder		X
Bolts, nuts, screws, studs, and other types of threaded fasteners	Missing, broken, stripped, fractured, or loose	X	
Electrical assembly	Wiring cut, abraded, not properly joined, loose at terminal or not inclosed where required	X	
	Adequate slack not provided for wiring to relieve strain or excessive insulation stripped from wiring		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (continued)

Examine	Defect	Classification Major	Minor
Lubrication (where applicable)	Not lubricated where required	X	
	Insufficiently lubricated		X
	Not specified type lubrication fitting, affecting serviceability	X	
	Lubrication fitting not readily accessible for servicing		X
Assembly	Component not properly assembled or secured, but not affecting serviceability e.g., lockwasher missing from metal fastener		X
	Unit perceptibly out of square or alignment	X	
Identification marking	Missing, incomplete, not legible		X
Instruction manual	Missing, incomplete, not legible	X	
Repair parts list	Missing, incomplete, not legible	X	

4.2.2.2 Dimensional examination. The end item shall be examined to determine compliance with dimensional requirements. Any deviation from specified requirements shall constitute a defect. The inspection level shall be S-3 with and AQL of 2.5 expressed in terms of defects per hundred units.

4.2.2.3 Testing of the end item. The tests specified under 4.3 shall be performed on each sample floor polisher. The inspection level shall be level II with an AQL of 2.5 expressed in terms of defects per hundred units.

4.3 Tests.

4.3.1 Performance test. The polisher shall be operated continuously for not less than 5 minutes in each of the following operations:

(1) Floor buffing using the buffing pads specified in 3.8.1 or 3.8.2 as applicable.
(2) Floor polishing using the polishing brushes specified in 3.8.1 or 3.8.2 as applicable.
(3) Floor scrubbing using the scrubbing brushes specified in 3.8.1 or 3.8.2 as applicable.

The buffing and polishing operation shall be conducted on composition tile or smooth linoleum. The scrubbing operation shall be conducted on smooth wood or concrete floors or on composition tile or linoleum coated with hardened wax. During each operation the polisher shall be observed for the following:

(a) Overall saitsfactory performance.
(b) Width of buffing, polishing, and scrubbing swaths to determine conformance to 3.4.
(c) Freedom from objectional noise and vibration to determine conformance to 3.6.2.
(d) Rotation of the brushes in opposite directions from each other to determine conformance to 3.6.2.

4.3.2 Brush speeds. Polishing brushes in accordance with 3.8.1 or 3.8.2, as applicable, shall be attached to the polisher. The polisher shall be operated on a previously polished composition tile floor and the brush speeds measured to determine conformance to 3.6.2.1. The brush speeds may be determined during the polishing operation specified in 4.3.1 providing the floor is of previously polished composition tile. When polishers are provided with an additional slower speed (see 3.6.2.1) they shall be tested for the scrubbing operation to determine that the lower brush speed is proper for the intended use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

4.3.3 Brush attachment and removal. Brushes shall be attached to and removed from the polisher drive shafts to determine conformance to 3.8.3.2. Examination shall be made to determine that the attached brushes are held securely to the polisher drive shafts.

4.3.4 Liquid dispenser test. When liquid dispensers are required (see 3.8.1 and 3.8.2), they shall be tested to determine conformance to 3.8.3.3. The dispenser shall be attached to the polisher and filled to capacity with water. The dispenser valve shall be operated to determine that regulation and flow of liquid to the brushes is proper. The polisher shall be operated for normal floor scrubbing or polishing while the dispenser tank is filled. The dispensing equipment shall be observed for any leaks and spilling of liquid. At the conclusion of the tests the dispensing equipment shall be removed from the polisher.

4.4 Inspection of preparation for delivery. An inspection shall be made to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with table II. For examination of contents, the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operation. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects.

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each complete polisher shall be packaged in accordance with MIL-P-116, method IIb,

5.1.2 Level B. Each complete polisher shall be packaged in a box conforming to PPP-B-636, class domestic, grade 275, style optional. The electric cord shall, if attached, be securely wound on the brackets provided and the plug secured to prevent unwinding; if detached, the cord should be coiled to a minimum safe diameter and the coil tied with a minimum of two cotton tape ties and secured to the polisher. The polisher and accessories shall be cushioned and braced in the box to prevent movement during transit. Sealing and closure shall be as specified in the appendix to the box specification.

5.1.3 Level C. Each complete polisher shall be packaged in accordance with the supplier's standard commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. The polishers shall be packed in boxes conforming to PPP-B-621, class 2, style optional, or PPP-B-601, overseas type, style optional. The boxes shall be strapped in accordance with the appendix to the applicable box specification. Strapping shall be zinc coated. The gross weight of each box shall not exceed 200 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. The polishers shall be packed in boxes conforming to PPP-B-636, type CF, class domestic, style optional, in quantities not to exceed the weight limitations of the box specification. All flaps of the fiberboard shipping containers shall be sealed with an adhesive, commercially used for the product being packed, by application throughout the entire area of contact between the flaps, or by a combination of metal stitching the bottom flaps and sealing the top flaps with adhesive. The containers shall be reinforced with bands of filament tape in accordance with the appendix to the container specification. Alternatively reinforcing may be by the two strip tape method described in Uniform Freight Classification Rule 41, section 7, using tape conforming to PPP-T-45.

5.2.3 Level C. The polishers shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Civilian agencies. In addition to any special marking by the contract or order (see 6.2), shipments shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military requirements. In addition to any special marking required by the contract or order (see 6.2), shipments shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The floor polishers covered by this specification are intended for light duty domestic use in wet or dry scrubbing and also polishing tile or linoleum covered floors, and for rug shampooing.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Size floor polisher required (see 1.2.1).
(c) Finish and color if different from 3.5.2.
(d) Additional slower speed, if required (see 3.6.2.1).
(e) Type motor required if different from 3.7.1.
(f) Motor operational requirements if supply circuit is different from 3.7.1.
(g) When rug shampooing brushes shall be furnished (see 3.8.1 and 3.8.2).
(h) When liquid dispensers shall be furnished (see 3.8.1 and 3.8.2).
(i) Level of packaging required (see 5.1).
(j) Level of packing required (see 5.2).
(k) Special marking if required (see 5.3.1 and 5.3.2).

GSA DC 67-18882

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.