00-P-570E
October 16, 1969
SUPERSEDING
Int. Fed. Spec. 00-P-00570d(GSA-FSS)
January 12, 1968 and
Fed. Spec. 00-P-570c
August 7, 1964

FEDERAL SPECIFICATION

POLISHER, FLOOR, ELECTRIC (COMMERCIAL TYPE)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers concentrated weight, single-brush, two-brush, and divided weight, electric-motor driven, commercial type floor polishing machines.

1.2 Classification.

1.2.1 Class, styles and sizes. The floor polishers shall be of the following classes, styles, and sizes, as specified (see 6.2):

Class A - Concentrated weight single-brush.

Style 1 - Regular duty.
Style 2 - Hospital duty.

Class B - Concentrated weight, two-brush.
Class C - Divided weight.

1.2.1.1 Sizes. Sizes of machines shall be as shown in tables I, II, and III.

2. APPLICABLE DOCUMENTS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

L-P-393 - Plastic Molding, Polycarbonate Resin, Injection and Extruded.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple Wall.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Ft. Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 7910

Source: https://assist.dla.mil -- Downloaded: 2015-08-24T13:55Z
Check the source to verify that this is the current version before use.
Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-P-116 - Preservation, Methods of.
MIL-L-10547 - Liners, Case, and Sheet Overwrap; Water-Vapor Proof or Waterproof, Flexible.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U. S. Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristics Requirement for Equipment.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-810 - Environmental Test Methods.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids, or request for proposal shall apply:

National Classification Board:

National Motor Freight Classification.

(Application for copies shall be addressed to the National Classification Board, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

Underwriters' Laboratories, Inc. (UL) Standard:

No. 73 Motor-Operated Appliances.

(Copies may be obtained from the Underwriters' Laboratories, Inc., 1285 Walt Whitman Rd., Melville, L.I. New York 11749; 207 East Ohio St., Chicago, Ill., 60611; and 1655 Scott Blvd., Santa Clara, Calif., 95050.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Conformance to Underwriters' Laboratories, Inc. The contractor shall submit to the contracting agency proof that the polisher he proposes to supply under this specification conforms to the commercial floor polisher requirements of UL Standard No. 73. The label, or listing with re-examination of the Underwriters' Laboratories, Inc. may be accepted as evidence that the polishers conform to this requirement. In lieu of the label or listing, the contractor may submit independent proof, satisfactory to the contracting agency, that the polisher conforms to the applicable requirements of the published standard, including methods of tests of UL Standard No. 73.

3.1.1 Contractor compliance. Compliance with the preliminary requirements of 3.1 does not absolve the contractor from complete compliance with the other requirements of this specification in order to secure acceptance of his polishers.

3.2 Preproduction sample. When specified (see 6.2), a complete polisher of the class, style and size, as applicable, which the contractor proposes to deliver shall be submitted to the contracting officer or made ready at the plant for approval. When the preproduction sample is approved, it shall be retained by the contractor as a sample for subsequent production on the contract. The sample may be included in the quantity required for last shipment.

Source: https://assist.dla.mil -- Downloaded: 2015-08-24T13:55Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.3 Materials. Materials used in the construction of the polishers shall be as specified herein. When materials are not definitely specified, they shall be of the quality normally used for the purpose in commercial practice. All materials shall be new and unused, and free from any defects or imperfections which might affect appearance or serviceability.

3.4 Design and construction. The polishers covered herein shall be of the contractor's current production design, convenient to operate and entirely adequate for the purpose intended. Resistance to wear, damage, misalignment, and derangement shall be inherent in the design and construction consistant with the intended utilization for heavy duty use. All parts subject to wear shall be readily accessible for repair or adjustment. Components and assemblies shall correspond to the requirements specified herein.

3.4.1 Housing for Navy use. When specified for Navy use (see 6.2), the housing shall be of nonconducting material such as polycarbonate in accordance with L-P-393.

3.5 Electrical requirements. Unless otherwise specified (see 6.2), the polisher shall operate on a nominal 120 volt, 60 cycle, single phase supply.

3.5.1 Wiring. All wiring, cord, plug and grounding shall be in accordance with UL 73. The cord shall have a grounding attachment plug and unless otherwise specified (see 6.2), shall have a minimum free length of not less than 50 feet of yellow colored, 3-conductor cord, measured from the point of entry into the polisher. The cord at its point of entry shall be guarded to prevent it being chafed and shall be durably reinforced with a well-anchored rubber or thermoplastic sleeve. Means shall be provided for coiling cord on clips on the vertical portion of the handle in a manner not to interfere with the operation of the machine when only a portion of the cord is being used.

3.5.2 Switch. Class A and class C polishers shall have a quick break switch for starting and stopping the motor. The switch shall operate easily and reliably and be conveniently located. The switch shall automatically open the motor circuit the moment the operator releases the handle of the machine. The switch for the class B polishers need not be of the automatic type. The switch shall be mounted at an appropriate angle to facilitate actuation while the operators hands are on the handle bar and the handle tube is in a median operational position. The switch shall be capable of performing acceptably after being subjected to 50,000 operational cycles with an inductive load such as that caused by the starting and running torque of the polisher. Acceptable evidence of meeting the operational cycles requirement shall be a certified test report from a recognized independent testing laboratory acceptable to the contracting officer, indicating that the switches have been tested as in 4.4.3 and meet this requirement.

3.5.3 Grounding. The grounding conductor in cord shall be connected to the motor frame and to all metal parts exposed to touch and likely to become energized by any leakage current or derangement in power conductors. The grounding circuit shall not depend on moveable joints. The resistance in ohms from the motor frame to the ground connection on the plug end of the 50-foot cord shall be less than 1 ohm.

3.5.4 Resistance to humidity. When specified for shipboard use (see 6.2), the polisher shall be subjected to and withstand the humidity test of MIL-STD-810, Method 507, procedure I.

3.5.5 Leakage current. After the humidity test of 3.5.4 the leakage current to case of polisher with motor running shall not exceed 0.5 milliamperes, without a radio interference suppression filter installed. Where a filter is installed in accordance with 3.17, the leakage current to case shall not exceed 5.0 milliamperes. Acceptable evidence of meeting these requirements shall be a certified test report from a recognized independent testing laboratory acceptable to the contracting officer, indicating that the polishers have been tested as in 4.4.4 and meet this requirement.

3.6 Operating handle. The adjustable operating handle shall include a metal handle bar and a metal handle tube designed and constructed to perform their respective functions without detaching, bending, or distorting. The handle bar shall be provided with suitable nonmetallic handgrips. Means shall be provided for positively securing the handle in an upright position for storage and various convenient operating positions.

3.7 Wheels. The polisher shall be mounted on two substantial wheels placed in such a position as to facilitate the movement of the machine in any direction on the floor. The wheels shall have a running surface of suitable resilient material which will not mar or scratch the floor or floor covering under ordinary service conditions. The wheel assembly including the wheels, axle or axles, and the associated wheel carriage assembly, shall be designed and constructed to perform their respective functions without misaligning, bending or malfunctioning under heavy duty service conditions. Unless otherwise specified (see 6.2), wheels shall comply with the size specified in tables I, II, or III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.8 Brushes. Unless otherwise specified (see 6.2), each polisher shall be furnished with a set of brushes for polishing and a set for scrubbing.

3.8.1 Brush construction. Unless otherwise specified (see 6.2), brushes shall be circular in shape with either one piece or sectional backing blocks of either laminated or solid construction as hereinafter specified. The machine shall be so constructed that the brushes may be readily replaced without the use of special tools. The diameter of the extremity of bristles, measured parallel to the brush back shall not be more than 2-1/2 inches larger than the diameter of the brush back. The diameter and the area of the brush as specified in tables I, II and III shall be measured at the free end of the tufts with no weight applied on the brush.

3.8.1.1 Polishing brushes. Unless otherwise specified (see 6.2), polishing brushes for class A and class B machines shall be one piece and class C machines shall be sectional. One-piece brushes shall be laminated with a minimum of nine layers of plywood of approximately equal thickness with a total thickness of not less than one inch. Sectional brushes may be laminated or solid.

3.8.1.1.1 Back or block. The back or block of both laminated and solid polishing brushes shall be made from maple, beech or birch. Plywood, if used, shall be firmly built up and shall be assembled under heavy pressure with the use of casein, blood albumen glue, or equally effective and suitable adhesive. The one-piece brush shall be built upon a circular, one-piece, laminated back. Unless otherwise specified, (see 6.2), the sectional brush shall be built on segments of either solid or laminated wood of sizes and shapes furnished by the machine manufacturer as original equipment. The backs shall be so finished as to withstand use with water without warping or other deterioration that will affect the utility of the brush.

3.8.1.1.2 Plate. Each brush shall have a suitable metal plate securely attached to it. The plate shall be adaptable to the machine model upon which it is to be used. This plate shall afford a secure and efficient attachment of the brush to the machine and shall also permit easy and convenient detachment. The plate shall be capable of being easily removed for use on other brushes.

3.8.1.1.3 Tufts. Polishing brush tufts shall be made of approximately 60 percent tampico and 40 percent palmetto fiber, well mixed. The tufts shall be inserted in holes in the brush block of not less than 1/4 inch nor more than 5/16 inch in diameter and shall be securely wired in the block or held in place by any other suitable means. The holes for the tufts shall be drilled on 1/2 inch centers and symmetrically arranged covering the brush block and shall be such that the normal flare of the brush will, with exception of the center hole, afford a practically continuous and effective polishing area of fiber over the area specified in tables I, II and III for the various size brushes. The tufts shall have a free length of not less than 1-1/2 inches when measured at right angles to the surface of the brush block. The free ends of the tufts shall form a uniform surface parallel to the surface of the brush block so that the machine will operate with no apparent wobble. The peripheral tufts in the brush block shall have a suitable spread or flare which will permit brush contact with the floor up to a vertical surface, such as walls and baseboards.

3.8.1.2 Scrubbing brushes. Scrubbing brushes shall be as specified for polishing brushes except that the scrubbing brush may have a heavy metal back instead of the plywood and plate construction and the tufts shall be made of 100 percent palmetto fiber.

3.9 Frame. The frame enclosing the operating mechanism shall be designed and durably constructed and reinforced, if necessary, in a manner to be compact and sufficiently rugged to withstand, without damage conditions likely to be encountered in rigorous, heavy-duty service. The brush cover shall extend outward and down to form an apron covering the entire back of the brush as well as the full width of its edge and shall be of a strong and durable malleable material.

3.10 Bumper. There shall be securely attached, around that portion of the apron flange which can come into contact with baseboards, walls, or furniture, a substantial, readily replaceable rubber or vinyl plastic bumper not less than 3/4 inch in vertical direction which will not dent or mark objects with which it comes in contact. The method of holding this bumper in place shall be such that it cannot be readily dislodged in machine operation. If metal is used in holding bumper in place, it shall be either countersunk or embedded into the bumper material so that it cannot come into contact with vertical surfaces, even after a reasonable amount of wear of the bumper has taken place.

3.11 Drives. Unless otherwise specified (see 6.2), power for operating the machine shall be transmitted through gear drives. The gear drives shall be enclosed in chambers sealed against loss of lubricant and possible admission of water or any foreign material. Means shall be provided for inspection and replacement of worn parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.12 Lubrication. All parts requiring lubrication shall be adequately lubricated upon assembly and shall be so mounted that they may be lubricated through normal maintenance procedures. Machines shall be ready to operate on delivery with no additional lubrication.

3.13 Feed line and water tank. Provision shall be made in all machines to feed water to the brush fibers. A fitting, to be provided with each machine, shall be such that only connections to hose, control, and tank shall be necessary to complete the waterfeed equipment. When specified (see 6.2), machines shall be furnished complete with suitable equipment consisting of a corrosion-resistant metal or plastic tank, a suitable feed line, and control for the purpose of carrying water to the fitting required on all machines. The capacity of the tank shall be that normally furnished by the producer for the size machine but not less than 7 quarts. The tank shall be attached to the handle of the machine by means of suitable metal clamps or brackets and be readily removable without the aid of special tools. It may also be placed over the housing of the machine provided it is readily removable without the use of special tools. The tank shall have a cover or a splash apron to preclude the possibility of water falling out while the machine is in operation. The water feed control shall be conveniently located on or near the handle grips of the machine.

3.14 Exposed metal parts. All exposed metal parts shall be made of corrosion-resisting metal, or other metal adequately protected with a corrosion-resisting metal plating or other suitable protective coating.

3.15 Pad holder assemblies. All polishers shall be designed for adapting nylon or steel wool pad holder assemblies.

3.16 Detail requirements.

3.16.1 Class A. Class A machines shall be constructed so that the entire weight of the machine rests directly on the brush during operation. The speed reducing mechanism shall produce a speed of the brush suitable for the purpose intended, but not in excess of 225 r.p.m. while the machine is operating on a linoleum floor.

3.16.1.1 Wheel mounting.

3.16.1.1.1 Movable wheels. The wheels or wheel mechanism shall be mounted on a movable axle. The entire mechanism shall be constructed so that the machine may be rolled on the wheels. During operation of the machine, the entire mechanism shall be raised so that the entire weight of the machine rests on the brush.

3.16.1.1.2 Fixed wheels. Fixed wheels shall be positioned so that the entire weight of the machine rests on the brush during operation and on the wheels for transportation.

3.16.1.2 Class A, style 1. Machines shall be furnished in the sizes specified in table I and shall conform to the requirements of all applicable paragraphs in this specification.

3.16.1.3 Class A, style 2. All the general specifications of table I are applicable, plus special motor which shall be fully enclosed and cooled by convection. No air currents which could possibly contain contaminated material shall be utilized in cooling internal inacessible mechanisms of motor or other components. In order to keep the noise level to a minimum, the internal ring gear shall be mounted in a system of compression springs for maximum shock resistance or burnished fitted gears shall be provided in the gear reducer unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE I. Class A, styles 1 and 2 machines, polishing and scrubbing, electric, concentrated weight, single-brush

Size	Overall diameter of brush fiber (minimum)	Area of polishing brush fiber (minimum)	Continuous rating of motor (minimum)	Weight of machine complete with one brush (minimum)	Wheel diameter (minimum)
	Inches	Sq. Inch	Horsepower	Pounds	Inches
1	10-1/2	70	1/4	40	2-1/2
2	12-1/2	100	1/3	50	2-1/2
3	14-1/2	140	1/2	60	3-1/2
4	17	200	3/4	75	3-1/2
5	19	240	1	100	4-1/2
6	21	300	1	105	5
7	22	340	1	125	5

3.16.2 Class B. Class B machines shall be constructed so that the entire weight of the machine rests directly on two brushes. The speed reducing mechanism shall produce a speed of the brushes suitable for the purpose intended, but not exceeding 325 r.p.m. while the machine is operating on a linoleum floor.

3.16.2.1 Wheel mounting. The wheels or wheel mechanism shall be mounted on a movable axle. The entire mechanism shall be constructed so that the machine may be rolled on the wheels. During operation of the machine, the mechanism shall be raised so that the entire weight of the machine rests on the brushes.

3.16.2.2 Sizes. Class B machines shall be furnished in the following sizes and shall conform to the requirements specified in table II.

TABLE II. Class B machines, polishing and scrubbing, electric, concentrated weight, two-brush

Size	Overall diameter of brush fiber (minimum)	Total polishing brush fiber area (minimum)	Continuous rating of motor (minimum)	Weight of machine complete with two brushes	Wheel diameter (minimum)
	Inches	Sq. Inch	Horsepower	Pounds	Inches
1	7	70	1/2	60 to 105	3
2	10	135	3/4	115 to 175	3-1/2

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.16.3 Class C. Class C machines shall be constructed so that the motor rests on a frame or carriage having wheels at the rear and the brush at the front, with the weight of the machine divided between the brush and wheels. The minimum weight on the brush shall be as stated in table III for the respective size of machine. If an additional weight is required over the brush in order to meet the pressure requirements, it shall be of compact design and free from projections which may interfere with satisfactory operation of the machine in confined spaces. It shall be attached to a permanent part of the machine and no part of the weight shall project beyond the housing. Unless the weight is built into the machine and is out of sight in normal use, means shall be provided for readily attaching or removing the weight from the machine without the use of special tools. The speed reducing mechanism shall produce a speed of the brush suitable for the purpose intended, but not in excess of 250 r.p.m. while operating on a linoleum floor.

3.16.3.1 Wheel mounting. The wheels shall be mounted on one or more rigid axles and shall be in contact with the floor at all times.

3.16.3.2 Sizes. Class C machine shall be furnished in the following sizes and shall conform to the requirements in table III:

TABLE III. Class C machines, polishing and scrubbing, electric, divided weight

Size	Overall diameter of brush fiber (minimum)	Area of polishing brush fiber (minimum)	Continuous rating of motor (minimum)	Weight of machine, complete, including removable weight, if any	Weight on bristles including removable weight if any and one brush[1] (minimum)	Wheel diameter (minimum)	Height not including handle (maximum)
	Inches	Sq. Inch	Horsepower	Pounds	Pounds	Inches	Inches
1	10-1/2	45	1/4	55 to 85	35	2-1/2	11
2	12-1/2	70	1/3	70 to 110	45	2-1/2	14
3	14-1/2	90	1/2	90 to 135	55	3	14
4	17-1/2	150	3/4	115 to 175	70	3-1/2	15

[1] The weight on the bristles shall be determined with the handle of the machine in an operating position and the cord resting on the floor.

3.17 Electromagnetic interference control.

3.17.1 Army purchases. The unit shall meet the electromagnetic interference control requirements and test limits for class IIB equipment as specified in MIL-STD-461.

3.17.2 Navy and Air Force purchases. When specified (see 6.2), the units shall meet the electromagnetic interference control requirements and test limits of class IIB equipment as specified in MIL-STD-461.

3.18 Color and finish. Unless otherwise specified (see 6.2), the polisher shall be finished according to the manufacturer's standard practice.

3.19 Manuals, instructions and parts.

3.19.1 Operating and service instructions. The contractor's standard handbook or pamphlet of operating and service instructions shall be furnished with each polisher.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.19.2 Parts manual. When specified (see 6.2), the contractor shall furnish with each polisher one manual containing complete operation, maintenance, and repair instructions, wiring diagrams and illustrated parts data section. The parts data section shall include the contractor's part number, description of part, quantity of each part used in the end item and cost of parts (prevailing at time of contract award). The illustration of the parts may be a drawing or a picture and shall be cross-referenced to the applicable part number to provide a definite identification of the illustration. Parts for the same or different model numbers shall not have the same part number unless the parts are interchangeable.

3.20 Name and data plates. Except on procurement for civil agencies, each polisher covered by this specification shall be marked for identification in accordance with MIL-STD-130. For procurement of civil agencies, the plate may be in accordance with the manufacturer's standard practice, provided it is legibly and permanently marked with the manufacturer's name or trademark of such known character that the source of manufacture of the polisher may be readily determined and contains the type or model and size of the polisher and the electrical characteristics, as applicable.

3.21 Workmanship. The completely fabricated polisher shall conform to the quality and grade of product covered by this specification. The polisher shall be free from defects such as fractures, splits, punctures, tears, dents, creases, bows, miscasts, deteriorations, or malformations. There shall be no sharp edges, burrs, or slivers.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements, as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Preproduction sample inspection. When a preproduction sample is required (see 3.2), it shall be examined for defects listed in table IV and tested in accordance with 4.4.1 and 4.4.3 and when applicable 4.4.2 and 4.4.4.

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be in accordance with the provisions of MIL-STD-105, except where otherwise indicated.

4.3.1 Components and material inspection. In accordance with 4.1, components and materials shall be inspected and tested with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.3.2 End item inspection. A lot shall consist of all polishers of the same class, style, and size offered for inspection at one time. The sample unit shall be one polisher.

4.3.2.1 Visual and dimensional examination. The completely assembled end item shall be examined for defects in finish, construction, workmanship, marking and nonconformance with dimensional requirements. Defects shall be as classified in table IV. The inspection level shall be level II with an acceptable quality level (AQL) of 4.0 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of defects

Examine	Defect	Classification	
		Major	Minor
Finish	Not finished where required.	X	
	Type of finish not as specified or blistered, peeled, chipped or area of no film or thin film.	X	
	Any component or assembly that is painted or otherwise coated where serviceability may be affected.	X	
	Any area of rust.		X
Dimensions	Dimensions not in accordance with the specified requirements.	X	
Class	Not class specified.	X	
Style	Not style specified.	X	
Size	Not size specified.	X	
Construction and workmanship, general	Part missing or not specified type or size (except as otherwise indicated herein).		X
	Fractured, split, punctured, torn, dented, creased, deteriorated, bowed, sprung, malformed, decayed or otherwise impaired.	X	
	Defective or otherwise damaged but not affecting serviceability		X
	Misplaced, loose or not in proper alignment.	X	
	Sharp burr, sliver, or splinter that may be injurious to personnel.	X	
	Component not readily accessible for servicing where required.		X
Welding or brazing (where required)	Missing, incomplete, burn holes, cracked, fractured, or otherwise not fused.	X	
	Slag inclusion, undercut, not smooth and uniform, scale or flux deposits not removed.		X
Soldering (where applicable)	Missing, not adherent or incomplete, cold solder joints.	X	
	Not clean (flux or flux residue not removed), not smooth (surface not finished neatly) or pin holes in solder.		X
Bolts, nuts, screws, studs, and other types of fasteners	Missing, broken, stripped, factured or loose.	X	
Electric assembly	Wiring cut, abraded, not properly joined, loose at terminal, or not inclosed in specified conduit where required.	X	
	Cord not yellow colored.	X	
	Adequate slack not provided for wiring to relieve strain or excessive insulation stripped from wiring.		X
	Cord not durably reinforced and properly anchored.	X	
	Grounding conductor not connected to motor frame and to all dead metal parts which are liable to become energized.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of defects (Con.)

Examine	Defect	Classification	
		Major	Minor
Assembly	Any component not properly assembled or secured.	X	
	Unit perceptible out of square or alignment.	X	
Marking identification, instruction manual, wiring diagrams (where applicable)	Missing, incomplete, not legible, not as specified.	X	

4.3.2.2 Testing of the end product. When a preproduction sample is not required, the initial production unit shall be tested as specified in 4.4.1 and when applicable, 4.4.2. Tests outlined in 4.4.1 shall be performed on each lot offered for acceptance. The inspection level shall be level S-1 with an AQL of 4.0 defects, expressed in defects per hundred units.

4.4 Tests.

4.4.1 Operational test. The polisher shall be equipped with a polishing brush or brushes specified in 3.8.1.1, and operated for 2 hours on a waxed linoleum floor or a steel plate. The machine shall be operated at full rated voltage. During and after the 2 hour operation, the polisher shall be observed and examined for the following:

(a) Quietness of operation and freedom from vibration.
(b) Overheating of motor.
(c) Lubrication and leakage of lubricant.
(d) Replacement of brush without the use of special tools.
(e) Provision for feeding water to the scrubbing brush.
(f) Uniformity, continuity, size of polishing area and proximity of brush contact up to a vertical surface.
(g) Resistance in ohms from the motor frame to ground connection on the plug end of the 50-foot cord in less than 1 ohm.

4.4.2 Electromagnetic interference control tests. The equipment shall be tested in accordance with Test Methods CE03 and RE02 of MIL-STD-462 to determine compliance with the requirements of 3.17.

4.4.3 Switch endurance test. The switch shall be subjected to an accelerated endurance test of 50,000 cycles of operation, at a rate of 18-24 cycles per minute at rated current and maximum rated voltage with a power factor of 0.75 - 0.80. Any electrical or mechanical failure, undue burning or pitting of contacts, loosening of parts, or any other defects which could appreciably diminish the usefulness and reliability of the switch shall be cause for rejection.

4.4.4 Humidity test. When polishers are required to meet the requirements of 3.5.4, subject preproduction sample of polishers to standard humidity test MIL-STD-810, Method 507, procedure I. Operate the polisher as specified in 4.4.1. During the test, measure the leakage of current between the ground conductor and the power conductor, and between the motor frame and the power conductors. The milliammeter used to measure the leakage current shall not induce a voltage drop in the measuring circuit greater than 1 percent of the polisher's supply voltage. Any leakage current in excess of the values specified in 3.5.5 shall constitute failure of this test.

4.5 Examination of preparation for delivery. An examination will be made to determine that packaging, packing, and marking as required by section 5 of this specification are complied with. Defects will be scored as specified in table V. The sample unit shall be one shipping container fully prepared for delivery. The lot size shall be the number of containers in the inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

TABLE V. Examination of preparation for delivery

Examination	Defect
Markings	Missing; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Component missing, damaged, or otherwise defective.
Workmanship	Inadequate application of components such as incomplete closure of case liners, strapping, sealing, braces, blocking and cushioning inadequate, improper or missing; bolts and closures improperly affixed; components improperly secured, inadequate stapling, bulging or distortion of containers.
Weight	Gross weight exceeds requirements.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The brushes and handle, when applicable, shall be disassembled from the polisher.

5.1.1.2 Handbook of instructions. The handbook of instructions shall be packaged method IC-1 in accordance with MIL-P-116.

5.1.2 Level C. The polishers shall be packaged in accordance with the supplier's commercial practice.

5.2 Packing. Packing shall be levels A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Polishers up to 65 pounds. Each polisher whose net weight does not exceed 65 pounds shall be packed in a close-fitting box conforming to PPP-B-636, class 2, V3c or V3s, style RSC. Blocking and bracing shall be provided. The box shall be closed, sealed, and strapped in accordance with the appendix to the box specification.

5.2.1.2 Polishers over 65 pounds. Each polisher whose net weight exceeds 65 pounds shall be packed in a close-fitting box conforming to PPP-B-621, class 2, style 4, or PPP-B-640, class 2, style E. Blocking and bracing shall be provided. The fiberboard box shall be closed and sealed in accordance with the appendix to the box specification. Each wood box shall be provided with a case liner conforming to MIL-L-10547, type I or II, grade C. Strapping shall be in accordance with the appendix to the applicable box specification.

5.2.2 Level B.

5.2.2.1 Polishers up to 65 pounds. Each polisher whose net weight does not exceed 65 pounds shall be packed in a close-fitting box conforming to PPP-B-636, class domestic, style RSC. Blocking and bracing shall be provided. The box shall be closed in accordance with the appendix to the box specification.

5.2.2.2 Polishers over 65 pounds. Each polisher whose net weight exceeds 65 pounds shall be packed in a close-fitting box conforming to PPP-B-621, class 1 or PPP-B-640, class 1. Blocking and bracing shall be provided. The boxes shall be closed in accordance with the appendix to the applicable box specification.

5.2.3 Level C. The polishers shall be packed in a manner which will insure arrival at destination in satisfactory condition and be acceptable to the carrier at lowest rates. Containers and packaging shall comply with Uniform Freight Classification rules or National Motor Freight Classification rules.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special markings required by the contract or order (see 6.2), the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military activities. In addition to any special markings required by the contract or order (see 6.2), the packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The machines covered by this specification are intended for heavy duty commercial use in wet or dry scrubbing, also for polishing and buffing wood and tile or linoleum covered floors, and for rug shampooing.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Required class, style, and size (see 1.2).
(c) Whether preproduction sample is required (see 3.2).
(d) When special housing material is required for Navy use (see 3.4.1).
(e) Electrical requirements, if different (see 3.5).
(f) Cord length, if different (see 3.5.1).
(g) When humidity test is required (see 3.5.4).
(h) Wheel size, if different (see 3.7).
(i) Quantity of brushes, if different (see 3.8).
(j) Brush shape or construction, if different (see 3.8.1, 3.8.1.1, and 3.8.1.1.1).
(k) Drives, if different (see 3.11).
(l) Water tank, feed line and control, if required (see 3.13).
(m) When electromagnetic interference control is required (see 3.17.2).
(n) Color, if different (see 3.18).
(o) Parts manual, if required (see 3.19.2).
(p) Selection of applicable level of packaging and packing requirements (see 5.1 and 5.2).
(q) Marking, if different (see 5.3).

6.3 Service guarantee. It is suggested that the purchasing officer include the following clause in the invitation for bids:

Service Guarantee. The contractor guarantees the equipment against defective material, workmanship and performance for a period of 1 year, said guarantee to run from date of acceptance of the equipment by the Government. The contractor agrees to furnish, without cost to the Government, replacement of all parts and material which are found to be defective during the guarantee period. Replacement of material and parts shall be furnished to the Government at the point of installation, if installation is within the continental United States, or f.o.b.; the continental United States port to be designated by the purchasing officer if installation is outside of the continental United States. Cost of installation of replacement material and parts shall be borne by the Government.

6.4 Electromagnetic compatibility. The contracting officer should submit a copy of the Test Report required in MIL-STD-461 to the Commanding General, U. S. Army Electronics Command, Attn: AMSEL-RD-GF, Fort Monmouth, N. J., 07703, for approval.

MILITARY INTEREST:

Custodians:
Army - GL
Navy - YD
Air Force - 84

User activities:
Army - CE
Navy - CG, MC

Review activities:
Army - GL, EL, MD
Navy - SH, YD
Air Force - 84, 85

Preparing activity:
GSA-FSS

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies of documents referenced herein. Price of this specification cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.