OO-P-570E
AMENDMENT-2
November 4, 1981

# FEDERAL SPECIFICATION

## POLISHER, FLOOR, ELECTRIC (COMMERCIAL TYPE)

This amendment, which forms a part of Federal Specification OO-P-570E, dated October 16, 1969, approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

1.1 Scope. Add "These cleaners shall be designed to operate on 120 V a.c., 60 Hz, single phase, or when specified on 220 V a.c., 50 Hz (see 3.5)."

PAGE 3

3.4.1 Housing for Navy use. Delete in its entirety.

3.5.1 Wiring. Delete the second sentence and substitute the following: "The electrical cable assembly shall be in accordance with Federal Specification J-C-175 with the following designation: J-C-175 S1C2DNY for use with 120 V a.c., 60 Hz only. The cord shall have a minimum free length of not less than 50 feet of yellow colored, three conductor cord, measured from the point of entry into the polisher."

3.5.3 Grounding. Delete the first and second sentences and substitute the following: "The grounding conductor in the cable assembly referenced in 3.5.1 shall form a continuous conductor path from the point of attachment on the motor housing to the wall recepticle when the machine is connected and ready for operation. The grounding path shall not incorporate any movable joints."

PAGE 4

3.8.1 Brush construction. Delete the first sentence and substitute the following: "Unless otherwise specified (see 6.2), brushes shall be circular in shape with either one piece or sectional backing blocks fabricated from solid wood, laminated wood, or compression molded wood particles. Water, detergents, or solvents common in floor maintenance shall not warp, delaminate, swell, or otherwise deteriorate the block which would impair brush utility."

FSC 7910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.

3.8.1.1 Polishing brushes. Delete the second and third sentences and substitute the following: "One piece brushes shall be laminate (9 ply minimum) wood or compression molded wood particles. Back thickness shall be not less than 1 inch. Sectional brushes may be of solid, laminated, or compression molded constructions."

3.8.1.1.1 Back or block. Delete the third and fourth sentences and substitute the following: "The one piece brush back shall be of circular laminated wood or compression molded wood particles construction. The sectional brush shall be fabricated from solid wood, laminated wood, or compression molded wood particles segments of sizes and shapes furnished by the machine manufacturer or original equipment."

3.8.1..1.3 Tufts. Delete the first sentence and substitute the following: "Polishing brush tufts shall be made of approximately 60 percent Tampico and 40 percent Palmyra fiber, well mixed."

3.8.1.2 Scrubbing brushes. Delete the first sentence and substitute the following: "Scrubbing brushes shall be as specified for polishing brushes except that the scribbing brush may have a heavy metal back and the tufts shall be made of 100 percent palmetto fiber or 100 percent basine fiber."

PAGE 5

3.13 Feed line and water tank. Add at the end of the paragraph the following: "The waterfeed fitting shall be provided as a component part of the waterfeed accessory kit. An opening shall be provided in the base casting for this fitting. This opening shall be plugged unless the waterfeed accessory kit is specified."

PAGE 6

Table 1. Change the following weights in column 5 as follows:
Size 5 - from 100 pounds to 90 pounds
Size 6 - from 105 pounds to 95 pounds
Size 7 - from 125 pounds to 105 pounds.

PAGE 12

6.2 Ordering Data. Add (r) voltage, as required (see 1.1).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:59Z
Check the source to verify that this is the current version before use.