00-S-236C
March 31, 1975
SUPERSEDING
00-S-236B
April 19, 1968

FEDERAL SPECIFICATION

SAW, CIRCULAR, TABLE TYPE, WOODWORKING SINGLE TILTING ARBOR, FLOOR MOUNTED

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers electric motor driven, tilting arbor, table type, circular saws.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Types and sizes. This specification covers electric motor driven, tilting arbor circular saws of the following types and sizes. The type and size saw required for specified procurements shall be as specified (see 6.2.1).

Type I - Direct driven tilting arbor

Size 12 - 12 inch diameter saw blade
Size 14 - 14 inch diameter saw blade
Size 16 - 16 inch diameter saw blade
Size 18 - 18 inch diameter saw blade
Size 20 - 20 inch diameter saw blade

FSC 3220

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

Type II - Belt driven tilting arbor

Size 10 - 10 inch diameter saw blade
Size 12 - 12 inch diameter saw blade
Size 14 - 14 inch diameter saw blade

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specification:

GGG-B-440 - Blade, Circular Saw, Woodworking

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the currentversion before use.

Military Specifications:

MIL-M-18058 - Machinery, Metal and Woodworking, Support Equipment and Associated Repair Parts, Preparation for Delivery of.

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Laws and Regulations:

Occupational Safety and Health Act (OSHA) of 1970:

29CFR1910 - Occupational Safety and Health Standard.

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Bureau of Standards (NBS) Handbook:

H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

American Gear Manufacturers Association AGMA 360

Manual for Machine Tool Gearing

(Application for copies should be addressed to the American Gear Manufacturers' Association, 1330 Massachusetts Ave., NW Washington, DC 20005.)

National Electrical Manufacturers' Association (NEMA) Standards

MG-1 Motors and Generators

IC-1 Industrial Controls

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 155 East 44th St., New York, NY 10017.)

3. REQUIREMENTS

3.1 Classification of requirements. The requirements for the product are as classified herein as follows:

Requirement	Paragraph
First Article approval	3.2
General requirements	3.3
Detailed requirements	3.4
Performance requirements	3.5

3.2 First Article approval. If First Article approval is required (see 6.2.1 and 6.4), inspection therefor shall be in accordance with section 4. A First Article comprises a preproduction model or initial production sample; approval involves testing and evaluating the First Article for conformance with the requirements herein before, or in the initial stage of, production under a contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.3 General requirements.

3.3.1 Design. The saw shall be one of the manufacturers' current models, new and unused. The design shall be such as to provide safe and convenient operation. The construction and design shall include all components, parts and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.3.2 Controls. All operating controls shall be located convenient to the operator except as otherwise specified herein.

3.3.3 Safety and health requirements. Covers or other safety devices shall be provided for all parts of the machine presenting safety hazards which can be guarded without substantial interference to operation of the machine. All guards shall be removable to provide easy access to guarded parts. Except as otherwise specified by the procuring activity, the machine shall comply with the standards promulgated under OSHA applicable to the machine itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2.1 and 6.5).

3.3.4 Lubrication. All bearing (except sealed, permanently lubricated type), mating gears, rotating, and sliding parts shall be provided with means for lubrication. All oil holes, grease fittings, and filler caps shall be easily accessible.

3.3.5 Interchangeability. All parts subject to replacement shall be manufactured to definite dimensional and tolerance standards which will permit installation of replacement parts without modification to the part or equipment.

3.3.6 Construction. The saw shall be constructed of parts which are new, without defects, and free of repair. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.7 Castings and forgings. All castings and forgings shall be fess of scale and mismatching. No process such as welding, peening, plugging, or filling with metallic paste shall be used for reclaiming any defective part.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.3.8 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.9 Fastening devices. All screws, pins, bolts, and similar parts shall be installed in such a manner as to prevent change of tightness. Those subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

3.3.10 Surfaces. All surfaces of castings, forgings, molded parts, stampings, and welded parts shall be cleaned and free from sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be commensurate with the manufacturer's commercial practice.

3.3.11 Painting. Unless otherwise specified (see 6.2.1), the saw shall be painted in accordance with the manufacturer's commercial practice.

3.3.12 Threads. All threaded parts shall be in the inch system and shall conform to Handbook H28.

3.3.13 Plates. All words on speed and feed indicating plates and on instruction plates shall be in the English language. Letters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background.

3.3.14 Gears. All gears used in the saw and its components shall be machined in the inch system and shall conform to the applicable requirements of AGMA 360.

3.3.15 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

Points of application

Service interval

Type of lubricant

Viscosity

Military or Federal Specification Number of required lubricants

3.3.16 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate identifying the machine in accordance with MIL-STD-130 shall be securely attached to each saw. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each such caption is clear as to its identity.

Nomenclature

Manufacturer's name

Manufacturer's model designation

Manufacturer's serial number

Power input (volts, total amps, phase, frequency)

Largest diameter blade accommodated (inches)

Contract Number or Order Number

Federal Stock Number, National Stock Number or Plant Equipment Code

Date of manufacture

U S

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.3.17 Technical data. Data shall be furnished as specified (see 6.3).

3.3.18 Workmanship. Workmanship of the saw and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

3.4 Detailed requirements.

3.4.1 Components. Saws covered herein shall consist essentially of a frame supporting the saw blade arbor and its elevating and tilting mechanisms, drive system, and table and such other components necessary to meet the requirements stated herein.

3.4.1.1 Frame. The frame shall be of such mass and shall have sufficient strength and rigidity to support the working parts of the saw. The frame support and maintain alignment of the arbor with the table and be constructed to provide both vertical and tilting arbor adjustments in relation to the workpiece support surface of the table. The frame shall have provisions on its base for attaching to the floor or foundation. The frame of type I saws shall contain such features that are necessary to dispose of sawdust and chips through an exhaust outlet shaped for connection to a pneumatic conveyor system. Type II saw frames shall include a storage bin with a clean-out door for sawdust and chip removal.

3.4.1.2 Table. The table shall be mounted stationary to the frame, providing a horizontal workpiece support surface, which is 3 feet, ± 2 inches, above the frame base mounting surface. The table top surface shall be flat within 0.005 inch per foot. The table top surface shall have a finish not rougher than 65 microinches. The table shall be fitted with removable throat plates or other provisions as necessary, to limit side clearances on each side of the saw blade to 1/2 inch or less, and facilitate mounting of arbor attachments. The table shall have parallel slots on each side of the saw blade to accept a miter attachment. The slots shall span the complete table length and be parallel to the sides of the saw blade within 0.005 inch per foot. Each table shall have a linear scale graduated in increments not greater than 1/16 inch. Each quarter inch scale graduation shall be longer than the others and each inch graduation shall be numbered. The scale shall reveal the distance between the saw blade side and the face of the fence. Table dimensions shall conform to table I. Special tables and table dimensions shall be as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.1.3 Elevating and tilting mechanisms. The saw shall have elevating and a tilting mechanisms which will support and provide manual control for depth and angle of the saw blade cutting through workpieces hand-fed across the table. The elevating mechanism shall provide vertical travel of the saw blade to the cutting depth specified in table I. The tilting mechanism shall provide a tilt range for the saw blade from vertical position, 90 degrees to the table workpiece support surface, through 45 degrees tilt. The tilting and elevating mechanism shall be so constructed that when the saw blade is manually positioned, by a handwheel control that the mechanism secures the blade in that position through sawing operations. The manual control handwheel shall easily adjust the elevating mechanism and the tilting mechanism, or a separate handwheel for each function, shall easily actuate elevation and tilting adjustments. The tilting mechanism shall include a graduated scale, in degrees to indicate the degree of a saw blade tilt. The scale shall be accurate to plus or minus one degree, with each five degrees bearing a number, corresponding to the angle of saw blade tilt. The elevating and tilting mechanisms shall have provisions for adjustments to maintain component alignment and working tolerances.

3.4.1.4 Blade guard, material spreader and anti-kickback device. The exposed portion of the saw blades above the table shall be covered by a guard. The guard shall automatically adjust to the thickness of workpieces being hand-fed across the table, and remain in contact with the workpiece at all times to prevent accidental physical contact with the blade. The guard shall be constructed to resist blows and strains incidental to sawing operations, in order to protect the operator from flying splinters and broken saw teeth. The blade guard shall be mounted so that its operation shall be positive and alignment with the saw is maintained through the entire elevation and tilt ranges. The mounting shall be such that it will adequately resist reasonable side thrust or other force which would disrupt alignment. Each saw shall have a material spreader of a size which is slightly thinner than the saw kerf. Each saw shall have an anti-kickback device. The material spreader and anti-kickback device shall be constructed and located on the saw in such a manner that their alignment with the blade is constant. The blade guard, material spreader and anti-kickback device shall either swing clear or be easily removable to facilitate dado operations. Once these operations are completed the blade guard, material spreader and anti-kickback device shall either swing back into aligned position with the blade or be easily mounted on the saw in an aligned position with the blade.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.

3.4.1.5 Fence. The saw shall have a fence that serves as a guide for the workpiece as it is hand-fed into the saw blade. The fence shall have a height of not less than 2 inches. The fence shall either be double faced or reversible to facilitate its use on either side of the saw blade. The fence support shall allow the fence to be positioned across the entire table width. The fence face, for guiding workpieces, shall be within plus or minus one degree of a right angle to the workpiece support surface of the table. The fence on type I saws shall have a length as required to span that part of the table from the front edge of the table to not less than 12 inches beyond the saw blade arbor. The fence on type II saws shall span the entire length of the table. Manual controls shall securely lock the fence in adjusted positions. The fence alignment with the side of the saw blade shall be within 0.005 inch per foot. When specified (see 6.2.1), the fence on type I saws shall be mounted on extended rails or tables that enables greater ripping capacity as specified. When specified (see 6.2.1), the fence shall be either of the box type, tilting universal type, or non-tilting universal type each having micrometer adjustment capabilities.

3.4.1.6 Miter attachments. Each saw shall be furnished with a miter attachment. The attachment shall consist essentially of a bar that slides in the table slots paralleling the saw blade. The bar shall support a material rest which has swivel capabilities of not less than 45 degrees right and left of the bar. The adjustment device shall securely lock the material rest in any position within the swivel range. The miter attachment shall have a scale graduated in increments not larger than one degree, that indicates the angle to the saw blade to which the material rest is swiveled. Each five degrees of the scale shall be numbered. The graduations shall have an accuracy within plus or minus one degree. With the material rest secured in adjustment for producing angular and square cuts the miter attachment shall allow the operator to manually feed workpieces easily into the saw blade.

3.4.1.7 Drive. The drive on type I saws shall be the direct drive type. The arbor flanges for driving the circular saw blade shall be mounted directly on the motor shaft. The drive on type II saws shall be of the V-belt type. The circular saw blade arbor flanges and V-belt pulley shall be mounted on the arbor shaft and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

supported by ball or roller bearings. The arbor shall be driven by V-belts from a pulley mounted on the motor shaft. The V-belt drive shall have means for belt alignment and maintaining belt tension. Saws shall be provided with a means of holding the arbor for removing and replacing saw blades. When specified (see 6.2.1), the saw shall have a brake or other means that will stop the circular saw blade rotation, at maximum no load blade speed, within a time period of 10 seconds.

3.4.1.8 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall be in accordance with this paragraph. The system shall be in accordance with the applicable requirements of National Electrical Manufacturer's Association (NEMA) Standards. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit fed through a fused safety disconnect switch. The machine shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. A transformer and nominal 115 volt control circuit shall be provided.

3.4.1.9 Motor. Motors shall conform to NEMA MG-1, and shall have ball or roller bearings. Horsepower ratings shall conform to the requirements shown under "standard" in table I. When specified (see 6.2.1), motor horsepower rating shall be one of the horsepower ratings shown under "optional" in table I, as specified. Unless otherwise specified (see 6.2.1) each motor shall be totally enclosed fan cooled (TEFC). Unless otherwise specified, motor controls shall conform to NEMA IC-1, shall have a type I enclosure and a magnetic starter providing overload and under-voltage protection.

3.4.2 Sizes and capacities. The sizes and capacities of the saw shall meet the requirements of table I.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes and capacities

Characteristic	Type I					Type II		
	Size 12	Size 14	Size 16	Size 18	Size 20	Size 10	Size 12	Size 14
Largest diameter blade accommodated, inches	12	14	16	18	20	10	12	14
Table dimensions, inches	32x34	32x34	36x40	40x44	40x44	27x36	38x48	38x48
Arbor diameter, inches	1	1	1	1	1	5/8	5/8	1
Depth of cut, blade inches,								
90 degrees	2-1/4	3-1/4	4	4-3/4	5-1/2	3-1/8	4-1/8	5-1/8
45 degrees	1-1/2	2	2-1/2	3	3-1/2	2-1/8	2-7/8	3-5/8
Rip capacity (blade to face of fence), inches								
Right	20	20	24	24	24	25	30	30
Left	12	12	15	15	15	15	20	20
Cut off capacity, blade to front edge of table, inches	14	14	17	17	17	12-1/4	16	16
Dado width, inches	2	2	2	3	3	13/16	13/16	1
Motor horsepower								
Standard	2	2	5	5	5	1-1/2	3	5
Optional	3 or 5	3 or 5	7-1/2 or 10	7-1/2 or 10	7-1/2 or 10	2 or 3	5	7-1/2
Arbor RPM	3600	3600	3600	3600	3600	4000	3750	3750

Note: Requirements are not less than those shown.

3.4.3 Standard equipment. Unless otherwise specified (see 6.2.1), the following equipment shall be furnished with each saw.

(a) One set of hand tools normally furnished by the manufacturer

(b) One combination type saw blade of the size specified in table I and conforming to the requirements of Federal Specification GGG-B-440

3.4.4 Optional equipment. Optional equipment and accessories shall be furnished as specified (see 6.2.1).

3.4.5 Electromagnetic interference control. When specified (see 6.2.1), equipment procured under this specification shall comply with the requirements of MIL-STD-461.

3.4.6 Fungus control. When required (see 6.2.1), fungus control shall be as specified.

3.5 Performance requirements.

3.5.1 Sawing capability and accuracy. The saw shall be capable of performing ripping and cross cutting operations in wood workpieces having a thickness equal to the capacity specified in table I. The saw shall also be capable of performing angular cuts with the saw blade tilted through a 45 degree angle to the workpiece support surface of the table. The saw shall be capable of ripping workpieces, 1 inch thick being hand fed at a safe even feed rate, averaging 1 to 1-1/2 inches per second. The tilting arbor and the miter attachment shall provide compound mitering capabilities on workpieces. Cuts in workpieces shall be parallel to the guiding surface of the fence, perpendicular to the material rest of the miter gauge (set for a square cut), and perpendicular to the surface supported by the table to an accuracy of 0.015 inch per foot.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure suppliers and services conform to prescribed requirements.

4.2 First Article inspection. When First Article approval is required under 3.2, First Article inspection shall be performed. Unless otherwise specified (see 6.2.1), First Article inspection shall comprise the examination in 4.4 and all tests in 4.5. Failure to pass the examination or test shall be cause for denial of the First Article approval.

4.3 Quality conformance inspection. Each saw shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.4, the tests in 4.5.1 through 4.5.2 and the inspection in 4.6. Failure to pass the examination or test shall be cause for rejection.

4.4 Examination. The saw and equipment shall be examined to determine compliance with the requirements in 3.3 through 3.4.6.

4.4.1 Safety and health requirements. The saw shall be examined to determine compliance with all OSHA requirements concerning the machine itself, and for compliance with other safety and health requirements specified by the procuring activity (see 3.3.3, 6.2.1, and 6.5).

4.5 Tests.

4.5.1 Operational test. The saw shall be operated for not less than 15 minutes. The elevating and tilting mechanism, fence and mitering attachment shall be actuated and the electrical controls and motor shall function in accordance with the requirements specified herein.

4.5.2 Performance tests. The saw shall be subjected to the following tests. Failure to meet the requirements shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4.5.2.1 Test workpiece material. The type of wood used as test workpieces shall be at the option of the supplier in accomplishing the performance tests.

4.5.2.2 Ripping test. A test workpiece of not less than one inch thickness and 30 inches in length shall be hand-fed at a feed rate averaging 1 to 1-1/2 inches per second. The circular saw blade shall extend through the top surface of the test workpiece approximately 1/32 inch during the ripping test. The ripped edges of the workpiece shall be straight within 0.015 inch per linear foot, with the workpiece resting on the saw table and the ripped edge positioned to the fence.

4.5.2.3 Mitering test. Two test workpieces of equal size, having a width not less than 4 inches, a thickness not less than 1 inch, and a length not less than 12 inches shall be used to perform the mitering test. The saw blade shall be tilted 45 degrees to the workpiece support surface of the table. The material rest, on the mitering attachment, shall be swiveled to a 45 degree angle to the saw blade side. One of the workpieces shall be placed to the material rest by hand, and a compound miter shall be produced by the saw. The material rest shall be swiveled to 45 degrees in the opposing angle, to the side of the saw blade, and a compound angle shall be produced on the end of the second test workpiece. The two test workpieces shall be placed on the saw table with one edge of each test workpiece aligned to the fence by hand. The two test workpieces shall have a mating compound mitered joint, with the angles proving equal, within 2 degrees.

4.5.3 Electromagnetic interference control tests. Equipment requiring electromagnetic interference control testing shall be tested for compliance with 3.4.5.

4.6 Inspection for preparation for delivery. Preservation-packaging, packing, and marking shall be inspected to determine compliance with the requirements of section 5.

5. PREPARATION FOR DELIVERY

5.1 Preservation, packaging and packing. Unless otherwise specified (see 6.2.1), preservation, packaging and packing shall be in accordance with MIL-M-18058. Level of preservation, packaging and packing shall be as specified (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

5.2 Marking. Marking shall be in accordance with 5.2.1 or 5.2.2.

5.2.1 Civil agencies. In addition to the markings required by the contract or order, marking shall be in accordance with Federal Standard No. 123.

5.2.2 Military activities. In addition to any special marking required by the contract or order, unit packaged, intermediate packages, and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. Saws covered by this specification are intended for use in ripping, cross cutting, beveling and mitering of wood workpieces.

6.2 Ordering data.

6.2.1 Procurement requirements. Purchasers should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the following:

(a) Title, number, and date of this specification.

(b) Type and size saw required (see 1.2.1).

(c) First Article approval, if required (see 3.2 and 6.4).

(d) Exceptions and additional safety and health requirements (see 3.3.3 and 6.6).

(e) Painting, if different (see 3.3.11).

(f) Lubrication chart, if different (see 3.3.15).

(g) Nameplate, if different (see 3.3.16).

(h) Describe special table and specify table dimensions, if required (see 3.4.1.2).

(i) Extended rails for greater ripping capacity, if required (see 3.4.1.5).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

(j) Fence, if different (see 3.4.1.5).

(k) Brake, if required (see 3.4.1.7).

(l) Electrical system, if different (see 3.4.1.8).

(m) Optional horsepower motor, if required (see 3.4.1.9).

(n) Control enclosure and motor enclosure, if different (see 3.4.1.9).

(o) Standard equipment, if different (see 3.4.3).

(p) Optional equipment, if required (see 3.4.4).

(q) Electromagnetic interference control, if required (see 3.4.5).

(r) Fungus control, if required (see 3.4.6).

(s) First Article inspection, if different (see 4.2).

(t) Quality conformance inspection, if different (see 4.3).

(u) Requirements for preparation for delivery and applicable levels of preservation, packaging, and packing (see 5.1).

6.3 Contract data requirements. Required technical data, such as operators manuals, parts lists, foundation and anchor bolt plans, wiring diagrams and other instructions for operation and maintenance as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract (see 3.3.1.7).

6.4 First Article. When First Article approval is required under 3.2, the solicitation should include complete information concerning examination, testing, and approval.

6.5 Occupational Safety and Health Act (OSHA). Paragraph 3.3.3 required compliance only with OSHA requirements concerning the machine itself. These requirements include, but are not limited to,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

the following sections of the OSHA Standards:

29 CFR 1910.144 - Safety Color Code for Marking Physical Hazards
29 CFR 1910.212 - General Requirements for all Machines
29 CFR 1910.213 - Woodworking Machinery Requirements
29 CFR 1910.219 - Mechanical Power Transmission Apparatus

Since this specification does not require compliance with OSHA requirements concerning the operating environment, procuring agencies should insert additional requirements under 6.2(d) that will integrate the new machine into the work environment without exceeding OSHA hazard levels. OSHA standards applicable to this specification which are pertinent to the operating environment are:

29 CFR 1910.93 - Air Contaminants
29 CFR 1910.95 - Occupational Noise Exposure

The above sections are cited to assist procuring agencies in complying with OSHA. The machine user should measure and evaluate his safety and health requirements based on the entire content of OSHA standards.

MILITARY CUSTODIANS:

Army - ME
Navy - SH
Air Force - 84

Review Activities:

Army - ME
Navy - YD

User activities:

Army - WC

Preparing activity:

DSA - IP

CIVIL AGENCIES INTEREST:

GSA-FSS

Project Number:

3220-0077

U. S. GOVERNMENT PRINTING OFFICE : 1975 - 585-651/1558

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 45 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE OO-S-236C Saw, Circular, Table Type, Woodworking Single Tilting Arbor, Floor Mounted

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.