OO-S-240E
October 27, 1976
SUPERSEDING
Fed. Spec. OO-S-240D
May 12, 1972 and
MIL-S-80217
15 January 1971

FEDERAL SPECIFICATION

# SAWS, POWER,HACK, 6 INCH THRU 24 INCH WORKPIECE CAPACITY

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for use of all Federal agencies.

## 1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers manual and automatic bar feed hack saws for cutting off bars, rods, pipe, tubing and structural shapes of ferrous and non-ferrous metals.

1.2 Classification.

1.2.1 Styles and sizes. Power hack saws covered by this specification shall be of the following styles and sizes. The style and size required shall be as specified (see 6.2.1). Dimensions shown in inches, represent the workpiece capacity, based on minimum dimensions of the largest rectangular workpiece cross section, accommodated by each size hack saw listed.

Style I - Manual bar stock feed, non-automatic cutting

Style II - Automatic bar stock feed, automatic cutting

Size 6 - 6 inch width x 6 inch height
Size 10 - 10 inch width x 10 inch height
Size 12 - 12 inch width x 12 inch height
Size 14 - 14 inch width x 14 inch height
Size 18 - 18 inch width x 18 inch height
Size 20 - 20 inch width x 20 inch height
Size 24 - 24 inch width x 24 inch height

FSC 3405

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

## 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Standard:

Fed. Std. No. 123 - Marking for Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Forth Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specification and Standards from established distribution points in their agencies.)

Military Specification:

MIL-M-18058 - Machinery, Metal and Woodworking, Preparation for Delivery of.

Military Standards:

MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Governmental:

Occupational Safety and Health Act (OSHA) of 1970:

| | |
|---|---|
| Title 29, Code of Federal Regulations, Chapter XVII, Part 1910, and amendments | Occupational Safety and Health Administration Standards |

National Bureau of Standards (NBS) Handbook:

H-28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Non-Governmental:

Joint Industrial Council (JIC):

ECP-1 - Electrical Standards for General Purpose Machine Tools

(Application for copies should be addressed to the National Machine Tool Builders' Association, 7901 Westpark Drive, McLean, VA 22101.)

American Gear Manufacturers Association (AGMA):

AGMA 360 - Manual for Machine Tool Gearing.

(Application for copies should be addressed to the American Gear Manufacturers Association, 1330 Massachusetts Ave., NW, Washington, DC 20005.)

3. REQUIREMENTS

3.1 Classification of requirements. The requirements for the saws are classified herein as follows:

| Requirement | Paragraph |
|---|---|
| First Article approval | 3.2 |
| General requirements | 3.3 |
| Detailed requirements | 3.4 |
| Performance requirements | 3.5 |



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

3.2 First Article approval. If First Article approval is required (see 6.2.1 and 6.4), inspection therefor shall be in accordance with Section 4. A First Article comprises a preproduction model or initial production sample; approval involves testing and evaluating the First Article for conformance with the requirements herein before, or in the initial stage of, production under a contract.

3.3 General requirements.

3.3.1 Design. The saw shall be one of the manufacturer's current models, new and unused. The design shall be such as to provide safe and convenient operation. The construction and design shall include all components, parts and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.3.1.1 Controls. All operating controls shall be located convenient to the operator except as otherwise specified herein.

3.3.1.2 Safety and health requirements. Covers or other safety devices shall be provided for all parts of the machine presenting safety hazards which can be guarded without substantial interference to operation of the machine. All guards shall be removable to provide easy access to guarded parts. Except as otherwise specified by the procuring activity, the machine shall comply with the standards promulgated under OSHA applicable to the machine itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2.1 and 6.5).

3.3.1.3 Lubrication. All bearings (except sealed, permanently lubricated type), mating gears, rotating, and sliding parts shall be provided with means for lubrication. All oil holes, grease fittings, and filler caps shall be easily accessible.

3.3.1.4 Interchangeability. All parts subject to replacement shall be manufactured to definite dimensional and tolerance standards which will permit installation of replacement parts without modification to the part or equipment.

3.3.2 Construction. The saw shall be constructed of parts which are new, without defects, and free of repair. The structure shall be capable of withstanding all forces encountered during operation of the machine to its maximum rating and capacity without permanent distortion.

3.3.2.1 Castings and forgings. All castings and forgings shall be free of scale and mismatching. No process such as welding, peening, plugging, or filling with metallic paste shall be used for reclaiming any defective part.



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.

3.3.2.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.2.3 Fastening devices. All screws, pins, bolts, and similar parts shall be installed in such a manner as to prevent change of tightness. Those subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently deformed.

3.3.2.4 Surfaces. All surfaces of castings, forgings, molded parts, stampings, and welded parts shall be cleaned and free from sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be commensurate with the manufacturer's commercial practice.

3.3.2.5 Painting. Unless otherwise specified (see 6.2.1), the saw shall be painted in accordance with the manufacturer's commercial practice.

3.3.2.6 Threads. All threaded parts shall be in the inch system and shall conform to Handbook H28.

3.3.2.7 Plates. All words on speed and feed indicating plates and on instruction plates shall be in the English language. Letters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background.

3.3.2.8 Gears. All gears used in the saw and its components shall be machined in the inch system and shall conform to applicable requirements of AGMA 360.

3.3.3 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be permanently and securely attached to each saw. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of application
Service interval
Type of lubricant
Viscosity
Military or Federal Specification Number of required lubricants



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.3.4 Nameplate. Unless otherwise specified (see 6.2.1), a corrosion-resistant metal nameplate identifying the saw in accordance with MIL-STD-130 shall be securely attached to each saw. The nameplate shall contain the information listed below. If the saw is a special model, the model designation shall include the model of the basic standard saw and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each such caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's serial number
Manufacturer's model designation
Power input (volts, total amps, phase, frequency)
Workpiece capacity, rectangular dimensions, inches
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture
U S

3.3.5 Technical data. Data shall be furnished as specified (see 6.3).

3.3.6 Workmanship. The saws and accessories shall be free from defects such as incomplete welds, rust, cracks, or other defects that may impair their operation, durability, or serviceability.

3.4 Detail requirements.

3.4.1 Components. Saws covered herein shall consist essentially of a base, saw blade frame, reciprocating drive mechanism, feed mechanism, work holding vise and a coolant system. In addition, the style II hack saws shall have an automatic bar feed unit.

3.4.1.1 Base. The base shall support the saw frame, drive mechanism, feed mechanism, workholding vise and such other components mounted thereon. The base shall have sufficient strength and rigidity to support the working parts of the saw and a workpiece equalling the maximum capacity of the saw. Rigidity shall be such that alignment of all parts is maintained to the degree necessary to produce cutting rates and accuracies specified herein. The base shall have access openings for maintaining internal mechanisms and removal of chips. The base shall have means of leveling and securing the saw to the floor or foundation. When specified (see 6.2.1), the base of size 18 x 18 and 24 x 24 saws shall have such features as necessary to position the saw blade for producing cuts of not less than 45 degrees through the workpiece axis. Either the base shall be constructed to swivel or columns supporting the blade drive and feed mechanism shall be adjustable, horizontally. When this feature is furnished, a non-swivel vise (3.4.15) shall be furnished on the saw. A degree scale shall provide cutting any angle through 45 degrees to the workpiece axis.



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.1.2 Frame. A frame supporting the saw blade under tension shall reciprocate either on anti-friction bearings or on gibbed ways. All parts in the reciprocating frame shall either be adjustable or replaceable to maintain working tolerances and necessary alignment of parts. The frame shall function in such a manner that at the end of each cut, the frame shall return to, and remain in, the elevated or retracted position for loading the next workpiece.

3.4.1.3 Blade drive mechanism. The blade drive mechanism shall consist of an electric motor operating in conjunction with a belt, transmission device and chain drive system, or combinations thereof. The blade drive mechanism shall provide reciprocal blade strokes per minute, either through a number of speed selections, or a speed range which is infinitely variable, to meet the requirements of table I. When specified (see 6.2.1), either a single blade speed, multiple blade speeds or infinitely variable blade speeds shall be furnished as required.

3.4.1.4 Blade feed mechanism. The blade feed mechanism shall be either mechanical, hydraulic or combination mechanical and hydraulic. The blade feed system shall have either manual adjustments or controls to provide efficient, automatic cutting pressures required for various sizes, shapes and materials to be cut. The blade feed system shall operate in conjunction with the reciprocating action of the saw blade, automatically applying pressure on the cutting stroke and lifting the blade on the return non-cutting stroke, while maintaining positive feed rates through entire cut off cycles.

3.4.1.5 Worktable and vise. The worktable and vise shall have strength and rigidity to support and hold a ferrous workpiece of a size equal to the maximum rated capacity, required by table I, while producing a metal removal rate required by table II. Unless otherwise specified in 3.4.1.6, the worktable shall be so constructed that coolant will gravity flow back to the sump or reservoir. The vise shall be of the quick acting type. Unless otherwise specified (see 6.2.1), style I saws shall have a vise of the swivel type and style II saws shall have a non-swivel type vise. The swivel vise shall be capable of being positioned to cut a workpiece at any angle from 90 degrees through 45 degrees to the workpiece axis.

3.4.1.6 Coolant system. Unless otherwise specified (see 6.2.1), each saw shall be equipped with a coolant system. The coolant system shall consist essentially of a sump or reservoir, a power driven pump, coolant control, a removable strainer and necessary piping. The sump or reservoir shall have a capacity to provide continuous flow of coolant and have means for filling, draining and cleaning. Means shall be provided to observe the coolant level within the reservoir or sump.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.1.7 Bar feed unit. Style II saws shall have a bar feed unit which shall feed the workpiece in increments over a range of 1/4 inch or less, to 24 inches or more, with a repeatable accuracy ± 0.010. The bar feed unit shall consist essentially of powered vises and a feeding mechanism. The vises shall have means of applying clamping pressure on thin wall tubing, without distortion or other damage to the tubing; and also apply adequate pressure to securely retain workpieces which are solid and of maximum size within the capacity of the saw. The vises may be operated either electrically, hydraulically, mechanically or combinations thereof. When specified (see 6.2.1), the bar feed unit shall have a cut counter for selecting the number cuts to be made. The counter shall have a mechanism that will stop the saw when the selected number of cuts are completed. The bar feed unit shall be automatic after manual actuation of the cycle start button. The bar feeder, conveyor and vise assembly shall feed the workpiece to the preselected length, the vise shall clamp the workpiece and the saw blade shall cut the workpiece. Upon completion of the cut, the head shall retract and the above cycle shall be repeated until the last cut, after which the saw shall stop. The bar feed unit shall also stop the saw, in the event the workpiece is consumed, prior to completion of the selected number of cuts.

3.4.1.7.1 Loading and discharge tracks. Style II hack saws shall be provided with workpiece loading and discharge tracks. Unless otherwise specified (see 6.2.1), the loading track shall be 12 feet in length or longer, and the discharge track shall be 42 inches in length or longer. The tracks shall be so constructed that cut workpieces will not fall back into the saw blade.

3.4.1.8 Workpiece support stands. When specified (see 6.2.1), each Style I hack saw shall be furnished with three stock support stands. The stands shall be of the roller type capable of accommodating a workpiece of the maximum rated size of the saw. The stands shall incorporate means for height adjustment.

3.4.1.9 Hydraulic system. Hydarulic systems, when furnished, shall be complete with pumps, valves, piping, cylinders, and pressure controls. Overpressure protection shall be provided in pressure lines and on the low side of each pressure reducing valve. Means shall be provided to determine and maintain fluid level.

3.4.2 Sizes and capacities. The sizes and capacities of the saws shall meet the requirements of table I.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

TABLE I. Sizes and Capacities.

| Characteristics | | Size 6 | Size 10 | Size 12 | Size 14 | Size 18 | Size 20 | Size 24 |
|---|---|---|---|---|---|---|---|---|
| Size, rectangular dimensions, workpiece cross section, inches | | | | | | | | |
| Normal 90° cutoff | | 6x6 | 10x10 | 12x12 | 14x14 | 18x18 | 20x20 | 24x24 |
| Angular 45° cutoff | | 4x6 | 6x10 | 7x12 | 9x14 | 12x18 | 14x20 | 15x24 |
| Blade data: | | | | | | | | |
| Length, inches | Standard | 14 | 18 | 18 | 21 | 24 | 24 | 36 |
| | Optional | - | 17-19 | 21 | 18-24 | 30 | 30 | 30 |
| Stroke, inches | Standard | 5 | 5 | 6 | 6 | 4½ | 6 | 8 |
| | Optional | 5½ | 6 | - | - | - | - | 6 |
| Strokes, per minute | | 55-125 | 50-125 | 50-145 | 50-145 | 35-145 | 35-145 | 25-145 |
| Motor Horsepower | | | | | | | | |
| | Standard | 1 | 3 | 5 | 5 | 3 | 5 | 5 |
| | Optional | 1½-3 | 2-5 | 7½ | 7½ | 5-7½ | 7½ | 10 |

NOTE: Requirements are not less than those shown. Where a range is shown, the required performance is from the stated minimum or less to the stated maximum or more.

TABLE II. Performance.

| | Size 6 | Size 10 | Size 12 | Size 14 | Size 18 | Size 20 | Size 24 |
|---|---|---|---|---|---|---|---|
| Cutting rates (SAE 1045 cold rolled steel bar, square inches per minute) | *3 | 5 | 7 | 7 | 5 | 5 | 5 |

* Cutting rate for 1-1/2 HP 4 and 3 HP 5.





Source: https://assist.dla.mil -- Downloaded: 2026-02-26T11:58Z
Check the source to verify that this is the current version before use.

3.4.3 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall be in accordance with this paragraph. The system shall be in accordance with the applicable requirements of JIC Electrical Standards for General Purpose Machine Tools. Each machine shall draw all of its electrical power from a single 230/460 volt, 3 phase, 60 Hz circuit fed through a fused safety disconnect switch. The machine shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when installed shall be mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in table 15-1 of JIC Standards for the disconnect fuse rating.

3.4.4 Motors. Motors shall have ball or roller bearings. Unless otherwise specified (see 6.2.1), continuous duty horsepower ratings shall conform to the requirements of table I. When specified (see 6.2.1), the saw shall be equipped with a motor having the optional horsepower stated in table I. When specified (see 6.2.1), motors shall be of the squirrel cage, induction type. Unless otherwise specified (see 6.2.1), each motor shall be single speed and meet the requirements of a dripproof enclosure.

3.4.5 Standard equipment. Unless otherwise specified (see 6.2.1), the following equipment shall be furnished with each saw:

(a) One set of hand tools normally furnished by the manufacturer.
(b) Chart or data plate indicating recommended speeds and feeds for general hack sawing operations.
(c) Worklight.
(d) Stock stop gage.
(e) Saw blades, high speed steel edge; 6 each, 6 teeth per inch and 6 each, 10 teeth per inch.

3.4.6 Optional equipment. Optional equipment and accessories shall be furnished as specified (see 6.2.1).

3.4.7 Electromagnetic interference control. When specified (see 6.2.1), equipment procured under this specification shall comply with the requirements of MIL-STD-461.

3.4.8 Fungus control. When required (see 6.2.1), fungus proofing shall be as specified.

3.5 Performance requirements.

3.5.1 Cutting rate and accuracy. The saw shall be capable of cutting workpieces, which are flat and perpendicular to the workpiece axis within $\pm$ 0.002 inch per inch, at the cutting rates listed in table II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all insoection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First Article inspection. When First Article approval is required under 3.2, First Article inspection shall be performed. Unless otherwise specified (see 6.2.1), First Article inspection shall comprise the examination in 4.4 and all tests in 4.5. Failure to pass the examination or any test shall be cause for denial of the First Article approval.

4.3 Quality conformance inspection. Each saw shall be subjected to quality conformance inspection prior to being offered for acceptance. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.4, the tests in 4.5.1 through 4.5.2 and the inspection in 4.6. Failure to pass the examination or test shall be cause for rejection.

4.4 Examination. The saw and equipment shall be examined to determine compliance with the requirements in 3.3 through 3.4.8.

4.4.1 Safety and health requirements. The saw shall be examined to determine compliance with all OSHA requirements concerning the saw itself, and for compliance with other safety and health requirements specified by the procuring activity (see 3.3.1.2, 6.2.1, and 6.5).

4.5.1 Operational test. The saw shall be operated at no load for not less than 30 minutes. Proper operation of all controls, motors, adjusting mechanism, and accessories shall be verified during the trial period.

4.5.2 Sawing test. The type saw blade used in the sawing test shall be at the option of the supplier. The workpiece shall have a nominal dimension equal to the rated capacity of the saw. Either a round or rectangular shaped workpiece may be used in the sawing test. The saw blade selected by the supplier shall make three cuts or more through a SAE 1045 cold rolled steel workpiece. The metal removal rate, flatness and perpendicularity shall conform to 3.5.1 and table II.



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.

4.5.3 Electromagnetic interference test. Equipment requiring electromagnetic interference control shall be tested for compliance with 3.4.7.

4.6 Packaging inspection. Preservation, packing, and marking shall be inspected to determine compliance with the requirements of scetion 5.

5. PREPARATION FOR DELIVERY.

5.1 Preservation, packing and marking. Unless otherwise specified (see 6.2.1), preservation, packing and marking shall be in accordance with MIL-M-18058. Level of preservation and packing shall be as specified (see 6.2.1).

5.2 Marking.

5.2.1 Civil agencies. In addition to the markings required by the contract or order, marking shall be in accordance with Federal Standard No. 123, when specified (see 6.2.1).

6. NOTES

6.1 Intended use. Hack saws covered b this specification are intended for use on various ferrous and non-ferrous materials.

6.2 Ordering data.

6.2.1 Procurement requirements. Purchasers should specify their requirements in procurement documents, including whether each choice is required or not required, by entering an appropriate statement identified to each of the following:

(a) Title, number and date of this specification.
(b) Style and size saw required (see 1.2.1).
(c) First Article approval, if required (see 3.2 and 6.4).
(d) Exceptions and additional safety and health requirements (see 3.3.1.2 and 6.5).
(e) Painting, if different (see 3.3.2.5).
(f) Lubrication chart, if different (see 3.3.3).
(g) Nameplate, if different (see 3.3.4).
(h) Base features for angular cuts (see 3.4.4.1).
(i) Blade speeds, if different (see 3.4.1.3).
(j) Describe type vise, if different (see 3.4.1.5).
(k) Delete coolant system, if not required (see 3.4.1.6).
(l) Cut counter if required (see 3.4.1.7).
(m) Describe loading and discharge requirements for type II saws, if different (see 3.4.1.7.1).
(n) Workpiece support stands, if required (see 3.4.1.8).
(o) Electrical system, if different (see 3.4.3).



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

(p) Motor horsepower rating, specify optional H.P., if required (see 3.4.4 and table I).
(q) Motor, if squirrel cage induction type is required (see 3.4.4 and 6.6).
(r) Motor, number of speeds and type of enclosure, if different (see 3.4.4).
(s) Standard equipment, if different (see 3.4.5).
(t) Optional equipment, if required (see 3.4.6).
(u) Electromagnetic interference control, if required (see 3.4.7).
(v) Type fungus proofing, if required (see 3.4.8).
(w) First Article inspection, if different (see 4.2).
(x) Quality conformance inspection, if different (see 4.3).
(y) Electromagnetic interference control test, if different (see 4.5.3).
(z) Requirements for preparation for delivery and applicable levels of preservation and packing required (see 5.1).
(aa) When civil agency marking is required (see 5.2.1).

6.3 Contract data requirements. Required technical data such as operators manuals, parts lists, foundation and anchor bolt plans, wiring diagrams and other instructions for operation and maintenance as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated into the contract (see 3.3.5).

6.4 First Article. When first article approval is required under 3.2, the solicitation should include complete information concerning examination, testing, and approval.

6.5 Occupational Safety and Health Act (OSHA). Paragraph 3.3.1.2 required compliance only with OSHA requirements concerning the machine itself. These requirements include, but are not limited to, the following sections of the OSHA Standards:

1910.144 - Safety Color Code for marking Physical Hazards
1910.212 - General Requirements for all Machines
1910.219 - Mechanical Power Transmission Apparatus

Since this specification does not require compliance with OSHA requirements concerning the operating environment, procuring agencies should insert additional requirements under 6.2(d) that will integrate the new machine into the work environment without exceeding OSHA hazard levels. OSHA sections applicable to this specification which are pertinent to the operating environment are:

1910.95 - Occupational Noise Exposure

The above sections are cited to assist procuring agencies in complying with OSHA. The machine user should measure and evaluate his safety and health requirements based on the entire content of OSHA standards.



Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the current version before use.

6.6 Squirrel cage induction motors. Procuring activities should exercise due caution in requiring this motor type (see 3.4.4 and 6.2.1), particularly when variable speed motors are involved. The requirements may eliminate the commercial equipment of some, or all, potential suppliers.

MILITARY CUSTODIANS:

Army - WC
Navy - SH

Review Activities:

Army - WC
Navy - SH
DGSC - GS

User Activities:

Army - WV
Navy - OS, YD

CIVIL AGENCIES COORDINATING ACTIVITIES:

GSA - FSS

Preparing Activity:

DSA - IP

Project Number:

3405-0053

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 35 cents each.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

FOLD

HEADQUARTERS
DEFENSE INDUSTRIAL PLANT EQUIPMENT CENTER
MEMPHIS, TENNESSEE 38114

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY
DoD-304

U.S.MAIL

Commander
Defense Industrial Plant Equipment Center
ATTN: DIPEC-TFM
Memphis, TN 38114

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE OO-S-240E Saws, Power, Hack, 6 Inch thru 24 Inch Workpiece Capacity

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.