00-S-256/1A
November 16, 1978
SUPERSEDING
00-S-256/1
January 28, 1970

FEDERAL SPECIFICATION

SEWING MACHINES, INDUSTRIAL; FLATBED, SINGLE-NEEDLE, MACHINES

The complete requirements for procuring the sewing machines described herein shall consist of this document and the issue in effect of Specification 00-S-256.

This detailed specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for single-needle, flatbed, industrial sewing machines.

1.2 Classification. The sewing machines shall be of the following stitch types and classes, as specified (see 6.2).

Stitch type 301 (lock)

Class 2 - Light and medium duty
Class 3 - Medium-heavy duty
Class 4 - Heavy duty
Class 6 - Extra-heavy duty

Stitch type 101 (chain)

Class 1 - Light duty basting edge
Class 3 - Basting edge, with edge worker

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

FSC 3530

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Class 2, stitch type 301. The machine shall be equipped with a bobbin winder and a knee lifter. The machine shall operate at not less than 4,800 stitches per minute with 8-18 stitches per inch (3-7 stitches/cm). Working space to the right of the needle shall consist of not less than 8 inches (203 mm) and not greater than 13 inches (330 mm). The machine shall have a feed A mechanism. The machine shall be automatically lubricated, and the mounting shall be fully submerged.

3.2 Class 3, stitch type 301. The machine shall be provided with a knee lifter. The machine shall operate at not less than 2,000 stitches per minute with 6-20 stitches per inch (2-8 stitches/cm). Working space shall consist of not less than 9-1/2 inches (241 mm) and not greater than 14 inches (356 mm). The machine shall have a reversible feed A mechanism. The machine shall be nonautomatically lubricated, and the mounting shall be fully submerged.

3.3 Class 4, stitch type 301. The machine shall be provided with a foot lifter. The machine shall operate at not less than 2,200 stitches per minute with 6-12 stitches per inch (2-5 stitches/cm). Working space at the right of the needle shall consist of not less than 9-1/2 inches (241 mm) and not greater than 11 inches (280 mm). The machine shall have a reversible feed A mechanism. The machine shall be nonautomatically lubricated, and the mounting shall be fully submerged.

3.4 Class 6, stitch type 301. The machine shall conform to table I and a knee lifter shall be provided with a B feed mechanism machine. The machine lubrication shall be nonautomatic; and the mounting shall be fully submerged. A ten speed motor with inching capacity may be furnished, if the machine head is supplied without a front hand wheel. The motor shall be not less than 1/2 hp (373 W). The table top shall have a multi-plywood core.

TABLE I.

Feed	Speed (not less than) stitches per minute	Stitches per inch, (stitches/cm)	Working space, inches (mm) to the right of the needle)	Table top dimensions width x length, minimum, inches (mm)
B	400	2-1/2 - 8 (1/2 - 1/3)	14-1/2 to 19-1/2 (368 to 495)	30 x 58 (762 x 1473)
H	1100	2-1/2 - 8 (1/2 - 1/3)	29-1/2 to 30-1/2 (749 to 775)	20 x 66 (508 x 1676)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

3.5 Class 1, stitch type 101. The machine shall be provided with a knee lifter. The machine shall operate at a speed not less than 4,000 stitches per minute with 4-8 stitches per inch (2-3 stitches/cm). Working space at the right of the needle shall consist of not less than 4-1/2 inches (114 mm) and not greater than 12 inches (304 mm). The machine shall have a feed A mechanism. The machine shall be semi-automatically lubricated, and the mounting shall be fully submerged.

3.6 Class 3, stitch type 101. The machine shall be provided with a knee lifter. The machine shall operate at a speed not less than 1,200 stitches per minute with 2-4 stitches per inch (1-2 stitches/cm). The machine shall be equipped with a power operated device for working out and basting the edge. The machine shall have a feed A mechanism. The machine shall be nonautomatically lubricated. The mounting shall be nonsubmerged.

4. QUALITY ASSURANCE PROVISIONS

This section does not apply to this specification.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

6. NOTES

6.1 Intended use. Stitch type 301, class 2 machines shall be suitable for stitching flags, guidons, chevrons, light and medium weight shirts, dresses, coats, trousers, work clothing, blankets, suits, overcoats, and uniforms. Stitch type 301, class 3 machines shall be suitable for stitching, repairing, and darning on uniforms, work clothing, and underwear. Stitch type 301, class 4 machines shall be suitable for stitching heavy canvas, tents, tarpaulins, sails, and awnings. Stitch type 301, class 6 machines shall be suitable for stitching heavy canvas, tents, tarpaulins, sails, and awnings. Stitch type 101, class 1 machines shall be suitable for basting edges and collars of coats, jackets and overcoats. Stitch type 101, class 3 machines shall be suitable for basting edges and collars of coats, jackets and overcoats.

6.2 Ordering data. In addition to ordering data of the general specification, the purchaser should include the following information as applicable:

(a) Title, number and date of this specification.
(b) Stitch type and class machine required (1.2).

6.3 Deletion data. Styles A and C stitching designators were deleted in this revision.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:58Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Air Force - 99

Review activity:

DLA - GS

User activities:

Navy - SA, MC

Preparing activity:

Army - GL

Civil Agency Coordinating Activities:

GSA-FSS
VA-DMS

Project No. 3530-0063-1

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.