INCH-POUND

OO-S-256/1B
November 10, 1992
SUPERSEDING
OO-S-256/1A
INT. AMENDMENT-1 (Army - GL)
November 14, 1990 and
OO-S-256/1A
November 16, 1978

FEDERAL SPECIFICATION SHEET

SEWING MACHINES, INDUSTRIAL; FLATBED,

SINGLE-NEEDLE, MACHINES

This specification sheet is approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal Agencies.

The complete requirements for procuring the sewing machines described herein shall consist of this document and the latest revision in effect of Specification OO-S-256/GEN.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the specific requirements for a single-needle, flatbed, industrial sewing machine.

1.2 Classification. The sewing machines shall be of the following stitch types and classes, as specified (see 6.2).

Stitch type 301 (lock)

Class 2 - Light duty

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3530

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.

Class 3 - Light-medium duty
Class 4 - Heavy duty
Class 6 - Extra-heavy duty

Stitch type 101 (chain)

Class 1 - Light duty basting edge
Class 3 - Basting edge, with edge worker

2. APPLICABLE DOCUMENTS

This section does not apply to this specification.

3. REQUIREMENTS

3.1 Class 2, stitch type 301. The machine shall be equipped with a bobbin winder and a knee lifter. The machine shall have a nominal maximum speed of not less than 4800 stitches per minute with 8-18 stitches per inch. Working space to the right of the needle shall consist of not less than 8 inches and not greater than 13 inches. The machine shall have a type "A" feed mechanism. The machine shall be automatically lubricated, and the mounting shall be fully submerged.

3.2 Class 3, stitch type 301. The machine shall be equipped with reversible type "A" feed with the capability of sewing fabrics that range from light to medium weight such as nylon, cotton duck, synthetics, various coated and laminated fabrics, light to medium weight tapes and webbing, and shall utilize metric needle sizes 80 through 60. The machine shall be suitable for use with sizes A, B, C, D, E, and FF thread. The machine shall have a nominal maximum speed of not less than 2000 or greater than 2200 stitches per minute. The machine shall be nonautomatically lubricated. Each machine shall be supplied with a bobbin winder, knee operated presser foot lifter and thread stand. The machine shall be equipped with a horizontal axis oscillating shuttle, central bobbin and link take-up lever. The machine shall be equipped with a push down hand operated reverse feed lever which is spring loaded to normally return to the forward feed position. The mounting shall be fully submerged. The machine feed dog shall have 3 rows of teeth with a minimum of 16 teeth per inch. The stitching shall be a minimum of 5 to an unlimited number of stitches per inch. The stitch length adjustment shall be made with the use of a numerically marked rotary knob using a detent knob or other lock mechanism. The machine shall provide a minimum clearance of 1/4 inches under the presser foot. The presser foot shall be the hinged type. Working space to the right of the needle shall be not less than 10 inches and not greater than 11 inches. The machine shall be 18-3/4 $\pm$ 1/4 inches by 7 $\pm$ 1/4 inches by 10 $\pm$ 1/2 inches.

3.3 Class 4, stitch type 301. The machine shall be provided with a knee lifter. The machine shall have a nominal maximum speed of not less than 2200 stitches per minute with 6-12 stitches per inch. Working space to the right

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:58Z
Check the source to verify that this is the currentversion before use.

of the needle shall consist of not less than 9-1/2 inches and not greater than 11 inches. The machine shall have a reversible type "A" feed mechanism. The machine shall be nonautomatically lubricated, and the mounting shall be fully submerged.

3.4 Class 6, stitch type 301. The machine shall conform to table I and a hand or foot lifter shall be provided with a type "B" feed mechanism machine. The machine lubrication shall be nonautomatic, and the mounting shall be fully submerged. On an "H" feed machine only, a ten speed motor with inching capacity may be furnished, if the machine head is supplied without a front or center hand wheel. The motor shall be not less than 1/2 hp. The table top shall have a multi-plywood core.

TABLE I. Class 6, stitch type 301 machines

Feed	Nominal maximum speed (not less than) stitches per minute	Stitches per inch	Working space, inches to the right of the needle	Table top dimensions width X length minimum, inch
B	400	2-1/2 - 8	14-1/2 to 19-1/2	30 X 58
H	1100	2-1/2 - 8	29-1/2 to 30-1/2	20 X 66

3.5 Class 1, stitch type 101. The machine shall be provided with a knee lifter. The machine shall have a nominal maximum speed of not less than 4000 stitches per minute with 4-8 stitches per inch. Working space to the right of the needle shall consist of not less than 4-1/2 inches and not greater than 12 inches. The machine shall have a type "A" feed mechanism. The machine shall be semiautomatically lubricated, and the mounting shall be fully submerged.

3.6 Class 3, stitch type 101. The machine shall be provided with a knee lifter. The machine shall have a nominal maximum speed of not less than 1200 stitches per minute with 2-4 stitches per inch. The machine shall be equipped with a power operated device for working out and basting the edge. The machine shall have a type "A" feed mechanism. The machine shall be nonautomatically lubricated. The mounting shall be nonsubmerged.

4. QUALITY ASSURANCE PROVISIONS

This section does not apply to this specification.

5. PREPARATION FOR DELIVERY

This section does not apply to this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use.

Stitch type 301, class 2 machine shall be suitable for stitching flags, guidons, chevrons, light and medium weight shirts, dresses, coats, trousers, work clothing, blankets, suits, overcoats, and uniforms.

Stitch type 301, class 3 machines shall be suitable for stitching, repairing, and darning on uniforms, work clothing, and underwear.

Stitch type 301, class 4 machines shall be suitable for stitching mackintoshes, bedding, oiled clothing, pile and sheepskin lined coats, and light and medium canvas goods.

Stitch type 301, class 6 machines shall be suitable for stitching heavy canvas, tents, tarpaulins, sails, and awnings.

Stitch type 101, class 1 machines shall be suitable for basting edges and collars of coats, jackets, and overcoats.

Stitch type 101, class 3 machines shall be suitable for basting edges and collars of coats, jackets, and overcoats.

6.2 Ordering data. In addition to the ordering data of the general specification, the purchaser should include the following information as applicable:

a. Title, number, and date of this specification sheet.
b. Stitch type and class of machine required (see 1.2).

Custodians

Army - GL
Air Force - 99

Review Activities

Air Force - 84
DLA - GS

User Activities

Navy - SA, MC

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS

PREPARING ACTIVITY:

Army - GL

(Project 3530-0092)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.