MIL-C-3965/23B
AMENDMENT 1
2 July 1971

MILITARY SPECIFICATION SHEET

Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Nonpolarized, High Etched Foil) - 85°C (Voltage Derated to 125°C), Styles CL72 and CL73

This amendment forms a part of Military Specification Sheet MIL-C-3965/23B, dated 26 August 1970, and is mandatory for use by all Departments and Agencies of Department of Defense.

Page 4

Temperature Cycling: Delete "DF (max) - 115% of Table I value" and substitute "DF (max) - 115% of initial requirement".

Moisture Resistance: Delete "DF (max) - 115% of Table I value" and substitute "DF (max) - 115% of initial requirement".

Stability at Low and High Temperature: Step 1 (+25°C): Delete "DV (max)- Shall not exceed initial requirement" and substitute "DF (max) - Shall not exceed initial requirement".
Step 5: Delete "Step 5 (+25°C)" and substitute "Step 5 (+125°C):" Delete Δ Cap - Within $\pm$ 10% of initial measurement" and substitute "Δ Cap - Within + 75% of initial measurement".

Custodians:
Army - EL
Navy - EC
Air Force 80

Review Activities:
Army - MI
Navy - SH
Air Force 11, 17
DSA - ES

User Activities:
Army -
Navy - AS, MC, OS
Air Force 19

Preparing Activity:
Air Force 80

(Project 5910-1041-14)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:03Z
Check the source to verify that this is the current version before use.