MILITARY SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (NONSOLID ELECTROLYTE), TANTALUM, (POLARIZED, SINTERED SLUG) - 85°C (VOLTAGE DERATED TO 125°C), STYLES CL17 AND CL18

This amendment forms a part of Military Specification Sheet MIL-C-3965/19E, dated 26 August 1970, and is approved for use by all Departments and Agencies of the Department of Defense.

stitute ".025 ± .010".
- .005

Page 2

TABLE I, column 7, delete "Power factor (max)" in its entirety and substitute the following: "

Dissipation factor (max)
%
41.0
74.0
148.0
22.5
39.8
79.0
13.0
24.8
50.2
16.1
13.0
24.8
52.0
16.1
22.5
24.8
52.0
16.1
22.5
16.1
23.5
16.1
22.5
16.1
23.5

"

NOTE: The margin of this amendment is marked with an asterisk to indicate where a change from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - SH
Air Force - 11, 17, 80
DSA - ES

User activities:
Army -
Navy - AS, MC, OS
Air Force -

Preparing activity:
Air Force - 85

Project No. 5910-1174-2