MILITARY SPECIFICATION SHEET

Capacitors, Fixed, Electrolytic (Nonsolid Electrolyte), Tantalum, (Polarized, Sintered Slug) - 85°C (Voltage Derated to 125°C), Styles CL10 and CL13

This amendment forms a part of Military Specification Sheet MIL-C-3965/20E, dated 26 August 1970, and is mandatory for use by all Departments and Agencies of Department of Defense.

Page 2

Table I Capacitor Characteristics: Delete sixth column in its entirety "Power Factor (max)". Substitute: The following "Dissipation Factor (max)" values for the corresponding Type Designations.

Type Designation	Dissipation Factor (max) %
CL1-BC700TPG	53.0
CL1-BC141TPG	53.0
CL1-BD500TPG	37.5
CL1-BD101TPG	37.5
CL1-BF280TPG	21.4
CL1-BF560TPG	21.4
CL1-BH200TPG	15.0
CL1-BH400TPG	15.0
CL1-BK120TPG	9.1
CL1-BK250TPG	9.6
CL1-BM080TPG	6.1
CL1-BM160TPG	6.1
CL1-BR040TPG	6.1
CL1-BR080TPG	6.1
CL1-BS2R5TPG	5.7
CL1-BS050TPG	5.7
CL1-BT020TPG	6.1
CL1-BT040TPG	6.1

Custodians:
Army - EL
Navy - EC
Air Force 80

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:02Z
Check the source to verify that this is the current version before use.

MIL-C-3965/20E
AMENDMENT 1

Review Activities:
Army - MI
Navy - SH
Air Force 11, 17
DSA - ES

User Activities:
Army -
Navy - AS, MC, OS
Air Force 19

Preparing Activity:
Air Force 80

(Project 5910-1041-11)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:02Z
Check the source to verify that this is the current version before use.